IRIM @ TRECVid

Collaboration between French labs for a joint participation to TRECVid video semantic indexing task

DGA Workshop - July 6th, 2010

www.IRIT.fr/~Herve.Bredin

Outline

- TRECVid
- IRIM
- IRIM @ TRECVid 2009

TRECVid


- TREC Video Retrieval Evaluation
 - Every year, since 2001
 - Organized by the National Institute for Standards and Technology

"Encourage research in information retrieval by providing a large test collection, uniform scoring procedures, and a forum for organizations interested in comparing their results"

TRECVid 2010

- Semantic indexing
- Known-item search
- Content-based copy detection
- Surveillance event detection
- Instance search (pilot)
- Event detection in Internet multimedia (pilot)


Semantic Indexing @TRECVid




Semantic Indexing @TRECVid


- Input (provided by the organizers)
 - Training/Development set
 - 200 hours video with shot boundaries
 - Annotations for 130 "semantic concepts" at shot level
 - Test set
 - 200 hours video with shot boundaries
- Output (submitted by participants)
 - 130 sorted lists of 2000 shots most likely to contain each concept

Various Approaches to Semantic Indexing





Various Approaches to Semantic Indexing



Expertise required in multiple fields

video processing machine learning multimodal noisy data fusion few positive samples

IRIM

In the framework of GdR



- Stands for "Indexation & Recherche d'Information Multimédia"
- Coordinated by J. Benois-Pineau (LABRI), G. Quénot (LIF), M. Cord (LIP6) & H. Bredin (IRIT)
- Help french labs participate to TRECVid
 - Collaborate and share expertise
 - Avoid starting from scratch for newcomers

IRIM (2)



2 workshops a year (pre/post TRECVid)


- sponsored thematic workshop

"Scalable and cross-media indexing"

mrim.imag.fr/irim/

14 labs in 2009

IRIM @ TRECVid 2009



- 100+ descriptors
- Video

Color: global and regional histograms

Texture: Gabor filters, wavelets, ...

Shape: edge orientations, local descriptors

Motion: optical flow

Face detection

Audio
 Energy
 Spectral centroid
 Mel-Frequency Cepstrum Coefficients


- Multiple classifiers
 k-Nearest Neighbors
 Support Vector Machine
- Multiple fusion algorithms
 Genetic fusion
 Weighted combination

Average Precision


$$AP = \frac{\sum_{r=1}^{N} \delta_r \cdot \text{precision@r}}{\sum_{r=1}^{N} \delta_r}$$

N number of shots

 δ_r I if shot r is relevant, 0 otherwise precision@r ratio of relevant samples in top r list



Performance overview



- Best descriptors are visual
 Variant of Scale-Invariant Feature Transform (MAP = 0.0644)
- Best audio descriptor
 Mel-Frequency Cepstrum Coefficient (MAP = 0.019)
- Late fusion
 Depends on the combination of selected descriptors & classifiers
 0.092 < MAP < 0.132

TRECVid 2009 official results

- 222 runs
- MediaMill U of AmsterdamMAP = 0.228
- IRIM submitted 18 runs0.092 < MAP < 0.132
- #10 among 40 participants
- Average = 0.071 / Median = 0.051

Lessons learned

- From our runs
 - A+V is better than V-only.

 though, no major improvement (yet?)
 - Even weak descriptors can help.
- From others
 - Use multiple frames per shot.
 - Re-rank.

Agenda 2010

- 2010-08-09: submission deadline
- 2010-09-17: results available
- 2010-11-15: workshop @ NIST

IRIM @ TRECVId

mrim.imag.fr/irim trecvid.nist.gov

DGA Workshop - July 6th, 2010

www.IRIT.fr/~Herve.Bredin