

# 1

## Exploring the Oracle Database Architecture

ORACLE

### Objectives


After completing this lesson, you should be able to:

- List the major architectural components of Oracle Database
- Explain memory structures
- Describe background processes
- Correlate logical and physical storage structures
- Describe pluggable databases
- Describe ASM storage components



ORACLE


## Oracle Database Server Architecture: Overview



1 - 3

ORACLE

## Oracle Database Instance Configurations




1 - 4

ORACLE

## Connecting to the Database Instance


- Connection: Communication between a user process and an instance
- Session: Specific connection of a user to an instance through a user process



1 - 5

ORACLE

## Oracle Database Memory Structures




1 - 6

ORACLE

## Shared Pool

- Is a portion of the SGA
- Contains:
  - Library cache
    - Shared SQL area
  - Data dictionary cache
  - Server result cache




1 - 7

ORACLE

## Database Buffer Cache

- Is part of the SGA
- Holds copies of data blocks that are read from data files
- Is shared by all concurrent users




1 - 8

ORACLE

## Redo Log Buffer

- Is a circular buffer in the SGA
- Holds information about changes made to the database
- Contains redo entries that have the information to redo changes made by operations such as DML and DDL




1 - 9

## Large Pool

Provides large memory allocations for:


- Session memory for the shared server and the Oracle XA interface
- I/O server processes
- Oracle Database backup and restore operations



1 - 10

## Java Pool

Java pool memory is used to store all session-specific Java code and data in the JVM.




ORACLE

1 - 11

## Streams Pool

Streams pool memory is used exclusively by Oracle Streams to:


- Store buffered queue messages
- Provide memory for Oracle Streams processes



ORACLE

1 - 12

## Program Global Area (PGA)



1 - 13

ORACLE


## Process Architecture

- **User process**
  - Is the application or tool that connects to the Oracle database
- **Database processes**
  - **Server process:** Connects to the Oracle instance and is started when a user establishes a session
  - **Background processes:** Are started when an Oracle instance is started
- **Daemon / Application processes**
  - Networking listeners
  - Grid Infrastructure daemons

1 - 14

ORACLE

## Process Structures




1 - 15

ORACLE

## Database Writer Process (DBWn)

Writes modified (dirty) buffers in the database buffer cache to disk:

- Asynchronously while performing other processing
- To advance the checkpoint




1 - 16

ORACLE



## Log Writer Process (LGWR)

- Writes the redo log buffer to a redo log file on disk
  - When a user process commits a transaction
  - When an online redo log switch occurs
  - When the redo log buffer is one-third full or contains 1 MB of buffered data
  - Before a DBWn process writes modified buffers to disk
  - When three seconds have passed since the last write
- Serves as coordinator of LGnn processes and ensures correct order for operations that must be ordered




1 - 17

ORACLE

## Checkpoint Process (CKPT)

- Records checkpoint information in
  - Control file
  - Each data file header
- Signals DBWn to write blocks to disk




1 - 18

ORACLE

## System Monitor Process (SMON)

- Performs recovery at instance startup
- Cleans up unused temporary segments




1 - 19

ORACLE

## Process Monitor Process (PMON)

- Performs process recovery when a user process fails
  - Cleans up the database buffer cache
  - Frees resources that are used by the user process
- Monitors sessions for idle session timeout




1 - 20

ORACLE

## Listener Registration Process (LREG)

Registers information about the database instance and dispatcher processes with the Oracle Net Listener




1 - 21

ORACLE

## Archiver Processes (ARCn)


- Copy redo log files to a designated storage device after a log switch has occurred
- Can collect transaction redo data and transmit that data to standby destinations



1 - 22

ORACLE


## Database Storage Architecture



1 - 23

ORACLE

## Logical and Physical Database Structures




1 - 24

ORACLE

## Segments, Extents, and Blocks


- Segments exist in a tablespace.
- Segments are collections of extents.
- Extents are collections of data blocks.
- Data blocks are mapped to disk blocks.



ORACLE

1 - 25

## Tablespaces and Data Files



ORACLE

1 - 26

## SYSTEM and SYSAUX Tablespaces

- The `SYSTEM` and `SYSAUX` tablespaces are mandatory tablespaces that are created at the time of database creation. They must be online.
- The `SYSTEM` tablespace is used for core functionality (for example, data dictionary tables).
- The auxiliary `SYSAUX` tablespace is used for additional database components.
- The `SYSTEM` and `SYSAUX` tablespaces should not be used for application data.

ORACLE

1 - 27

## Oracle Container Database: Introduction


- *Pluggable database*: Is a set of database schemas that appears logically to users and applications as a separate database
- *Multitenant container database*: Has a database instance and database files at the physical level
- All pluggable databases share:
  - Background processes
  - Shared/process memory
  - Oracle metadata

ORACLE

1 - 28

## Automatic Storage Management


- Is a portable and high-performance cluster file system
- Manages Oracle database files
- Manages application files with ASM Cluster File System (ACFS)
- Spreads data across disks to balance load
- Mirrors data in case of failures
- Solves storage management challenges



1 - 29

ORACLE

## Interacting with an Oracle Database: Memory, Processes, and Storage



1 - 30

ORACLE

## Summary

In this lesson, you should have learned how to:

- List the major architectural components of Oracle Database
- Explain memory structures
- Describe background processes
- Correlate logical and physical storage structures
- Describe pluggable databases
- Describe ASM storage components

ORACLE

1 - 31