


Introduction to Data Definition Language in Oracle

HR Application Scenario



Lesson Agenda


- Database objects
- CREATE TABLE statement
- Data types
- Overview of constraints: NOT NULL, UNIQUE, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE statement
- DROP TABLE statement



3

Database Objects

Object	Description
Table	Is the basic unit of storage; composed of rows
View	Logically represents subsets of data from one or more tables
Sequence	Generates numeric values
Index	Improves the performance of some queries
Synonym	Gives alternative name to an object




4

Naming Rules for Tables and Columns

Ensure that the table names and column names:

- Begin with a letter
- Are 128 characters long
- Contain only A–Z, a–z, 0–9, _, \$, and #
- Do not duplicate the name of another object owned by the same user
- Are not Oracle server–reserved words



5

Lesson Agenda

- Database objects
- **CREATE TABLE statement**
- Data types
- Overview of constraints: NOT NULL, UNIQUE, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE statement
- DROP TABLE statement



6

CREATE TABLE Statement

- You must have:
 - The CREATE TABLE privilege
 - A storage area

```
CREATE TABLE [schema.]table  
    (column datatype [DEFAULT expr][, ...]);
```

- You specify:
 - The table name
 - The column name, column data type, and column size



7



Creating Tables

- Create the table:

```
CREATE TABLE dept  
    (deptno      NUMBER(2),  
     dname       VARCHAR2(14),  
     loc         VARCHAR2(13),  
     create_date DATE DEFAULT SYSDATE);
```

table DEPT created.

- Confirm table creation:

```
DESCRIBE dept
```

Name	Null	Type
DEPTNO		NUMBER(2)
DNAME		VARCHAR2(14)
LOC		VARCHAR2(13)
CREATE_DATE		DATE

8



Lesson Agenda

- Database objects
- CREATE TABLE statement
- Data types
- Overview of constraints: NOT NULL, UNIQUE, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE statement
- DROP TABLE statement



9

Data Types

Data Type	Description
VARCHAR2 (size)	Variable-length character data
CHAR (size)	Fixed-length character data
NUMBER (p, s)	Variable-length numeric data
DATE	Date and time values
LONG	Variable-length character data (up to 2 GB)
CLOB	Maximum size is (4 gigabytes - 1) * (DB_BLOCK_SIZE).
RAW and LONG RAW	Raw binary data
BLOB	Maximum size is (4 gigabytes - 1) * (DB_BLOCK_SIZE initialization parameter (8 TB to 128 TB)).
BFILE	Binary data stored in an external file (up to 4 GB)
ROWID	A base-64 number system representing the unique address of a row in its table

10

DEFAULT Option

- Specify a default value for a column in the CREATE TABLE statement.

```
... hire_date DATE DEFAULT SYSDATE, ...
```

- Literal values, expressions, or SQL functions are legal values.
- Another column's name or a pseudocolumn is an illegal value.
- The default data type must match the column data type.

```
CREATE TABLE hire_dates  
(id          NUMBER(8),  
  hire_date DATE DEFAULT SYSDATE);
```

```
Table HIRE_DATES created.
```

11



Lesson Agenda

- Database objects
- CREATE TABLE statement
- Data types
- Overview of constraints: NOT NULL, UNIQUE, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE statement
- DROP TABLE statement




12



Including Constraints

- Constraints enforce rules at the table level.
- Constraints ensure consistency and integrity of the database.
- The following constraint types are valid:
 - NOT NULL
 - UNIQUE
 - PRIMARY KEY
 - FOREIGN KEY
 - CHECK



13



Defining Constraints

- Syntax:

```
CREATE TABLE [schema.]table
  (column datatype [DEFAULT expr]
   [column_constraint],
   ...
   [table_constraint][,...]);
```

- Column-level constraint syntax:

```
column [CONSTRAINT constraint_name] constraint_type,
```

- Table-level constraint syntax:

```
column,...
  [CONSTRAINT constraint_name] constraint_type
  (column, ...),
```

14



Defining Constraints: Example

- Example of a column-level constraint:

```
CREATE TABLE employees(  
  employee_id NUMBER(6)  
  CONSTRAINT emp_emp_id_pk PRIMARY KEY,  
  first_name VARCHAR2(20),  
  ...);
```

- Example of a table-level constraint:

```
CREATE TABLE employees(  
  employee_id NUMBER(6),  
  first_name VARCHAR2(20),  
  ...  
  job_id VARCHAR2(10) NOT NULL,  
  CONSTRAINT emp_emp_id_pk  
    PRIMARY KEY (EMPLOYEE_ID));
```

15



NOT NULL Constraint

Ensures that null values are not permitted for the column:

EMPLOYEE_ID	FIRST_NAME	LAST_NAME	SALARY	COMMISSION_PCT	DEPARTMENT_ID	EMAIL	PHONE_NUMBER	HIRE_DATE
100	Steven	King	24000	(null)	90	SKING	515.123.4567	17-JUN-87
101	Neena	Kochhar	17000	(null)	90	NKOCHHAR	515.123.4568	21-SEP-89
102	Lex	De Haan	17000	(null)	90	LDEHAAN	515.123.4569	13-JAN-93
103	Alexander	Hunold	9000	(null)	60	AHUNOLD	590.423.4567	03-JAN-90
104	Bruce	Ernst	6000	(null)	60	BERNST	590.423.4568	21-MAY-91
107	Diana	Lorentz	4200	(null)	60	DLORENTZ	590.423.5567	07-FEB-99
124	Kevin	Mourgos	5800	(null)	50	KMOURGOS	650.121.5234	16-NOV-99
141	Trenna	Rajs	3500	(null)	50	TRAJS	650.121.8009	17-OCT-95
142	Curtis	Davies	3100	(null)	50	CDAVIES	650.121.2994	29-JAN-97
143	Randall	Matos	2600	(null)	50	RMATOS	650.121.2874	15-MAR-98
144	Peter	Vargas	2500	(null)	50	PVARGAS	650.121.2004	09-JUL-98
149	Eleni	Zlotkey	10500	0.2	80	EZLOTKEY	011.44.1344.429018	29-JAN-00
174	Ellen	Abel	11000	0.3	80	EABEL	011.44.1644.429267	11-MAY-96
176	Jonathon	Taylor	8600	0.2	80	JTAYLOR	011.44.1644.429265	24-MAR-98
178	Kimberely	Grant	7000	0.15	(null)	KGRANT	011.44.1644.429263	24-MAY-99
200	Jennifer	Whalen	4400	(null)	10	JWHALEN	515.123.4444	17-SEP-87
201	Michael	Hartstein	13000	(null)	20	MHARTSTE	515.123.5555	17-FEB-96
202	Pat	Fay	6000	(null)	20	PFAY	603.123.6666	17-AUG-97
205	Shelley	Higgins	12000	(null)	110	SHIGGINS	515.123.8080	07-JUN-94
206	William	Gietz	8300	(null)	110	WGIEZT	515.123.8181	07-JUN-94

NOT NULL constraint
(Primary Key enforces
NOT NULL constraint.)


NOT NULL
constraint

Absence of NOT NULL constraint (Any row
can contain a null value for this column.)

16



UNIQUE Constraint



17



UNIQUE Constraint


Define at either the table level or the column level:

```
CREATE TABLE employees(  
  employee_id      NUMBER(6),  
  last_name        VARCHAR2(25) NOT NULL,  
  email            VARCHAR2(25),  
  salary           NUMBER(8,2),  
  commission_pct   NUMBER(2,2),  
  hire_date        DATE NOT NULL,  
  ...  
  CONSTRAINT emp_email_uk UNIQUE(email));
```

18




PRIMARY KEY Constraint



19

FOREIGN KEY Constraint



20

FOREIGN KEY Constraint

Define at either the table level or the column level:

```
CREATE TABLE employees(  
    employee_id      NUMBER(6),  
    last_name        VARCHAR2(25) NOT NULL,  
    email            VARCHAR2(25),  
    salary           NUMBER(8,2),  
    commission_pct   NUMBER(2,2),  
    hire_date        DATE NOT NULL,  
    ...  
    department_id    NUMBER(4),  
    CONSTRAINT emp_dept_fk FOREIGN KEY (department_id)  
        REFERENCES departments(department_id),  
    CONSTRAINT emp_email_uk UNIQUE(email));
```

21



CHECK Constraint

- Defines a condition that each row must satisfy
- Cannot reference columns from other tables

```
..., salary      NUMBER(2)  
    CONSTRAINT emp_salary_min  
        CHECK (salary > 0),...
```



22



CREATE TABLE: Example

```
CREATE TABLE teach_emp (  
    empno      NUMBER(5) PRIMARY KEY,  
    ename      VARCHAR2(15) NOT NULL,  
    job        VARCHAR2(10),  
    mgr        NUMBER(5),  
    hiredate   DATE DEFAULT (sysdate),  
    photo      BLOB,  
    sal        NUMBER(7,2),  
    deptno     NUMBER(3) NOT NULL  
            CONSTRAINT admin_dept_fkey  
REFERENCES  
            departments(department_id));
```

23



Violating Constraints

Department 55 does not exist.

```
UPDATE employees  
SET   department_id = 55  
WHERE department_id = 110;
```



Error starting at line : 1 in command -

```
UPDATE employees  
SET   department_id = 55  
WHERE department_id = 110
```

Error report -

ORA-02291: integrity constraint (ORA1.EMP_DEPT_FK) violated - parent key not found

24



Violating Constraints

You cannot delete a row that contains a primary key that is used as a foreign key in another table.

```
DELETE FROM departments
WHERE department_id = 60;
```



```
Error starting at line : 1 in command -
delete from departments
where department id = 60
Error report -
ORA-02292: integrity constraint (ORAI.EMP_DEPT_FK) violated - child record found
```

25



Lesson Agenda

- Database objects
- Data types
- CREATE TABLE statement
- Overview of constraints: NOT NULL, UNIQUE, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE statement
- DROP TABLE statement



26



Creating a Table Using a Subquery

- Create a table and insert rows by combining the `CREATE TABLE` statement and the `AS subquery` option.

```
CREATE TABLE table  
    [(column, column...)]  
AS subquery;
```

- Match the number of specified columns to the number of subquery columns.
- Define columns with column names and default values.



27



Creating a Table Using a Subquery

```
CREATE TABLE    dept80  
AS  
    SELECT  employee_id, last_name,  
            salary*12 ANNSAL,  
            hire_date  
    FROM      employees  
    WHERE     department_id = 80;
```

Table DEPT80 created.

```
DESCRIBE dept80
```

Name	Null	Type
EMPLOYEE_ID		NUMBER(6)
LAST_NAME	NOT NULL	VARCHAR2(25)
ANNSAL		NUMBER
HIRE_DATE	NOT NULL	DATE

28



Lesson Agenda

- Database objects
- Data types
- CREATE TABLE statement
- Overview of constraints: NOT NULL, UNIQUE, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE statement
- DROP TABLE statement




29

ALTER TABLE Statement

Use the ALTER TABLE statement to:

- Add a new column
- Modify an existing column definition
- Define a default value for the new column
- Drop a column
- Rename a column
- Change table to read-only status



30

ALTER TABLE Statement

Use the ALTER TABLE statement to add, modify, or drop columns:

```
ALTER TABLE table
ADD          (column datatype [DEFAULT expr]
              [, column datatype]...);
```

```
ALTER TABLE table
MODIFY      (column datatype [DEFAULT expr]
              [, column datatype]...);
```

```
ALTER TABLE table
DROP (column [, column] ...);
```

31



Adding a Column

- You use the ADD clause to add columns:

```
ALTER TABLE dept80
ADD          (job_id VARCHAR2(9));
```

Table DEPT80 altered.

- The new column becomes the last column:

EMPLOYEE_ID	LAST_NAME	ANNSAL	HIRE_DATE	JOB_ID
1	149 Zlotkey	126000	29-JAN-16	(null)
2	174 Abel	132000	11-MAY-12	(null)
3	176 Taylor	103200	24-MAR-14	(null)
4	206 Gietz	99600	07-JUN-10	(null)



32



Modifying a Column

- You can change a column's data type, size, and default value.

```
ALTER TABLE dept80  
MODIFY (last_name VARCHAR2(30));
```

Table DEPT80 altered.

Size of the last_name
column is modified.

- A change to the default value of a column affects only subsequent insertions to the table.



33



Dropping a Column

Use the `DROP COLUMN` clause to drop columns that you no longer need from the table:

```
ALTER TABLE dept80  
DROP (job_id);
```

Table DEPT80 altered.

	EMPLOYEE_ID	LAST_NAME	ANNSAL	HIRE_DATE
1	149	Zlotkey	126000	29-JAN-16
2	174	Abe1	132000	11-MAY-12
3	176	Taylor	103200	24-MAR-14
4	206	Gietz	99600	07-JUN-10



34



Read-Only Tables

You can use the ALTER TABLE syntax to:

- Put a table in read-only mode, which prevents DDL or DML changes during table maintenance
- Put the table back into read/write mode

```
ALTER TABLE employees READ ONLY;  
  
-- perform table maintenance and then  
-- return table back to read/write mode  
  
ALTER TABLE employees READ WRITE;
```



35



Lesson Agenda

- Database objects
- Data types
- CREATE TABLE statement
- Overview of constraints: NOT NULL, UNIQUE, PRIMARY KEY, FOREIGN KEY, CHECK constraints
- Creating a table using a subquery
- ALTER TABLE statement
- DROP TABLE statement



36




Dropping a Table

- Moves a table to the recycle bin
- Removes the table and all its data entirely if the `PURGE` clause is specified
- Invalidates dependent objects and removes object privileges on the table

```
DROP TABLE dept80;
```

```
Table DEPT80 dropped.
```



37



Summary

In this lesson, you should have learned how to use the `CREATE TABLE`, `ALTER TABLE`, and `DROP TABLE` statement to create a table, modify a table and columns, and include constraints.

- Categorize the main database objects
- Review the table structure
- List the data types that are available for columns
- Create a simple table
- Explain how constraints are created at the time of table creation



38

