Interpretable Machine Learning

Hendra Bunyamin Maranatha Christian University October 4, 2023

Table of Content

Prerequisites

Pemahaman mengenai

- Perbedaan masalah regresi & klasifikasi.
- Model *machine learning* seperti linear regression.
- Statistika $\Rightarrow$ distribusi marginal.

Github repository

The repository

Table of Content

What is Interpretability?

- Interpretability is the degree to which a human can understand the cause of a decision (Miller, 2019).

- Interpretability is the degree to which a human can consistently predict the model's result (Kim et al., 2016).

The higher the interpretability of a machine learning model, the easier it is for someone to comprehend why certain decisions or predictions have been made.

- Christoph Molnar (a statistician, a machine learner)

A model is better interpretable than another model if its decisions are easier for a human to comprehend than decisions from the other model.

- Christoph Molnar

Taksonomi Teknik Interpretability†

- Berbagai taksonomi teknik *Interpretability* dapat dibaca di Molnar (2022).

- Kita berfokus pada taksonomi berdasarkan **model-specific** atau **model-agnostic**.

Teknik Interpretasi Model yang Spesifik (*Not Limited*)†

Algorithm	Linear	Interaction	Task
Linear regression	✓	✗	regr
Logistic regression	✗	✗	class
Decision trees	✗	✓	class, regr
RuleFit	✓	✓	class, regr
Naïve-Bayes	✗	✗	class
k-nearest neighbors	✗	✗	class, regr

Table of Content

Metode Model-Agnostic

- Memisahkan penjelasan dari model machine learning mempunyai beberapa keuntungan (Ribeiro et al., 2016).
- Keuntungan terbesar metode ini adalah **fleksibilitas**nya.
- Pengembang model machine learning bebas menggunakan model machine learning apa saja.

Aspek yang Diinginkan[†]

Aspek yang diinginkan dari penjelasan model-agnostic (Ribeiro et al., 2016) adalah

- Model flexibility,
- Explanation flexibility, and
- Representation flexibility.

High Level Look (Molnar, 2022)†



Table of Content

Global Methods

Global Methods

- Global methods menjelaskan **the average behavior** of a machine learning model.

Global Methods

- Global methods menjelaskan **the average behavior** of a machine learning model.
- Global methods $\approx$ **expected values** based on the distribution of the data.

Global Methods

- Global methods menjelaskan **the average behavior** of a machine learning model.
- Global methods $\approx$ **expected values** based on the distribution of the data.
- Contoh: $\hat{f}(x_1, x_2, x_3) =$ fungsi prediksi dengan 3 fitur.
  Untuk melihat efek x_1 pada fungsi prediksi, maka

$$\hat{g}(x_1) = \sum_{x_2} \sum_{x_3} \hat{f}(x_1, x_2, x_3).$$

Table of Content

Partial Dependence Plot (PDP)†

- PDP menunjukkan **efek marginal satu atau dua fitur** pada hasil prediksi sebuah model machine learning (Friedman, 2001).
- PDP dapat menunjukkan hubungan antara target dan fitur apakah linier, monotonik atau lebih kompleks.

Definisi Fungsi Partial Dependence†

Bila
x_S = fitur-fitur yang akan diplot oleh fungsi partial dependence,
X_C = fitur-fitur lainnya dalam model machine learning $\hat{f}$, maka

$$\hat{f}_S(x_S) = E_{X_C}\left[\hat{f}(x_S, X_C)\right] = \int \hat{f}(x_S, X_C)\, d\mathbb{P}(X_C).$$

Estimasi Fungsi Partial Dependence†

Fungsi partial $\hat{f}_S$ diestimasi dengan menghitung rata-rata di *train set* (metode Monte Carlo):

$$\hat{f}_S(x_S) = \frac{1}{n}\sum_{i=1}^{n}\hat{f}(x_S, x_C^{(i)}).$$

Estimasi Fungsi Partial Dependence†

Fungsi partial $\hat{f}_S$ diestimasi dengan menghitung rata-rata di *train set* (metode Monte Carlo):

$$\hat{f}_S(x_S) = \frac{1}{n}\sum_{i=1}^{n}\hat{f}(x_S, x_C^{(i)}).$$

Asumsi: fitur di C tidak berkorelasi dengan fitur di S.

Bagaimana dengan fitur kategorikal?†

- Untuk setiap nilai kategori, kita hitung nilai PDP dengan "memaksa" semua instance data mempunyai nilai kategori yang sama.

- Hitung rata-rata dari semua nilai PDP yang sudah diperoleh.

Contoh: #Sepeda yang dipinjam (1/3)

- Model machine learning, *random forest* dilatih.
- PDP plot $\Rightarrow$ visualisasi relationship yang model sudah pelajari.

Contoh: #Sepeda yang dipinjam (2/3)†



Contoh: #Sepeda yang dipinjam (3/3)†



Contoh: Prediksi Lead $\Rightarrow$ Customer[1†]

- Perusahaan edukasi (X Education) menjual online courses ke profesional industri.

- Perusahaan memasarkan course-course pada beberapa website dan search engines like Google.

[1]link dataset

Contoh: Prediksi Lead $\Rightarrow$ Customer

- Lead origin
- Lead source
- Do Not Email
- Do Not Call
- Converted
- TotalVisits
- Total Time Spent on Website
- Page Views Per Visit
- Last activity
- Country
- Specialization
- How did you hear about X Education
- What is your current occupation
- What matters most to you in choosing this course
- Search

PDP for Model Prediksi Converted & Total Time Spent on Website



PDP for Model Prediksi Converted & What is Your Occupation



Contoh: Kanker Serviks (Fernandes and Fernandes, 2017)

- Age in years
- Number of sexual partners
- First sexual intercourse (age in years)
- Number of pregnancies
- Smoking yes or no
- Smoking (in years)
- Hormonal contraceptives yes or no
- Hormonal contraceptives (in years)
- Intrauterine device yes or no (IUD)
- Number of years with an intrauterine device (IUD)
- Has patient ever had a sexually transmitted disease (STD) yes or no
- Number of STD diagnoses
- Time since first STD diagnosis
- Time since last STD diagnosis
- The biopsy results : "Healthy" or "Cancer". Target outcome.

Contoh: Kanker Serviks† (1/2)



Contoh: Kanker Serviks† (2/2)



Table of Content

Advantages†

- Perhitungan PDP *intuitif*.
- Dalam kasus tidak ada korelasi, interpretasi PDP jelas.
- PDP mudah untuk diimplementasi.
- Perhitungan PDPs mempunyai interpretasi *causal* (Zhao and Hastie, 2021).

Disadvantages†

- Jumlah maksimum fitur yang realistik dalam PDPs = 2.
- Beberapa PD plots tidak menampilkan distribusi dari fitur.
- Asumsi *independence* adalah masalah terbesar dengan PD plots $\Rightarrow$ *Accumulated Local Effect* (ALE) plots.
- Efek heterogeneous mungkin dapat tersembunyi $\Rightarrow$ kurva Individual Conditional Expectation (ICE).

Softwares

- R programming language: package `iml`, `pdp`, atau `DALEX`.
- Python programming language: `scikit-learn` atau library `PDPBox`

References I

Fernandes, Kelwin, C. J. and Fernandes, J. (2017). Cervical cancer (Risk Factors). UCI Machine Learning Repository. DOI: https://doi.org/10.24432/C5Z310.

Friedman, J. H. (2001). Greedy function approximation: a gradient boosting machine. *Annals of statistics*, pages 1189–1232.

Kim, B., Khanna, R., and Koyejo, O. O. (2016). Examples are not enough, learn to criticize! criticism for interpretability. *Advances in neural information processing systems*, 29.

Miller, T. (2019). Explanation in artificial intelligence: Insights from the social sciences. *Artificial intelligence*, 267:1–38.

Molnar, C. (2022). *Interpretable Machine Learning*. 2 edition.

Ribeiro, M. T., Singh, S., and Guestrin, C. (2016). Model-agnostic interpretability of machine learning. In *ICML Workshop on Human Interpretability in Machine Learning (WHI)*.

Zhao, Q. and Hastie, T. (2021). Causal interpretations of black-box models. *Journal of Business & Economic Statistics*, 39(1):272–281.