



# Smart Meter

SINGLE-PHASE/THREE-PHASE



## SIMPLE & EASY

LCD display, easy to set and check



## ENERGY EFFICIENT

Overall power consumption  $\leq 1$  W



## ACCURATE

Class 1 measurement accuracy

## TECHNICAL SPECIFICATIONS

| MODEL                               | DDSU666    | DTSU666                 | DTSU666 1.5(6)A<br>200A CT |
|-------------------------------------|------------|-------------------------|----------------------------|
| <b>GENERAL DATA</b>                 |            |                         |                            |
| Dimension (W*H*D) [mm]              | 36*85*66   | 72*100*85               | 72*100*85                  |
| Mounting type                       |            | DIN35 Rail              |                            |
| Weight (including cables) [kg]      | 1.2        | 1.5                     | 1.5                        |
| <b>POWER SUPPLY</b>                 |            |                         |                            |
| Power grid type                     | 1P2W       | 3P4W                    | 3P4W                       |
| Input voltage (phase voltage) [Vac] |            | 176 ~ 288               |                            |
| Power consumption [W]               | $\leq 0.8$ | $\leq 1$                | $\leq 1$                   |
| <b>MEASUREMENT RANGE</b>            |            |                         |                            |
| Line voltage [Vac]                  | /          | 304 ~ 499               | 304 ~ 499                  |
| Phase voltage [Vac]                 |            | 176 ~ 288               |                            |
| Current [A]                         | 0 ~ 60     | 0 ~ 80                  | 0 ~ 200                    |
| <b>MEASUREMENT ACCURACY</b>         |            |                         |                            |
| Voltage [%]                         |            | $\pm 0.5$               |                            |
| Current / Power / Energy [%]        |            | $\pm 1$                 |                            |
| Frequency [Hz]                      |            | $\pm 0.01$              |                            |
| <b>COMMUNICATION</b>                |            |                         |                            |
| Interface                           |            | RS485                   |                            |
| Baud rate [bps]                     |            | 9600                    |                            |
| <b>ENVIRONMENT</b>                  |            |                         |                            |
| Operating temperature range [°C]    |            | -25 ~ +55               |                            |
| Storage temperature range [°C]      |            | -40 ~ +70               |                            |
| Operating humidity [%RH]            |            | 5 ~ 95 (Non-condensing) |                            |
| <b>OTHERS</b>                       |            |                         |                            |

Accessories

/

/

3 CT 200A(1m)

