

ZBYN AD 2.1 机场地名代码和名称 Aerodrome location indicator(ICA0 / IATA) and name

ZBYN/TYN-太原/武宿 TAIYUAN/Wusu

ZBYN AD 2.2 机场地理位置和管理资料 Aerodrome geographical and administrative data

1	机场基准点坐标及其在机场的位置 ARP coordinates and site at AD	N37°44.9' E112°37.8' 1600m inwards THR13L
2	机场基准点与城市的位置关系 Direction and distance from city	156° GEO, 13.8km from city Wu Yi Square
3	机场标高、基准温度、低温均值 ELEV/Reference temperature/Mean low temperature	788.0 m/30.6°C(JUL)/-11.1°C(JAN)
4	机场标高位置的大地水准面波幅 Geoid undulation at AD ELEV PSN	
5	磁差（测量年份）及年变率 VAR(Year)/Annual change	5°53'W(2025)/-
6	机场管理部门、地址、电话、传真、AFS 地址、电子邮箱、网址 AD administration/Address/Telephone/Telefax/AFS/ E-mail/Website	Taiyuan International Airport Co.Ltd No.199, Taiyu Road, Taiyuan, Shanxi province, China Post code:030031 TEL:86-351-7012317 FAX:86-351-7287111 AFS:ZBYNZPZX
7	允许飞行种类 Types of traffic permitted(IFR/VFR)	IFR-VFR
8	机场性质/飞行区指标 Military or civil airport/Reference code	CIVIL/4E
9	备注 Remarks	Nil

ZBYN AD 2.3 工作时间 Operational hours

1	机场开放时间 AD Operational hours	H24
2	海关和移民 Customs and immigration	H24
3	卫生健康部门 Health and sanitation	H24
4	航空情报服务讲解室 AIS Briefing Office	H24
5	空中交通服务报告室 ATS Reporting Office	H24
6	气象服务讲解室 MET Briefing Office	H24

7	空中交通服务 Air Traffic Service	H24
8	加油服务 Fuelling	H24
9	地勤服务 Handling	H24
10	安保服务 Security	H24
11	除冰服务 De-icing	H24
12	备注 Remarks	Nil

ZBYN AD 2.4 地勤服务和设施 Handling services and facilities

1	货物装卸设施 Cargo-handling facilities	Platform lift, baggage transporter, baggage trailer, container trailer, luggage towing vehicle
2	燃油牌号 Fuel types	Jet Fuel No.3
3	滑油牌号 Oil types	Nil
4	加油设施/能力 Fuelling facilities & Capacity	Refueling truck(18,500L, 20,000L and 35,000L): 15L/s
5	除冰设施 De-icing facilities	16 de-icers, de-icing fluid(FCY-1A, FCY-2, FCY9311)
6	过站航空器机库 Hangar space for visiting aircraft	Nil
7	过站航空器的维修设施 Repair facilities for visiting aircraft	Line maintenance available for B737-700/800/900ER(CFM56), A319/A320/A321, ARJ21-700, B787(HNA Technic), A330(HNA Technic), B737-8(LEAP-1B)
8	备注 Remarks	Ground power unit, ground air supply unit, passenger boarding stairs, potable water supply vehicle, sewage vehicle, aircraft tow-tractor, bridge power equipment and air conditioner, follow-me vehicle, lift truck for disabled

ZBYN AD 2.5 旅客设施 Passenger facilities

1	宾馆 Hotels	In the city
2	餐饮 Restaurants	At AD and in the city
3	交通工具 Transportation	Buses, taxis, subway

4	医疗设施 Medical facilities	First-aid at AD, hospital in the city
5	银行和邮局 Bank and Post Office	At AD
6	旅行社 Tourist Office	Nil
7	备注 Remarks	Nil

ZBYN AD 2.6 援救与消防服务 Rescue and fire fighting services

1	机场消防等级 AD category for fire fighting	CAT 9
2	援救设备 Rescue equipment	Fire fighting facilities: Primary foam tender, heavy-load foam tender, rapid intervention vehicle, heavy-load water tank truck, illumination truck, command car, dry-chemical tender, disassembly rescue truck and logistic truck. Rescue equipment: Hydraulic pressure scissor, toothless cutter, life-saving air-cushion, plasma cutting equipment, fire hook, positive smoke exhauster, infrared thermometer, combustible gas detector.
3	搬移受损航空器的能力 Capability for removal of disabled aircraft	For A380 and below(except landing gear totally damaged), landing gear trailer, air cushion, tethered hoisting equipment, traction rack, mobile surface operation devices, crosstie, steel plate
4	备注 Remarks	Nil

ZBYN AD 2.7 可用季节- 扫雪 Seasonal availability-clearing

1	可用季节及扫雪设备类型 Seasonal availability/Types of clearing equipment	All seasons Snow blowers, snow ploughs, snow slinger
2	扫雪顺序 Clearance priorities	RWY, TWY, Apron
3	备注 Remarks	Nil

ZBYN AD 2.8 停机坪、滑行道及校正位置数据 Aprons, taxiways and check locations data

1	停机坪道面和强度 Apron surface and strength	道面 Surface	CONC
		强度 Strength	PCR 960/R/B/W/T : Stands Nr. 201-208 PCR 950/R/B/W/T : Stands Nr. 101-110, 200 PCR 910/R/A/W/T : Stands Nr. 209-212, 301L, 301R, 301-303, 302L, 302R PCR 900/R/A/W/T : Stands Nr. 401-403 PCR 890/R/A/W/T : Stands Nr. 404-412, 411L, 411R, 412L, 412R, 413L

			PCR 890/R/B/W/T : Stands Nr.304, 305, 307, 308, 315-318, 413, 414, 413R, 414L, 414R PCR 350/R/C/W/T : Stands Nr. 309-314
2	滑行道宽度、道面和强度 Taxiway width, surface and strength	宽度 Width	70m : H2-H5 61.6m : H1, H6 54m : B1, B2 39m : A7, G7, T6 38m : E4, EL, G2, G4, G6, K2, K3, K6, K11, K12, T3-T5 34m : B3-B5 31m : A1 30.5m : G1, K1, K15 29.5m : E7 28.5m : A2, A4, A6, A8 27m : A3, A5 23m : A, B0, E, G, G3, G5, K, K4, K5, K7-K10, M1, M2, T7
		道面 Surface	ASPH : A3, A5, A7, E4(FM north to south 0m-59.5m), E7(FM north to south 0m-83.5m), EL CONC : A, A1, A2, A4, A6, A8, B0-B5, D, E(FM west to east 634m-2336m), E4(FM north to south 59.5m-146m), E7(FM north to south 83.5m-157.5m), G, G1-G7, H, H1-H6, K, K1-K12, K15, M1, M2, T3-T7
		强度 Strength	PCR 3680/F/A/X/T : E7(FM north to south 0m-83.5m) PCR 1950/F/C/X/T : A5 PCR 1920/F/C/X/T : A7 PCR 1750/F/C/X/T : A3 PCR 1190/F/C/X/T : E4(FM north to south 0m-59.5m), EL PCR 1180/R/A/W/T : A1 PCR 1120/R/B/W/T : B2 PCR 1100/R/A/W/T : A(FM west to east 3200m-3600m) PCR 1100/R/B/W/T : B1 PCR 1070/R/A/W/T : B3, B4 PCR 1060/R/A/W/T : B5 PCR 1000/R/A/W/T : A8 PCR 990/R/A/W/T : A2 PCR 980/R/B/W/T : A(FM west to east 2300m-3200m) PCR 950/R/A/W/T : E7(FM north to south 83.5m-157.5m), T7 PCR 930/R/A/W/T : G3, G5, K4, K5, K7-K10 PCR 920/R/A/W/T : E(FM west to east 634m-2336m), E4(FM north to south 59.5m-146m), G, G1, G2, G4, G6, G7, H, H1-H6, K, K1-K3, K6, K11, K12, K15, T3-T6 PCR 900/R/B/W/T : D PCR 890/R/B/W/T : B0(BTN Stands Nr.304, 305, 307, 308 and 315-318) PCR 860/R/B/W/T : A(FM west to east 0m-2300m)

			PCR 770/R/A/W/T : M1, M2 PCR 660/R/B/W/T : A4, A6 PCR 350/R/C/W/T : B0(BTN Stands Nr.309-314)
3	高度表校正点的位置及其标高 ACL location and elevation	Nil	
4	VOR 校正点 VOR checkpoints	Nil	
5	INS 校正点 INS checkpoints	Nil	
6	备注 Remarks	Nil	

ZBYN AD 2.9 地面活动引导和管制系统与标识

Surface movement guidance and control system and markings

1	航空器机位号码标记牌、滑行道引导线、航空器目视停靠引导系统的使用 Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands	Taxiing guidance signs at all intersections of TWY and RWY. Taxiing guidance signs at all holding positions. Aircraft stand identification sign boards at all stands. Guide lines at all TWYs. Guide lines at all aprons. Marshalling assistance for all aircraft stands.	
2	跑道和滑行道标志及灯光 RWY and TWY marking and LGT	跑道标志 RWY markings	THR, RWY designation, edge line, RWY center line, TDZ, aiming point, Center circle(13R/31L)
		跑道灯光 RWY lights	RTHL, WBAR, REDL, RCLL, RTZL(31L), RENL
		滑行道标志 TWY markings	Edge line, center line, enhanced TWY center line, TWY shoulder marking, No-entry(G3, G5, K4, K5, K7-K10), RWY holding position, intermediate holding position
		滑行道灯光 TWY lights	Edge line lights, center line lights(E, E4, E7, EL, G, G1-G7, H, H1-H6, K, K1-K12, K15, M1, M2, T3-T7), No-entry bar(G3, G5, K4, K5, K7-K10), RETILs, intermediate holding position lights
3	停止排灯和跑道警戒灯 Stop bars and runway guard lights	Runway guard lights: G1, G2, G4, G6, G7, K1-K3, K6, K11, K12, K15	
4	其它跑道保护措施 Other runway protection measures	Nil	
5	备注 Remarks	RWY turn around marking : RWY13L/31R G(BTN G1&G2): green and yellow center line lights G(BTN G2&T7): green center line lights	

ZBYN AD 2.10 机场障碍物 Aerodrome obstacles

半径 15 千米内主要障碍物 (相对 13L/31R 跑道中心)					
Obstacles within 15km of the center of RWY13L/31R					
障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志, 灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
1	2	3	4	5	6
STACK 001	STACK	012/787	810.9		
MT 002	MT	017/9000	1032.7		
MT 003	MT	025/11250	1154.1		
Control TWR 004	Control TWR	035/658	855.9	LGT	RWY13L/31R RNAV ILS/DME z, ILS/DME y final approach
BLDG 005	BLDG	037/4148	885.1	LGT	
MT 006	MT	044/14200	1371.6		
BLDG 007	BLDG	108/6318	859.3	LGT	
BLDG 008	BLDG	112/3570	836.2	LGT	
Antenna 009	Antenna	119/3954	840.0		
BLDG 010	BLDG	119/7111	884.9	LGT	
BLDG 011	BLDG	128/6807	868.6		RWY13L take-off path
TRANSMISSION _LINE 012	TRANSMISSION _LINE	129/5964	825.9	LGT	
Antenna 013	Antenna	129/12837	921.1	LGT	
BLDG 014	BLDG	131/9448	900.0		RWY13R take-off path

半径 15 千米内主要障碍物 (相对 13L/31R 跑道中心)

Obstacles within 15km of the center of RWY13L/31R

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志, 灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
Antenna 015	Antenna	133/12664	859.3	LGT	
Antenna 016	Antenna	136/4541	829.8		RWY13R take-off path
BLDG 017	BLDG	136/5500	840.5		
Antenna 018	Antenna	137/4464	819.8		RWY13R take-off path
BLDG 019	BLDG	137/5371	840.4		RWY13R take-off path
BLDG 020	BLDG	138/7840	876.3		RWY13R take-off path
Antenna 021	Antenna	139/1271	792.5	LGT	
BLDG 022	BLDG	260/4937	873.7	LGT	
Antenna 023	Antenna	263/5931	839.2	LGT	
BLDG 024	BLDG	282/5215	858.0		
BLDG 025	BLDG	287/4925	850.0	LGT	
Antenna 026	Antenna	308/1494	792.4	LGT	
BLDG 027	BLDG	310/7148	859.6		
BLDG 028	BLDG	311/11685	928.9	LGT	RWY13L/13R GP INOP final approach
BLDG 029	BLDG	312/4319	821.2	LGT	RWY31R take-off path
BLDG 030	BLDG	317/3572	803.0	LGT	RWY31R take-off path

半径 15 千米内主要障碍物 (相对 13L/31R 跑道中心)

Obstacles within 15km of the center of RWY13L/31R

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志, 灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
Antenna 031	Antenna	317/3588	804.3	LGT	RWY31R take-off path
BLDG 032	BLDG	317/7051	873.8	LGT	RWY31R take-off path
BLDG 033	BLDG	317/7280	878.8		RWY31R take-off path
BLDG 034	BLDG	323/10696	991.7		RWY13L/13R VOR/DME final approach
BLDG 035	BLDG	324/4305	833.8		
BLDG 036	BLDG	324/10667	846.1		
BLDG 037	BLDG	326/6560	850.3	LGT	
BLDG 038	BLDG	329/5573	845.3	LGT	
BLDG 039	BLDG	332/10674	1012.0	LGT	
Control TWR 040	Control TWR	339/1132	825.4	LGT	
BLDG 041	BLDG	341/4551	860.1	LGT	
BLDG 042	BLDG	353/5711	894.5	LGT	
BLDG 043	BLDG	360/4801	880.8		

半径 15 千米-50 千米内主要障碍物 (相对 13L/31R 跑道中心)

Obstacles within 15 to 50km of the center of RWY13L/31R

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志、灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
MT 044	MT	010/20200	1123		
MT 045	MT	034/22400	1637		
WINDMILL 046	WINDMILL	035/28229	1938		Sector
MT 047	MT	035/38000	1749		
MT 048	MT	037/15900	1392		
MT 049	MT	051/41800	1715		
MT 050	MT	123/33100	1165		
MT 051	MT	124/48500	1584		
MT 052	MT	130/32000	1150		
Antenna 053	Antenna	131/20035	958		RWY31L/31R ILS/DME y and VOR/DME intermediate approach
Trees 054	Trees	133/30687	1236		RWY31L/31R VOR/DME initial approach
MT 055	MT	134/27400	1061		
Trees 056	Trees	135/32259	1302		RWY31L/31R ILS/DME y initial approach
Trees 057	Trees	136/28930	1142		
MT 058	MT	140/36600	1356		
MT 059	MT	142/44300	1631		

半径 15 千米-50 千米内主要障碍物 (相对 13L/31R 跑道中心)

Obstacles within 15 to 50km of the center of RWY13L/31R

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志、灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
MT 060	MT	143/28200	996		
MT 061	MT	259/43000	1297		
MT 062	MT	265/23400	1149		
MT 063	MT	273/44400	1723		
MT 064	MT	275/29000	1073		
MT 065	MT	275/52806	2160		Sector
TRANSMISSION _LINE 066	TRANSMISSION_L INE	284/27274	1890		RWY13L/13R/31L/31R conventional arrival
Trees 067	Trees	300/25523	1411		RWY13R ILS/DME y and VOR/DME intermediate approach
Trees 068	Trees	301/27608	1521		RWY13L/13R ILS/DME y and VOR/DME initial approach
MT 069	MT	302/18600	1176		
MT 070	MT	302/31100	1449		
Antenna 071	Antenna	303/24466	1376		RWY13L ILS/DME y and VOR/DME intermediate approach; RWY13R VOR/DME intermediate approach
Antenna 072	Antenna	304/27512	1470		RWY13L/13R ILS/DME y initial approach
MT 073	MT	304/28700	1490		

半径 15 千米-50 千米内主要障碍物 (相对 13L/31R 跑道中心)

Obstacles within 15 to 50km of the center of RWY13L/31R

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志、灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
MT 074	MT	311/18700	1078		
Antenna 075	Antenna	311/27424	1468		RWY13L VOR/DME initial approach
STACK 076	STACK	314/17500	974		
MT 077	MT	325/38300	1585		
MT 078	MT	327/41200	1677		
MT 079	MT	327/45100	1702		
BLDG 080	BLDG	328/15200	1016	LGT	
MT 081	MT	337/42400	1699		
Trees 082	Trees	347/45744	1627		RWY13L/13R/31L/31R conventional arrival
MT 083	MT	350/46500	1712		

Remarks:

ZBYN AD 2.11 提供的气象情报、气象观测和报告

Meteorological information provided & meteorological observations and reports

提供的气象情报

Meteorological information provided

1	相关气象台的名称 Associated MET Office	Shanxi MET office of ATMB
2	气象服务时间、服务时间以外的责任气象台 Hours of service/MET Office outside hours	H24
3	负责编发 TAF 的气象台、有效时段、发布间隔 Office responsible for TAF preparation/Periods of	Shanxi MET office of ATMB;24h;6h

	validity/Interval of issuance	
4	趋势预报及发布间隔 Trend forecast/Interval of issuance	trend 30min
5	所提供的讲解或咨询服务 Briefing/Consultation provided	Briefing provided: P, T
6	飞行文件及其使用语言 Flight documentation/Language(s) used	chart, International MET Codes, Abbreviated Plain Language Text;Ch, En
7	讲解或咨询服务时可利用的图表和其它信息 Charts and other information available for briefing or consultation	Synoptic charts, significant weather charts, upper W/T charts, satellite and radar material, AWOS real-time data
8	提供气象情报的辅助设备 Supplementary equipment available for providing information	FAX, MET Service Terminal, MET radar echo chart, satellite cloud chart, AWOS data displayer
9	提供气象情报的空中交通服务单位 ATS units provided with information	ACC, APP, TWR
10	其他信息 Additional information	TEL: 86-351-7287872
气象观测和报告 Meteorological observations and reports		
1	机场观测类型与频率、自动观测设备 Type & frequency of observation /Automatic observation equipment	Half hourly plus special observation/Yes
2	气象报告类型及所包含的补充资料 Type of MET Report/Supplementary information included	METAR, SPECI
3	观测系统及安装位置 Observation system/Site(s)	RVR EQPT A: 112m SW of RCL, 360m inward THR13L; B: 95m SW of RCL, 1850m inward THR31R; C: 112m SW of RCL, 352m inward THR31R; D: 116m S of RCL, 305m inward THR13R; E: 116m S of RCL, 1750m inward THR31L; F: 116m S of RCL, 325m inward THR31L. SFC wind sensors 13L: 118m SW of RCL, 360m inward THR13L; RWY center: 105m SW of RCL, 1850m inward THR31R; 31R: 118m SW of RCL, 382m inward THR31R; 13R: 120m S of RCL, 315m inward THR13R; RWY center: 120m S of RCL, 1740m inward THR31L; 31L: 120m S of RCL, 335m inward THR31L. Ceilometer 13L: 118m SW of RCL, 354m inward THR13L;

		31R: 118m SW of RCL, 352m inward THR31R; 13R: 120m S of RCL, 340m inward THR13R; 31L: 20m N of RCL, 940m on the extension of THR31L.
4	观测系统的工作时间 Hours of operation for meteorological observation system	H24
5	气候资料 Climatological information	Climatological tables AVBL
6	其他信息 Additional information	Nil

ZBYN AD 2.12 跑道物理特征 Runway physical characteristics

跑道号码 RWY Designator	真方位和 磁方位 TRUE & MAG BRG	跑道长宽 Dimensions of RWY(m)	跑道强度、跑道和停 止道道面 RWY strength/ Surface of RWY /SWY	跑道入口坐标、 跑道末端坐标、 跑道入口大地水 准面波幅 THR coordinates & RWY end coordinates & THR geoid undulation	跑道入口标高和 精密进近跑道接 地带最高标高 THR elevation & highest elevation of TDZ of precision APP RWY	跑道和停止道坡 度 Slope of RWY/SWY
1	2	3	4	5	6	7
13L	126.99° GEO 133° MAG	3600×45	PCR 740/R/A/W/T CONC/CONC	Nil	THR 775.4m	0.47%(300m)/0.14%(700m)/0.26%(500m)/0.35%(1700m)/0.2%(400m)
31R	307.01° GEO 313° MAG	3600×45	PCR 740/R/A/W/T CONC/ASPH	Nil	THR 785.8m	-0.2%(400m)/-0.35%(1700m)/-0.26%(500m)/-0.14%(700m)/-0.47%(300m)
13R	127.00° GEO 133° MAG	3600×45	(0-800m) PCR 970/R/A/W/T (800-2800m) PCR 820/R/A/W/T (2800-3600m) PCR 970/R/A/W/T CONC/-	Nil	THR 778.3m	0.34%(2238m)/0.25%(60m)/0.16%(1302m)

跑道号码 RWY Designator	真方位和 磁方位 TRUE & MAG BRG	跑道长宽 Dimensions of RWY(m)	跑道强度、跑道和停 止道道面 RWY strength/ Surface of RWY /SWY	跑道入口坐标、 跑道末端坐标、 跑道入口大地水 准面波幅 THR coordinates & RWY end coordinates & THR geoid undulation	跑道入口标高和 精密进近跑道接 地带最高标高 THR elevation & highest elevation of TDZ of precision APP RWY	跑道和停止道坡 度 Slope of RWY/SWY
1	2	3	4	5	6	7
31L	307.02° GEO 313° MAG	3600×45	(0-800m) PCR 970/R/A/W/T (800-2800m) PCR 820/R/A/W/T (2800-3600m) PCR 970/R/A/W/T CONC/-	Nil	THR 788.0m	-0.16%(1302m)/- 0.25%(60m)/-0.3 4%(2238m)
跑道号码 RWY Designator	停止道长宽 SWY dimensions (m)	净空道长宽 CWY dimensions (m)	升降带长宽 Strip dimensions (m)	跑道端安全区 长宽 RESA dimensions (m)	拦阻系统的 位置及描述 Location& Description of arresting system	无障碍物区 OFZ
1	8	9	10	11	12	13
13L	60×75	Nil	3720×280	240×90	Nil	-
31R	60×75	Nil	3720×280	240×90	Nil	-
13R	Nil	Nil	3720×280	240×90	Nil	-
31L	Nil	Nil	3720×280	240×90	Nil	-
Remarks: 13L/31R: RWY shoulder: 15m on each side. 13R/31L: RWY shoulder: 7.5m on each side; RWY13R/31L grooved: 6mm(upper width)×4mm(lower width)×6mm(depth). Distance between RCL of RWY13R/31L and RWY13L/31R is 490m, RWY13R THR is 1350m east of RWY13L THR. RWY13R/31L center circle marking: 1800m of THR13R and THR31L respectively.						

ZBYN AD 2.13 公布距离 Declared distances

跑道号码 RWY Designator	可用起飞滑跑距离 TORA(m)	可用起飞距离 TODA(m)	可用加速停止距离 ASDA(m)	可用着陆距离 LDA(m)	备注 Remarks
1	2	3	4	5	6
13L	3600	3600	3660	3600	Nil
13L	3350	3350	3410	-	FM A7
31R	3600	3600	3660	3600	Nil

跑道号码 RWY Designator	可用起飞滑跑距离 TORA(m)	可用起飞距离 TODA(m)	可用加速停止距离 ASDA(m)	可用着陆距离 LDA(m)	备注 Remarks
31R	3150	3150	3210	-	FM A2
13R	3600	3600	3600	3600	Nil
13R	3360	3360	3360	-	FM K12
31L	3600	3600	3600	3600	Nil
31L	3360	3360	3360	-	FM K2

ZBYN AD 2.14 进近和跑道灯光 Approach and runway lighting

跑道 号码 RWY Desig nator	进近灯 类型、长 度、强度 APCH LGT type/ LEN/ /INTST	入口灯 颜色、翼 排灯 THR LGT colour/ WBAR	目视进近坡度 指示系统类 型、位置、仰 角、跑道入口 最低眼高 Type of VASIS/Position /Angle/MEHT	接地 带 灯长 度 TDZ LGT LEN	跑道中线灯长度、 间隔、颜色、强度 RWY center line LGT LEN/Spacing /Colour/INTST	跑道边灯长度、间 隔、颜色、强度 RWY edge LGT LEN/Spacing /Colour/INTST	跑道末端灯 颜色 RWY end LGT colour	停止道灯长 度、颜色 SWY LGT LEN /Colour
1	2	3	4	5	6	7	8	9
13L	PALS CAT I SFL 900 m LIH	GREEN Yes	PAPI LEFT 360m inward THR13L 3° 18.2m	Nil	3600 m spacing 30m 0-2700m, WHITE 2700-3300m, RED/WHITE 3300-3600m, RED VRB LIH	3600 m spacing 60m 0-3000m, WHITE 3000-3600m, YELLOW VRB LIH	RED	Nil
31R	PALS CAT I SFL 720 m LIH	GREEN Yes	PAPI LEFT 485m inward THR31R 3° 21.4m	Nil	3600 m spacing 30m 0-2700m, WHITE 2700-3300m, RED/WHITE 3300-3600m, RED VRB LIH	3600 m spacing 60m 0-3000m, WHITE 3000-3600m, YELLOW VRB LIH	RED	Nil
13R	PALS CAT I SFL 900 m LIH	GREEN Yes	PAPI LEFT 415m inward THR13R 3° 21.1m	Nil	3600 m spacing 15m 0-2700m, WHITE 2700-3300m, RED/WHITE 3300-3600m, RED VRB LIH	3600 m spacing 60m 0-3000m, WHITE 3000-3600m, YELLOW VRB LIH	RED	Nil

跑道 号码 RWY Designator	进近灯 类型、长 度、强度 APCH LGT type/ LEN/ /INTST	入口灯 颜色、翼 排灯 THR LGT colour/ WBAR	目视进近坡度 指示系统类 型、位置、仰 角、跑道入口 最低眼高 Type of VASIS/Position /Angle/MEHT	接地 带 灯长 度 TDZ LGT LEN	跑道中线灯长度、 间隔、颜色、强度 RWY center line LGT LEN/Spacing /Colour/INTST	跑道边灯长度、间 隔、颜色、强度 RWY edge LGT LEN/Spacing /Colour/INTST	跑道末端灯 颜色 RWY end LGT colour	停止道灯长 度、颜色 SWY LGT LEN /Colour
31L	PALS CAT III SFL 900 m LIH	GREEN Yes	PAPI LEFT 465m inward THR31L 3° 21.3m	900 m	3600 m spacing 15m 0-2700m, WHITE 2700-3300m, RED/WHITE 3300-3600m, RED VRB LIH	3600 m spacing 60m 0-3000m, WHITE 3000-3600m, YELLOW VRB LIH	RED	Nil
Remarks: RWY13L、RWY31R APCH LGT:U/S due to construction RWY13L、RWY31R runway lighting:U/S due to construction								

ZBYN AD 2.15 其它灯光,备份电源 Other lighting, secondary power supply

1	机场灯标或识别灯标位置、特性和工作时间 ABN/IBN location, characteristics and hours of operation	Nil
2	着陆方向标和风向标位置和灯光 LDI/ WDI location and LGT	WDI: 13L:122m S of RCL, 310m inward THR13L, LGTD; 31R:122m S of RCL, 330m inward THR31R, LGTD; 13R:92.5m N of RCL, 410m inward THR13R, LGTD; 31L:92.5m S of RCL, 477m inward THR31L, LGTD. WDI of RWY13L/31R U/S due to construction
3	滑行道边灯和滑行道中线灯 TWY edge and center line lighting	TWYs G, G1-G7, K1-K12, K15: green and yellow center line lights TWYs E, E4, E7, EL, G, H, H1-H6, K, M1, M2, T3-T7: green center line lights All TWYs: blue edge line lights
4	备份电源及转换时间 Secondary power supply/Switch-over time	Dual feed, diesel engine driven generator/15s, UPS/1s
5	备注 Remarks	Nil

ZBYN AD 2.16 直升机着陆区域 Helicopter landing area

1	TLOF 坐标或 FATO 入口坐标及大地水准 面波幅 Coordinates TLOF or THR of FATO, Geoid undulation	Nil
---	--	-----

2	TLOF 和 (或) FATO 标高 TLOF and/or FATO elevation	Nil
3	TLOF 和 FATO 区域范围、道面、强度和标志 TLOF and FATO area dimensions,surface, strength, marking	Nil
4	FATO 的真方位和磁方位 True and MAG BRG of FATO	Nil
5	公布距离 Declared distance available	Nil
6	进近灯光和 FATO 灯光 APP and FATO lighting	Nil
7	备注 Remarks	Nil

ZBYN AD 2.17 空中交通服务空域 ATS airspace

空域名称和水平范围 Designation and lateral limits		垂直范围 Vertical limits	空域分类 Airspace class	空中交通服务单位 呼号和使用语言 ATS unit callsign Language	工作时间 Hours of applicability	备注 Remarks
1	2	3	4	5	6	7
Taiyuan tower control area	The area enclosed by the following four points:N37°44'47" E112°22'20"-N37°56'33" " E112°32'45"-N37°44'52" " E112°52'26"-N37°33'06" "E112°42'01"	SFC-1500m(inclusive)(QNH)				
Fuel dumping area	N3736E11303-N3720E11328-N3712E11321-N3728E11258-N3736E11303	Above 4000m				
Altimeter setting region and TL/TA	Same as Taiyuan APP airspace boundaries	TL 3600m TA 3000m 3300m(QNH≥1031hPa) 2700m(QNH≤979hPa)				

ZBYN AD 2.18 空中交通服务通信设施 ATS communication facilities

服务名称 Service designation	呼号 Callsign	频率 Frequency (MHz)	卫星话音通信 号码 SATVOICE number	登录地址 Logon address	工作时间 Hours of operation	备注 Remarks
1	2	3	4	5	6	7
ATIS		126.45			H24	
APP	Taiyuan Approach	APP01:119.2 (125.55)			H24	
		APP02:119.55 (125.55)			H24	
TWR	Taiyuan Tower	118.25 (124.35)			H24	
GND	Taiyuan Ground	121.8			H24	
	Taiyuan Delivery	121.925			HO	DCL available contact Taiyuan GND when U/S
APN	Taiyuan Apron	121.675			H24	
EMG		121.5			H24	

ZBYN AD 2.19 无线电导航和着陆设施 Radio navigation and landing aids

设施名称及类型、磁差、支持运行类别、 Name and type of aid, VAR, Type of supported OPS, Declination of VOR/ILS	识别 ID	频率、波道 Frequency/ Channel number	工作 时间 Hours of operation	发射天线坐标 及相对位置 Coordinates of transmitting antenna/ Position	DME 发射 天线标高 Elevation of DME transmitting antenna	备注 Remarks
1	2	3	4	5	6	7
Taiyuan VOR/DME	TYN	113.1 MHz CH 78X	H24	N37°45.2' E112°37.0' 301°MAG/1523m FM ARP	787 m	For DME: beyond 38NM on R061° for STAR U/S; beyond 35.7NM on R080° for SID U/S; beyond 36NM on R238° for STAR U/S; beyond 32NM on R356° for SID and STAR U/S.

设施名称及类型、磁差、支持运行类别、VOR/ILS 磁偏角 Name and type of aid, VAR, Type of supported OPS, Declination of VOR/ILS	识别 ID	频率、波道 Frequency/ Channel number	工作 时间 Hours of operation	发射天线坐标 及相对位置 Coordinates of transmitting antenna/ Position	DME 发射 天线标高 Elevation of DME transmitting antenna	备注 Remarks
LOC 13L ILS CAT I	ICC	110.9 MHz		131°MAG/255m FM RWY13L end		Beyond 10° rightside of front course U/S, beyond 20NM of front course U/S. U/S
GP 13L		330.8 MHz		122m W of RCL, 310m inside THR13L		Angle 3°, RDH 15 m U/S
DME 13L	ICC	CH 46X (110.9 MHz)				Co-located with GP 13L U/S
LOC 31R ILS CAT I	IBB	109.3 MHz		311°MAG/260m FM RWY31R end		Beyond 22NM of front course U/S. U/S
GP 31R		332.0 MHz		122m W of RCL, 331m inside THR31R		Angle 3°, RDH 15 m U/S
DME 31R	IBB	CH 30X (109.3 MHz)				Co-located with GP 31R U/S
LOC 13R ILS CAT I	INP	109.7 MHz		133°MAG/285m FM RWY13R end		Beyond -10° of front course U/S, beyond 21NM of front course U/S
GP 13R		333.2 MHz		125m S of RCL, 291m inside THR13R		Angle 3°, RDH 15.8 m
DME 13R	INP	CH 34X (109.7 MHz)			779m	Co-located with GP 13R
IM 31L		75 MHz		On the RWY extension line, 345m SE of THR31L		
LOC 31L ILS CAT III	IMK	108.55 MHz		313°MAG/285m FM RWY31L end		Beyond 19NM of front course U/S, beyond ±33° of front course U/S; CAT I operation only

设施名称及类型、磁差、支持运行类别、VOR/ILS 磁偏角 Name and type of aid, VAR, Type of supported OPS, Declination of VOR/ILS	识别 ID	频率、波道 Frequency/ Channel number	工作 时间 Hours of operation	发射天线坐标及相对位置 Coordinates of transmitting antenna/ Position	DME 发射 天线标高 Elevation of DME transmitting antenna	备注 Remarks
GP 31L		329.75 MHz		125m S of RCL, 318m inside THR31L		Angle 3°, RDH 15.7 m
DME 31L	IMK	CH 22Y (108.55 MHz)			787m	Co-located with GP 31L

ZBYN AD 2.20 本场规定

ZBYN AD 2.20 Local aerodrome regulations

1. 机场使用规定

1. Airport operations regulations

1.1 未安装二次雷达应答机或二次雷达应答机故障的航空器，需事先获得空中交通管制部门的批准；

1.1 Take off/landing of aircraft without SSR transponder or with SSR transponder failure need prior approval from ATC;

1.2 所有技术试飞需事先申请，并在得到空中交通管制部门批准后方可进行。

1.2 Each and every technical test flight shall be filed in advance and conducted only after clearance has been obtained from ATC.

1.3 太原机场塔台数字化放行（DCL）全天提供服务。出港航空器可通过数据链通信和人工语音播发两种方式取得放行许可。通过数据链通信电文发布的管制许可和指令，以数据链通信方式回复，无需使用语音方式复诵或确认。如不具备相应功能或对放行许可存在疑义，向塔台管制员语音确认。

1.3 DCL is available for 24 hours. Departure aircraft can obtain ATC clearance via data link or voice broadcast. Data link issued ATC clearance and instruction shall be replied, no need to repeat or confirm by voice. If there is any doubt about the clearance, contact TWR controller by voice.

2. 跑道和滑行道的使用

2. Use of runways and taxiways

2.1 可以通过塔台申请引导车和拖车服务。

2.1 Follow-me vehicle service and towing service are available via Tower Control.

2.2 非全跑道运行程序

2.2 Intersection departure procedures

a. 管制运行需要的情况下，塔台管制员可以指挥航空

a. When ATC operation needed, TWR controller can

器 13L 跑道使用 A7 滑行道(31R 跑道使用 A2 滑行道) 非全跑道起飞, 如机组不能接受在放行时向塔台特别说明;

instruct aircraft to conduct intersection departure on RWY13L via TWY A7 (TWY A2 for RWY31R) , if flight crew cannot accept, inform TWR when clearance is issued;

b. 管制运行需要的情况下, 塔台管制员可以指挥航空器 13R 跑道使用 K12 滑行道(31L 跑道使用 K2 滑行道)非全跑道起飞, 如机组不能接受在放行时向塔台特别说明。

b. When ATC operation needs, TWR controller can instruct aircraft to conduct intersection departure on RWY13R via TWY K12 (TWY K2 for RWY31L) , if flight crew cannot accept, inform TWR when clearance is issued.

2.3 机场冲突多发地带运行要求

2.3 Hot spot procedure

2.3.1 机动区冲突多发地带位置见 ZBYN-机场图和停机位置图;

2.3.1 Refer to ZBYN-Aerodrome chart and Aerodrome parking chart;

2.3.2 在机场活动区内运行的航空器需严格按照下述的要求运行:

2.3.2 Aircraft operating within the maneuvering area must follow the requirements below:

HS1: B3, A6 与 A 滑的交叉区域

HS1: intersections of TWYs B3、A6 and A

31R 跑道运行时, 航空器沿 A 滑行道滑行通过 A6 时, 注意观察并避让由 A6 脱离的航空器。夜间、低能见度运行时, 离场航空器由 B3 左转滑入 A 滑行道时注意观察地面标志, 避免误入 A6 滑行道。

When RWY31R is in operation, aircraft crossing TWY A6 along TWY A shall pay attention and avoid aircraft vacating RWY via TWY A6. When at night or in low visibility operation, aircraft turning left from TWY B3 to TWY A shall pay attention to ground markings and avoid taxiing into TWY A6 by mistake.

13R 跑道运行时, 同时有航空器沿 A 滑行道和 B3 滑行道滑向 A6 时, 注意观察并避让。夜间、低能见度运行时, 离场航空器沿 B3 左转滑入 A6 滑行道时注意观察地面标志, 避免滑错。

When RWY13R is in operation, aircraft taxiing to TWY A6 along TWY A and TWY B3 at the same time, aircraft shall pay attention and avoid conflict. When at night or in low visibility operation, aircraft turning left from TWY B3 to TWY A6 shall pay attention to ground markings and avoid taxiing errors.

HS2: A4 与 A 滑的交叉区域

HS2: intersections of TWYs A4 and A

13L 跑道运行时，落地航空器 A3 脱离后在经 A 滑行道滑行时应在 A3 之前的 A 滑行道主动避让在 A4 连续落地脱离的航空器。同样在 A2 脱离的航空器应主动避让 A3、A4 脱离的航空器。	When RWY13L is in operation, landing aircraft vacating via TWY A3 should avoid aircraft vacating via TWY A4, landing aircraft vacating via TWY A2 should avoid aircraft vacating via TWY A4 or A3.
HS3: EL 与 E 滑的交叉区域	HS3: intersections of TWYs EL and E
31L 跑道运行时，离场航空器滑行至该位置时注意观察地面标志，避免过滑与进港航空器发生冲突。13R 跑道运行时，落地航空器应注意观察避让 E 滑上的航空器。	When RWY31L is in operation, departure aircraft shall pay attention to ground markings when taxiing to that position to avoid conflict with arrival aircraft. When RWY13R is in operation, landing aircraft shall pay attention and avoid aircraft on TWY E.
HS4: T3, K8 与 K 滑的交叉区域	HS4: intersections of TWYs T3, K8 and K
31L 跑道运行时，离场航空器沿 T3 滑行道左转滑入 K 滑行道时，注意观察并避让由 K8 脱离的航空器，夜间、低能见度运行时，离场航空器沿 T3 滑行道左转滑入 K 滑行道时注意观察地面标志，避免误入 K8 滑行道。	When RWY31L is in operation, departure aircraft turning left and taxiing to TWY K via TWY T3 shall pay attention and avoid aircraft vacating from TWY K8. When at night or in low visibility operation, aircraft turning left to TWY K along TWY T3 shall pay attention to ground markings and avoid taxiing into TWY K8 by mistake.
2.4 为规范航空器进入跑道和落地后的跑道占用时间，提高跑道容量，根据太原机场跑道及其快速脱离道布局，做如下要求（湿跑道或污染跑道除外）：	2.4 For optimizing RWY occupancy time and increasing RWY capacity, according to the layout of RWYs and rapid-exit TWYs, requirements as follows except for wet or contaminated RWY:
2.4.1 起飞航空器：	2.4.1 For departure aircraft
a. 航空器从跑道外等待点至对正跑道并做好立即离场准备应不超过 60s；	a. Aircraft shall taxi from RWY holding position to RWY, finish RWY alignment and get prepared to departure immediately within 60s.
b. 如果机组认为无法在上述要求的时间内完成，须在到达跑道外等待点之前向塔台管制员说明。	b. If flight crew consider they cannot fulfill the process within the required time, flight crew shall inform TWR

- 2.4.2 落地航空器：

a.中型机（含）以下机型从飞越跑道入口至完全脱离跑道应不超过 50 秒；

b.重型机（含）以上机型从飞越跑道入口至完全脱离跑道应不超过 70 秒；

c.如果机组认为无法在上述要求的时间内完成，须在 与塔台建立联系时尽早通知塔台管制员。
- 2.4.2 For landing aircraft

a. Medium aircraft or below shall fully vacate RWY within 50s after flying over THR.

b. Heavy aircraft or above shall fully vacate RWY within 70s after flying over THR.

c. If flight crew consider that they cannot fulfill the process within the required time, flight crew shall inform TWR as soon as possible.
- 2.5 禁止翼展 36m（含）以上的航空器在跑道做 180° 掉头，允许翼展 36m（不含）以下的航空器滑行至 13L/31R 跑道两端沿掉头线掉头。

2.5 180°turn around on RWY is strictly forbidden for all aircraft, only aircraft with wingspan less than 36m can turn around on RWY13L/31R ends.
- 2.6 滑行道的滑行限制

2.6 Taxiing limits:

滑行道/TWYs	航空器翼展限制/wing span limits for aircraft
A, A1, A8, B1(S of C)	80m
A2-A7, B2(S of C),B3-B5, C, E4, E7, E(W of EL) , EL, G, G1-G7, H, H1-H2 (N of H) , H3-H6, K, K1-K12, K15, M1, M2, T7, T3-T6	65m
B1(N of C), C1	52m
B0,B2(N of C), C2, D, E(E of EL)	36m
Note: 1.TWY C1: TWY C1 available for aircrafts with wingspan 52m(include)-80m(exclusive), when TWY B1 north of TWY C U/S.2.TWY B1: The TWY B1 between north of TWY C & stand Nr.209 available for aircrafts with wingspan 52m(include)-65m(exclusive), when TWY C1 U/S.3.A6: Aircraft taxi from TWY A6 and turn right to enter TWY A shall be with wingspan less than 52m, aircraft taxi from TWY A and turn left to enter TWY A6 shall be with wingspan less than 52m.	

2.7 B777、B787、A330、A340、A350 系列机型在 A1、A2、A8、B3、B4、B5 滑行道运行时，需采用偏置转弯。

2.8 滑行指令 ROUTE 描述：

13R 跑道运行：

13R 出港滑行路线：ROUTE01：A6—E4—T6

13R 进港滑行路线：ROUTE02：K—T4—EL—A5

31L 跑道运行：

翼展 36m（不含）以下航空器 31L 出港滑行路线：

ROUTE11：A5—EL—E—T3—K

31L 进港滑行路线：

ROUTE12：K—T6—E4—A6

3. 机坪和机位的使用

3.1 太原机场机坪的停机位和廊桥的使用，需提前向机场管理机构提出申请。

3.2 停机位 101-106、201-212 为廊桥机位；

3.2.1 B737、B757、B767、B747、B777、A300、A320、A340 航空器进入指定廊桥机位时，前轮必须停在“T”字线标示位置上。

3.3 机位使用规定

3.3.1 凡进入停机位 101-106、108、109、200-212、301-305、301L、301R、302L、302R、307-318、401-410 的航空器，均沿滑行线进入“T”字机位，前轮停放在对应航空器表示的位置；准备离港时，由牵引车沿线推至滑行线后，在机务人员的指挥下开车，滑出机坪。

2.7 B777, B787, A330, A340 and A350 series of aircrafts taxiing on TWYs A1, A2, A8, B3, B4 and B5 shall implement offset turning.

2.8 Taxiing instructions:

RWY13R operation:

Departure: ROUTE01:A6-E4-T6

Arrival: ROUTE02:K-T4-EL-A5

RWY31L operation:

For departure aircraft with wingspan 36m(exclusive):

ROUTE11:A5-EL-E-T3-K

Arrival: ROUTE12:K-T6-E4-A6

3. Use of aprons and parking stands

3.1 The use of stands within apron and boarding bridges request prior applications to AD administration.

3.2 Boarding bridges are available on stands Nr. 101-106, 201-212;

3.2.1 When B737/ B757/ B767/ B747/ B777/ A300/ A320/ A340 entering boarding bridge stand, the nose gear shall be parked on T-shape line.

3.3 Use regulations of stands

3.3.1 Stands Nr. 101-106, 108, 109, 200-212, 301-305, 301L, 301R, 302L, 302R, 307-318 and 401-410 are T-shaped stands. Aircraft shall enter via taxiing line and with the front wheel parked on the corresponding marking position of aircraft; for departure, aircraft shall be pushed back by tow tractor to taxiing line, then follow the guidance of ground staff to start-up and taxi

- 3.3.2 凡进入停机位 411-414、411L、411R、412L、412R、413L、413R、414L、414R 的航空器，均沿滑行线进入“T”字机位，前轮停放在对应航空器表示的位置；准备离港时，由牵引车沿线推至滑行线后，在机务人员的指挥下开车，滑出机坪，或在机务人员的指挥下开车，自滑出机坪。

3.3.3 进入停机位 107、110 的航空器，均沿滑行线进入“T”字机位，前轮停放在对应航空器表示的位置；准备离港时，由牵引车沿线推至滑行线后，在机务人员的指挥下开车，滑出机坪；符合自滑机型限制（机长≤32.51m，翼展≤30m）的航空器可在机务人员的指挥下开车，自滑出机坪。

3.4 机位使用限制
- out of the apron.

3.3.2 Stands Nr.411-414, 411L, 411R, 412L, 412R, 413L, 413R, 414L and 414R are T-shaped stands. Aircraft shall enter via taxiing line and with the front wheel parked on the corresponding marking position of aircraft; for departure, aircraft shall be pushed back by tow tractor to taxiing line, then follow the guidance of ground staff to start-up and taxi out of the apron or taxi out by itself.

3.3.3 Stands Nr.107 and 110 are T-shaped stands. Aircraft shall enter via taxiing line and with the front wheel parked on the corresponding marking position of aircraft; for departure, aircraft shall be pushed back by tow tractor to taxiing line, then follow the guidance of ground staff to start-up and taxi out of the apron; aircraft (with the length ≤32.51m, wing span ≤30m) can follow the guidance of ground staff to start-up and taxi out of the apron by itself.

3.4 Limits for aircraft parking on the following stands:

停机位/Stands	航空器翼展限制/Wing span limits for aircraft	机身长度限制/Fuselage limits for aircraft
Nr.301, 302	80m	79m
Nr.411-414	65m	75.5m
Nr. 209		75.4m
Nr. 201		71m
Nr. 208	52m	54.94m

Nr. 301R, 303	48.6m	
Nr.411R	48m	56m
Nr. 211, 301L	45m	54.43m
Nr. 101-110, 401-410, 200, 210, 411L, 412L, 412R, 413L, 413R, 414L, 414R	36m	45m
Nr. 202-204, 206, 207, 212, 302L, 302R		45.06m
Nr. 205, 307, 308, 315-318		44.51m
Nr. 304, 305	30.2m	45m
Nr. 309-311	28.5m	29.4m
Nr. 312-314	19.2m	14.86m

3.5 停机位 APU 替代设施

3.5 Equipments replace APU on the following stands:

3.5.1 太原机场桥载设备的具体参数

3.5.1 Equipment parameters of the boarding bridge

停机位/Stands	400Hz 电源功率/台 400Hz power supply(kVA)	400Hz 电源台数/桥 Number of 400Hz power	桥载空调制冷量/台 Power of air conditioning system(kW)	桥载空调台数/桥 Number of air conditioning system
Nr. 101-106, 202-207, 212	90	1	refrigeration 140 heating 72	1
Nr. 208, 210, 211	90	1	refrigeration 210 heating 102	1
Nr. 201, 209	90	2	refrigeration 316 heating 147	1

3.5.2 太原机场远机位 APU 替代设施具体参数

3.5.2 Equipment parameters on remote stands

停机位/Stand	航空器地面 400Hz 静变电源总功率 (kVA) /台 400Hz power supply(kVA)	航空器地面 400Hz 静变电源插头数/台 Number of 400Hz power power	航空器地面空调功 率 kW Power of air conditioning system(kW)	航空器地面空调送 风软管/台 Number of air conditioning system
Nr. 301L, 301R, 302L, 302R, 307, 308, 317, 318, 402-410	90	1	refrigeration 165 heating 60	1

3.6 本场全部机位必须在地面引导车的引导下进入停
机位。

3.6 All aircrafts shall follow the follow-me vehicle to the
parking stands.

3.7 机坪管制运行管理规定

3.7 APN control operation rules

3.7.1 机坪管制的范围为：A 滑行道（不含）以北全
部投用的停机位及机坪范围内的所有滑行道,具体滑
行道包含：C、C1、C2、D、B0、B1（C 以北）、B2
（C 以北）。G 滑行道（不含）以南全部投用的停机
位及机坪范围内的所有滑行道，具体滑行道包含：H、
H1、H2、H3、H4、H5、H6、M1、M2。

3.7.1 APN control area: all available parking stands and
all TWYs within apron in the north of TWY
A(excluded), including TWYs C, C1, C2, D, B0,
B1(north of C),B2(north of C); All available parking
stands and all TWYs within apron in the south of TWY
G(excluded), including H, H1, H2, H3, H4, H5, H6, M1,
M2.

3.7.2 本场停放在以下机位的航空器推出时，联系机
坪管制获取“红蓝线”推出指令，并按要求推出至滑行
道。

3.7.2 Aircraft parking on the following stands shall
contact APN for 'red line' and 'blue line' push-back
instructions, then follow the instructions to push back to
TWY.

3.7.2.1 近机位

3.7.2.1 Bridge stands

停机位/Stands	推出后航空器所在滑行道编号和机头朝向/TWY and nose direction after push-back	
	红线/Red line	蓝线/Blue line
101-106, 201,208	NW of TWY C	SE of TWY C
202-205	N of TWY B2	E of TWY C2
206, 207	N of TWY B2	S of TWY B2
209	SW of TWY B1	SE of TWY C
210, 211	SW of TWY B1	NE of TWY B1
212	behind stand Nr.212 NW	NE of TWY B1

3.7.2.2 远机位

3.7.2.2 Remote stands

停机位/Stands	推出后航空器所在滑行道编号和机头朝向/TWY and nose direction after push-back	
	红线/Red line	蓝线/Blue line
107-110, 200, 402-413, 411L, 411R, 412L, 412R, 413L, 413R, 414L	NW of TWY C	SE of TWY C
301L, 301R, 302L, 302R	SW of TWY C1	NE of TWY C1
401, 414, 414R	NW of TWY C	Not available
301-305, 307-318	Push-back in one direction only, contact APN for push-back instruction without red and blue line instruction	

3.7.3 机坪管制范围内离港航空器推出开车滑行:

3.7.3 Within APN control area, departure aircraft pushing back shall:

3.7.3.1 航空器向太原放行 (Delivery) 申请放行许可, 空中交通管制放行许可的申请不早于发动机开车前 10min 进行;

3.7.3.1 Apply for delivery clearance from Taiyuan Delivery not earlier than 10 minutes before engine start-up.

- 3.7.3.2 经太原放行（Delivery）同意后，航空器向太原机坪（APN）申请推出开车许可；
- 3.7.3.2 When obtained clearance from Taiyuan Delivery, apply for push-back and engine start-up clearance to APN.
- 3.7.3.3 航空器准备完毕，首次联系太原机坪（APN）时，机组应向机坪管制员通报停机位编号；“准备完毕”意味着机组确保：
- 3.7.3.3 When aircraft is getting prepared, flight crew shall inform parking stands Nr. to controller on the initial contact with APN, 'Getting prepared' means flight crew shall ensure:
- a. 航空器舱门锁闭；
 - a. Aircraft cabin door is locked
 - b. 航空器安全区域没有车辆、设备、障碍物及地面无关保障人员；
 - b. No vehicles, equipments, obstacles or unnecessary ground staff at the aircraft safe area;
 - c. 航空器已完全做好开车准备；
 - c. Aircraft is ready to start-up;
 - d. 牵引车已经连接上了航空器（自滑出港除外）。
 - d. Aircraft connected with tow-tractor (except for aircraft taxiing out on own power).
- 3.7.3.4 航空器取得太原机坪（APN）许可后推出开车，推出时需向太原机坪（APN）证实推出方向或程序，太原机坪（APN）发布许可指令后，机组应在 3min 之内执行，超过 3min 仍未推出开车视为指令失效，机组需要重新申请推出开车；在得到太原机坪（APN）的明确指令前，航空器不得擅自推出、开车或滑行；
- 3.7.3.4 When obtained push-back and start-up clearance from APN, aircraft shall verify push-back direction or procedures with APN before push-back. Aircraft shall follow APN instructions within 3 minutes or re-apply the clearance if not fulfill in time. Push-back, start-up or taxiing without APN clearance is forbidden.
- 3.7.3.5 本场实施“闪灯即推”运行规则，机组开启航空器防撞灯的时机应严格限定在收到推出开车许可后，禁止提前开启；遇特殊情况除外（包括但不限于 APU 失效）；
- 3.7.3.5 The 'Push-back after flashing lights' rule is implemented, aircraft shall turn on the collision avoidance light after receiving push-back and start-up clearance, turn on the light in advance is forbidden; except for special circumstances (including but not limited to APU failure);
- 3.7.3.6 本场实施“边推边开”运行规则，当停机位和推出路线符合运行限制时，航空器须在推出过程中进行开车作业；不能在推出过程中进行开车作业的，机场
- 3.7.3.6 The 'simultaneous push-back and engine start' rule is implemented, when stands and push-back routes comply with the operation restrictions, aircraft shall

不保证优先提供近机位使用；停机位 305-318、402（沿蓝线推出时）、414L（沿蓝线推出时）因运行限制禁止执行“边推边开”；其余停机位均可执行；	start-up during the push-back process; if it is not available, the airport can not promise the priority use of bridge stands; all stands can implement 'simultaneous push-back and engine start' except for stands Nr.305-318, 402 (when pushed back along blue line) and 414L (when pushed back along blue line);
3.7.3.7 航空器向太原机坪(APN)申请并征得同意后，方可原机位启动一侧发动机，再向太原机坪（APN）申请推出开车许可；	3.7.3.7 With APN clearance, aircraft shall start up engine on one side at the parking stand, then apply push-back and engine start-up clearance to APN.
3.7.3.8 航空器推出开车后，向太原机坪（APN）申请滑行许可；	3.7.3.8 When aircraft push-back and engine start-up, apply taxiing clearance to APN.
3.7.3.9 航空器在进入太原塔台（TWR）管制责任区前，由太原机坪（APN）指示联系相应的塔台管制。	3.7.3.9 Aircraft shall contact with TWR control with APN instructions before entering the TWR control area.
3.7.4 机坪管制范围内进港航空器滑行：航空器进入机坪前，联系太原机坪（APN）获取停机位信息，并申请进一步滑行许可，机组与机坪管制确认后，跟随引导车滑行。	3.7.4 Within apron control areas, arrival aircraft shall contact APN for stands information and further taxiing clearance before entering apron, then follow the follow-me vehicle.
3.8 未经机坪管制许可，严禁航空器利用自身动力滑行或使用牵引车拖曳。	3.8 Aircraft taxiing with own power or be towed is strictly forbidden without APN control clearance.
3.9 航空器试车	3.9 Engine run-ups
3.9.1 经机坪管制许可试车后，在指定位置进行，并始终保持双向通讯联系，试车结束后需向机坪管制报告。未经机坪管制许可，严禁机坪内试车。	3.9.1 Engine run-ups are subject to APN clearance, and shall be carried out at a designated location, keep contact and inform APN when finished. Engine run-ups on apron without APN clearance is strictly forbidden.
3.9.2 严禁在廊桥附近和客机坪上大功率试车或进行发动机排故调试。	3.9.2 Fast engine run-ups, or trouble-shooting and testing of engine on apron or nearby boarding bridge are strictly forbidden.
3.10 航空器准备完毕，由机组向机坪管制申请除防冰	3.10 When aircraft is getting prepared, flight crew shall

许可，经机坪管制许可后，航空器在指定位置进行，除防冰结束后向机坪管制报告。

apply to APN for deicing clearance. Deicing shall be carried out at a designated location with APN clearance. Contact APN when finished.

4. 低能见度运行

4. Low visibility operation

无

Nil.

5. 直升机飞行限制，直升机停靠区

5. Helicopter operation restrictions and helicopter parking/docking area

无

Nil

6. 警告

6. Warning

6.1 机场东北距山较近，且在 360°-040°范围内工厂烟囱密集，高度 1200m 以上，航空器起降时应予注意。

6.1 Flight crew shall pay attention to the mountain on NE of AD and the chimneys BTN 360° & 040° of AD, altitude above 1200m.

6.2 本场 170°方位 30km 附近常年有直升机低高度活动。

6.2 Helicopter low-level activities are in the area of 30km from 170° of airport all the year round.

ZBYN AD 2.21 减噪程序

ZBYN AD 2.21 Noise abatement procedures

无

Nil

ZBYN AD 2.22 飞行程序

ZBYN AD 2.22 Flight procedures

1. 总则

1. General

1.1 除经塔台特殊许可外，在塔台管制区内的飞行，必须按照仪表飞行规则进行。

1.1 Flights within Tower Control Area shall operate under IFR unless special clearance has been obtained from Tower Control.

2. 起落航线

2. Traffic circuits

31L 和 13L 为左起落航线，31R 和 13R 为右起落航线；起落航线高度：高度 1100-1300m (QNH)。

Left traffic circuit: RWY31L and RWY13L; Right traffic circuit: RWY31R and RWY13R; Altitude of traffic circuit: 1100-1300m(QNH).

3. 仪表飞行程序

3. IFR flight procedures

3.1 严格按照航图中公布的进、离场程序飞行。如果

3.1 Strict adherence is required to the relevant

需要，航空器可在空中交通管制部门指定的航路、导航台或定位点上空等待或做机动飞行。

3.2 特殊规定

3.2.1 太原机场西北方向地形较高，RWY13L/13R 运行时，航空器驾驶员需注意：（1）航空器高度 2100m 以下，从左侧切入航向道时，不应穿越航向道；（2）进近过程中，不应向右偏离航向道，否则存在低于雷达引导高度（MVA）的风险。

3.2.2 由于地形，当航空器正在被雷达引导，必须保持空中交通管制最后指定的高度，直至航空器进入仪表进近程序。

3.2.3 应严格飞行程序中的速度限制要求。

3.3 等待程序

见仪表进近图。

4. 雷达程序和/或 ADS-B 程序

4.1 雷达引导进港程序：以太原机场跑道两边延长线为中心，双三边的雷达引导程序，三边宽度 15km。正切跑道前三边高度 2400m 或以上。

arrival/departure procedures published in the aeronautical charts. Aircraft may, if necessary, hold or maneuver on an airway, over a navigation facility or a fix designated by ATC.

3.2 Special rules

3.2.1 Due to the terrain on the NW of AD is relatively high, when operating on RWY13L/13R, flight crew should pay attention to the following: (1) Crossing the localizer is forbidden when aircraft intercepting the localizer from the left side at the altitude below 2100m. (2) During the approaching, aircraft should not deviate to the right side of the localizer, otherwise there is a risk of flying below the minimum vectoring altitude(MVA) for radar guidance.

3.2.2 Due to the terrain, aircraft under radar vectoring must maintain last assigned altitude by ATC until entering the IAP.

3.2.3 Strict adherence to speed limits in flight procedures.

3.3 Holding procedure

Refer to Instrument approach charts.

4. Radar procedures and/or ADS-B procedures

4.1 Radar vector procedure for arrival: Radar vector procedure for both downwind legs based on the extension line from both ends of the runway with 15km apart from. The assigned altitude on each downwind should be 2400m or above prior to abeam the runway in use.

4.2 雷达引导出港：

保持一边上升至 2700m（或 ATC 指令），雷达引导加入离场程序点。

4.3 雷达引导复飞程序：复飞航空器保持跑道航向上升到 1800m（或 ATC 指令），雷达引导飞航向 040°，再转向三边，加入雷达引导进港程序再次进近。

4.4 太原管制区内实施雷达管制，区域管制最低水平间隔 9.3km，进近管制最低水平间隔 5.6km。

5. 无线电通信失效程序

参见 AIP GEN3.4.5 中的仪表飞行规则航空器地空双向无线电通信失效通用程序。

6. 目视飞行程序

无

7. 目视飞行航线

太原进近管制区、太原塔台管制区实施目视间隔。

8. 其它规定

8.1 航空器驾驶员联系管制单位后应向管制员报告“重型”或“HEAVY”。

8.2 进场航空器进入进近管制区首次联系时，应向管制员主动报告通报代码和当前保持的高度。

4.2 Radar vector procedure for departure

Climb to 2700m and maintain for upwind leg(or follow ATC instructions), and follow radar vectoring to the intersection of departure procedures.

4.3 Radar vector procedure for a missed approach:

Normally request aircraft to maintain runway heading, climb to 1800m(or follow ATC instructions), radar vector to fly heading 040°, then turn to downwind to follow radar procedure for another approach.

4.4 Radar control within Taiyuan Control Area has been implemented. The minimum horizontal separation is 9.3km for Area control, the minimum horizontal separation is 5.6km for Approach control.

5. Radio communication failure procedures

Refer to AIP GEN3.4.5 general procedures for aircraft under instrument flight rule with air-ground two-way radio communication failure.

6. Procedures for VFR flights

Nil

7. VFR route

Visual separation is implemented within Taiyuan APP Control Area and Taiyuan TWR Control Area.

8. Other regulations

8.1 Flight crew shall report 'HEAVY' to ATC after contacting control unit.

8.2 Arrival aircraft shall report the code of the flight and the current altitude to the controller when entering the

APP control area.

ZBYN AD 2.23 其它资料

ZBYN AD 2.23 Other information

鸟情资料

Bird's information

机场全年有鸟类活动，留鸟主要为喜鹊、云雀、家鸽、斑鸠。春季3月至5月、秋季8月底至11月初为候鸟迁徙季节，迁徙鸟类主要为家燕、乌鸦、沙锥。机场在飞行区常态化开展驱鸟作业以减少鸟类活动。主要措施有喷洒驱鸟剂和灭虫剂、生态环境治理、钛镭弹和脉冲炮驱赶、声波类和视觉类驱鸟设备驱赶等。常见鸟类及活动规律如下：

Activities of bird flocks are found in the whole year. The resident birds are magpies, skylark, pigeons and turtledoves. Migrating birds are mainly swallows, crows and snipes. Migrating seasons are from Mar.to May and from the end of Aug.to the beginning of Nov.Aerodrome Authority resorts to dispersal methods to reduce bird activities, including spraying bird repellent and insect repellent, ecological environment management, Titanium mine bomb, pulse gun, voice bird repellent equipment, visual bird repellent equipment etc.

Common birds and activity rules are as follows:

Main bird species	Time of activity	Activity area	Flight height(m)
Pigeon(Columba)	Annual	Over RWY THR, villages and communities outside the boundary of RWY31L	0-500
Magpie(Pica pica)		Grass on both sides of the RWY, grass BTN the RWY and TWYs	0-100
Turtledove(Streptopelia decaocto)		Grass around the flight area boundary	
Pheasant(Phasianus colchicus)		Flight area and the surrounding grass	0-80
Sparrow(Passer montanus)		Around the boundary of	0-20

		flight area	
Skylark(<i>Alauda arvensis</i>)		Around the boundary of flight area, grass around the RWY	
Grey starling(<i>Sturnus cineraceus</i>), Merl(<i>Turdus merula</i>)	FM Mar. to May	Flight area and the surrounding grass	0-30
Amur falcon(<i>Falco amurensis</i>), Kestrel(<i>Falco tinnunculus</i>), Sparrow hawk(<i>Accipiter nisus</i>)		Over flight area	0-500
Anas poecilorhyncha(<i>Anas poecilorhyncha</i>), Mallard(<i>Anas platyrhynchos</i>), Snipe(<i>Gallinago gallinago</i>)	FM Apr. to Oct.	Water area around flight area	0-200
Long ear owl(<i>Asio otus</i>), Short ear owl(<i>Asio flammeus</i>)		Over flight area	
Swallow(<i>Hirundo rustica</i>), Hawk swallow(<i>Apus apus</i>)		THR13 and THR31	
Hoopoe(<i>Upupa epops</i>)		Around the boundary of flight area, grass about 90m off the RWY	0-60
Crow(<i>Corvus corone</i>)	FM Oct. to Feb. next year, 02:00-05:00 and 07:00-09:30 a.m.	Over flight area, villages and communities outside the boundary of RWY13R	0-600

		and RWY31L	
--	--	------------	--