

ZGGG AD 2.1 机场地名代码和名称 Aerodrome location indicator(ICA0 / IATA) and name

ZGGG/CAN-广州/白云 GUANGZHOU/Baiyun

ZGGG AD 2.2 机场地理位置和管理资料 Aerodrome geographical and administrative data

1	机场基准点坐标及其在机场的位置 ARP coordinates and site at AD	N23°23.6' E113°18.5' Center of RWY 02L/20R
2	机场基准点与城市的位置关系 Direction and distance from city	007° GEO, 30.7km from city center(Haizhu Square)
3	机场标高、基准温度、低温均值 ELEV/Reference temperature/Mean low temperature	15.2 m/35.1°C(JUL)/10.5°C(JAN)
4	机场标高位置的大地水准面波幅 Geoid undulation at AD ELEV PSN	
5	磁差(测量年份)及年变率 VAR(Year)/Annual change	3°0'W/-
6	机场管理部门、地址、电话、传真、AFS 地址、电子邮箱、网址 AD administration/Address/Telephone/Telefax/AFS/ E-mail/Website	Guangzhou Baiyun International Airport Co., Ltd Headquarters Office Building of GBIAC, South Area of Guangzhou Baiyun International Airport, Huadu District, Guangzhou, Guangdong province, China Post code:510405 TEL:86-20-36066878 FAX:86-20-36066878 AFS:ZGGGVNXX
7	允许飞行种类 Types of traffic permitted(IFR/VFR)	IFR-VFR
8	机场性质/飞行区指标 Military or civil airport/Reference code	CIVIL/RWY02L/20R, RWY02R/20L: 4F; RWY01L/19R, RWY01R/19L, RWY03/21: 4E
9	备注 Remarks	Nil

ZGGG AD 2.3 工作时间 Operational hours

1	机场开放时间 AD Operational hours	H24
2	海关和移民 Customs and immigration	HS or O/R
3	卫生健康部门 Health and sanitation	HS or O/R
4	航空情报服务讲解室 AIS Briefing Office	H24
5	空中交通服务报告室 ATS Reporting Office	H24

6	气象服务讲解室 MET Briefing Office	H24
7	空中交通服务 Air Traffic Service	H24
8	加油服务 Fuelling	HS or O/R
9	地勤服务 Handling	HS or O/R
10	安保服务 Security	H24
11	除冰服务 De-icing	Nil
12	备注 Remarks	Nil

ZGGG AD 2.4 地勤服务和设施 Handling services and facilities

1	货物装卸设施 Cargo-handling facilities	Platform lift(30 tonnes), fork lift(7 tonnes), baggage transporter, cargo tow tractor, freight processing system (1.5 tonnes) and container bulk cargo processing system (13.6 tonnes).
2	燃油牌号 Fuel types	Jet A-1
3	滑油牌号 Oil types	Nil
4	加油设施/能力 Fuelling facilities & Capacity	Refueling pipeline: 228.7 L/s Hydrant Dispenser: 20L/s (single hose flow rate), 58L/s (dual hose flow rate) Tanker Truck: 13L/s (single hose flow rate), 37L/s (dual hose flow rate)
5	除冰设施 De-icing facilities	Nil
6	过站航空器机库 Hangar space for visiting aircraft	Hangar Nr.10 is divided into maintenance area and painting area. Maintenance area can accommodate one wide body aircraft(A380), two wide body aircraft(B747) and five narrow body aircraft(B737, A320), or one wide body aircraft(A380) , nine narrow body aircraft(B737/B757, A320/A321, C909/919). The painting area can accommodate one wide body aircraft(A380) and two narrow body aircraft(one B737 and one B757, A320/A321, or C909/919, and one B737/A320/C909/919, by nose to tail arrangement). Hangar Nr.11 can accommodate eight narrow body aircraft(B737/B757, A320/A321, C909/919). Hangar Nr.18 can accommodate one wide body aircraft(A380), five wide body aircraft(B747), and five narrow body aircraft(B737/B757, A320/A321, C909/919).

7	过站航空器的维修设施 Repair facilities for visiting aircraft	Line maintenance, engine changes available for various types of aircraft on request. Spare parts and other maintenance work by prior arrangement. circuits maintenance is available.
8	备注 Remarks	Nil

ZGGG AD 2.5 旅客设施 Passenger facilities

1	宾馆 Hotels	At AD
2	餐饮 Restaurants	At AD
3	交通工具 Transportation	Passenger's coaches, taxis, rail transit
4	医疗设施 Medical facilities	First aid center and ambulances at AD, hospital in the city
5	银行和邮局 Bank and Post Office	At AD
6	旅行社 Tourist Office	At AD
7	备注 Remarks	Nil

ZGGG AD 2.6 援救与消防服务 Rescue and fire fighting services

1	机场消防等级 AD category for fire fighting	CAT 10
2	援救设备 Rescue equipment	Firefighting vehicles: rapid deployment vehicle, primary foam tender, heavy foam tender, rescue and demolition vehicle. Rescue equipments: emergency rescue equipment, crane, fork lift, disassembly rescue truck, communication and command truck.
3	搬移受损航空器的能力 Capability for removal of disabled aircraft	MTOW up to A380. Removal equipment: uplift air cushion, jack, mobile surface operation devices, sleeper, aircraft moving trailer, landing gear hanger, tractor, crane, lifting rigging, etc.
4	备注 Remarks	Nil

ZGGG AD 2.7 可用季节- 扫雪 Seasonal availability-clearing

1	可用季节及扫雪设备类型 Seasonal availability/Types of clearing equipment	All seasons Not applicable
2	扫雪顺序 Clearance priorities	Not applicable

3	备注 Remarks	Nil
---	---------------	-----

ZGGG AD 2.8 停机坪、滑行道及校正位置数据 Aprons, taxiways and check locations data

1	停机坪道面和强度 Apron surface and strength	道面 Surface	CONC
		强度 Strength	PCR 1450/R/A/W/T : Maintenance apron, STAG apron PCR 1400/R/A/W/T : 309-328, 319L/R, 320L/R, 324L/R-327L/R PCR 1350/R/A/W/T : 432-437 PCR 1290/R/A/W/T : 101-112 PCR 1230/R/A/W/T : 113-123 PCR 1210/R/A/W/T : 161-164 PCR 1160/R/A/W/T : 301-308, 168-173 PCR 1120/R/A/W/T : GY07-GY10, 144-153, 149L/R, 154-160, 160L/R, 165-167 PCR 1070/R/A/W/T : 329, 330, 417-419 PCR 1050/R/A/W/T : 124-133 PCR 1030/R/A/W/T : 201-213, 401-406, 401L/R-406L/R, FedEx apron PCR 1020/R/A/W/T : 214-223 PCR 970/R/A/W/T : 500A, 500B, 501-515, 501L-514L, SF01-SF08, SF08L/R PCR 950/R/A/W/T : 134L, 134-137 PCR 930/R/A/W/T : 224-236, 238, 240, 238L/R, 240L/R PCR 920/R/A/W/T : 264-270, 273-276 PCR 910/R/A/W/T : 254, 254L/R, 255, 255L/R, GY01-GY05 PCR 900/R/A/W/T : 331-338 PCR 890/R/A/W/T : 815, 816, 816L/R, 818, 819, 819L/R, 821, 822, 822L/R, 824, 830-834, 838, 870-876, 870L/R -876L/R, 881, 882, 914, 916, 916L/R, 917, 919, 919L/R, 920, 922, 922L/R, 923, 930-934, 938, 939, 941-943, 943L/R, 945, 946, 946L/R, 947, 948, 948L/R, 949, 970-972, 970L/R -972L/R, 974, 975, TEST 02, CG01-CG05, CG10-CG14, GL01 PCR 880/R/A/W/T : 271, 271L/R, 272, 272L/R, 277-279 PCR 870/R/A/W/T : 516-518 PCR 840/R/A/W/T : 407-416, TEST 01 PCR 830/R/A/W/T : 251-253, 256-263, 430, 431 PCR 740/R/A/W/T : FBO Apron PCR 640/R/A/W/T : 701-710, 825-829, 835-837, 860-862, 880, 888-892, 903-913, 924-929, 935-937, 940, 944, 950, 960-963, 973, CG06, TEST 03
2	滑行道宽度、道面和强度 Taxiway width, surface and strength	宽度 Width	70m : J35-J37, J56, L32-L38, Q12-Q14, V1(BTN T12 & T13) 56m : C(BTN T3 & T4), C4 53m : J23 50m : L4-L8(BTN A & C), L9(BTN B & C), L10(BTN A & C), L11(BTN A & C), L14(BTN A & C), L15(BTN A & C), L21, Q7-Q9, Q15

			48m : J2, J6-J12(west of D), J14, J18, J20, Q6 46.5m : L31, L39 44m : A(BTN T1 & T2, BTN L21 & L22), A2, A9, A10, B(BTN T1 & T2, BTN L5 & L6, BTN T3 & T4, BTN L7 & L8), C(BTN T1 & T2, BTN L5 & L6, BTN L7 & L8), M2, M9, N2, N3, N10, P14, Q10, Q11(west of Q), Q16, W2, W9, Y4, Y17 42.5m : J44 39.2m : J43 39m : C1, E(BTN T1 & T2, BTN J7 & J8, BTN J9 & J10, BTN J20 & T4), F(BTN J1 & J2, BTN J20 & T4), F2, F9, J7-J10(east of D), L3(west of C), L5-L8(west of C), L22 38.5m : Q11(east of Q) 37.5m : J41 36m : B(BTN L15 & T3), C(BTN L15 & T3) 34m : B(BTN L21 & L22), C(BTN L11 & L14), L4(west of C) 33.5m : L25, W1, W10 30m : B(BTN L14 & L15), P1-P13 28m : C(BTN L14 & L15) 25m : A(BTN T2 & L21), A1, A3, A4, A7, A8, A11, B(BTN T2 & L5, BTN L6 & L7, BTN L8 & L14, BTN T4 & L21), C(BTN T2 & L5, BTN L6 & L7, BTN L8 & L11), M(north of M10), M1, M3, M4, M7, M8, M10, Q(BTN Q10 & Q6), Q17, T1(west of D, east of C), T2(west of D, east of C), T3, T4(west of D, east of C1), Y(south of Y1), Y1-Y3, Y5, Y6, Y8, Y11, Y13-Y16, Y18 23m : A5, A6, B(north of L22, south of T1), B1, B2, D, D4, E(south of T1, BTN T2 & J7, BTN J8 & J9, BTN J10 & J20, BTN T4 & H2), F(BTN J2 & J20), F1, F3-F8, F10, GT4(BTN GT1 & Y20), H, H1, H2, J, J1, J21, K, K1, L16, M(south of T62), M5, M6, N, N1, N4-N9, N11, Q(north of Q6, BTN J43 & Q10, south of J41), R, R3-R5, S1-S3, T1(BTN C & D), T2(BTN C & D), T4(BTN C1 & D), T5-T7, T11-T13, T61-T66, U, V, W, W3-W8, Y(north of Y1), Y7, Y9, Y10, Y12, Y19, Y20 18m : J3, J22(BTN D & D4) 15m : C5, L26, L27
		道面 Surface	ASPH : P3(inward 76m from the runway edge), P4(inward 76m from the runway edge), Y3(inward 176m from the runway edge), Y5(inward 145m from the runway edge), Y7(inward 162m from the runway edge), Y9(inward 162m from the runway edge), Y11(inward 176m from the runway edge), Y13(inward 176m from the runway edge) CONC : A, A1-A11, B, B1, B2, C, C1, C4, C5, D, D4, E, F, F1-F10, GT1-GT4, H, H1, H2, J, J1-J3, J6-J23, J35-J37, J41, J43, J44, J56, K, K1, L3-L16, L18, L21, L22, L24-L27, L31-L39, M, M1-M10, N, N1-N11, P1, P2, P3(outward 76m from the runway edge), P4(outward 76m from the runway edge), P5-P14, Q, Q6-Q17, QL, R, R3-R5, S1-S3, T1-T7, T11-T13,

			T61-T66, U, V, V1, W, W1-W10, Y, Y1, Y2, Y3(outward 176m from the runway edge), Y4, Y5(outward 145m from the runway edge), Y6, Y7(outward 162m from the runway edge), Y8, Y9(outward 162m from the runway edge), Y10, Y11(outward 176m from the runway edge), Y12, Y13(outward 176m from the runway edge), Y14-Y20
		强度 Strength	PCR 1630/R/A/W/T : Y3(outward 176m from the runway edge), Y5(outward 145m from the runway edge), Y7(outward 162m from the runway edge), Y9(outward 162m from the runway edge), Y11(outward 176m from the runway edge), Y13(outward 176m from the runway edge) PCR 1500/R/A/W/T : A7, A8 PCR 1470/R/A/W/T : A3, A4 PCR 1450/R/A/W/T : L24 PCR 1440/R/A/W/T : L5(east of C) PCR 1400/R/A/W/T : A6, L18 PCR 1390/R/A/W/T : A5 PCR 1380/R/A/W/T : C5, L6(east of C), M7, M8, Y14, Y16 PCR 1370/R/A/W/T : L5(west of C) PCR 1350/R/A/W/T : D4, J20, J22, L4(east of C), L8(east of C), M3, M4, Y6, Y8 PCR 1340/R/A/W/T : J14 PCR 1320/R/A/W/T : L21, L22, M1, M2, Y2, Y4 PCR 1310/R/A/W/T : J12, L6(west of C) PCR 1300/R/A/W/T : L8(west of C) PCR 1290/R/A/W/T : A11, F3-F5, L4(west of C), L7(east of C), M6, Y12 PCR 1280/R/A/W/T : A1, F6-F8 PCR 1270/R/A/W/T : M5, M9, M10, Y10, Y17, Y18 PCR 1260/R/A/W/T : J7(west of D) PCR 1250/R/A/W/T : L12, L14 PCR 1240/R/A/W/T : J8(west of D), L11 PCR 1230/R/A/W/T : L7(west of C), L9(east of C) PCR 1220/R/A/W/T : A PCR 1210/R/A/W/T : J10(west of D), L13 PCR 1200/F/A/W/T : P3(inward 76m from the runway edge), P4(inward 76m from the runway edge), Y3(inward 176m from the runway edge), Y5(inward 145m from the runway edge), Y7(inward 162m from the runway edge), Y9(inward 162m from the runway edge), Y11(inward 176m from the runway edge), Y13(inward 176m from the runway edge) PCR 1200/R/A/W/T : F1, F10, J6(west of D) PCR 1190/R/A/W/T : J1, P9-P14 PCR 1170/R/A/W/T : P1, P2, P5-P8 PCR 1160/R/A/W/T : C4, J21, L3, L16, T1, T2, T4 PCR 1150/R/A/W/T : Y15 PCR 1140/R/A/W/T : A10, J9(west of D), L10(east of C), Y1

		PCR 1130/R/A/W/T : A2, M(north of M10) PCR 1120/R/A/W/T : F, J(east of stand Nr.170), L10(west of C) PCR 1110/R/A/W/T : C1, J8(east of D), P3(outward 76m from the runway edge), P4(outward 76m from the runway edge) PCR 1090/R/A/W/T : J10(east of D), T3, Y(south of Y1) PCR 1070/R/A/W/T : J7(east of D), J11(west of D) PCR 1060/R/A/W/T : Q(BTN Q10 & Q6), Q6-Q10, Q11(west of Q), Q16, Q17 PCR 1050/R/A/W/T : J18, L9(west of C) PCR 1040/R/A/W/T : L15 PCR 1030/R/A/W/T : C, F2, F9, J2, J6(east of D), Q15 PCR 1020/R/A/W/T : J9(east of D) PCR 1000/R/A/W/T : B(BTN T1 & L22) PCR 970/R/A/W/T : D, L25 PCR 950/R/A/W/T : E(BTN J1 & J22) PCR 930/R/A/W/T : J11(east of D) PCR 920/R/A/W/T : J19 PCR 910/R/A/W/T : J13 PCR 900/R/A/W/T : L26, L27 PCR 890/R/A/W/T : A9, B(south of T1, north of L22), B1, B2, E(north of J22, south of J1), H, H1, H2, J23, J35-J37, J41, J43, J44, J56, K, K1, L31-L39, M(south of T62), N, N1-N3, N10, N11, Q(north of Q6, BTN J43 & Q10, south of J41), Q11(east of Q), Q12-Q14, R, R3-R5, S1-S3, T5-T7, T11-T13, T61-T66, U, V, V1, W, W1-W10, Y(north of Y1), Y19, Y20 PCR 880/R/A/W/T : J(west of stand Nr.170) PCR 870/R/A/W/T : QL PCR 840/R/A/W/T : J3 PCR 830/R/A/W/T : J15-J17 PCR 820/R/A/W/T : N4-N9 PCR 740/R/A/W/T : GT1-GT4
3	高度表校正点的位置及其标高 ACL location and elevation	East Nr.1 apron: elevation 14.6m; East Nr.2 apron: elevation 13.6m; East Nr.3 apron: elevation 13.6m; West apron: elevation 13.2m.
4	VOR 校正点 VOR checkpoints	Nil
5	INS 校正点 INS checkpoints	Nil
6	备注 Remarks	Nil

ZGGG AD 2.9 地面活动引导和管制系统与标识

Surface movement guidance and control system and markings

1	航空器机位号码标记牌、滑行道引导线、航空器目视停靠引导系统的使用 Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands	Taxiing guidance signs at all intersections of TWY and RWY. Taxiing guidance signs at all holding positions. Aircraft stand identification sign boards at all stands. Guide lines at all TWYs. Guide lines at all aprons. Visual docking guidance system at aircraft stands Nr. 144-173, 236, 238, 238L, 238R, 240, 240L, 240R, 251-255, 257-279, 815, 816, 818, 819, 821, 822, 824-838, 910-914, 916, 917, 919, 920, 922-939, Marshalling assistance for other aircraft stands.	
2	跑道和滑行道标志及灯光 RWY and TWY marking and LGT	跑道标志 RWY markings	THR(RWY20R THR displaced), RWY designation, edge line, RWY center line, TDZ, aiming point
		跑道灯光 RWY lights	RTHL, WBAR, REDL, RCLL, RTZL(02L, 02R, 20L, 20R), RENL
		滑行道标志 TWY markings	Edge line, center line, enhanced TWY center line, No-entry(A3-A8, F3-F8, Y3, Y5-Y14, Y16, M3-M8, N4-N9, W3-W8), RWY holding position, intermediate holding position
		滑行道灯光 TWY lights	Edge line retroreflective markers(TWY T1, T2(BTN C & D), T3, T4(BTN B & E), Y, M(BTN M10 & Q10), Y17, Y19, M9, M10, P9-P14), edge line lights, center line lights, No-entry bar , RETILs, intermediate holding position lights
3	停止排灯和跑道警戒灯 Stop bars and runway guard lights	Runway guard lights	
4	其它跑道保护措施 Other runway protection measures	Nil	

5	备注 Remarks	The direction of following Taxiways without guidance signsboards, guidance signs on ground only: 1.Taxiway R from southwest to northeast, turning to Taxiway R and Taxiway L36. 2.Taxiway R from northwest to southeast, turning to Taxiway R and Taxiway L35. 3.Taxiway S2 from northeast to southwest, turning to Taxiway S1 and Taxiway J44. 4.Taxiway S2 from southeast to northwest, turning to Taxiway J35 and Taxiway S3. 5.Taxiway S3 from north to south, turning to Taxiway S2 and Taxiway J35. 6.Taxiway Q15 from south to north, turning to Taxiway Q11. 7.Taxiway U from south to north, turning to Taxiway T62. 8.Taxiway U from north to south, turning to Taxiway T61. 9.Taxiway W from north to south, turning to Taxiway T65. 10.Taxiway R4 from south to north, turning to Taxiway T65. 11.Taxiway R4 from north to south, turning to Taxiway T64. 12.Taxiway M from south to north, turning to Taxiway T65. 13.Taxiway M from north to south, turning to Taxiway T64. 14.Taxiway W5 from southeast to northwest, turning to Taxiway W and Taxiway L36. 15.Taxiway W6 from northeast to southwest, turning to Taxiway L36 and Taxiway W.
---	---------------	--

ZGGG AD 2.10 机场障碍物 Aerodrome obstacles

半径 15 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志, 灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
1	2	3	4	5	6
MT 001	MT	004/6036	67.5		
MT 002	MT	005/5754	65.3		
MT 003	MT	009/11045	131.7		
MT 004	MT	009/11586	140.4		
BLDG 005	BLDG	012/13926	349.4		
MT 006	MT	012/14223	363.7		
MT 007	MT	014/3975	56.4		RWY02L Take-off path
MT 008	MT	015/14561	421.7		
Moving OBST 009	Moving OBST	016/2435	24.7		RWY02L Take-off path Aircraft moving on TWY B1(west of Y)
MT 010	MT	016/14742	400.0		
MT 011	MT	017/13494	282.5		
MT 012	MT	017/14449	367.2		
BLDG 013	BLDG	018/3273	35.0		RWY02L Take-off path
MT 014	MT	018/11648	138.3		

半径 15 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志, 灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
MT 015	MT	018/14360	361.4		RWY21 GP INOP final approach
BLDG 016	BLDG	020/3063	31.4		RWY02L Take-off path
Moving OBST 017	Moving OBST	021/2679	28.0		RWY02L Take-off path Aircraft moving on TWY B2(east of Y)
BLDG 018	BLDG	021/2932	29.6		RWY02L Take-off path
BLDG 019	BLDG	026/3641	40.0		
BLDG 020	BLDG	026/4933	57.0		RWY02R Take-off path
MT 021	MT	027/5799	62.1		
BLDG 022	BLDG	030/3918	45.0		
BLDG 023	BLDG	030/10025	140.0		
Moving OBST 024	Moving OBST	032/2494	29.3		RWY02R Take-off path Aircraft moving on TWY B2(east of Y)
BLDG 025	BLDG	032/4048	55.0		
BLDG 026	BLDG	033/6419	95.0		
BLDG 027	BLDG	034/4153	57.0		
MT 028	MT	035/14037	401.8		
MT 029	MT	035/14838	457.0		RWY03 traditional departure, missed approach

半径 15 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志, 灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
BLDG 030	BLDG	036/4217	58.0		
BLDG 031	BLDG	038/8036	115.0		
MT 032	MT	038/10041	190.1		
MT 033	MT	038/12696	340.1		RWY03 PBN departure
MT 034	MT	042/12297	247.7		
TRANSMISSION _LINE 035	TRANSM MISSION_L INE	049/7444	144.3		
MT 036	MT	052/9224	215.6		Circling CAT C
Antenna 037	Antenna	057/3694	59.3		RWY03 Take-off path
BLDG 038	BLDG	064/2556	41.4		RWY03 Take-off path
BLDG 039	BLDG	072/2188	35.4		RWY03 Take-off path
MT 040	MT	128/12940	278.7		Surveillance Vectoring Sector Nr.1
MT 041	MT	131/12158	251.1		Circling CAT D
Control TWR 042	Control TWR	147/1473	86.0		
BLDG 043	BLDG	171/10255	160		RWY21 traditional, PBN departure
Antenna 044	Antenna	173/6397	54.7		

半径 15 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志, 灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
BLDG 045	BLDG	180/10385	119.0		
TRANSMISSION _LINE 046	TRANSMISSION_L INE	181/9310	91.6		RWY21 Take-off path
BLDG 047	BLDG	181/10283	108		RWY21 Take-off path
Antenna 048	Antenna	182/6970	57.6		RWY21 Take-off path
BLDG 049	BLDG	182/9991	103		RWY21 Take-off path
Moving OBST 050	Moving OBST	187/3591	27.7		RWY20L Take-off path Aircraft moving on TWY T61(west of M)
TRANSMISSION _LINE 051	TRANSMISSION_L INE	188/7869	76.6		
Moving OBST 052	Moving OBST	195/3468	26.9		RWY20L Take-off path Aircraft moving on TWY T61(west of M)
Antenna 053	Antenna	199/6570	49.7		
BLDG 054	BLDG	200/4020	46.0		RWY20R Take-off path
BLDG 055	BLDG	200/8128	98.0		RWY20L/20R Take-off path
Moving OBST 056	Moving OBST	201/2933	33.4		RWY20R Take-off path Aircraft moving on TWY Y20
BLDG 057	BLDG	201/3812	37.0		RWY20R Take-off path
BLDG 058	BLDG	201/8184	100.0		RWY20L/20R Take-off path

半径 15 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志, 灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
BLDG 059	BLDG	202/8262	111.0		RWY20R Take-off path
BLDG 060	BLDG	202/8331	115.0		RWY20R Take-off path
BLDG 061	BLDG	206/8695	110.0		RWY19L Take-off path
BLDG 062	BLDG	209/7473	86.0		RWY19L Take-off path
BLDG 063	BLDG	210/7745	94.7		RWY19L Take-off path
Pole 064	Pole	219/5201	36.8		
BLDG 065	BLDG	221/6569	57.0		RWY19L Take-off path
BLDG 066	BLDG	224/9499	113.0		
BLDG 067	BLDG	225/7351	70.0		RWY19R Take-off path
BLDG 068	BLDG	226/6484	57.0		
Moving OBST 069	Moving OBST	229/3809	26.2		RWY19L Take-off path Aircraft moving on TWY H1
MT 070	MT	238/4758	34.8		RWY19R Take-off path
BLDG 071	BLDG	244/4894	57.0		
BLDG 072	BLDG	245/4882	57.0		
BLDG 073	BLDG	246/5039	57.0		
BLDG 074	BLDG	247/5030	57.0		

半径 15 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志, 灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
BLDG 075	BLDG	256/1298	72.0	LGT	
Antenna 076	Antenna	270/9960	186.3	LGT	
Control TWR 077	Control TWR	277/1138	126.5	LGT	Circling CAT A
Antenna 078	Antenna	286/7255	162.1	LGT	Circling CAT B
Antenna 079	Antenna	304/4524	110.4	LGT	
BLDG 080	BLDG	328/4672	39.0		
BLDG 081	BLDG	331/4420	38.0		RWY01L Take-off path
BLDG 082	BLDG	332/4486	40.0		RWY01L Take-off path
Moving OBST 083	Moving OBST	335/2982	26.3		RWY01R Take-off path Aircraft moving on TWY E(north of T4)
MT 084	MT	335/3465	31.3		RWY01R Take-off path
BLDG 085	BLDG	335/4095	38.0		
MT 086	MT	335/5624	43.0		
BLDG 087	BLDG	337/4648	45.2		RWY01L Take-off path
BLDG 088	BLDG	339/7902	102.0		
MT 089	MT	342/3780	43.2		RWY01R Take-off path

半径 15 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志, 灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
BLDG 090	BLDG	343/4288	45.0		
BLDG 091	BLDG	343/4671	50.0		
BLDG 092	BLDG	344/4843	57.0		
BLDG 093	BLDG	349/4368	55.0		RWY01R Take-off path
MT 094	MT	351/5840	67.4		RWY01L Take-off path
MT 095	MT	359/5961	66.2		

半径 15 千米-50 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15 to 50km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志、灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
TOWER 096	TOWER	004/16328	481		
MT 097	MT	004/16331	468		RWY19R GP INOP final approach
MT 098	MT	006/56689	892		RWY21 PBN+ILS initial approach
MT 099	MT	008/22013	484		RWY21 traditional initial approach
MT 100	MT	010/38041	325		
MT 101	MT	014/15146	430		RWY20L GP INOP final approach

半径 15 千米-50 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15 to 50km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志、灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
MT 102	MT	015/18303	535		RWY19L/19R/20L/20R/21 traditional, PBN+ILS intermediate approach; Surveillance Vectoring Sector Nr.4
MT 103	MT	017/51237	488		RWY21 traditional initial approach
MT 104	MT	020/15868	494		RWY01L traditional departure; RWY02L traditional departure, traditional, PBN+ILS missed approach; RWY02R traditional, PBN+ILS missed approach
MT 105	MT	022/66954	1219		RWY19L/19R/20L/20R/21 traditional holding; Surveillance Vectoring Sector Nr.10
MT 106	MT	023/16044	477		
MT 107	MT	030/16000	436		
MT 108	MT	030/38747	348		
MT 109	MT	038/37941	464		
MT 110	MT	039/37112	498		
MT 111	MT	039/39017	524		
MT 112	MT	040/38688	593		RWY21 traditional initial approach
MT 113	MT	045/47861	578		

半径 15 千米-50 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15 to 50km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志、灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
MT 114	MT	050/118424	1436		RWY01L/01R/02L/02R/03 PBN arrival; Surveillance Vectoring Sector Nr.13
MT 115	MT	057/67284	1190		RWY19L/19R/20L/20R/21 traditional arrival; Surveillance Vectoring Sector Nr.8
MT 116	MT	064/59174	1211		RWY19L/19R/20L/20R/21 PBN arrival; Surveillance Vectoring Sector Nr.11
MT 117	MT	067/54558	1024		PBN sector
MT 118	MT	076/29851	607		
MT 119	MT	079/37885	798		Sector(CEN, POU); Surveillance Vectoring Sector Nr.6
MT 120	MT	080/31911	627		Sector(TAN, CON)
MT 121	MT	102/72161	1230		Sector(TAN, CON)
MT 122	MT	103/73279	1282		Surveillance Vectoring Sector Nr.9
MT 123	MT	129/18805	542		RWY21 PBN departure
MT 124	MT	139/15463	403		RWY21 traditional, PBN+ILS missed approach
Antenna 125	Antenna	165/18813	420		Surveillance Vectoring Sector Nr.2
TOWER 126	TOWER	177/43264	343		RWY03 traditional initial approach; Surveillance Vectoring Sector Nr.12
Antenna 127	Antenna	179/16203	261		

半径 15 千米-50 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15 to 50km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志、灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
GENERAL_UTIL ITY 128	GENERA L_UTILIT Y	181/27471	396		
Antenna 129	Antenna	181/31378	600	LGT	Sector(POU, CEN); Surveillance Vectoring Sector Nr.3
Antenna 130	Antenna	187/22982	401		RWY02L/02R/03 traditional, PBN+ILS intermediate approach
Antenna 131	Antenna	193/27919	253		RWY01R traditional intermediate approach
BLDG 132	BLDG	194/23613	213		
MT 133	MT	218/107804	809		Surveillance Vectoring Sector Nr.5
MT 134	MT	219/92405	805		Sector(POU, CEN)
MT 135	MT	249/77608	904		RWY01L/01R/02L/02R/03 traditional arrival
MT 136	MT	257/84816	1001		Surveillance Vectoring Sector Nr.7
MT 137	MT	276/19999	419		
MT 138	MT	319/18100	399		
MT 139	MT	332/21950	583		RWY01L traditional, PBN departure; RWY01L/01R PBN+ILS missed approach
MT 140	MT	339/36303	469		RWY21 traditional initial approach
MT 141	MT	340/38914	666		RWY19L/19R/20L/20R/21 traditional holding

半径 15 千米-50 千米内主要障碍物 (相对机场 ARP)

Obstacles within 15 to 50km of ARP

障碍物名称 或编号 Obstacle ID/ Designation	障碍物类 型 Obstacle type	障碍物位置 磁方位(°)/距离(m) Obstacle position MAG BRG(degree)/DIST(m)	标高或 (高) Elevation /(Height) (m)	障碍物标志、灯光 类型及颜色 Obstacle marking /Lighting Type & Colour	影响的飞行程序及 起飞航径区/备注 Flight procedure/take-off path area affected & Remarks
MT 142	MT	340/47002	779		
MT 143	MT	347/19047	463		RWY01L traditional, PBN departure; RWY01L/01R traditional missed approach
MT 144	MT	348/67299	902		
Remarks:					

ZGGG AD 2.11 提供的气象情报、气象观测和报告

Meteorological information provided & meteorological observations and reports

提供的气象情报

Meteorological information provided

1	相关气象台的名称 Associated MET Office	Guangzhou ATMB MET Center of CAAC
2	气象服务时间、服务时间以外的责任气象台 Hours of service/MET Office outside hours	H24
3	负责编发 TAF 的气象台、有效时段、发布间隔 Office responsible for TAF preparation/Periods of validity/Interval of issuance	Guangzhou ATMB MET Center of CAAC;9h, 30h;3h, 6h
4	趋势预报及发布间隔 Trend forecast/Interval of issuance	trend 30min
5	所提供的讲解或咨询服务 Briefing/Consultation provided	Briefing provided: P, T Consultation provided: P, T
6	飞行文件及其使用语言 Flight documentation/Language(s) used	Chart, International MET Codes, Abbreviated Plain Language Text;Ch,En
7	讲解或咨询服务时可利用的图表和其它信息 Charts and other information available for briefing or consultation	Synoptic charts, significant weather forecast charts, upper-air W/T charts, meteorological satellite and weather radar images, AWOS real-time data, SIGMET and AIRMET information, Aerodrome warnings, Numerical forecast product graph
8	提供气象情报的辅助设备 Supplementary equipment available for providing	MET Service Terminal

	information	
9	提供气象情报的空中交通服务单位 ATS units provided with information	TWR, APP, DEP
10	其他信息 Additional information	VOLMET: Operational hours(UTC) Frequency(MHZ) 0001-0800 8.849(13.285) 0800-1545 5.673(3.458) Consultation Tel: 86-20-86122571
气象观测和报告 Meteorological observations and reports		
1	机场观测类型与频率、自动观测设备 Type & frequency of observation /Automatic observation equipment	Half hourly plus special observation/Yes
2	气象报告类型及所包含的补充资料 Type of MET Report/Supplementary information included	METAR, SPECI
3	观测系统及安装位置 Observation system/Site(s)	RVR EQPT A: 113m W of RCL, 342m inward THR01R B: 112m W of RCL, 1799m inward THR01R C: 113m W of RCL, 342m inward THR19L D: 113m E of RCL, 342m inward THR02L E: 115m E of RCL, 1712m inward THR02L F: 118m E of RCL, 533m inward THR20R G: 115m E of RCL, 336m inward THR02R H: 115m E of RCL, 1500m inward THR02R J: 115m E of RCL, 318m inward THR20L K: 107m W of RCL, 340m inward THR01L L: 107m W of RCL, 1680m inward THR01L M: 107m W of RCL, 345m inward THR19R N: 107m E of RCL, 354m inward THR03 O: 107m E of RCL, 354m inward THR21 P: 107m E of RCL, 1760m inward THR03 SFC wind sensors 01L: 119m W of RCL, 340m inward THR01L 19R: 119m W of RCL, 357m inward THR19R 01L/19R center: 119m W of RCL, 1680m inward THR01L 01R: 110m W of RCL, 348m inward THR01R 19L: 110m W of RCL, 360m inward THR19L 01R/19L center: 110m W of RCL, 1809m inward THR01R 02L: 110m E of RCL, 348m inward THR02L 20R: 110m E of RCL, 552m inward THR20R 02L/20R center: 120m E of RCL, 1712m inward THR02L 02R: 120m E of RCL, 336m inward THR02R

		20L: 110m E of RCL, 338m inward THR20L 02R/20L center: 120m E of RCL, 1500m inward THR02R 03: 119m E of RCL, 378m inward THR03 21: 119m E of RCL, 378m inward THR21 03/21 center: 119m E of RCL, 1760m inward THR03 Ceilometer: 01L: 107m W of RCL, 352m inward THR01L 19R: 107m W of RCL, 357m inward THR19R 01R: 78m W of RCL, 330m outward THR01R 19L: 78m W of RCL, 330m outward THR19L 02L: 78m E of RCL, 330m outward THR02L 20R: 78m E of RCL, 330m outward THR20R 02R: 73m W of RCL, 320m outward THR02R 20L: 81m W of RCL, 320m outward THR20L 03: 107m E of RCL, 366m inward THR03 21: 107m E of RCL, 366m inward THR21
4	观测系统的工作时间 Hours of operation for meteorological observation system	H24
5	气候资料 Climatological information	Climatological tables AVBL
6	其他信息 Additional information	Nil

ZGGG AD 2.12 跑道物理特征 Runway physical characteristics

跑道号码 RWY Designator	真方位和 磁方位 TRUE & MAG BRG	跑道长宽 Dimensions of RWY(m)	跑道强度、跑道和停 止道道面 RWY strength/ Surface of RWY /SWY	跑道入口坐标、 跑道末端坐标、 跑道入口大地水 准面波幅 THR coordinates & RWY end coordinates & THR geoid undulation	跑道入口标高和 精密进近跑道接 地带最高标高 THR elevation & highest elevation of TDZ of precision APP RWY	跑道和停止道坡 度 Slope of RWY/SWY
1	2	3	4	5	6	7
01L	014.00° GEO 017° MAG	3400×45	PCR 890/R/A/W/T CONC/-	Nil	THR 13.0m TDZ 13.0m	0%
19R	194.00° GEO 197° MAG	3400×45	PCR 890/R/A/W/T CONC/-	Nil	THR 13.0m TDZ 13.0m	0%
01R	013.99° GEO 017° MAG	3600×45	PCR 1130/R/A/W/T CONC/-	Nil	THR 12.4m TDZ 12.8m	0.04%(920m)/0% (760m)/0.03%(64 0m)/0%(1280m)

跑道号码 RWY Designator	真方位和 磁方位 TRUE & MAG BRG	跑道长宽 Dimensions of RWY(m)	跑道强度、跑道和停 止道道面 RWY strength/ Surface of RWY /SWY	跑道入口坐标、 跑道末端坐标、 跑道入口大地水 准面波幅 THR coordinates & RWY end coordinates & THR geoid undulation	跑道入口标高和 精密进近跑道接 地带最高标高 THR elevation & highest elevation of TDZ of precision APP RWY	跑道和停止道坡 度 Slope of RWY/SWY
1	2	3	4	5	6	7
19L	193.99° GEO 197° MAG	3600×45	PCR 1130/R/A/W/T CONC/-	Nil	THR 13.0m TDZ 13.0m	0%(1280m)/-0.03 %(640m)/0%(760 m)/-0.04%(920m)
02L	014.00° GEO 017° MAG	3800×60	PCR 1210/R/A/W/T CONC/-	Nil	THR 13.8m TDZ 14.4m	0.07%(1960m)/-0 .11%(1120m)/0% (120m)/0.12%(60 0m)
20R	194.00° GEO 197° MAG	3800×60	PCR 1210/R/A/W/T CONC/-	Nil	THR 14.7m DTHR 14.5m TDZ 14.5m	-0.12%(600m)/0 %(120m)/0.11% (1120m)/-0.07%(1 960m)
02R	014.00° GEO 017° MAG	3800×60	PCR 1170/R/A/W/T CONC/-	Nil	THR 13.3m TDZ 14.0m	0.08%(1100m)/0. 05%(815m)/0%(8 05m)/-0.04%(496 m)/-0.14%(584m)
20L	194.00° GEO 197° MAG	3800×60	PCR 1170/R/A/W/T CONC/-	Nil	THR 13.5m TDZ 14.6m	0.14%(584m)/0.0 4%(496m)/0%(80 5m)/-0.05%(815 m)/-0.08%(1100 m)
03	014.00° GEO 017° MAG	3600×45	PCR 890/R/A/W/T CONC/-	Nil	THR 14.5m TDZ 14.5m	-0.27%(562m)/0 %(2418m)/0.26% (620m)
21	194.00° GEO 197° MAG	3600×45	PCR 890/R/A/W/T CONC/-	Nil	THR 14.6m TDZ 14.6m	-0.26%(620m)/0 %(2418m)/0.27% (562m)
跑道号码 RWY Designator	停止道长宽 SWY dimensions (m)	净空道长宽 CWY dimensions (m)	升降带长宽 Strip dimensions (m)	跑道端安全区 长宽 RESA dimensions (m)	拦阻系统的 位置及描述 Location & Description of arresting system	无障碍物区 OFZ

1	8	9	10	11	12	13
01L	Nil	Nil	3520×280	240×150	Nil	-
19R	Nil	Nil	3520×280	240×150	Nil	-
01R	Nil	Nil	3720×300	240×150	Nil	-
19L	Nil	Nil	3720×300	240×150	Nil	-
02L	Nil	Nil	3920×300	240×150	Nil	-
20R	Nil	Nil	3920×300	240×150	Nil	-
02R	Nil	Nil	3920×300	240×150	Nil	-
20L	Nil	Nil	3920×300	240×150	Nil	-
03	Nil	Nil	3720×280	240×150	Nil	-
21	Nil	Nil	3720×280	240×150	Nil	-

Remarks: 01L/19R: RWY shoulder: 7.5m on each side.

01R/19L: RWY shoulder: 7.5m on each side.

02L/20R: RWY shoulder: 7.5m on each side;

THR20R displaced 200m inwards.

02R/20L: RWY shoulder: 7.5m on each side.

03/21: RWY shoulder: 7.5m on each side;

1.RWY01L/19R, 01R/19L, 02L/20R, 02R/20L and 03/21 grooved: 6mm×6mm×32mm.

2.Distance between RCL of RWY01R/19L and RCL of RWY02L/20R is 2200m; RWY19L end is 400m south of RWY20R end; RWY01R end is 600m south of RWY02L end.

3.Distance between RCL of RWY02R/20L and RCL of RWY02L/20R is 400m; RWY20L end is 600m south of RWY20R end; RWY02R end is 600m south of RWY02L end.

4.Distance between RCL of RWY01L/19R and RCL of RWY01R/19L is 915m; RWY19R end is 200m north of RWY19L end, RWY01L end is flush with RWY01R end.

5.Distance between RCL of RWY03/21 and RCL of RWY02R/20L is 1530m; RWY21 end is 1300m south of RWY20L end; RWY03 end is 1500m south of RWY02R end.

ZGGG AD 2.13 公布距离 Declared distances

跑道号码 RWY Designator	可用起飞滑跑距离 TORA(m)	可用起飞距离 TODA(m)	可用加速停止距离 ASDA(m)	可用着陆距离 LDA(m)	备注 Remarks
1	2	3	4	5	6
01L	3400	3400	3400	3400	Nil
01L	2940	2940	2940	-	FM N10
19R	3400	3400	3400	3400	Nil
19R	3180	3180	3180	-	FM N2
19R	2870	2870	2870	-	FM N3
01R	3600	3600	3600	3600	Nil
01R	3380	3380	3380	-	FM F9
19L	3600	3600	3600	3600	Nil

跑道号码 RWY Designator	可用起飞滑跑距离 TORA(m)	可用起飞距离 TODA(m)	可用加速停止距离 ASDA(m)	可用着陆距离 LDA(m)	备注 Remarks
19L	3380	3380	3380	-	FM F2
02L	3800	3800	3800	3800	Nil
02L	3580	3580	3580	-	FM A10
20R	3800	3800	3800	3600	THR displaced 200m inwards
20R	3580	3580	3580	-	FM A2
02R	3800	3800	3800	3800	Nil
02R	3500	3500	3500	-	FM Y17
02R	3300	3300	3300	-	FM M9
20L	3800	3800	3800	3800	Nil
20L	3500	3500	3500	-	FM Y4
03	3600	3600	3600	3600	Nil
03	3380	3380	3380	-	FM W9
21	3600	3600	3600	3600	Nil
21	3380	3380	3380	-	FM W2

ZGGG AD 2.14 进近和跑道灯光 Approach and runway lighting

跑道 号码 RWY Desig nator	进近灯 类型、长 度、强度 APCH LGT type/ LEN/ /INTST	入口灯 颜色、翼 排灯 THR LGT colour/ WBAR	目视进近坡度 指示系统类 型、位置、仰 角、跑道入口 最低眼高 Type of VASIS/Position /Angle/MEHT	接地 带 灯长 度 TDZ LGT LEN	跑道中线灯长度、 间隔、颜色、强度 RWY center line LGT LEN/Spacing /Colour/INTST	跑道边灯长度、间 隔、颜色、强度 RWY edge LGT LEN/Spacing /Colour/INTST	跑道末端灯 颜色 RWY end LGT colour	停止道灯长 度、颜色 SWY LGT LEN /Colour
1	2	3	4	5	6	7	8	9
01L	PALS CAT I SFL 900 m LIH	GREEN Yes	PAPI LEFT 447m inward THR01L 3° 21.2m	Nil	3400 m spacing 15m 0-2500m, WHITE 2500-3100m, RED/WHITE 3100-3400m, RED VRB LIH	3400 m spacing 60m 0-2800m, WHITE 2800-3400m, YELLOW VRB LIH	RED	Nil

跑道 号码 RWY Desig nator	进近灯 类型、长 度、强度 APCH LGT type/ LEN/ /INTST	入口灯 颜色、翼 排灯 THR LGT colour/ WBAR	目视进近坡度 指示系统类 型、位置、仰 角、跑道入口 最低眼高 Type of VASIS/Position /Angle/MEHT	接地 带 灯长 度 TDZ LGT LEN	跑道中线灯长度、 间隔、颜色、强度 RWY center line LGT LEN/Spacing /Colour/INTST	跑道边灯长度、间 隔、颜色、强度 RWY edge LGT LEN/Spacing /Colour/INTST	跑道末端灯 颜色 RWY end LGT colour	停止道灯长 度、颜色 SWY LGT LEN /Colour
19R	PALS CAT I SFL 900 m LIH	GREEN Yes	PAPI LEFT 451m inward THR19R 3° 21.2m	Nil	3400 m spacing 15m 0-2500m, WHITE 2500-3100m, RED/WHITE 3100-3400m, RED VRB LIH	3400 m spacing 60m 0-2800m, WHITE 2800-3400m, YELLOW VRB LIH	RED	Nil
01R	PALS CAT I SFL 900 m LIH	GREEN Yes	PAPI LEFT 420m inward THR01R 3° 21.0m	Nil	3600 m spacing 30m 0-2700m, WHITE 2700-3300m, RED/WHITE 3300-3600m, RED VRB LIH	3600 m spacing 60m 0-3000m, WHITE 3000-3600m, YELLOW VRB LIH	RED	Nil
19L	PALS CAT I SFL 900 m LIH	GREEN Yes	PAPI LEFT 420m inward THR19L 3° 20.3m	Nil	3600 m spacing 30m 0-2700m, WHITE 2700-3300m, RED/WHITE 3300-3600m, RED VRB LIH	3600 m spacing 60m 0-3000m, WHITE 3000-3600m, YELLOW VRB LIH	RED	Nil
02L	PALS CAT II SFL 900 m LIH	GREEN Yes	PAPI LEFT 440m inward THR02L 3° 21.7m	900 m	3800 m spacing 15m 0-2900m, WHITE 2900-3500m, RED/WHITE 3500-3800m, RED VRB LIH	3800 m spacing 60m 0-3200m, WHITE 3200-3800m, YELLOW VRB LIH	RED	Nil

跑道 号码 RWY Desig nator	进近灯 类型、长 度、强度 APCH LGT type/ LEN/ /INTST	入口灯 颜色、翼 排灯 THR LGT colour/ WBAR	目视进近坡度 指示系统类 型、位置、仰 角、跑道入口 最低眼高 Type of VASIS/Position /Angle/MEHT	接地 带 灯长 度 TDZ LGT LEN	跑道中线灯长度、 间隔、颜色、强度 RWY center line LGT LEN/Spacing /Colour/INTST	跑道边灯长度、间 隔、颜色、强度 RWY edge LGT LEN/Spacing /Colour/INTST	跑道末端灯 颜色 RWY end LGT colour	停止道灯长 度、颜色 SWY LGT LEN /Colour
20R	PALS CAT II SFL 900 m LIH	GREEN Yes	PAPI LEFT 446m inward DTHR20R 3° 20.8m	900 m	3600 m spacing 15m 0-2700m, WHITE 2700-3300m, RED/WHITE 3300-3600m, RED VRB LIH	3800 m spacing 60m 0-200m, RED 200-3200m, WHITE 3200-3800m, YELLOW VRB LIH	RED	Nil
02R	PALS CAT II SFL 900 m LIH	GREEN Yes	PAPI LEFT 457m inward THR02R 3° 21.8m	900 m	3800 m spacing 15m 0-2900m, WHITE 2900-3500m, RED/WHITE 3500-3800m, RED VRB LIH	3800 m spacing 60m 0-3200m, WHITE 3200-3800m, YELLOW VRB LIH	RED	Nil
20L	PALS CAT II SFL 900 m LIH	GREEN Yes	PAPI LEFT 462m inward THR20L 3° 22.3m	900 m	3800 m spacing 15m 0-2900m, WHITE 2900-3500m, RED/WHITE 3500-3800m, RED VRB LIH	3800 m spacing 60m 0-3200m, WHITE 3200-3800m, YELLOW VRB LIH	RED	Nil
03	PALS CAT I SFL 900 m LIH	GREEN Yes	PAPI LEFT 476m inward THR03 3° 21.1m	Nil	3600 m spacing 15m 0-2700m, WHITE 2700-3300m, RED/WHITE 3300-3600m, RED VRB LIH	3600 m spacing 60m 0-3000m, WHITE 3000-3600m, YELLOW VRB LIH	RED	Nil

跑道 号码 RWY Desig nator	进近灯 类型、长 度、强度 APCH LGT type/ LEN/ /INTST	入口灯 颜色、翼 排灯 THR LGT colour/ WBAR	目视进近坡度 指示系统类 型、位置、仰 角、跑道入口 最低眼高 Type of VASIS/Position /Angle/MEHT	接地 带 灯长 度 TDZ LGT LEN	跑道中线灯长度、 间隔、颜色、强度 RWY center line LGT LEN/Spacing /Colour/INTST	跑道边灯长度、间 隔、颜色、强度 RWY edge LGT LEN/Spacing /Colour/INTST	跑道末端灯 颜色 RWY end LGT colour	停止道灯长 度、颜色 SWY LGT LEN /Colour
21	PALS CAT I SFL 900 m LIH	GREEN Yes	PAPI LEFT 479m inward THR21 3° 21.2m	Nil	3600 m spacing 15m 0-2700m, WHITE 2700-3300m, RED/WHITE 3300-3600m, RED VRB LIH	3600 m spacing 60m 0-3000m, WHITE 3000-3600m, YELLOW VRB LIH	RED	Nil
Remarks:								

ZGGG AD 2.15 其它灯光,备份电源 Other lighting, secondary power supply

1	机场灯标或识别灯标位置、特性和工作时间 ABN/IBN location, characteristics and hours of operation	Nil
2	着陆方向标和风向标位置和灯光 LDI/ WDI location and LGT	WDI: 01L: 98m W of RCL, 447m inward THR01L; 19R: 98m E of RCL, 451m inward THR19R; 01R: 100m W of RCL, 420m inward THR01R; 19L: 113m E of RCL, 420m inward THR19L; 02L: 113m W of RCL, 440m inward THR02L; 20R: 100m E of RCL, 473m inward THR20R; 02R: 105m W of RCL, 457m inward THR02R; 20L: 105m E of RCL, 462m inward THR20L; 03: 98m W of RCL, 476m inward THR03; 21: 98m E of RCL, 479m inward THR21.
3	滑行道边灯和滑行道中线灯 TWY edge and center line lighting	All TWYs: green center line lights, blue retroreflective markers, blue edge line lights
4	备份电源及转换时间 Secondary power supply/Switch-over time	Secondary power supply available/1s. Diesel generator set/ < 15s. UPS/<1s.
5	备注 Remarks	Nil

ZGGG AD 2.16 直升机着陆区域 Helicopter landing area

1	TLOF 坐标或 FATO 入口坐标及大地水准面波幅 Coordinates TLOF or THR of FATO, Geoid undulation	Nil
2	TLOF 和 (或) FATO 标高 TLOF and/or FATO elevation	Nil
3	TLOF 和 FATO 区域范围、道面、强度和标志 TLOF and FATO area dimensions,surface, strength, marking	Nil
4	FATO 的真方位和磁方位 True and MAG BRG of FATO	Nil
5	公布距离 Declared distance available	Nil
6	进近灯光和 FATO 灯光 APP and FATO lighting	Nil
7	备注 Remarks	Nil

ZGGG AD 2.17 空中交通服务空域 ATS airspace

空域名称和水平范围 Designation and lateral limits		垂直范围 Vertical limits	空域分类 Airspace class	空中交通服务单位呼号和使用语言 ATS unit callsign Language	工作时间 Hours of applicability	备注 Remarks
1	2	3	4	5	6	7
Main Fuel Dumping area		Above 4000m				See Fuel Dumping Area Chart
Alternative Fuel Dumping area		Above 4000m				See Fuel Dumping Area Chart
Altimeter setting region and TL/TA	Same as Guangzhou APP	TL 3300(QNH≥980hPa) 3600(QNH < 980hPa) TA 2700				

ZGGG AD 2.18 空中交通服务通信设施 ATS communication facilities

服务名称 Service designation	呼号 Callsign	频率 Frequency (MHz)	卫星话音通信 号码 SATVOICE number	登录地址 Logon address	工作时间 Hours of operation	备注 Remarks
1	2	3	4	5	6	7
ATIS		127.0 (Chinese)			H24	D-ATIS available
		128.6 (English)			H24	D-ATIS available
APP	Guangzhou Approach	APP01:126.55 (127.75)			H24	
		APP02:119.7 (127.75)			by ATC	
		APP03:126.35 (119.6)			by ATC	
		APP04:121.05 (124.2)			by ATC	
		APP05:120.4 (124.2)			by ATC	
		APP06:121.175 (127.75)			by ATC	
		APP07:119.425 (124.2)			by ATC	
		APP08:125.6 (124.2)			by ATC	
TWR	Baiyun Tower	TWR(01L/19R):118. 8 (118.875)			HO	West two Tower
		TWR(01R/19L):118. 325 (118.875)			HO	West one Tower
		TWR(02L/20R):123 .55 (118.875)			HO	East one Tower
		TWR(02R/20L):118. 25 (118.875)			HO	East two Tower
		TWR(03/21):118.1 (118.875)			by ATC	East three Tower
GND	Baiyun Ground	GND(East one):121.75 (122.125)			H24	East one Ground

服务名称 Service designation	呼号 Callsign	频率 Frequency (MHz)	卫星语音通信 号码 SATVOICE number	登录地址 Logon address	工作时间 Hours of operation	备注 Remarks
1	2	3	4	5	6	7
		GND(East two):121.6 (122.125)			H24	East two Ground
		GND(East three):121.55 (122.125)			HO	East three Ground
		GND(West one):121.85 (122.125)			HO	West one Ground
		GND(West two):121.65 (122.125)			HO	West two Ground
APN	Baiyun Apron	121.975			HO	Apron Delivery
		APN(East one):121.825 (121.975)			HO	East one Apron
		APN(East two):121.625 (121.7)			HO	East two Apron
		APN(East three):121.7 (121.625)			H24	East three Apron
		APN(West):121.775 (121.975)			H24	West Apron
Delivery	DELIVERY	DELIVERY01:121.95			H24	DCL available
		DELIVERY02:122.175			by ATC	DCL available Use for departure flight on apron(east of TWY Q), except FedEx apron & STAG apron, it will be merged into DELIVERY01 when not open.
EMG		121.5			H24	

ZGGG AD 2.19 无线电导航和着陆设施 Radio navigation and landing aids

设施名称及类型、磁差、支持运行类别、 VOR/ILS 磁偏角 Name and type of aid, VAR, Type of supported OPS, Declination of VOR/ILS	识别 ID	频率、波道 Frequency/ Channel number	工作 时间 Hours of operation	发射天线坐标 及相对位置 Coordinates of transmitting antenna/ Position	DME 发射 天线标高 Elevation of DME transmitting antenna	备注 Remarks
1	2	3	4	5	6	7
Cencun VOR/DME	CEN	114.6 MHz CH 93X	H24	N23°09.1' E113°25.0' 160° MAG/ 28960m FM ARP	108 m	
Conghua VOR/DME	CON	113.0 MHz CH 77X	H24	N23°35.3' E113°35.2' 055° MAG/ 35890m FM ARP	77 m	For DME: Beyond 16NM on R011° for HLDG, beyond 29NM on R320° for STAR U/S.
Gaoyao VOR/DME	GYA	116.5 MHz CH 112X	H24	N23°04.2' E112°29.2'		For VOR/DME: Beyond 21NM on R093°, beyond 23NM on R097°, R320°-R358° clockwise U/S.
Longmen VOR/DME	LMN	116.3 MHz CH 110X	H24	N23°38.9' E114°19.6'	39 m	
Pingzhou VOR/DME	POU	114.1 MHz CH 88X	H24	N23°01.3' E113°11.4' 199° MAG/ 43000m FM ARP	27 m	For VOR/DME: Beyond 22NM on R009° for SID U/S; For VOR: Beyond 33NM on R339° for SID U/S; For DME: Beyond 25NM on R339° for SID U/S.
Shilong VOR/DME	SHL	115.7 MHz CH 104X		N23°05.5' E113°51.0'		U/S.

设施名称及类型、磁差、支持运行类别、VOR/ILS 磁偏角 Name and type of aid, VAR, Type of supported OPS, Declination of VOR/ILS	识别 ID	频率、波道 Frequency/ Channel number	工作 时间 Hours of operation	发射天线坐标 及相对位置 Coordinates of transmitting antenna/ Position	DME 发射 天线标高 Elevation of DME transmitting antenna	备注 Remarks
Yingde VOR/DME	YIN	113.5 MHz CH 82X	H24	N24°11.4' E113°24.9'	167 m	For VOR/DME: Beyond 30NM on R184° for SID, beyond 30NM on R185° for SID, beyond 31NM on R189° for SID U/S; For DME: Beyond 26NM on R199° for SID, beyond 39NM on R218° for SID U/S.
Yuantan VOR/DME	TAN	112.5 MHz CH 72X	H24	N23°40.1' E113°14.5' 350°MAG/ 31550m FM ARP	184 m	
NDB	FO	410 kHz		197°MAG/ 29050m FM ARP		U/S
LOC 01L ILS CAT I	IGW	109.5 MHz		017°MAG/310m FM RWY01L end		Coverage 25NM
GP 01L		332.6 MHz		125m E of RCL, 318m inward THR01L		Angle 3° , RDH 16.5 m Coverage 10NM
DME 01L	IGW	CH 32X (109.5 MHz)			17m	Co-located with GP 01L
LOC 19R ILS CAT I	IKU	108.95 MHz		197°MAG/310m FM RWY19R end		Beyond 20NM of front course U/S
GP 19R		329.15 MHz		125m W of RCL, 315m inward THR19R		Angle 3° , RDH 16.6 m Coverage 16.6NM Beyond +5° of front course U/S
DME 19R	IKU	CH 26Y (108.95 MHz)			18m	Co-located with GP 19R
LOC 01R ILS CAT I	IOO	109.3 MHz		017°MAG/340m FM RWY01R end		Coverage 25NM

设施名称及类型、磁差、支持运行类别、 VOR/ILS 磁偏角 Name and type of aid, VAR, Type of supported OPS, Declination of VOR/ILS	识别 ID	频率、波道 Frequency/ Channel number	工作时间 Hours of operation	发射天线坐标及相对位置 Coordinates of transmitting antenna/ Position	DME 发射 天线标高 Elevation of DME transmitting antenna	备注 Remarks
GP 01R		332.0 MHz		122m W of RCL, 318m inward THR01R		Angle 3° , RDH 16.7 m Coverage 10NM
DME 01R	IOO	CH 30X (109.3 MHz)			20m	Co-located with GP 01R
LOC 19L ILS CAT I	IPP	111.5 MHz		197°MAG/340m FM RWY19L end		Beyond 20NM of front course U/S
GP 19L		332.9 MHz		122m W of RCL, 323m inward THR19L		Angle 3° , RDH 17 m Coverage 17NM Beyond +3° of front course U/S
DME 19L	IPP	CH 52X (111.5 MHz)			18m	Co-located with GP 19L
LOC 02L ILS CAT I	IBB	110.75 MHz		017°MAG/310m FM RWY02L end		Coverage 25NM
GP 02L		330.05 MHz		130m E of RCL, 317m inside THR02L		Angle 3° , RDH 16.1 m Coverage 10NM
DME 02L	IBB	CH 44Y (110.75 MHz)			20m	Co-located with GP 02L
LOC 20R ILS CAT I	IAA	110.75 MHz		197°MAG/310m FM RWY20R end		Beyond 22NM of front course U/S
GP 20R		330.05 MHz		130m E of RCL, 328m inward DTHR20R		Angle 3° , RDH 17.2 m Beyond 14.3NM of front course U/S Below 1.60°U/S
DME 20R	IAA	CH 44Y (110.75 MHz)			20m	Co-located with GP 20R
IM 02R		75 MHz		197°MAG/340m FM THR02R		
LOC 02R ILS CAT I	IDM	108.5 MHz		017°MAG/310m FM RWY02R end		Beyond +/- 4°of 17NM-25NM U/S Beyond +32°of front course U/S

设施名称及类型、磁差、支持运行类别、VOR/ILS 磁偏角 Name and type of aid, VAR, Type of supported OPS, Declination of VOR/ILS	识别 ID	频率、波道 Frequency/ Channel number	工作 时间 Hours of operation	发射天线坐标 及相对位置 Coordinates of transmitting antenna/ Position	DME 发射 天线标高 Elevation of DME transmitting antenna	备注 Remarks
GP 02R		329.9 MHz		130m E of RCL, 305m inward THR02R		Angle 3° , RDH 15 m Coverage 10NM
DME 02R	IDM	CH 22X (108.5 MHz)				Co-located with GP 02R
IM 20L		75 MHz		017°MAG/340m FM THR20L		
LOC 20L ILS CAT I	IXL	111.9 MHz		197°MAG/310m FM RWY20L end		Beyond 20NM of front course U/S
GP 20L		331.1 MHz		130m E of RCL, 303m inward THR20L		Angle 3° , RDH 16.5 m Coverage 16.6NM Below 1.65°U/S
DME 20L	IXL	CH 56X (111.9 MHz)				Co-located with GP 20L Beyond 18NM U/S
LOC 03 ILS CAT I	IYW	111.35 MHz		017°MAG/310m FM RWY03 end		Coverage 25NM
GP 03		332.15 MHz		125m E of RCL, 322m inward THR03		Angle 3° , RDH 16.7 m Coverage 15NM
DME 03	IYW	CH 50Y (111.35 MHz)			15m	Co-located with GP 03
LOC 21 ILS CAT I	IFX	110.35 MHz		197°MAG/310m FM RWY21 end		Beyond 22NM of front course U/S
GP 21		334.85 MHz		125m E of RCL, 322m inward THR21		Angle 3° , RDH 16.5 m Coverage 13NM
DME 21	IFX	CH 40Y (110.35 MHz)			16m	Co-located with GP 21

ZGGG AD 2.20 本场规定**1. 机场使用规定**

1.1 禁止未安装二次雷达应答机的航空器起降。

1.2 航空器在本场推出开车及地面滑行时，须开启应答机且应答机不应向外报告高度，进入停机位后，须关闭应答机。

1.3 本场不接收运动飞机、滑翔机、载人气球、滑翔伞、飞艇等航空器。

1.4 所有技术试飞、表演飞行需事先向机场管理机构申请，并在得到空中交通管制部门批准后方可进行。

1.5 本场可供 A380-800 及其以下机型使用。

2. 跑道和滑行道的使用

2.1 跑道运行规则：

2.1.1 向北运行：RWY01L 主要用于进场；RWY01R 主要用于离场；RWY02L 主要用于离场；RWY02R 主要用于进场；RWY03 进、离场混合运行。

向南运行：RWY19R 主要用于进场；RWY19L 主要用于离场；RWY20R 主要用于离场；RWY20L 主要用于进场；RWY21 进、离场混合运行。

2.1.2 平行跑道同时仪表运行规则：

2.1.2.1 广州白云机场实施平行跑道同时仪表试验运

ZGGG AD 2.20 Local aerodrome regulations**1. Airport operations regulations**

1.1 Takeoff/landing of aircraft without SSR transponder are forbidden.

1.2 Transponder shall be turned on and shall not report its altitude to public while aircraft is taxiing or being pushed back. Aircraft shall turn off the transponder after entering the stand.

1.3 Sport aircraft, glider, manned balloon, paraglider and airship are not accepted.

1.4 Each and every technical test flight and display flight shall be filed in advance and conducted only after clearance has been obtained from ATC.

1.5 Maximum aircraft to be available: A380 and equivalent.

2. Use of runways and taxiways

2.1 General rules for the use of runways:

2.1.1 Northbound Operations: RWY01L mainly for arrivals; RWY01R mainly for departures; RWY02L mainly for departures; RWY02R mainly for arrivals; RWY03 mixed arrivals/departures.

Southbound Operations: RWY19R mainly for arrivals; RWY19L mainly for departures; RWY20R mainly for departures; RWY20L mainly for arrivals; RWY21 mixed arrivals/departures.

2.1.2 Instrument operating rules for parallel runways:

2.1.2.1 Guangzhou Baiyun Airport has implemented

行, ATC 将根据空中流量和运行条件, 以满足下列条件作为前提, 选择运行模式:

a. 跑道 01L/19R 与 01R/19L, 同时运行时采用隔离平行运行模式, 跑道 01L/19R 用于落地, 01R/19L 用于起飞。

b. 跑道 01L/19R 与 02L/20R、02R/20L、03/21 可采用隔离平行运行、独立平行离场、相关平行仪表进近、独立平行仪表进近模式。

c. 跑道 01R/19L 与 02L/20R、02R/20L、03/21 可采用隔离平行运行、独立平行离场、相关平行仪表进近、独立平行仪表进近模式。

d. 跑道 02L/20R 与 03/21 可采用隔离平行运行、独立平行离场、相关平行仪表进近、独立平行仪表进近模式。

e. 跑道 02R/20L 与 03/21 可采用隔离平行运行、独立平行离场、相关平行仪表进近、独立平行仪表进近模式。

simultaneous instrument approach experiment

operations for parallel runways. ATC will select the

operational mode based on air traffic and operational conditions, under the premise of meeting the following requirements:

a. When Runways 01L/19R and 01R/19L operate simultaneously, segregated operations shall be used with Runway 01L/19R for arrivals and Runway 01R/19L for departures.

b. Runway 01L/19R with Runway 02L/20R, 02R/20L, or 03/21 may be operated in any of the following modes: segregated operations, independent parallel instrument departures, dependent parallel instrument approaches, or independent parallel instrument approaches.

c. Runways 01R/19L with Runway 02L/20R, 02R/20L, or 03/21 may be operated in any of the following modes: segregated operations, independent parallel instrument departures, dependent parallel instrument approaches, or independent parallel instrument approaches.

d. Runways 02L/20R and 03/21 may be operated in any of the following modes: segregated operations, independent parallel instrument departures, dependent parallel instrument approaches, or independent parallel instrument approaches.

e. Runways 02R/20L and 03/21 may be operated in any of the following modes: segregated operations, independent parallel instrument departures, dependent parallel instrument approaches, or independent parallel

2.1.2.2 实施多跑道平行进近时,管制员在指挥航空器转向五边前,会根据流量指挥机组改用另一条落地跑道进近,机组在下降过程中应做好充分准备,如不能接受更改跑道,机组需及时报告,管制员根据空中情况决定航空器是否继续进近。

2.1.2.3 在实施独立平行仪表进近的航空器进入非侵入区 (NTZ) 时,进近 (雷达监控) 管制员会立即在塔台频率里超控塔台管制员的正常指令指挥进近航空器进行紧急避让。当其他航空器驾驶员在塔台频率里听到这样的指挥时,应尽可能在不影响 (雷达监控) 管制员的指令前提下与塔台管制员进行通信。

2.1.2.4 本场以及本场附近上空恶劣的天气对平行跑道的运行造成影响时,ATC 会将跑道混合运行模式降为半混合运行、隔离运行、单跑道运行。

2.1.3 为减少波道占用时间,航空器起飞离地后自行与塔台管制席位脱波 (不需要通话脱波),塔台将在 ATC 许可中明确脱波后应该联系的离场管制频率。

instrument approaches.

2.1.2.2 During multiple parallel runway approaches, controllers will instruct aircraft to switch to another landing runway based on traffic flow before turning onto final approach. Flight crews shall make full preparations during descent. If unable to accept the runway change, crews must report immediately, and controllers will determine whether the aircraft continues the approach based on prevailing conditions.

2.1.2.3 When an aircraft conducting independent parallel instrument approaches enters the No Transgression Zone(NTZ), the approach (radar monitoring) controller will immediately override the tower controller's normal instructions on the tower frequency to direct the approaching aircraft to take emergency avoidance action. When other aircraft pilots hear such instructions on the tower frequency, they should communicate with the tower controller as much as possible without affecting the (radar monitoring)controller's instructions.

2.1.2.4 When severe weather at the Guangzhou Baiyun Airport or in the surrounding airspace affects the operation of parallel runways, ATC will switch the operational mode to one of the following: semi-mixed operations, segregated operations, or single runway operations.

2.1.3 In order to avoid frequency congestion, pilot shall leave TWR frequency without radiotelephony instruction from controller as soon as airborne and

	contact APP immediately on the frequency assigned by ATC clearance.
2.1.4 地面风与跑道转换程序: 在转换使用跑道方向过程中, 短时使用跑道顺风分量超过 3.5m/s 但不大于 5m/s 时, 管制员收到该信息应及时通知相关航空器的驾驶员。航空器驾驶员应根据机型性能或者运行手册, 决定是否使用管制员安排的顺风跑道起飞或者着陆, 并将决定通知管制员。	2.1.4 When aircraft change direction of runway in use, if downwind speed is more than 3.5m/s and not exceeding 5m/s for short time, ATC controller shall inform flight crew. According to aircraft performance or operation handbook, pilot shall decide whether aircraft will take off or land on downwind runway allocated, then inform ATC controller.
2.2 跑道穿越规则	2.2 RWY crossing rules:
2.2.1 穿越跑道需按照管制员指令滑行至跑道等待点外等待。	2.2.1 Taxi following the instruction of ATC Control to the holding position and hold short of RWY;
2.2.2 收到穿越指令后需尽快实施穿越, 不得延误, 如有疑问请在穿越前证实。	2.2.2 Request TWR Control for crossing clearance; verify any questions prior to crossing.
2.2.3 航空器驾驶员需完整复诵所有跑道外等待和穿越跑道指令, 穿越结束后需报告“已脱离跑道”。	2.2.3 Repeat all the ATC instructions for clarity, then put in practice as soon as possible; finally, report to TWR Control 'RWY vacated'.
2.2.4 航空器沿 M1-Y2、P10-P9、P14-P13 由东向西穿越 02R/20L 跑道后, 在 Y 滑行道前确认位置, 然后按照管制员指令滑行, 避免越过 Y 滑行道侵入 02L/20R 跑道。	2.2.4 After crossing RWY02R/20L from east to west along M1-Y2, P10-P9, and P14-P13, ACFT shall confirm its position in front of TWY Y and taxi as instructed by ATC to avoid crossing TWY Y into RWY02L/20R.
2.2.5 航空器沿 P1-P2、P3-P4、A10-Y15 由西向东穿越 02L/20R 跑道后, 在 Y 滑行道前确认位置, 然后按照管制员指令滑行, 避免越过 Y 滑行道侵入 02R/20L 跑道。	2.2.5 After crossing RWY02L/20R from west to east along P1-P2, P3-P4 and A10-Y15, ACFT shall confirm its position in front of TWY Y, and then taxi as instructed by ATC to avoid crossing TWY Y into RWY02R/20L.
2.2.6 穿越跑道时, 航空器驾驶员应注意监听其他有	2.2.6 Flight crew shall monitor the TWR FREQ and

关跑道指令或信息，并注意观察跑道及附近的活动；
跟随起飞航空器后穿越跑道时，航空器驾驶员自行负责与起飞航空器之间的距离以免受喷流影响。

watch the activities on the RWY and around; While crossing RWY after the take-off aircraft, flight crew shall be responsible for the safety distance with the aircraft to avoid the effect of wake turbulence.

2.3 地面以及滑行道使用规则

2.3 Use of taxiways

2.3.1 管制范围的划分:

2.3.1 Rules of ATC scope as follows:

机场图上分别划设机坪管制，联邦机坪，翼通 FBO 机坪的范围图，剩下的机场图范围为空管塔台的管制范围。

The aerodrome chart delineates separate control areas for Apron Control, FedEx Apron, and FBO Apron. The remaining areas of the aerodrome chart fall under ATC Tower's jurisdiction.

具体管制移交点及移交方式听从管制员指令执行。

The specific hand-over point and mode shall be instructed by ATC.

2.3.2 滑行道的使用原则:

2.3.2 General rules for the use of taxiways:

2.3.2.1 航空器地面滑行过程中在进入下一管制单位责任区前，必须得到下一管制单位的许可。

2.3.2.1 A/C shall get clearance from next control unit before taxiing into next control unit area.

2.3.2.2 航空器在障碍物附近滑行时，速度应当减到 15km/h 以下。

2.3.2.2 IAS shall be slowed down to 15km/h and below, while aircraft is taxiing near the obstacles.

2.3.2.3 本场大功率试车，必须事先得到机场运行控制中心和 ATC 许可。

2.3.2.3 High power engine run up, prior clearance shall be obtained from operation control center and ATC;

2.3.2.4 B、D、E、GT1、GT3-GT4、J、J3、J6-J13、J15-J19、J21-22、L3-L10、L12-L13、L15-L16、L18-L26、L22、L24、M、Q、Q10、Q15-Q16、T1-T4、Y1、一号绕滑、二号绕滑、三号绕滑、四号绕滑、T61-T65 滑行道与机场服务车道交叉，航空器通过时应注意观察，防止与过往车辆发生冲突。

2.3.2.4 TWYs B, D, E, GT1, GT3-GT4, J, J3, J6-J13, J15-J19, J21-J22, L3-L10, L12-L13, L15-L16, L18-L26, L22, L24, M, Q, Q10, Q15-Q16, T1-T4, Y1, Nr.1-4 End Around Taxiway(EAT), and TWYs T61-T65 intersect with airport service roads. Aircraft operators shall maintain vigilant observation when crossing to prevent conflicts with vehicular traffic.

2.3.2.5 标准滑行路线使用规则

2.3.2.5 Standard Taxi Route Usage Rules

- a.管制员将根据停机位指挥进港航空器在标准滑行路线的中间节点或终点加入其他滑行道继续滑行。
- a. Controllers shall direct arriving aircraft to join other taxiways at intermediate nodes or the endpoint of standard taxi routes based on their parking positions.
- b.当管制员在标准滑行路线的中间节点指挥航空器加入其他滑行道时，意味着取消已发布标准滑行路线的剩余部分。
- b. When controllers instruct aircraft to join other taxiways at intermediate nodes of standard taxi routes, it signifies cancellation of the remaining portion of the issued standard taxi route.
- 2.3.2.6 空客 A380 使用 C 滑行道以西的 L4 滑行道滑行时，L3 滑行道停止使用。
- 2.3.2.6 When A380 taxiing on TWY L4 (west of TWY C), TWY L3 is forbidden to be used.
- 2.3.2.7 航空器进入 L3 滑行道前，应注意观察 C 滑行道以西的 L4 滑行道是否有空客 A380 机型使用，防止与 L4 滑上的 A380 发生冲突。
- 2.3.2.7 When A380 taxiing on TWY L4 (west of TWY C), TWY L3 is forbidden to be used. Before entering TWY L3, all aircraft should observe TWY L4 (west of TWY C), and avoid conflict with A380 taxiing on TWY L4.
- 2.3.2.8 停靠 815、821 机位翼展限制为 80m 的航空器原则上由 J35 滑行道进出机坪；停靠 CG12、CG13、CG14 机位翼展限制为 80m 的航空器原则上由 Q11 滑行道进出机坪。
- 2.3.2.8 Aircraft MAX wingspan 80m parked at stands 815 and 821 shall, in principle, enter and exit the apron via TWY J35; Aircraft MAX wingspan 80m parked at stands CG12, CG13 and CG14 shall, in principle, enter and exit the apron via TWY Q11.
- 2.3.2.9 M 滑（含）以东的东飞行区道面中，仅 M10（含）至 Y1（含）之间的 M 滑、Q11 至 Q6 之间的 Q 滑、J44 滑、J35 滑、Q6 滑-Q11 滑、Q14 滑-Q17 滑、S2 滑可用于翼展限制为 80m 的航空器滑行。
- 2.3.2.9 Among the pavement in the eastern flight area east of TWY M(inclusive), only the following taxiways can be used for taxiing of aircraft MAX wingspan 80m: the section of TWY M(BTN M10(inclusive) & Y1(inclusive)), the section of TWY Q(BTN Q11 & Q6), TWY J44, J35, Q6-Q11, Q14-Q17 and S2.
- 2.3.2.10 因飞行区道面等级差异，翼展限制为 80m 的航空器在东飞行区运行时，需严格执行管制员指令，做好道面标识观察，防止误入不适用等级道面。
- 2.3.2.10 Due to variations in movement area pavement classification, aircraft MAX wingspan 80m operating in the eastern movement area must strictly adhere to ATC

instructions, maintain vigilant observation of pavement markings, and prevent inadvertent entry onto non-compliant pavement surfaces.

2.3.2.11 航空器滑行过程禁止进入 T7 滑以北的 H 滑；
航空器滑行过程禁止进入 J23 滑。

2.3.2.11 Aircraft are prohibited from entering TWY H north of TWY T7 during taxiing; Aircraft are prohibited from entering TWY J23 during taxiing.

2.3.2.12 本场设置多个等待点（HP），详见停机位置图。

2.3.2.12 Multiple holding points (HP) are set up at the airport, as detailed in APDC.

HP Nr.	Operation limitation
HP1-HP3	Within FBO apron, arrival ACFT shall wait for follow-me vehicle at HP1 or by ATC. Departure ACFT shall contact with Baiyun Ground Control at HP3. Departure ACFT parking on stand YT14 shall contact with Baiyun Ground Control at stand.
HP4	No aircraft shall cross the holding point without the permission of Baiyun Ground Control.
HP5, HP6	TWY L5(west of HP5) and TWY L6(west of HP6) are forbidden to used simultaneously. ACFT without APN clearance are forbidden to crossing HP5 and HP6.
HP7, HP8	TWY J7(east of HP7) and TWY J8(east of HP8) are forbidden to used simultaneously. ACFT without APN clearance are forbidden to crossing HP7 and HP8.
HP9, HP10	TWY J9(east of HP9) and TWY J10(east of HP10) are forbidden to used simultaneously. ACFT without APN clearance are forbidden to crossing HP9 and HP10.
HP11	No aircraft shall cross the holding point without the

	permission of Baiyun Ground Control.
HP12	No aircraft shall cross the holding point without the permission of Baiyun Ground Control.
HP13	No aircraft shall cross the holding point without the permission of Baiyun Ground Control.
HP14	No aircraft shall cross the holding point without the permission of Baiyun Tower Ground Control.
HP15	ACFT without TWR clearance are forbidden to crossing HP15.
HP16	Departure ACFT without TWR clearance are forbidden to crossing HP16.
HP17	Arrival ACFT without APN clearance are forbidden to crossing HP17.
HP18	To prevent aircraft from inadvertently entering restricted End Around Taxiway(EAT) segments, aircraft shall not proceed beyond holding points without explicit Tower control clearance.
HP19	To prevent aircraft from inadvertently entering restricted End Around Taxiway(EAT) segments, aircraft shall not proceed beyond holding points without explicit Tower control clearance.
HP20	To prevent aircraft from inadvertently entering restricted End Around Taxiway(EAT) segments, aircraft shall not proceed beyond holding points without explicit Tower control clearance.
HP21	The aircraft taxiing southbound on TWY Y19 shall not cross this holding point without permission of Tower

	Control.
HP22	The aircraft taxiing southbound on TWY S2 shall not cross this holding point without permission of Tower Control.
HP23	The aircraft taxiing northbound on TWY S2 shall not cross this holding point without permission of Tower Control.

2.3.3 绕滑的使用原则

2.3.3 General rules for End Around Taxiway(EAT)

2.3.3.1 本场绕滑概况:

2.3.3.1 End Around Taxiway(EAT) Overview:

本场共设置了四条绕滑，分别命名为一号绕滑、二号绕滑、三号绕滑、四号绕滑。

The aerodrome has established four End Around Taxiway(EAT), designated as Nr.1 EAT, Nr.2 EAT,Nr.3 EAT, and Nr.4 EAT respectively.

一号绕滑（东北绕滑）: Q-B2-B 段、B1 段、Y-B2-B 段

Nr.1 EAT(Northeast EAT): Q-B2-B Segment, B1 Segment, Y-B2-B Segment

二号绕滑（东南绕滑）: T61-Y20-B 段、Y19-Y20-B 段

Nr.2 EAT(Southeast EAT): T61-Y20-B Segment, Y19-Y20-B Segment

三号绕滑（西南绕滑）: H（L51 以南）-H1-E（J1 以南）

Nr.3 EAT(Southwest EAT): H(South of L51)-H1-E(South of J1)

四号绕滑（西北绕滑）: H（T13 以北）-H2-E（T4 以北）

Nr.4 EAT(Northwest EAT): H(North of T13)-H2-E(North of T4)

2.3.3.2 绕滑运行程序

2.3.3.2 End Around Taxiway(EAT) Operating Procedures:

a. 01L/19R 跑道落地后，航空器应按标准滑行路线或管制指令加入三号或四号绕滑绕行;

a. After landing on RWY01L/19R, aircraft shall join Nr.3 EAT or Nr.4 EAT via standard taxi routes or ATC instructions;

b. 02R/20L 跑道落地后，停机位在 T1 航站楼和 T2 航

b. After landing on RWY02R/20L, aircraft parking at T1

站楼的航空器应沿着 Y 滑行道滑行加入标准滑行路线或按管制指令加入一号或二号绕滑绕行 02L/20R 跑道;

c. 03/21 跑道落地后, 停机位在 T1 航站楼和 T2 航站楼的航空器应按标准滑行路线或管制指令加入一号或二号绕滑绕行 02R/20L 跑道和 02L/20R 跑道。

2.3.3.3 绕滑使用限制

一号绕滑: 当 02R 跑道有航空器起飞时, B2、Q (Q8 以北) 仅适用于垂尾高度不超过 19.8m 的航空器滑行, B1、Y (Y2 以北)、M (M1 以北) 仅适用于垂尾高度不超过 12.7m 的航空器滑行;

当 02L 跑道有航空器起飞时, B (L22 以北)、B2 仅适用于垂尾高度不超过 19.8m 的航空器滑行, B1、Y (Y1 以北) 仅适用于垂尾高度不超过 12.7m 的航空器滑行;

20L 跑道用于降落时, 航空器一旦进入 B1、Y (Y2 以北)、M (M1 以北) 可能突破 20L 跑道进近保护面, 航空器应听从管制员等待指令;

20R 跑道用于降落时, 航空器一旦进入 B1、Y (Y1 以北) 可能突破 20R 跑道进近保护面, 航空器应听从管制员等待指令。

or T2 terminals shall follow TWY Y to join standard taxi routes or ATC instructions, enter Nr.1 EAT or Nr.2 EAT to bypass RWY02L/20R;

c. After landing on RWY03/21, aircraft parking at T1 or T2 terminals shall join Nr.1 EAT or Nr.2 EAT via standard taxi routes or ATC instructions to bypass RWY02R/20L and RWY02L/20R.

2.3.3.3 Using limits for EAT

Nr.1 EAT: When there is an aircraft taking off from RWY02R, only aircraft with a vertical tail height not exceeding 19.8m are allowed to taxi on B2 and Q(north of Q8); only aircraft with a vertical tail height not exceeding 12.7m are allowed to taxi on B1, Y(north of Y2) and M(north of M1).

When there is an aircraft taking off from RWY02L, only aircraft with a vertical tail height not exceeding 19.8m are allowed to taxi on B(north of L22) and B2; only aircraft with a vertical tail height not exceeding 12.7m are allowed to taxi on B1 and Y(north of Y1).

When RWY20L is used for landing, once an aircraft enters B1, Y(north of Y2) or M(north of M1), it may break through the approach protection surface of RWY20L, and the aircraft shall follow the controller's holding instruction.

When RWY20R is used for landing, once an aircraft enters B1 or Y(north of Y1), it may break through the approach protection surface of RWY20R, and the aircraft shall follow the controller's holding instruction.

二号绕滑：当 20L 跑道有航空器起飞时，T61（Q 以西）、Q（J31 以南）仅适用于垂尾高度不超过 19.8m 的航空器滑行，Y19、M（M10 以南）仅适用于垂尾高度不超过 12.7m 的航空器滑行；

当 20R 跑道有航空器起飞时，B（T1 以南）、Y20、T61（Q 以西）仅适用于垂尾高度不超过 19.8m 的航空器滑行，Y（Y15 以南）、Y19 仅适用于垂尾高度不超过 12.7m 的航空器滑行；

02L 跑道用于降落时，航空器一旦进入 B（T1 以南）、Y20、Y（Y15 以南）、Y19 滑行道可能突破 02L 跑道进近保护面，航空器应听从管制员等待指令。

02R 跑道用于降落时，航空器一旦进入 M（J31 以南）滑行道可能突破 02R 跑道进近保护面，航空器应听从管制员等待指令。

三号绕滑：当 19L 跑道有航空器起飞时，H（L51 以南）、H1、E（J1 以南）仅适用于垂尾高度不超过 19.8m 的航空器滑行。

四号绕滑：当 01R 跑道有航空器起飞时，H（T13 以北）、H2、E（T4 以北）仅适用于垂尾高度不超过 19.8m 的航空器滑行；19L 跑道用于降落时，航空器一旦进

Nr.2 EAT: When there is an aircraft taking off from RWY20L, only aircraft with a vertical tail height not exceeding 19.8m are allowed to taxi on T61(west of Q) and Q(south of J31); only aircraft with a vertical tail height not exceeding 12.7m are allowed to taxi on Y19 and M(south of M10).

When there is an aircraft taking off from RWY20R, only aircraft with a vertical tail height not exceeding 19.8m are allowed to taxi on B(south of T1), Y20 and T61(west of Q); only aircraft with a vertical tail height not exceeding 12.7m are allowed to taxi on Y(south of Y15) and Y19.

When RWY02L is used for landing, once an aircraft enters Taxiways B(south of T1), Y20, Y(south of Y15) or Y19, it may break through the approach protection surface of RWY02L, and the aircraft shall follow the controller's holding instruction.

When RWY02R is used for landing, once an aircraft enters TWY M(south of J31), it may break through the approach protection surface of RWY02R, and the aircraft shall follow the controller's holding instruction.

Nr.3 EAT: When ACFT takes off from RWY19L, TWYs H(south of L51), H1, E(south of J1) are only AVBL for ACFT with height (including vertical tail) no more than 19.8m.

Nr.4 EAT: When ACFT takes off from RWY01R, TWYs H(north of T13), H2, E(north of T4) are only AVBL for ACFT with height (including vertical tail) no more

入 J22 与 H2 之间的 E 滑行道可能突破 19L 跑道进近保护面，航空器应听从管制员等待指令。

2.3.4 对机组的要求：

a. 听清并重复地面管制员的滑行指令，尤其是界限性指令，发现疑问及时证实。

b. 在推出时向机坪管制证实使用跑道、推出方向。

c. 在脱离跑道首次与地面管制联系时，尤其在低能见度情况下，必须向地面管制报告脱离的跑道和所使用的滑行道等具体位置。

d. 专机滑行路线以管制员通知为准。

e. 对于重型机及 A380 机型，当机组与管制员首次建立联系时，飞行员必须在其航班呼号后分别增加“HEAVY”、“SUPER”内容。

2.3.5 滑行道翼展限制

than 19.8m. When RWY 19L is used for landing, ACFT entering TWY E (BTN J22 and H2) may break the approach protection surface of RWY 19L, ACFT should follow the controller's instructions to wait.

2.3.4 Requirements for pilots:

a. Repeat the whole taxiing instructions issued by GND Control, especially boundary instruction and make it clear when there is a doubt;

b. While pushed back from parking stand, verify the pushing direction and the approved RWY designation to APN;

c. After vacating RWY, especially under conditions of low visibility, report the RWY designation and TWY designation on initial contact with GND;

d. Taxiing routes of special flight will be instructed by ATC.

e. For heavy load aircraft or A380, pilot shall add "HEAVY", "SUPER" following the call sign when aircrew establish first contact with ATC.

2.3.5 Wing span limits for TWY

滑行道/TWYs	航空器翼展限制 (m) /Wing span limits for aircraft(m)
A, A1-A11, B(BTN L22 & T1), C(BTN L9 & T4), J35, J44, L12, L13, L24(south of stand Nr.318), M(north of M10), M1-M10, P1-P14, Q(BTN Q6 & Q11), Q6-Q17, S2, T5, V, Y(BTN Y1 & Y18), Y1-Y18	≤80
B(north of L22), B(south of T1), B1, B2, E, H, H1, H2,	≤65

J, J9(east of D), J21, J22(BTN D & E), J23, J36, J37, J41, J43, J56, K, K1, L3, L4(west of C), L16, L24(north of stand Nr.318), L31-L39, M(south of T62), N, N1-N11, Q(BTN Q11 & J43), Q(north of Q6), Q(south of J41), QL, R, R3-R5, S3, T6, T7, T11-T13, T61-T66, U, V1, W, W1-W10, Y19, Y20	
J10(east of D), L7(west of C), L8(west of C), L25	≤52
C5, GT1-GT4, J13, J15-J17, J18(east of D), J19, J22(BTN D & D4), L9(west of C), L10(west of C), L15(west of C), L26, L27, S1	≤36

注：当 02R 跑道有航空器起飞时，B2、Q（Q8 以北）仅适用于垂尾高度不超过 19.8m 的航空器滑行，B1、Y（Y2 以北）、M（M1 以北）仅适用于垂尾高度不超过 12.7m 的航空器滑行；

Remarks: When an aircraft is taking off from RWY02R, only aircraft with a vertical tail height not exceeding 19.8m are allowed to taxi on B2 and Q(north of Q8); only aircraft with a vertical tail height not exceeding 12.7m are allowed to taxi on B1, Y(north of Y2) and M(north of M1).

当 02L 跑道有航空器起飞时，B（L22 以北）、B2 仅适用于垂尾高度不超过 19.8m 的航空器滑行，B1、Y（Y1 以北）仅适用于垂尾高度不超过 12.7m 的航空器滑行；

When an aircraft is taking off from RWY02L, only aircraft with a vertical tail height not exceeding 19.8m are allowed to taxi on B(north of L22) and B2; only aircraft with a vertical tail height not exceeding 12.7m are allowed to taxi on B1 and Y(north of Y1).

20L 跑道用于降落时，航空器一旦进入 B1、Y（Y2 以北）、M（M1 以北）可能突破 20L 跑道进近保护面，航空器应听从管制员等待指令；

When RWY20L is used for landing, once an aircraft enters B1, Y(north of Y2) or M(north of M1), it may breach the approach protection surface of RWY20L, and the aircraft shall follow the controller's holding instructions.

20R 跑道用于降落时，航空器一旦进入 B1、Y(Y1 以

When RWY20R is used for landing, once an aircraft

北)可能突破 20R 跑道进近保护面,航空器应听从管制员等待指令。

当 20L 跑道有航空器起飞时, T61 (Q 以西)、Q (J31 以南)仅适用于垂尾高度不超过 19.8m 的航空器滑行, Y19、M (M10 以南)仅适用于垂尾高度不超过 12.7m 的航空器滑行;

当 20R 跑道有航空器起飞时, B (T1 以南)、Y20、T61 (Q 以西)仅适用于垂尾高度不超过 19.8m 的航空器滑行, Y (Y15 以南)、Y19 仅适用于垂尾高度不超过 12.7m 的航空器滑行;

02L 跑道用于降落时,航空器一旦进入 B (T1 以南)、Y20、Y (Y15 以南)、Y19 滑行道可能突破 02L 跑道进近保护面,航空器应听从管制员等待指令。

02R 跑道用于降落时,航空器一旦进入 M (J31 以南)滑行道可能突破 02R 跑道进近保护面,航空器应听从管制员等待指令。

当 19L 跑道有航空器起飞时, H (L51 以南)、H1、E (J1 以南)仅适用于垂尾高度不超过 19.8m 的航空器滑行。

enters B1 or Y(north of Y1), it may breach the approach protection surface of RWY20R, and the aircraft shall follow the controller's holding instructions.

When an aircraft is taking off from RWY20L, only aircraft with a vertical tail height not exceeding 19.8m are allowed to taxi on T61(west of Q) and Q(south of J31); only aircraft with a vertical tail height not exceeding 12.7m are allowed to taxi on Y19 and M(south of M10).

When an aircraft is taking off from RWY 20R, only aircraft with a vertical tail height not exceeding 19.8m are allowed to taxi on B(south of T1), Y20 and T61(west of Q); only aircraft with a vertical tail height not exceeding 12.7m are allowed to taxi on Y(south of Y15) and Y19.

When RWY02L is used for landing, once an aircraft enters TWYs B(south of T1), Y20, Y(south of Y15) or Y19, it may breach the approach protection surface of RWY02L, and the aircraft shall follow the controller's holding instructions.

When RWY02R is used for landing, once an aircraft enters TWY M(south of J31), it may breach the approach protection surface of RWY02R, and the aircraft shall follow the controller's holding instructions.

When an aircraft is taking off from RWY19L, only aircraft with a vertical tail height not exceeding 19.8m are allowed to taxi on H(south of L51), H1 and E(south of J1).

当 01R 跑道有航空器起飞时, H (T13 以北)、H2、E (T4 以北) 仅适用于垂尾高度不超过 19.8m 的航空器滑行;

19L 跑道用于降落时, 航空器一旦进入 J22 与 H2 之间的 E 滑行道可能突破 19L 跑道进近保护面, 航空器应听从管制员等待指令。

当空客 A380 使用 L4 滑行道 (C 以西) 滑行时, 运行限制参见 2.3.3.6/2.3.3.7。

2.4 滑行道及机坪坡度

2.4.1 本场所有绕滑包括: 一号绕滑 (东北绕滑)、二号绕滑 (东南绕滑)、三号绕滑 (西南绕滑)、四号绕滑 (西北绕滑) 均存在坡度。

2.4.2 下列机位存在坡度: 831、903、904、905、906、907、908、909、910、911、912、913、914、916、916L、916R、917、920、922、922L、922R、923、924、925、926、927、928、929、931、932、972R、CG01、CG10、CG11、CG12、CG13、CG14 号机位。

2.5 离港航空器管制规定

2.5.1 离场航空器在预计关舱门前 10min 联系空管塔台放行管制, 申请放行许可。取得放行许可后, 由放行管制指示联系机坪管制。离港航空器准备好推出和开车时通知机坪管制, 并通报航空器停机位号和目的地。机坪管制负责发布推出、开车许可, 滑行路线等指令。在得到机坪管制的明确指令前, 航空器不得擅自推出、开车或滑行。在进入空管塔台地面管制责任

When an aircraft is taking off from RWY01R, only aircraft with a vertical tail height not exceeding 19.8m are allowed to taxi on H(north of T13), H2 and E(north of T4).

When RWY19L is used for landing, once an aircraft enters the section of TWY E(BTN J22 & H2), it may breach the approach protection surface of RWY19L, and the aircraft shall follow the controller's holding instructions.

While ACFT type A380 taxiing on TWY L4(west of C), other ACFT shall follow the rules of 2.3.2.6/2.3.2.7.

2.4 Taxiway and Apron Slopes

2.4.1 Nr.1-4 End Around Taxiway have slopes.

2.4.2 The stands have slopes: Stands 831, 903, 904, 905, 906, 907, 908, 909, 910, 911, 912, 913, 914, 916, 916L, 916R, 917, 920, 922, 922L, 922R, 923, 924, 925, 926, 927, 928, 929, 931, 932, 972R, CG01, CG10, CG11, CG12, CG13, CG14.

2.5 Requirements for departure ACFT

2.5.1 Departing aircraft shall contact TWR for delivery clearance 10min prior to the cabin door closed; Aircraft shall contact Apron Control upon receiving delivery clearance. Departing aircraft shall be ready to push-back and start-up, then contact Apron Control and report the parking stand number and destination. Apron Control issued information such as push-back and start-up

区前，由机坪管制指示联系相应的地面管制。空管塔台地面管制继续指挥航空器滑行，并在进入跑道等待位置之前联络塔台管制。

2.5.2 提供数字化放行系统（DCL）服务：

a. 预计撤轮挡时间（EOBT）前 30min 至 10min，航空器驾驶员应当向空中交通管制部门（ATC）申请放行许可；

b. DCL 报文中“NEXT FREQ”标示塔台放行频率；DCL 报文中“DEP FREQ”标示进近离场频率，是航空器离地后的首个联系频率。

2.5.3 为规范航空器进入跑道的跑道占用时间，提高跑道容量，起飞的航空器从接到管制员进跑道指令到对正跑道时间应控制在 60s 以内（湿跑道或污染跑道除外）。如机组认为无法在上述要求的时间内完成，须在到达跑道外等待点之前向塔台管制员说明。

2.5.4 为提高跑道容量，机组收到进跑道指令后需尽快完成起飞前准备工作，收到 ATC 发布的起飞许可后应立即开始起飞滑跑。机组需提前做好起飞准备，若预计进跑道后还需额外时间完成准备，应在进跑道前通知管制员。

clearance, taxiing routes etc. Push-back, start-up and taxiing without Apron Control clearance is strictly forbidden. Aircraft shall contact GND before entering into Ground Control Area. Ground Control continues control aircraft taxiing. Aircraft shall contact TWR before entering the runway holding positions.

2.5.2 Departure Clearance(DCL) service:

a. Within 30-10 minutes before Estimated Off-block Time (EOBT), pilot shall apply for delivery clearance from ATC;

b. The "NEXT FREQ" in DCL message is delivery FREQ, the "DEP FREQ" in DCL message is Approach/Departure FREQ which is the first FREQ for aircraft to contact after taking off.

2.5.3 For optimizing RWY occupancy time and increasing runway capacity, departure aircraft shall finish RWY alignment within 60s after receiving ATC instructions of entering RWY(except for wet or contaminated runway). If flight crew consider they cannot fulfill the process within the required time, inform TWR before reaching the RWY holding position.

2.5.4 To enhance runway capacity, flight crews shall complete pre-takeoff preparations promptly after receiving lineup clearance and immediately commence takeoff roll upon issuance of ATC takeoff clearance. Crews must prepare for takeoff in advance and, if anticipating additional preparation time after entering the runway, shall notify air traffic control prior to

2.5.5 同一跑道离场航空器之间的尾流间隔标准按照 RECAT-CN 标准执行。如因其他原因，机组需要比 RECAT-CN 标准更大的离场间隔，务必在进跑道前通知塔台管制员。必要时，为了减少后续航班的整体延误，ATC 还会调整起飞次序。

2.5.6 非全跑道离场

2.5.6.1 为了提升离场放飞效率，广州白云机场全面实施航空器使用非全跑道起飞离场程序，空管可能会通过要求航空器使用非全跑道离场来调整起飞顺序。

2.5.6.2 对于无法进行非全跑道起飞离场的航空器，机组在抄收管制放行许可时须向管制员说明。

2.6 进港航空器管制规定

2.6.1 速度限制

除 ATC 指令表速外，航空器性能许可时，进近过程中 IAF 至接地点，保持 IAS330km/h（180kt）直至接地点 8NM，且保持 IAS300km/h（160kt）至接地点 6NM。如果航空器不能执行上述速度限制，机组应及时通知 ATC 可用的速度。

runway entry.

2.5.5 The wake turbulence separation standards between departing aircraft on the same runway shall be implemented in accordance with RECAT-CN criteria. If crews require greater departure spacing than RECAT-CN standards for any reason, they must notify the Tower controller before entering the runway. When necessary, ATC may also adjust the takeoff sequence to minimize overall delays for subsequent flights.

2.5.6 Intersection Departure

2.5.6.1 In order to improve the efficiency of departure, Guangzhou Baiyun Airport has fully implemented the procedure of intersection departure. ATC may adjust the take-off order by requiring aircraft to use intersection departure.

2.5.6.2 For the ACFT that can not use intersection departure procedure, the pilot shall report to ATC upon receiving the ATC clearance.

2.6 Requirements for arrival ACFT

2.6.1 Speed limit

Except when ATC instructs indicated airspeed, aircraft shall maintain IAS 330 km/h (180 kt) from IAF to touchdown point until 8 NM from touchdown point, and maintain IAS 300 km/h (160kt) until 6 NM from touchdown point, provided aircraft performance permits. If unable to comply with these speed restrictions, flight crews shall promptly notify ATC of the achievable speed.

2.6.2 为了能够尽量缩小航空器起飞着陆间隔,使跑道的利用率最大化,并减少因着陆航空器长时间占用跑道导致后续进近航空器复飞的情况,着陆航空器应尽可能使用顺向且靠近接地点的第一或第二快速脱离道退出跑道,需要使用第三条快速脱离道及以远道口脱离跑道时,机组应在与塔台建立首次联系时进行通报。

2.6.3 着陆航空器从跑道入口到完全脱离跑道的时间应控制在 50s 以内(湿跑道或污染跑道除外),如机组认为无法在上述要求的时间内完成,须在建立航向道前通知进近管制员。

2.6.4 管制员可以根据运行条件通知航空器驾驶员落地后的预计脱离道口,如机组认为无法执行,应及早告知管制员。

2.6.5 同一跑道五边进近的航空器之间的尾流间隔要求按照 RECAT-CN 标准执行。

2.7 特殊机型运行规定

2.7.1 A380 机型地面运行区域

满足 A380 机型地面运行条件的区域包括:

2.6.2 To minimize the interval between aircraft takeoffs and landings, maximize runway utilization, and reduce cases where subsequent approaching aircraft have to go around due to landing aircraft occupying the runway for an extended period, landing aircraft should exit the runway via the first or second rapid exit taxiway that is in the same direction and closest to the touchdown point as much as possible. If it is necessary to exit the runway via the third rapid exit taxiway or any exit further along, the flight crew shall notify the tower when establishing initial contact with it.

2.6.3 Landing aircraft shall complete runway vacating within 50s after runway threshold crossing (except on wet/contaminated runways). If crews anticipate inability to meet this requirement, they must notify Approach Control before localizer establishment.

2.6.4 Controllers may notify flight crews of the anticipated exit taxiway based on operational conditions. If crews determine they cannot comply, they shall inform the controller at the earliest opportunity.

2.6.5 The wake turbulence separation requirements between aircraft on final approach for the same runway shall be implemented in accordance with RECAT-CN standards.

2.7 Operation requirements for A380 and B747-8

2.7.1 A380 Ground Operation Areas

The following areas are satisfied with B747-8 ground operations:

a.02L/20R、02R/20L 跑道;

b.M (含) 以西, C (含) 以东的东飞行区范围内, 除 A5、A6、Y7、Y9、Y10、Y12、M5、M6 外, 其余滑行道均可供 A380-800 机型地面运行; M 滑以东 Q (Q6 与 Q11 之间)、Q6-Q17、J44-S2-J35, 可供 A380-800 机型地面运行;

c.停机位: 105、106、117、129、147、149、155、319、320、815、821、CG12-14, 包括进出各机位的滑行道及机位引入线。

2.7.2 B747-8 机型地面运行区域

2.7.2.1 满足 B747-8 机型地面运行条件的区域包括:

a.01R/19L、02L/20R、02R/20L 跑道;

b.对于出港 B747-8, M (含) 以西, 除 C 与 D 之间的 T1、T2, L9 (C 以西), L10 (C 以西), C4 与 D4 之间的 T4, E (J1 以南), E (J22 以北), H1, H2, 西一跑道 (01R/19L) 以西的滑行道外, 其余滑行道均可供地面运行;

c.对于进港 B747-8, M (含) 以西, 除 E (J1 以南), E (J22 以北), H1, H2, 西一跑道 (01R/19L) 以西的滑行道外, 其余滑行道均可供地面运行;

d:M 滑以东 Q (Q6 与 Q11 之间)、Q6-Q17、J44-S2-J35, 可供 B747-8 机型地面运行;

e.停机位: 106、117、129、147、149、155、206、207、

a. RWY02L/20R, RWY02R/20L;

b. Within the eastern movement area west of TWY M(inclusive) and east of TWY C(inclusive), all taxiways except A5, A6, Y7, Y9, Y10, Y12, M5, and M6 are available for A380-800 ground operations; East of Taxiway M, the following taxiways are available for A380-800 ground operations: Q(BTN Q6 & Q11), Q6-Q17, J44-S2-J35.

c. Parking stands Nr.105, 106, 117, 129, 147, 149, 155, 319, 320, 815, 821, CG12-14 including TWYs in and out these stands and guidelines of these stands.

2.7.2 B747-8 Ground Operation Areas

2.7.2.1 The following areas are satisfied with B747-8 ground operations:

a. RWY01R/19L, RWY02L/20R, RWY02R/20L;

b. For departing B747-8 aircraft, west of M(inclusive), all taxiways are available for ground operations except T1(BTN C & D) and T2(BTN C & D), L9(west of C), L10(west of C), T4 between C4 and D4, E(south of J1), E(north of J22), H1, H2, and taxiways west of RWY01R/19L.

c. For arriving B747-8 aircraft, west of M(inclusive), all taxiways are available for ground operations except E(south of J1), E(north of J22), H1, H2, and taxiways west of RWY 01R/19L;

d: East of M, Q(BTN Q6 & Q11), Q6-Q17, J44--S2-J35 are available for B747-8 ground operations;

e. Parking Stands: 106, 117, 129, 147, 149, 155, 206,

218、271、277、319、320、401、402、501-514、324-327、815、821、CG12-14，包括进出各机位的滑行道及机位引入线；

f.B747-8 机型使用 F3、F4、F5 滑行道脱离跑道时，禁止右转加入 F 滑行道；B747-8 机型使用 F6、F7、F8 滑行道脱离跑道时，禁止左转加入 F 滑行道。

2.7.3 A380、B747-8 等翼展限制为 80m 的航空器仅限于在专用试车坪上开展试车工作。

2.8 机动区冲突多发地带运行要求

2.8.1 机动区冲突多发地带位置见 ADC, APDC

2.8.2 为减少运行差错，降低地面冲突和跑道入侵事件的发生概率，在机场活动区内运行的航空器需严格按照下述的要求运行。

HS1: Y15 与 Y 滑行道交叉点

航空器驾驶员在此区域滑行需加强对 20L 跑道脱离航空器的冲突观察，且注意识别 Y 滑行道与 P13 道口，避免误入。

HS2: 20L 跑道 ILS 保护区

航空器需穿越此区域进入使用跑道前，需按管制员指令在 ILS 保护区等待线外等待，避免误入 20L 跑道盲降保护区。

HS3: M 滑行道滑行冲突区域

207、218、271、277、319、320、401、402、501-514、

324-327、815、821、CG12-CG14，including all

associated taxiways and lead-in lines for these stands;

e.When B747-8 uses TWY F3, F4 and F5 to vacate the runway, it is forbidden to turn right to join TWY F;

When B747-8 uses TWY F6, F7 and F8 to vacate the runway, it is forbidden to turn left to join TWY F.

2.7.3 A380、B747-8 are allowed to carry out engine run-ups only at designated locations.

2.8 Hot spot procedure

2.8.1 Refer to ADC, APDC for Hot Spots location.

2.8.2 For the purpose of reducing errors that lead to ground conflicts and runway incursions, ACFT operating within the maneuvering area of Guangzhou airport must follow the requirements below:

HS1: Intersections of TWYs Y15 and Y

Aircraft operating in this taxiway area shall maintain enhanced vigilance for potential conflicts with aircraft vacating RWY20L, while ensuring positive identification of TWY Y and P13 intersection to prevent inadvertent entry.

HS2: RWY20L ILS Critical Area

Aircraft requiring to cross this area for runway entry shall hold at the ILS holding point as instructed by ATC to prevent inadvertent incursion into RWY20L ILS critical area.

HS3: Taxiway M Conflict Zone

航空器沿 M 从北往南滑行时，驾驶员应加强对右侧 02R 跑道脱离航空器的观察，发现冲突时及时减速避让；02R 跑道落地并向东脱离的航空器，驾驶员应加强对 M 滑行道上航空器活动的观察，发现冲突及时减速尽量避免驶入 M 滑。

When an aircraft is taxiing southward along TWY M, the pilot shall enhance observation of aircraft exiting RWY02R on the right side, and promptly decelerate to avoid collision if a conflict is detected. For aircraft that have landed on RWY02R and are exiting eastward, the pilot shall strengthen observation of aircraft activities on TWY M, and if a conflict is found, promptly decelerate and try to avoid entering TWY M.

HS4: N、T12、T13 交叉区域

HS4: N, T12, T13 Intersection Area

航空器沿 N 向北滑行转向 T12 滑时，因 T12 滑与 T13 滑位置接近，地面标识不易识别，容易错误转入 T13，航空器驾驶员在该区域滑行时应加强观察，听从管制员滑行指令，避免滑行错误。

Aircraft taxiing northbound along TWY N and turning onto TWY T12 shall exercise heightened visual awareness in this area due to proximity between TWY T12 and T13 taxiways and potentially unclear surface markings that may lead to inadvertent entry onto TWY T13. Pilots shall strictly adhere to ATC taxi instructions to prevent navigation errors.

3. 机坪和机位的使用

3. Use of aprons and parking stands

3.1 未经机坪管制同意，严禁航空器利用自身动力滑行或使用拖车拖行。

3.1 Push-back of aircraft on its own power or by tow car is strictly forbidden without Apron Control clearance.

3.2 本场全部机位必须在地面引导车的引导下进入停机位。

3.2 ACFT shall be guided by follow-me vehicle to enter into the whole stands.

3.3 航空器进出机位滑行规定

3.3 Rules to enter into or exit from stands

停机位编号 Stands Nr.	进入机位规定 Enter rules	滑出机位规定 Exit rules
319, 319L/R, 320, 320L/R, 321, 329, 418, 419, 430, 431, YT09-YT14, 860-862, 960-963	Taxi in by itself.	Taxi out by itself.

401L, 401R	Taxi in by itself.	Taxi out by itself or be pushed back by the tractor along the taxilines or be towed to the push-back holding positions, then start up and taxi out.
YL01-YL04	Taxi to stand stop line at TWY GT2 , then be pushed back into stand.	Taxi out by itself.
322, 323, GL01	Taxi in by itself.	Be pushed back by the tractor.
324-328, 324L/R-327L/R	Taxi to intermediate holding position(north of stand Nr.323) at TWY L22 and hold, then be pulled into stand by the tractor.	Be pushed back by the tractor along the taxilines or be towed to the push-back holding positions, then start up and taxi out.
Others	Taxi in by itself.	Be pushed back by the tractor along the taxilines or be towed to the push-back holding positions, then start up and taxi out.

当 YT05、YT06 机位停放航空器时，航空器不能进出 YL01 机位；当 YT06、YT07 机位停放航空器时，航空器不能进出 YL02 机位；当 YT07、YT08 机位停放航空器时，航空器不能进出 YL03、YL04 机位；当 416 机位未停放航空器，航空器可由 J3 滑行道从 401R 机位自滑出；当 415 机位未停放航空器，航空器可由 J3 滑行道从 401L 机位自滑出。

ACFT shall not enter into or exit from stand Nr. YL01 when stands Nr. YT05, YT06 being occupied. ACFT shall not enter into or exit from stand Nr. YL02 when stands Nr. YT06, YT07 being occupied. ACFT shall not enter into or exit from stands Nr. YL03, YL04 when YT07, YT08 being occupied. ACFT shall taxi out by itself from stands Nr. 401R via TWY J3 when stands Nr. 416 being unoccupied. ACFT shall taxi out by itself from stands Nr. 401L via TWY J3 when stands Nr. 415 being unoccupied.

3.4 航空器进出停机位的滑行道

3.4 Taxiway by which aircraft enter into/exit from stands

停机位/Stand Nr.	入口/Enter into stands by	出口/Exit from stands by
101, 102	L4	L4
103-105(except A380)	L4 or L3	L4
105(for A380)	L4	L4
106, 117, 118, 128, 147-149, 149L, 158-160, 160L/R	C	C
107	C or L5	C
129	C or L9	C
329	L5	L6
330	L5	L5
108-116	L5 or L6	L5 or L6
119	L7	L7
120-123, 124-126	L7 or L8	L7 or L8
127	L8	L8
130-133, 134L, 134-137	L9	L9
144-146, GY07-GY10	L10	L10
149R	C or L12	C or L12
150-153	L12	L12
154-157	L13	L13
161-164	L15	L15
165-170	L16	J
171-173, 277-279	J21	J
201-205	J6	J6
206-207, 218-219, 230, 231, 254,	D	D

254L, 255, 255R, 271, 271L/R, 272, 272R		
229	D or J10	D
208, 417	J7	J7
418-419	J7	J8
209-217	J7 or J8	J7 or J8
220-223	J9	J9
Nr.224-228	J9 or J10	J9 or J10
232-236, 238, 238L/R, 240, 240L/R	J11	J11
251-253, 254R, GY01-GY05	J13	J13
270	D or J18	D
255L	D or J14	D
256-263	J16	J15
264-269	J17	J18
272L, 273-276	J19 or J	J19 or J
301-308	L4 or L3	L3
309-314, 331-334	L18	L18
335-338	L20	L20
315-318, 324-328, 324L/R-327L/R	L24	L24
319-323, 319L/R, 320L/R	B	L24
401-406, 402L/R-406L/R	J6	J6
401L/R	J6	J3 or J6
407-416	J3	J3
430, 431	J16	J18
432-437	D-J22	J22-D4
500A, 500B, 501-515, 501L-514L	D	D

SF01-SF08, SF08L/R	L25	L25
YL05-YL08	GT1	GT1
YL09	GT1	GT2
YL01-YL04, YT01-YT03, YT05-YT08	GT2	GT2
YT09-YT14	GT2	GT4
YT15-YT19	GT4	GT4
516-518	J23	J23
701-710	H	H
GL01	V	V
815	S1 or S2 or J44	S1 or S2 or J44
816, 818, 819, 821, 822, 816L/R, 819L/R, 822R	S2	S2
822L	S2 or J35	S2
824	S2 or S3 or J35	S2 或 S3
825-827	S3	S3
828-829	S3 or J36	S3
830-831, 870-872, 930-931, 970-972, 870L/R-872L/R, 930L/R-932L/R	T63	T63
832-838	R4	R5
860-862	S2	Q
903、950	R or L33	R
904-906, 910-912, 916-917, 919-920, 922, 925-927, 940, 943-946, 948, 949, 916L/R, 919L/R,	R	R

922L/R, 943L/R, 946L, 948R		
941-942	R or L31	R
946R, 947, 948L	R or L32	R
907-909	R or L34	R
913-914	R or L35	R
923-924	R or L36	R
928-929	R or L37	R
932	T63	R3
933-938	R4	R3
939	R4	R3 or R5
960-963	R	U
873-876, 973-975, TEST 02-03, 873L/R-876L/R	T66	T66
880-882, 888-892, CG01-06, CG10-14	Q15	Q15
TEST 01	J3	J3

3.5 停机位限制

3.5 Limits for aircraft parking on the following stands

停机位编号/Stands Nr.	翼展限制/Wing span limits (m)
105, 106, 117, 129, 147, 149, 155, 319(when 319L/R U/S), 320(when 320L/R U/S), GL01, 815, 821, CG12-CG14, GL01	≤80
206, 207, 218, 271, 277, 401, 402, 501-514(when 501L-514L U/S)	≤68.5
101, 103, 104, 107, 109-111, 114, 116, 118, 128, 151,	≤65

152, 154, 158, 160, 165-168, 173, 201, 203-205, 220-222, 229, 231, 238(when 238L/R U/S), 240(when 240L/R U/S), 254, 255, 271, 272, 278, 279, 306-308, 321-323, 324-327(when 324L/R-327L/R U/S), 328, 403-406, 516-518, 816, 818, 819, 822, 824, 830-834, 838, 870-876, 881, 882, 914, 916, 917, 919, 920, 922, 923, 930-934, 938, 939, 941-943, 945-949, 970-972, 974, 975, TEST 02, CG01-CG05, CG10-CG11	
150, 169-172	≤61
108, 119-121, 125, 126, 148, 202, 208-213, 215-217, 219, 223, 230, 232-234, 301-305, 515, SF01-SF03, SF05-SF07, SF08(when SF08L/R U/S)	≤52
112, 113, 115, 122-124, 127, 130-133, 134L, 134-137, 144-146, 149L/R, 153, 156, 157, 159, 160L/R, 161-164, 214, 224-228, 235-236, 238L/R, 240L/R, 251-253, 254L/R, 255L/R, 256-270, 271L/R, 272L/R, 273-276, 310-318, 319L/R, 320L/R, 324L/R-327L/R, 329-338, 401L/R-406L/R, 407-419, 430-437, GY01-GY05, GY07-GY10, 500A, 500B, 501-505(when 501L-505L in use), 501L-505L, SF04, SF08L/R, YT05-YT12, YT15-YT18, YL05-YL08, 701-710, 816L/R, 819L/R, 822L/R, 825-829, 835-837, 860-862, 870L/R-876L/R, 880, 888-892, 903-913, 916L/R, 919L/R, 922L/R, 924-929, 935-937, 940, 943L/R, 944, 946L/R, 948L/R, 950, 960-963, 970L/R-972L/R, 973, TEST 03, CG06, TEST 01	≤36
102, 309, 506-514(when 506L-514L in use), 506L-514L	≤34.5
YT01-YT03, YL09	≤30

YL01-YL04, YT13, YT14, YT19	≤24
-----------------------------	-----

3.6 航空器在机坪滑行时，不得高速转弯或完全刹住一个（组）机轮转弯。

3.6 High-speed turn or turn with one (set) of wheels braked is forbidden, while an aircraft taxiing on apron.

3.7 试车坪使用规定

3.7 Rules of engine run-ups apron

3.7.1 试车坪运行规定

3.7.1 Rules of operation run-ups apron

原则上，使用 TEST 01 试车坪进行试车作业的航空器，需停放在 407 号停机位，由机务用拖车顶推进入 TEST 01 试车坪，试车作业结束后由机务用拖车牵引至 407 号机位停放。

When engine run-ups at stand TEST 01, the aircraft shall park at stand Nr.407, then be pushed into the run-ups apron by tow truck. After finish engine run-ups, aircraft shall be pulled into stand Nr.407 by tow truck;

原则上，使用 TEST 02/03 试车坪进行试车作业的航空器，先滑行至 T66 滑行通道的机位停止线，再顶推进停机位，试车作业结束后自滑出或由牵引车牵引出。

Aircraft utilizing TEST 02/03 run-up pads shall normally taxi to the parking stand stop line on TWY T66 first, then push back into the designated stand. After completing engine run-up operations, the aircraft shall either taxi out under its own power or be towed out by a tug.

3.7.2 机坪试车规定

3.7.2 Rules of apron's run-ups

发动机试慢车，需经机坪管制许可，并在指定的地点进行，试车结束后须向机坪管制报告。严禁在廊桥附近和客机坪上大功率试车或进行发动机排故调试。

Idle engine run-ups are subject to Apron Control clearance, and shall be carried out at a designated location, and report to Apron Control after finish engine run-ups. High power engine run up, or trouble-shooting and testing of engine near boarding bridges or on apron are strictly forbidden.

4. 低能见度运行

4. Low visibility operation

无

Nil

5. 直升机飞行限制，直升机停靠区

5. Helicopter operation restrictions and helicopter parking/docking area

无

Nil

6. 警告

6.1 邻近机场较多，飞行活动频繁，进出本机场的航空器，严格保持航迹和高度，并听从 ATC 指挥；

6.2 机场北端近处有部分处理后的小山包，呈平缓上坡状态，目视着陆时注意目测高度；

6.3 跑道北端外 12-18km 处 300-530m 的山对飞行影响较大，进离场时注意控制高度，该山南坡坡度较大，由北向南着陆时注意防止风切变影响。

6.4 机场周边的机场高速公路灯光与跑道灯光相似，注意识别。

6. Warning

6.1 Several airports near Guangzhou/baiyun airport, many flights exist around the airport, the departing/landing aircraft shall strictly keep the flight track and altitudes, and follow ATC instructions;

6.2 There are several hills with gentle slope near the north end of runway, keep caution on landing;

6.3 The ridges with altitude of 300-530m located at 12-18km from north end of RWY have an adverse effect to landing/departing aircraft, keep the altitude and keep caution to wind shear when aircraft landing from north to south.

6.4 The lighting systems along the airport expressway surrounding the aerodrome resemble runway lighting configurations - extreme caution must be exercised to maintain positive visual identification.

ZGGG AD 2.21 减噪程序**1 噪音限制规定**

1.1 飞机起飞减噪操作程序，用于起飞爬升阶段，目的在于确保飞行安全的前提下尽量减少噪音对地面的影响。

1.2 在保证安全超障和飞程序最低爬升梯度的条件下，要求所有飞行员执行以下减噪飞行操作程序，由于非管制原因不执行减噪飞行操作程序，飞行员须在起飞前告知空管并说明理由（校验飞行等特殊飞行除外）。

2 减噪程序

2.1 在飞机起飞性能允许情况下，尽可能使用减推力起飞。

2.2 在到达高 450m（1500ft）时，起始爬升速度 $V_2+20\text{km/h}$ （10kt），开始减功率/推力，减小机身角/俯仰角，保持可靠上升率和起飞襟翼/缝翼继续爬升。

2.3 保持减功率/推力和可靠的上升率，高度 900m（3000ft）以上时，平稳加速至航路爬升速度，按规定收襟翼/缝翼。

ZGGG AD 2.22 飞程序**1. 总则**

1.1 除经广州进近或塔台特殊许可外，在广州进近管制区和塔台管制区内的飞行，必须按照仪表飞行规则进行。

ZGGG AD 2.21 Noise abatement procedures**1 Noise restrictions**

1.1 Under the condition that aircraft performance allows, use the reduced thrust to take-off.

1.2 Upon condition of complying with the requirements of obstacle clearance and climb gradient required by flight procedure, the following operating procedures for the take-off climb shall be implemented. If the procedures can not be implemented due to any reason, pilot shall inform the ATC before take-off:

2 Noise abatement procedures

2.1 Under the condition that aircraft performance allows, use the reduced thrust to take-off.

2.2 At altitude 450m(1500ft), with a climb speed of V_2 plus 20km/h(10kt), reduce engine power/thrust to climb power/thrust and maintain a speed with flaps and slats in the take-off configuration;

2.3 Above altitude 900m(3000ft), accelerate and retract flaps/slats on schedule while maintaining a positive rate of climb, and complete the transition to normal en-route climb speed.

ZGGG AD 2.22 Flight procedures**1. General**

1.1 Flights within Guangzhou Approach Control Area and Tower Control Area shall operate under IFR unless special clearance has been obtained from Guangzhou

1.2 本场以 RNAV 飞行程序为主用程序（仅提供水平引导），传统飞行程序为备份程序，航空公司原则上只能执行 RNAV 飞行程序。如机组无法执行发布的 RNAV 飞行程序，须在首次联系时报告有关情况。

1.3 如需使用任何 BY ATC 程序需提前向管制员申请，得到管制员同意后方可使用。

2. 起落航线

02L/20R、02R/20L、03/21 跑道起落航线只准在跑道东侧进行，起落航线高度：A、B 类航空器 300m，C、D 类航空器 500-600m。

01L/19R、01R/19L 跑道起落航线只准在跑道西侧进行，起落航线高度：A、B 类航空器 300m，C、D 类航空器 500-600m。

3. 仪表飞行程序

3.1 严格按照航图中公布的进、离场程序和 ENR2.2.2 中公布的有关规定飞行。如果需要，航空器可在空中交通管制部门指定的航路、导航台或定位点上空等待或做机动飞行；

Approach Control or Tower Control.

1.2 RNAV procedures serve as the primary flight procedures at this aerodrome (providing lateral navigation only), with conventional procedures maintained as backup. Airlines shall normally operate RNAV procedures exclusively. Crews unable to execute published RNAV procedures must report the circumstances during initial contact.

1.3 Any request to use BY ATC procedures must be submitted to air traffic control in advance, and may only be implemented after obtaining explicit controller approval.

2. Traffic circuits

Traffic circuits of RWY02L/20R and 02R/20L shall be made to the east of RWY; altitudes of traffic circuits: 500-600m for aircraft CAT C/D, 300m for aircraft CAT A/B.

Traffic circuits of RWY01L/19R and 01R/19L shall be made to the west of RWY; altitudes of traffic circuits: 500-600m for aircraft CAT C/D, 300m for aircraft CAT A/B.

3. IFR flight procedures

3.1 Strict adherence is required to the relevant arrival/departure procedures published in the aeronautical charts and the relevant regulations published in subsection ENR2.2.2. Aircraft may, if necessary, hold or maneuver on an airway, over a navigation facility or a fix designated by ATC;

3.2 白云机场仪表进近程序, 除 ATC 特别指定, 均使用 RNAV ILS/DME Z 程序。

3.3 当 ATC 指令高度与进离场程序中各类限制高度有冲突时, 以 ATC 部门的指令高度为准。

3.4 为保证运行效率, ATC 将对未提前告知不能遵守指令速度或程序图公布速度限制的航空器重新安排落地次序。

3.5 航空器预计使用 01L、01R、02L、02R、03 跑道盲降进近, 但因性能原因不能执行爬升梯度大于 2.5% 的复飞程序时, 机组应当在管制员发布盲降许可前主动告知 ATC。

4. 雷达程序和/或 ADS-B 程序

4.1 广州进近管制区实施雷达管制, 对经雷达识别的航空器提供雷达间隔、雷达监视和雷达引导服务。

4.2 通常, 航空器自进入广州进近管制区起获得雷达引导和排序, 直至相应程序的中间进近航段或目视跑道。

4.3 雷达引导程序

4.3.1 通常, 航空器从 ENVIP、OLPAB、IKAVO、GYA、

3.2 For Baiyun Airport's instrument approach procedures, the RNAV ILS/DME Z procedure shall be used unless specifically assigned otherwise by ATC.

3.3 When there is a conflict between the altitude instructed by ATC and any altitude restrictions specified in the arrival/departure procedures, the altitude instructed by ATC shall take precedence.

3.4 To ensure operational efficiency, ATC will resequence aircraft that fail to notify their inability to comply with instructed speeds or published speed restrictions on procedure charts in advance.

3.5 When aircraft are expected to conduct ILS approaches to RWY01L, 01R, 02L, 02R, or 03 but cannot perform missed approach procedures with climb gradients exceeding 2.5% due to performance limitations, the flight crew must proactively inform ATC before the controller issues the ILS clearance.

4. Radar procedures and/or ADS-B procedures

4.1 Radar control within Guangzhou APP Area has been implemented, and provide such services as radar separating, radar surveillance and radar vectoring to radar-identified aircraft.

4.2 Normally, aircraft will be vectored and sequenced from entering into Guangzhou APP Area to the appropriate middle approach segment or to the time when RWY is in sight.

4.3 Radar Vector Procedures

4.3.1 Normally, aircraft enter Guangzhou Terminal Area

IDUMA 管制移交点进入广州终端区, 在繁忙时段, 为了最大限度的利用空域、减少流量控制, 进近管制员会根据空中运行态势进行雷达引导和排序, 雷达引导航迹将不同于公布的进场程序。特别是白云机场向北运行时 IKAVO、ENVIP 进港航班落在 01L/19R、01R/19L 跑道以及向南运行时 GYA 进港航班落在 01L/19R、01R/19L 跑道时, 与程序航迹差异最大。

via control transfer points ENVIP, OLPAB, IKAVO, GYA and IDUMA. During peak hours, to maximize airspace utilization and minimize flow control, Approach controllers will provide radar vectors and sequencing based on real-time traffic situations, resulting in trajectories that may differ significantly from published arrival procedures. This divergence is most pronounced when IKAVO and ENVIP arrival flights land on RWY01L/19R or 01R/19L during northbound operations at Baiyun Airport, and when GYA arrival flights land on RWY01L/19R or 01R/19L during southbound operations.

4.3.2 最低监视引导高度扇区

4.3.2 Surveillance Minimum Altitude Sectors

Sector 1	ALT limit: 600m or above
N232452E1132524- N232740E1131343- N232106E1131018- N231944E1130656- N230317E1130230- VOR'POU'- N225947E1131752- a circle with a radius of 6km centered on N230015E1132120- N230221E1131840- N230249E1131624- N230545E1131522- N231101E1131330- N231246E1131359- N232258E1132453- N232452E1132524	
Sector 2	ALT limit: 750m or above
N230545E1131522- N231101E1131330- N231246E1131359- N232258E1132453- N230954E1132121- a circle with a radius of 6.7km centered on N230656E1131907- N230545E1131522	
Sector 3	ALT limit: 900m or above
N232258E1132453- N232452E1132524- N232912E1132925- VOR'SHL'-IDUMA- N225254E1132900- N223730E1131942- N223822E1130905- D23.0POU DME arc- N230645E1124712- N233030E1125334- VOR'TAN'- N233405E1131520- N233223E1131505- N232740E1131343- N232106E1131018- N231944E1130656- N230317E1130230- VOR'POU'- N225937E1131833- N230214E1131915- N230249E1131624- N230545E1131522- a circle with a radius of 6.7km centered on N230656E1131907-	

N230954E1132121- N232258E1132453	
Sector 4	ALT limit: 850m or above
VOR'TAN'- N233405E1131520- N233223E1131505- N232740E1131343- N232452E1132524- N232912E1132925- VOR'CON'- N233839E1133140- a circle with a radius of 6km centered on N234057E1133409- N234333E1133121- N234822E1132538- N234712E1132122- N234807E1131528-VOR'TAN'	
Sector 5	ALT limit: 1200m or above
N223730E1131942- N223822E1130905- D23.0POU DME arc- N230645E1124712- N233030E1125334- VOR'TAN'- N234807E1131528- N233059E1123908- N233818E1122554- N231710E1122754- D13.0GYA DME arc- N230054E1124242- N230051E1122909- N224800E1122918- N224312E1122915- N222736E1124453- N222921E1125339- N223300E1131141- N223730E1131942	
Sector 6	ALT limit: 1200m or above
N234807E1131528- N234850E1132144- N235012E1132534- N235045E1132706- N235149E1132911- N235112E1133117- N235105E1133739- N234546E1134046- N233945E1133630- N232515E1134648- N230831E1135838- N230736E1140830- N225400E1140342- IDUMA- VOR'SHL'- N232912E1132925- VOR'CON'- N233839E1133140- a circle with a radius of 6km centered on N234057E1133409- N234333E1133121- N234822E1132538- N234712E1132122- N234807E1131528	
Sector 7	ALT limit: 1500m or above
N231710E1122754- D13.0GYA DME arc- N230054E1124242- N230051E1122909- N230418E1122907- N231710 E1122754	
Sector 8	ALT limit: 1500m or above
N234807E1131528- N234850E1132144- N235012E1132534- N235045E1132706- N235149E1132911- N235112E1133117- N235105E1133739- N234546E1134046- N233945E1133630- N232515E1134648- N232305E1141402- N233851E1141941- N234749E1141217- N240706E1135618- N241229E1132442- N233818E1122554- N233059E1123908- N234807E1131528(except a circle with a radius of 11km centered on N235744E1133120 and a circle with a radius of 11km centered on N233913E1134853)	
Sector 9	ALT limit: 1600m or above
N232515E1134648- N232305E1141402- N2307.6E11408.5- N230831E1135838- N232515E1134648	

Sector 10	ALT limit: 1550m or above
A circle with a radius of 11km centered on N235744E1133120	
Sector 11	ALT limit: 1550m or above
A circle with a radius of 11km centered on N233913E1134853	
Sector 12	ALT limit: 650m or above
N225947E1131752- N225937E1131833- N230214E1131915-- N230221E1131840- a circle with a radius of 6km centered on N230015E1132120- N225947E1131752	
Sector 13	ALT limit: 1750m or above
N240911E1125119-N242313E1130257-N242056E1132513-N241907E1134238-N241651E1140358-N240500E1141250-N234749E1141217-N240706E1135618-N241229E1132442-N233818E1122554-N235429E1123911-N240911E1125119	

5. 无线电通信失效程序

参见 AIP GEN3.4.5 中的仪表飞行规则航空器地空双向无线电通信失效通用程序。

5. Radio communication failure procedures

Refer to AIP GEN3.4.5 general procedures for aircraft under instrument flight rule with air-ground two-way radio communication failure.

6. 目视飞程序

6.1 经 ATC 许可, 广州进近和白云塔台管制区内可以由管制员通过目视航空器或由机组目视其他航空器配备目视间隔, 以提高运行安全和运行效率。

6. Procedures for VFR flights

6.1 Upon receiving ATC clearance, within the Guangzhou Approach and Guangzhou Baiyun Tower control areas, visual separation may be provided by ATC through visual observation of aircraft or by pilots visually observing other aircraft, to enhance operational safety and efficiency.

6.2 广州白云机场实施目视进近实验运行:

6.2 Guangzhou Baiyun Airport implements experimental visual approach operation.

6.2.1 实施条件

6.2.1 Implementation Conditions

6.2.1.1 广州白云机场在符合实施目视进近的天气条

6.2.1.1 When weather conditions are suitable for

件下,通过 ATIS 告知航空器驾驶员相应跑道可以实施的进近方式。

6.2.1.2 目视进近可以由航空器驾驶员申请或者管制员发起,得到对方认可后方可实施。

6.2.1.3 广州白云机场在实施平行跑道同时进近时,管制员采用雷达引导的方式指挥航空器使用 01L/19R 跑道, 02R/20L 跑道, 03/21 跑道实施目视进近。

6.2.1.4 广州白云机场仅在 01L 或 02R 或 03 号跑道实施短五边目视进近。实施前,航空器驾驶员要与管制员提前沟通并获得管制员同意方可执行。

6.2.2 航空器驾驶员须知

6.2.2.1 实施目视进近的航空器驾驶员报告目视着陆机场或者目视前机后,管制员可以发布目视进近指令。

6.2.2.2 实施目视进近的航空器驾驶员在任何情况下都必须保持对着陆机场或者前机持续能见,如果不能持续能见必须尽早告知管制员。

6.2.2.3 航空器驾驶员在接受目视进近许可前,管制员为航空器之间配备符合规定的安全间隔,接受目视进

implementing a visual approach, Guangzhou Baiyun Airport will inform aircraft pilots through the ATIS of the available approach procedure for the corresponding runway.

6.2.1.2 A visual approach may be requested by the aircraft pilot or initiated by ATC, and can only be implemented following mutual agreement.

6.2.1.3 When Guangzhou Baiyun Airport is implementing simultaneous approaches on parallel runways, the ATC directs aircraft using radar vectoring to utilize Runways 01L/19R, 02R/20L, and 03/21 for visual approach.

6.2.1.4 Guangzhou Baiyun Airport only permits short final visual approach on runway 01L, 02R, or 03. Before executing this, the pilot must communicate with the ATC in advance and obtain the approval from ATC.

6.2.2 Pilot's Information

6.2.2.1 When implementing a visual approach, after the pilot reports visual contact with the landing airport or the preceding aircraft, ATC may issue a visual approach clearance.

6.2.2.2 When implementing a visual approach, the pilot must maintain continuous visual contact with the landing airport or the preceding aircraft under all situations, and if unable to maintain such contact, must inform the controller ASAP.

6.2.2.3 Before the pilot accepts visual approach clearance, ATC shall provide prescribed safe separation

近许可之后，航空器驾驶员负责保持与地面障碍物之间的安全间隔并飞向着陆机场或者跟随前序航空器实施进近。当接受跟随前序航空器目视进近许可后，航空器驾驶员负责与同跑道前序航空器之间的安全间隔。

6.2.2.4 平行跑道同时进近时，目视进近或仪表进近的航空器均不得越过进近跑道的五边延长线。

6.2.2.5 执行目视进近时，除非管制员已发布速度指令，航空器驾驶员应当对航空器速度进行控制：距接地点 8NM 速度不小于 180kt，距接地点 6NM 速度不小于 160kt。实施短五边目视进近航空器可以自行掌握速度。

6.2.2.6 实施目视进近的航空器驾驶员落地后应尽快脱离跑道，着陆航空器从飞越跑道入口端至完全脱离跑道时间应控制在 50s 内，如需使用更长的时间占用跑道时，航空器驾驶员应在着陆前告知管制员。

6.2.3 应急程序

6.2.3.1 实施目视进近过程中，因失去目视参照物(机

between aircrafts. After accepting visual approach clearance, the pilot is responsible for maintaining safe separation from ground obstacles and proceeding to the landing airport or following the preceding aircraft to conduct the approach. After accepting visual approach clearance to follow the preceding aircraft, the pilot is also responsible for maintaining safe separation from the preceding aircraft on the same runway.

6.2.2.4 When implementing parallel runway simultaneous approaches, aircrafts which implementing visual or instrument approaches shall not cross the extended final leg of the runway they are approaching.

6.2.2.5 When implementing a visual approach, unless the ATC has issued speed instructions, the pilot shall control the aircraft speed: maintain a speed of no less than 180kt before reaching 8NM from the touchdown point, and no less than 160kt before reaching 6NM from the touchdown point. Aircrafts implementing a short final visual approach may determine their speed at their own discretion.

6.2.2.6 After landing, aircrafts implementing visual approach shall exit the runway ASAP. For landing aircraft, the time from passing the runway threshold to completely exiting the runway shall be controlled within 50s. If longer runway occupancy time is required, the pilot shall inform the ATC before landing.

6.2.3 Emergency Procedures

6.2.3.1 When implementing visual approach, if the

场、跑道或前序航空器)等原因无法完成目视进近时,航空器驾驶员应及时报告管制员,管制员根据航空器驾驶员意图协助其转为仪表进近、中止进近或复飞。

6.2.3.2 目视进近复飞时,航空器驾驶员按照管制员指令或参考仪表进近程序复飞方法执行,复飞过程中航空器驾驶员负责与地面障碍物的安全间隔。

6.3 机组在得到仪表进近指令后,应随时利用机载设备或目视监控周边航空器的运行状态,并尽可能建立航空器间的目视能见。

6.4 当管制员通报其他航空器相对位置时,机组应目视查找该航空器,并在看到该航空器后,向管制员报告建立目视能见。

6.5 航空器进近至决断高度时,会遇到在同一跑道上前面着陆的航空器正在脱离或即将脱离跑道,或者正在进行起飞滑跑的航空器即将离地的情况,机组需持续保持目视观察。

6.6 02L/20R 及 02R/20L 跑道为窄距运行跑道,02R/20L 进近航空器在进近至落地过程中,会遇到相邻跑道上的航空器正在起飞滑跑,机组需持续保持目视观察。

aircraft is unable to complete the visual approach due to the loss of visual references (caused by the airport, runway, or preceding aircraft), the pilot should promptly report to the ATC. The ATC will assist the pilot based on their intentions to transition to an instrument approach, terminate the approach, or go around.

6.2.3.2 During a visual approach go-around, the aircraft pilot shall adhere to ATC instructions or refer to the go-around procedures of the instrument approach procedure, and shall be responsible for maintaining safe separation from ground obstacles.

6.3 After receiving the instrument approaching instructions, pilot should use airborne equipment or visually monitor the operation status of surrounding aircraft at any time, and establish visual visibility between aircraft as possible.

6.4 When controllers provide the relative position of other aircraft, flight crews shall visually locate the traffic and report "traffic in sight" to ATC upon visual acquisition.

6.5 As approaching to DA, aircraft will encounter other aircraft which sliding at RWY. Pilot shall keep visual observation.

6.6 RWY02L/20R and 02R/20L are narrow-distance runways. Approaching and landing aircraft on RWY02R/20L will encounter other take-off sliding aircraft on adjacent runway. Pilot shall keep visual

	observation.
6.7 机组明确表示能够目视另一架航空器并接受目视间隔时，机组应当承担以下职责：	6.7 When visualising another aircraft and accepting visual intervals, pilot shall assume the following responsibilities:
6.7.1 始终保持对相关航空器的目视，并保持与相关航空器间的安全间隔；	6.7.1 Maintain a visualisation and a safe interval of the relevant aircraft.
6.7.2 为保持与相关航空器的安全间隔做机动飞行时，必须事先向管制员通报并征得管制员的同意；	6.7.2 When make manoeuvrable flight to maintain a safe interval with the relevant aircraft, inform the controller in advance and get the permission.
7. 目视飞行航线	7. VFR route
无	Nil
8. 其它规定	8. Other regulations
无	Nil

ZGGG AD 2.23 其它资料

鸟情资料

日常容易吸引鸟类进入活动。鸟类活动频繁区域主要涉及西一跑道（01R/19L）中段、西二跑道（01L/19R）南端（01L）、东一跑道（02L/20R）南端（02L）以及东二跑道（02R/20L）中段。鸟类主要集中在日间时段活动，夜间也有少量夜行性鸟类和蝙蝠活动，主要活动高度在 0-300m 之间。大多数鸟类为小型鸟类（体重 200g 以下），少量为大中型鸟类（体重 200g 以上），部分鸟类的飞行线路可能会与航空器的起降轨迹冲突，存在一定的鸟击风险。

ZGGG AD 2.23 Other information

Bird's information

Areas prone to regular bird activity primarily include: the mid-section of RWY01R/19L, the southern end of RWY01L/19R(01L direction), the southern end of RWY02L/20R (02L direction), and the mid-section of RWY02R/20L. Bird activity occurs predominantly during daylight hours, with limited nocturnal activity from night-flying species and bats, typically at altitudes of 0-300m. Most birds observed are small species(under 200g body weight), with occasional medium/large birds(over 200g). Some flight paths may intersect aircraft approach/departure trajectories, presenting bird strike risks.

常见鸟类活动规律如下:

Common bird activity patterns are as follows:

Species of bird	Time of activity	Flight height (m)	Activity routines
Herons(Egretta garzetta, Ardeola bacchus, Nycticorax nycticorax)	Throughout the year	0-200	Single or small clusters, but also mixed groups
Swallow(Hirundo rustica, Hirundo daurica)	March - November	0-50	Groups, or mixed groups
Raptors(Milvus migrans lineatus, Falco tinnunculus, Elanus caeruleus, Buteo japonicus)	Throughout the year	0-200	Single
Plovers(Glareola maldivarum)	March to September	0-50	Single or small clusters
Other small birds(Anthus richardi, Alauda arvensis)	November to June	0-10	Singly or in small groups, mixed with larks

在每年的候鸟迁徙季节（3月-5月和9月-11月）、300-5000m 为主的高度层、黄昏至次日清晨，经常有鸟类迁徙活动，包含鹭类等大中型鸟类和鸟群，本场及周边较大范围空域均有发现过境行为，鸟击风险较大，有时会造成处于航路飞行、下降、进近或爬升阶段的飞机损伤。

During annual migration seasons(March-May and September-November), bird migration activities frequently occur primarily at altitudes between 300-5000m, from dusk until the following morning. These include medium/large birds (such as herons/egrets) and flocks, with transit behaviors observed both within the aerodrome and surrounding airspace, presenting significant bird strike risks. Such strikes have occasionally caused damage to aircraft during enroute, descent, approach, or climb phases.

本场配备探鸟雷达和探鸟光电设备，配备驱鸟车、驱鸟炮、驱鸟弹药、声波驱鸟器、拦鸟网等设施设备，开展全天巡视驱赶，并对草坪、昆虫、其它动物、水体、树木等生态环境对象采取持续治理措施，减少引鸟因素。

The aerodrome is equipped with avian detection radar and electro-optical tracking systems, supported by bird dispersal vehicles, propane cannons, pyrotechnic ammunition, sonic repellent devices, and bird exclusion netting. Continuous patrols and dispersal operations are conducted 24/7, complemented by ongoing ecological management of turf areas, insect populations, wildlife attractants, water features, and vegetation to minimize bird attraction factors.