

Path Terminator	Waypoint ID	Fly over	Magnetic Course(°)	Turn Direction	Altitude (m)	IAS (kt)	VPA/TCH	Navigation Specification
TF	PM523							RNAV1
TF	PM522							RNAV1
TF	PM521							RNAV1
TF	PM520				3900	AT230		RNAV1
TF	MP3				3300	MAX210		RNAV1
RWY03/04L/04R STAR MEBN9E								
IF	MEBNA							RNAV1
TF	PP517							RNAV1
TF	PP515							RNAV1
TF	PP511							RNAV1
TF	PM508				4200	AT230		RNAV1
TF	PM507							RNAV1
TF	PM506							RNAV1
TF	PM505							RNAV1
TF	PM504							RNAV1
TF	PM503							RNAV1
TF	PM502							RNAV1
TF	PM501				4200	AT230		RNAV1
TF	MP3				3300	MAX210		RNAV1
RWY03/04L/04R STAR MEBN5N								
IF	MEBNA							RNAV1
TF	PP517				5100			RNAV1
TF	PP511							RNAV1
TF	MP3				3300	MAX210		RNAV1
RWY03/04L/04R STAR XISL5N								
IF	XISLI							RNAV1
TF	PP502							RNAV1
TF	PP512							RNAV1
TF	XSJ				3600	MAX210		RNAV1
RWY03/04L/04R STAR ELAS5N								
IF	ELASU							RNAV1
TF	IDPUG				3600	MAX210		RNAV1
RWY03/04L/04R STAR NIXA5N								
IF	NIXAS							RNAV1
TF	PP858				4800			RNAV1
TF	MP3				3300	MAX210		RNAV1
RWY03/04L/04R Holding(Outbound Time:1.5min)								
HM	PP516	Y	217	L	4500			RNAV1
HM	PP517	Y	217	R	5100			RNAV1
Changes: Procedure, Chart number.								