

Path Terminator	Waypoint ID	Fly over	Magnetic Course(°)	Turn Direction	Altitude (m)	IAS (kt)	VPA/TCH	Navigation Specification
RWY03/04L/04R Holding(Outbound Time:1min)								
HM	PM529	Y	110	L	3900			RNAV1
RWY21/22L/22R STAR XISL1A								
IF	XISLI							RNAV1
TF	PP502							RNAV1
TF	PP516							RNAV1
TF	PM457							RNAV1
TF	MP2				3300	MAX210		RNAV1
RWY21/22L/22R STAR XISL2B								
IF	XISLI							RNAV1
TF	PP502							RNAV1
TF	PM426				4500	AT230		RNAV1
TF	PM425							RNAV1
TF	PM424							RNAV1
TF	PM423							RNAV1
TF	PM422							RNAV1
TF	PM421							RNAV1
TF	PM420				4500	AT230		RNAV1
TF	MP1				3600	MAX210		RNAV1
RWY21/22L/22R STAR XISL3C (by ATC)								
IF	XISLI							RNAV1
TF	PP502							RNAV1
TF	PP516							RNAV1
TF	PM457				3900	AT230		RNAV1
TF	PM456							RNAV1
TF	PM455							RNAV1
TF	PM454							RNAV1
TF	PM453							RNAV1
TF	PM452							RNAV1
TF	PM451							RNAV1
TF	PM450				3900	AT230		RNAV1
TF	MP2				3300	MAX210		RNAV1
RWY21/22L/22R STAR LXI1A								
IF	LXI							RNAV1
TF	IGRID							RNAV1
TF	XSJ							RNAV1
TF	PP512							RNAV1
TF	MP2				3300	MAX210		RNAV1
Changes: Procedure, Chart number.								