

ZPPP/KMG

4P-11

KUNMING/Changshui

RNAV RWY03/04L/04R

VAR1.8°W

AD ELEV 2103.5

Kunming Approach							140°3600 230°ARP 3300 MSA 25NM BEARINGS ARE MAGNETIC. ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS. ALL DISTANCES IN NAUTICAL MILES.
D-ATIS 128.45	APP01 119.0 (125.55)	APP02 123.8 (125.55)	APP03 120.35 (127.9)	APP04 121.15 (126.55)	APP05 124.25 (127.9)	APP07 119.225	
Kunming Tower		TL TA	Notes: 1. Using this chart need ATC permission. 2. CDO terminated once ATC give heading instructions.				MEBNA-5N XISLI-5N ELASU-5N NIXAS-5N
TWR(E) 118.1 (118.85)	TWR(W) 130.6 (118.85)		6000 5400 5700(QNH≥1031hPa) 5100(QNH≤979hPa)				
Only used for CDO							

N

NOT TO SCALE

RNAV1
GNSS
or DME/DME/IRU
RADAR REQUIRED

or
RNP1
GNSS

NIXAS

189°

30

NIXAS-5N

PP858

4800

53

IAF MP3

3300

MAX210kt

MEBNA

217°

36

MEBNA-5N

PP517

5100

63

IAF IDPUG

3600

MAX210kt

XISLI

238°

10

XISLI-5N

PP502

25

IAF XSJ

3600

MAX210kt

PP511

31

PP512

25

JINNING

108.2 XSJ

CH 19X

N24 41.0E102 48.0

ELASU

047°

59

ELASU-5N

03,04L,04R

RWY	STAR	Database ID	ROUTING
03,04L,04R	MEBNA-5N	MEBN5N	MEBNA-PP517-PP511-MP3
	XISLI-5N	XISL5N	XISLI-PP502-PP512-XSJ
	ELASU-5N	ELAS5N	ELASU-IDPUG
	NIXAS-5N	NIXA5N	NIXAS-PP858-MP3

Changes: Procedure, Chart number.

Changes: Procedure, Chart number.