

INSTRUMENT
APPROACH
CHART-ICAO
ZPPP/KMG

5L-5

AD ELEV 2103.5
DTHR ELEV 2100.9

KUNMING/Changshui

RNAV ILS/DME z RWY04R

VAR1.8°W

Kunming Approach

Kunming Approach

D-ATIS 128.45

APP01 119.0 (125.55)

APP02 123.8 (125.55)

APP03 120.35 (127.9)

APP04 121.15 (126.55)

APP05 124.25 (127.9)

APP07 119.225

Kunming Tower

TWR(E) 118.1 (118.85)

TWR(W) 130.6 (118.85)

LOC ITH 111.7

Final Apch Crs 040°

FAF D12.4 ITH 3300(1200)

MISSED APPROACH
Climb straight ahead to D2.8 ITH at 2245 or above, turn RIGHT and track 055° MAG to 2700, turn RIGHT and direct to PP512, then track 217° MAG to PP934 at 3300, contact ATC.

TL 6000
TA 5400
5700(QNH≥1031hPa)
5100(QNH≤979hPa)

Note:
Approach speed limit:
Keep IAS180kt at IF, keep IAS more than 170kt until 8NM from touchdown, otherwise inform ATC.

3600
ARP
3300
MSA 25NM

BEARINGS ARE MAGNETIC.
ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS.
ALL DISTANCES IN NAUTICAL MILES.

GP INOP

DME (ITH)

ALT

IF C104R D16.2 ITH 3300 AT180kt

FAF GP INOP D12.4 ITH

GP INOP D3.6 ITH 2450 (350)

MAPt GP INOP D1.3 ITH

IF IDPUG 3600 MAX210kt

PP702 040°

PP703 040°

PP934 3300

PP512 MAX210kt

ILS/DME 040° 111.7 ITH

JINNING 108.2 XSJ CH 19X

RDH 16

THR displaced 300m

FAF-MAPt 11.1NM (GP INOP)

GS kt

min:sec

GP 3°/m/s

ILS/DME MAC 3.0% 0

ILS/DME MAC 2.5%

GP INOP

DA(H)

OCA(H)

RVR

VIS

MDA(H)

OCA(H)

RVR

VIS

D2.8 ITH 2245

055° 2700

Changes: New chart.