

INSTRUMENT
APPROACH
CHART-ICAO
ZPPP/KMG

5L-8

AD ELEV 2103.5
DTHR ELEV 2099.1

KUNMING/Changshui

ILS/DME y RWY21

VAR1.8°W

Kunming Approach

Kunming Approach

D-ATIS 128.45 **APP01 119.0 (125.55)** **APP02 123.8 (125.55)** **APP03 124.25 (127.9)** **APP04 121.15 (126.55)** **APP05 120.35 (127.9)** **APP07 119.225**

Kunming Tower

TWR(E) 118.1 (118.85) **TWR(W) 130.6 (118.85)** **LOC IBH 110.1** **Final Apch Crs 220°** **FAF D12.4 IBH 3300(1201)**

MISSED APPROACH
Climb straight ahead (with gradient ≥ 4.0%) to D2.7 IBH at 2285 or above, turn RIGHT and track 250° MAG to D8.0 IBH at 2700 or above (with gradient ≥ 4.0%), turn RIGHT to SGM at 3300, contact ATC.

Notes:
1. Approach speed limit: Keep IAS 180kt at IF, keep IAS more than 170kt until 8NM from touchdown, otherwise inform ATC.
2. Circling W of RWY only.
3. Missed approach turn MAX IAS 210kt.

Map Details:
• **PANLONG 110.8 XFA** CH 45X
• **3900 MAX 210kt**
• **D8.6 XFA**
• **IF D16.3 IBH 3300** AT 180kt
• **D14.0 XFA**
• **D46.0 XSJ**
• **D42.0 XSJ**
• **D26.0 XSJ 4200** MAX 210kt
• **D2.7 IBH 2285**
• **D8.0 IBH 2700**
• **3300 MAX 210kt**
• **XISHAN 110.6 SGM** CH 43X
• **JINNING 108.2 XSJ** CH 19X

MSA 25NM
BEARINGS ARE MAGNETIC. ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS. ALL DISTANCES IN NAUTICAL MILES.

GP INOP

DME (IBH)	2	4	6	8	10	12
ALT	2293	2487	2682	2876	3070	3264

FAF-MAPt 11.0NM (GP INOP)

GS kt	80	100	120	140	160	180
min:sec	8:15	6:36	5:30	4:43	4:08	3:40
GP 3°/m/s	2.1	2.7	3.3	3.8	4.3	4.9

ILS/DME MAG 4.0%

DA(H)	OCA(H)	RVR	VIS	MDA(H)	OCA(H)	RVR	VIS
2160(60)	2160(60)	800	800	2235(136)	2230(131)	1800	1800

GP INOP

MDA(H)	OCA(H)	VIS
2350(247)	2800	
2470(367)	3000	
2500(397)	4400	
2500(397)	5000	

CIRCLING

MDA(H)	OCA(H)	VIS
2350(247)	2800	
2470(367)	3000	
2500(397)	4400	
2500(397)	5000	

ILS HUD Special CAT I

(DH)	(RA)	RVR
(45)	(64)	450

ILS HUD Special CAT II

(DH)	(RA)	RVR
(30)	(33)	350

Changes: Procedure, Chart number.