

INSTRUMENT
APPROACH
CHART-ICAO
ZPPP/KMG

5L-9

AD ELEV 2103.5
THR ELEV 2098.0

KUNMING/Changshui

RNAV ILS/DME z RWY22L

VAR1.8°W

Kunming Approach

Kunming Approach

D-ATIS 128.45	APP01 119.0 (125.55)	APP02 123.8 (125.55)	APP03 124.25 (127.9)	APP04 121.15 (126.55)	APP05 120.35 (127.9)	APP07 119.225
-------------------------	-----------------------------------	-----------------------------------	-----------------------------------	------------------------------------	-----------------------------------	-------------------------

Kunming Tower

TWR(E) 118.1 (118.85)	TWR(W) 130.6 (118.85)	LOC IPB 109.95	Final Apch Crs 220°	FAF D9.3 IPB 3000(902)	MISSED APPROACH Climb straight ahead to D2.6 IPB at 2235 or above, turn LEFT and track 205°MAG to PP509 at 2700 or above, turn LEFT to XSJ at 3300, contact ATC.
------------------------------------	------------------------------------	--------------------------	-------------------------------	--	---

TL 6000
TA 5400
5700(QNH≥1031hPa)
5100(QNH≤979hPa)

Note:
Approach speed limit:
Keep IAS180kt at IF, keep IAS more than 170kt until 8NM from touchdown, otherwise inform ATC.
A APCH via PP417 only for CDO

The chart displays the Kunming area with various flight paths and altitudes. Key features include:

- Altitude Contours:** 2200, 2400, 2600, 2800, 3000, 3200, 3400, 3600, 3800, 4000, 4200, 4400, 4600, 4800, 5000, 5200, 5400, 5600, 5800, 6000, 6200, 6400, 6600, 6800, 7000, 7200, 7400, 7600, 7800, 8000, 8200, 8400, 8600, 8800, 9000, 9200, 9400, 9600, 9800, 10000.
- Navigation Aids:** ILS/DME 220° 109.95 IPB, FAF D9.3 IPB, GP INOP D1.4 IPB, GP INOP D9.3 IPB, GP INOP D16.0 IPB.
- Waypoints:** PP417, PP713, PP712, PP509, XSJ, ARP.
- Obstacles:** Various obstacles are shown with their MSL and AGL altitudes.
- Communication:** Frequencies for Tower, Unicom, and other services are listed.

GP INOP	DME (IPB)	2	3	4	5	6	7	8
	ALT	2292	2389	2486	2583	2680	2777	2874

ILS/DME MAPS 3.0% G

GS kt	80	100	120	140	160	180
min:sec	5:56	4:44	3:57	3:23	2:58	2:38
GP 3°m/s	2.1	2.7	3.3	3.8	4.3	4.9

① RVR 550 / ② RVR 650 can be implemented when using approved HUD or AP or FD for approach.
③ Maintain prescribed gradient to PP509.

ILS/DME MAPS 2.5%

DA(H)	OCA(H)	RVR	VIS	DA(H)	OCA(H)	RVR	VIS	MDA(H)	OCA(H)	RVR	VIS
A											
B	2158(60)	2158(60)	⑧800	800	2178(80)	2178(80)	⑧800	800	2230(132)	2230(132)	1700
C											
D											

Changes: New chart.