

INSTRUMENT
APPROACH
CHART-ICAO
ZPPP/KMG

5L-12

AD ELEV 2103.5
DTHR ELEV 2096.7

KUNMING/Changshui

CAT-I/II ILS/DME y RWY22R

VAR1.8°W

Kunming Approach

D-ATIS 128.45

APP01 119.0 (125.55)

APP02 123.8 (125.55)

APP03 124.25 (127.9)

APP04 121.15 (126.55)

APP05 120.35 (127.9)

APP07 119.225

Kunming Tower

TWR(E) 118.1 (118.85)

TWR(W) 130.6 (118.85)

LOC IKM 108.5

Final Appch Crs 220°

FAF D9.3 IKM 3000(903)

MISSED APPROACH
Climb straight ahead to D2.6 IKM at 2220 or above, turn LEFT and track 205°MAG to D13.0 IKM at 2700 or above, turn LEFT to XSJ at 3300, contact ATC.

Notes:
1. Missed approach turn MAX IAS210kt.
2. Approach speed limit:
Keep IAS180kt at IF, keep IAS more than 170kt until 8NM from touchdown, otherwise inform ATC.

TL 6000
TA 5400
5700(QNH≥1031hPa)
5100(QNH≤979hPa)

IAF 3900 MAX210kt
D9.5XFA 3000
D5.0XFA 3300
ILS/DME 220° 108.5 IKM
D2.6 IKM 2220
D13.0 IKM 2700
IAF D26.0XSJ 4200 MAX210kt
D15.0XFA
D46.0XSJ 3000
D42.0XSJ 3000
IF D16.0 IKM 3000
AT180kt
IAF R037°XSJ D60.0XSJ 4200 MAX210kt

PANLONG 110.8 XFA CH 45X
JINNING 108.2 XSJ CH 19X
3300 MAX210kt

KUNMING

MSA 25NM
BEARINGS ARE MAGNETIC.
ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS.
ALL DISTANCES IN NAUTICAL MILES.

GP INOP

DME (IKM)

ALT

MAPt GP INOP D1.4 IKM
GP INOP D5.3 IKM
FAF GP INOP D9.3 IKM
IF D16.0 IKM

RDH 16
THR displaced 500m

MDA 2300
2600

FAF-MAPT 7.9NM (GP INOP)

GS kt
min:sec
GP 3°/m/s

ILS/DME
DA(H)
OCA(H)
RVR
VIS

GP INOP
MDA(H)
OCA(H)
RVR
VIS

PALS CAT II
PAPI

D2.6 IKM
2220
210kt MAX LT

ILS CAT II
Autopilot to DH and below
Manual operation below DH

ILS HUD Special CAT I
(DH)
(RA)
RVR

A
B
C
D

2157(60)
2157(60)
550
800
2230(133)
2230(133)
1700
1700
(30)
(31)
300
300
(45)
(47)
450

Changes: Procedure, Chart number.