

ZSZS/HSN

VAR6.2°W

5L-1

AD ELEV 1.8
THR ELEV 1.8

ZHOUSHAN/Putuoshan

RNP ILS/DME z RWY18

Zhoushan Tower
TWR **118.05**
(124.35)

LOC IPT
108.75

Final Appch Crs
181°

FAF D7.2 IPT
700(698)

MISSED APPROACH
Climb straight ahead to 600, turn LEFT to ZS206 at 1200 or above, and fly to ZS205 to approach again, or join ZS206 holding pattern by ATC.

Note: **A** Approach after join ZS203 holding pattern and descend altitude due airspace restrictions only.

BEARINGS ARE MAGNETIC. ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS. ALL DISTANCES IN NAUTICAL MILES.

MSA 25NM

1200 ARP 1000

210°

360°

210°

122° 45'

122° 30'

122° 15'

122° 00'

30° 15'

30° 00'

29° 45'

1200

1000

400

300

200

100

CONTOUR INTERVALS

ZS203
D11.5 IPT
D12.1 HSN
900

IAF ZS204
1200
MAX210kt

IAF RULMU A
2400
or by ATC
MAX210kt

IAF ZS205
1200
MAX210kt

ZS206
1200
MAX210kt

1200
MAX230kt

1500
MAX230kt

ILS/DME
181° 108.75 IPT

ZHOUSHAN
112.3 HSN
CH 70X

606

503

430

320

200

100

325

154

379

228

377

550

204

298

334

391

302

257

207

324

181°

271°

091°

360°

001°

001°

091°

181°

360°

180°

11.4NM

7.0

2.9

1.0

0-0.2 -0.8

RDH 15

GP INOP

DME (IPT)

7

6

5

4

3

2

1

0

ALT

680

583

485

388

291

181°

700(698)

400

260

MDA

GP3°

HSN

IPT

IF ZS203
D11.5 IPT
D12.1 HSN

FAF GP INOP
D7.2 IPT
D7.8 HSN

GP INOP
D3.1 IPT
D3.7 HSN
300(298)

MAPt GP INOP
D1.2 IPT
D1.8 HSN

FAF-MAPT 6.0NM (GP INOP)

GS kt

80

100

120

140

160

180

min:sec

4:30

3:36

3:00

2:34

2:15

2:00

GP 3°fpm

420

530

640

740

850

960

③ RVR550 can be implemented when using approved HUD or AP or FD for approach.

PALS CAT I

PAPI

600

210kt MAX

LT

ZS206

1200

210kt MAX

ILS HUD Special CAT I

5.0%

DA(H)

OCA(H)

RVR

VIS

DA(H)

OCA(H)

VIS

MDA(H)

OCA(H)

VIS

MDA(H)

OCA(H)

VIS

CIRCLING

MDA(H)

OCA(H)

VIS

ILS HUD Special CAT I

5.0%

(DH)

(OCH)

(RA)

RVR

A

B

C

D

62(60)

62(60)

③ 800

800

142(140)

142(140)

2000

200(198)

190(188)

3200

490(488)

490(488)

4800

(45)

(45)

(46)

450

Changes: Procedure, VAR, MSA, chart number.