

INSTRUMENT APPROACH CHART-ICAO ZUGY/KWE

VAR1.8°W

5L-2

AD ELEV 1138.9
THR ELEV 1138.9

GUIYANG/Longdongbao

ILS/DME y RWY01L

D-ATIS(English)
126.825

D-ATIS(Chinese)
127.05

APP01
120.075
(119.45)

APP02
126.05
(119.45)

APP03
119.025
(119.725)

APP04
119.15
(119.725)

TWR
118.3
(118.05)

Guiyang Tower
TWR
118.525
(118.05)

LOC IGG
111.1

Final Appch Crs
012°

FAF
D9.9 IGG
2100(961)

MISSED APPROACH
Climb straight ahead to 1700, turn RIGHT to KWE at 2400 , contact ATC.

TL 3600
TA 3000
3300(QNH≥1031hPa)
2700(QNH≤979hPa)

Notes:
Speed limits as aircraft performance allows: keep IAS=170kt before 9.8NM from the touchdown point, and then keep IAS≥ 150kt until 6NM from the touchdown point.
Missed approach turning MAX IAS205kt.

2400

KWE

MSA 25NM

BEARINGS ARE MAGNETIC.
ALTITUDES, ELEVATIONS AND
HEIGHTS IN METERS.
ALL DISTANCES IN NAUTICAL MILES.

GP INOP	DME (IGG)	9	8	7	6	5	4	3		
	HGT (m)	2010	1913	1816	1719	1622	1525	1428		

IF
D12.3 IGG
D12.0KWE

FAF
D9.9 IGG
D9.6KWE

GP INOP
D5.3 IGG
D4.9KWE

MAPt
GP INOP
D2.4 IGG
D2.0KWE

KWE IGG

2100(961)

1900

1560

1650(511)

MDA

RDH
16.3

12.2NM

9.7

5.1

2.2

0

FAF-MAPt 7.5NM (GP INOP)						
GS kt	80	100	120	140	160	180
min:sec	5:38	4:30	3:45	3:13	2:49	2:30
GP 3°m/s	2.1	2.7	3.3	3.8	4.3	4.9

ILS/DME

GP INOP

CIRCLING

ILS HUD Special CAT I

DA(H)

OCA(H)

RVR

VIS

MDA(H)

OCA(H)

VIS

MDA(H)

OCA(H)

VIS

A,B,C,D

A

B

C

D

1199(60)

1199(60)

800

800

1365(227)

1364(226)

3500

1400(261)

1385(247)

4200

1450(311)

1447(309)

4200

1580(441)

1579(441)

5000

1610(471)

1608(470)

5000

(DH)

(45)

(RA)

(87)

RVR

450

Changes: ATIS FREQ.