

INSTRUMENT APPROACH CHART-ICAO ZUGY/KWE

5L-4

AD ELEV 1138.9
THR ELEV 1137.6

GUIYANG/Longdongbao

ILS/DME y RWY01R

VAR1.8°W

D-ATIS(English) 126.825		D-ATIS(Chinese) 127.05		APP01 120.075 (119.45)		APP02 126.05 (119.45)		APP03 119.025 (119.725)		APP04 119.15 (119.725)		Gwyang Tower TWR 118.3 (118.05)		2400 KWE MSA 25NM BEARINGS ARE MAGNETIC. ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS. ALL DISTANCES IN NAUTICAL MILES.
Guiyang Tower TWR 118.525 (118.05)		LOC ILR 111.35		Final Appch Crs 012°		FAF D9.9 ILR 2100(962)		MISSED APPROACH Climb straight ahead to 1700, turn RIGHT to KWE at 2400, contact ATC.						
TL 3600 TA 3000 3300(QNH≥1031hPa) 2700(QNH≤979hPa)		Notes: Speed limits as aircraft performance allows: keep IAS=170kt before 9.8NM from the touchdown point, and then keep IAS≥ 150kt until 6NM from the touchdown point. Missed approach turn MAX IAS205kt.												

GP INOP	DME (ILR)	9	8	7	6	5	4	3		
	HGT (m)	2009	1912	1815	1718	1621	1524	1427		

IF
D12.3 ILR
D12.0KWE

FAF GP INOP
D9.9 ILR
D9.6KWE

GP INOP
D5.3 ILR
D4.9KWE

MAPt GP INOP
D2.4 ILR
D2.0KWE

KWE ILR

2100(962)

1900

1560

1650(512)

MDA

0

12.2NM

9.7

5.1

2.2

0

GP3°

RDH 17.1

FAF-MAPt 7.5NM (GP INOP)							PALS CAT I PAPI 1700 205kt MAX RT KWE 114.3 & 2400	ILS HUD Special CAT I A,B,C,D (DH) (RA) RVR
GS kt	80	100	120	140	160	180		
min:sec	5:38	4:30	3:45	3:13	2:49	2:30		
GP 3°m/s	2.1	2.7	3.3	3.8	4.3	4.9		

⚠ RVR 550 can be implemented when using approved HUD or AP or FD for approach.

1700

205kt
MAX
RT

ILS/DME				GP INOP			CIRCLING			ILS HUD Special CAT I A,B,C,D (DH) (RA) RVR
DA(H)	OCA(H)	RVR	VIS	MDA(H)	OCA(H)	VIS	MDA(H)	OCA(H)	VIS	
A							1400(261)	1385(247)	4200	
B							1450(311)	1447(309)	4200	
C	1198(60)	1198(60)	800	800	1365(228)	1364(227)	3500	1580(441)	1579(441)	5000
D								1610(471)	1608(470)	5000

Changes: ATIS FREQ.