

INSTRUMENT
APPROACH
CHART-ICAO
ZUGY/KWE

VAR1.8°W

5L-5

AD ELEV 1138.9
THR ELEV 1134.3

GUIYANG/Longdongbao

RNAV ILS/DME z RWY19L

D-ATIS(English)
126.825

D-ATIS(Chinese)
127.05

APP01
120.075
(119.45)

APP02
126.05
(119.45)

APP03
119.025
(119.725)

APP04
119.15
(119.725)

TWR
118.3
(118.05)

Guiyang Tower
TWR
118.525
(118.05)

LOC IDL
111.55

Final Apch Crs
192°

FAF
D10.0 IDL
2100(966)

MISSED APPROACH
Climb straight ahead to 1900, turn LEFT to GY802 at 2400, contact ATC.

TL 3600
TA 3000
3300(QNH≥1031hPa)
2700(QNH≤979hPa)

Note:Speed limits as aircraft performance allows: keep IAS=170kt before 9.8NM from the touchdown point, and then keep IAS≥ 150kt until 6NM from the touchdown point.

2400
ARP

MSA 25NM

BEARINGS ARE MAGNETIC.
ALTITUDES, ELEVATIONS AND
HEIGHTS IN METERS.
ALL DISTANCES IN NAUTICAL MILES.

GP INOP	DME (IDL)	2	3	4	5	6	7	8		
	HGT (m)	1328	1425	1522	1619	1716	1814	1911		

KWE

IDL

MAPt GP INOP
D1.3 IDL
D3.4KWE

GP INOP
D3.3 IDL
D5.3KWE
1450(316)

FAF GP INOP
D10.0 IDL
D12.0KWE

IF
GY713
D17.5 IDL
D19.5KWE

THR displaced 200m
DIST to displaced THR

RDH
16.3

MDA
1440

GP3°

192°

2100(966)

1850

17.3NM

FAF-MAPt 8.6NM (GP INOP)

GS kt	80	100	120	140	160	180
min:sec	6:27	5:10	4:18	3:41	3:14	2:52
GP 3°m/s	2.1	2.7	3.3	3.8	4.3	4.9

⚠ RVR 550 can be implemented when using approved HUD or AP or FD for approach.

PALS CAT I
PAPI

1900

LT

GY802

2400

205kt
MAX

ILS HUD Special CAT I

A,B,C,D	(DH)	(RA)	RVR
(45)	(115)	450	

ILS/DME	GP INOP	CIRCLING	ILS HUD Special CAT I		
DA(H)	OCA(H)	MDA(H)	OCA(H)	VIS	A,B,C,D
		1400(261)	1385(247)	4200	(DH)
		1450(311)	1447(309)	4200	(RA)
		1580(441)	1579(441)	5000	(115)
		1610(471)	1608(470)	5000	RVR

Changes: ATIS FREQ.