

INSTRUMENT
APPROACH
CHART-ICAO
ZUGY/KWE

VAR1.8°W

5L-7

AD ELEV 1138.9
THR ELEV 1137.1

GUIYANG/Longdongbao
RNAV CAT I/II ILS/DME z RWY19R

D-ATIS(English) 126.825 **D-ATIS(Chinese) 127.05**

APP01 120.075 (119.45)	APP02 126.05 (119.45)	APP03 119.025 (119.725)	APP04 119.15 (119.725)	TWR 118.3 (118.05)
-------------------------------------	------------------------------------	--------------------------------------	-------------------------------------	---------------------------------

Guiyang Tower
TWR **118.525** (118.05)
LOC **IGY** **109.3**
Final Appch Crs **192°**
FAF **D9.9 IGY** 2100(963)

MISSED APPROACH
Climb straight to 1400, turn RIGHT to GY812 at 1800 or above, fly to GY823 at 2400, approach again or contact ATC.

Note: Speed limits as aircraft performance allows: keep IAS=170kt before 9.8NM from the touchdown point, and then keep IAS≥ 150kt until 6NM from the touchdown point.

GP INOP

DME (IGY)	2	3	4	5	6	7	8
HGT (m)	1329	1426	1523	1620	1717	1814	1911

THR displaced 300m
DIST to displaced THR

GS kt	80	100	120	140	160	180
min:sec	6:27	5:10	4:18	3:41	3:14	2:52
GP 3°m/s	2.1	2.7	3.3	3.8	4.3	4.9

FAF-MAPT 8.6NM (GP INOP)

ILS/DME MACG 3%	ILS/DME MACG 2.5%	GP INOP	CIRCLING	ILS CAT II MACG 3%	ILS HUD Special CAT I MACG 3%
DA(H) OCA(H) RVR VIS	DA(H) OCA(H) RVR VIS	MDA(H) OCA(H) RVR VIS	MDA(H) OCA(H) VIS	A,B,C,D	A,B,C,D
A			1400(261) 1385(247) 4200	(DH) (30)	(DH) (45)
B			1450(311) 1447(309) 4200	(OCH) (30)	(RA) (47)
C	1198(60) 1198(60) 550 800	1228(90) 1228(90) 900 900	1265(128) 1265(128) 1600 1600	Autopilot to DH and below RVR	RVR
D			1580(441) 1579(441) 5000	Manual operation A,B,C,D below DH RVR	450

Changes: ATIS FREQ.