

INSTRUMENT
APPROACH
CHART-ICAO
ZUGY/KWE

VAR1.8°W

5L-8

AD ELEV 1138.9
THR ELEV 1137.1

GUIYANG/Longdongbao

CAT I/II ILS/DME y RWY19R

D-ATIS(English)
126.825

D-ATIS(Chinese)
127.05

APP01
120.075
(119.45)

APP02
126.05
(119.45)

APP03
119.025
(119.725)

APP04
119.15
(119.725)

TWR
118.3
(118.05)

Guiyang Tower
TWR
118.525
(118.05)

LOC **IGY**
109.3

Final Apch Crs
192°

FAF **D9.9 IGY**
2100(963)

MISSED APPROACH
Climb straight ahead to 1900, turn LEFT to KWE at 2400, contact ATC.

TL 3600
TA 3000
3300(QNH±1031hPa)
2700(QNH±979hPa)

Notes:
Speed limits as aircraft performance allows: keep IAS=170kt before 9.8NM from the touchdown point, and then keep IAS≥ 150kt until 6NM from the touchdown point.
Missed approach turn MAX IAS205kt.

2400
KWE

MSA 25NM

BEARINGS ARE MAGNETIC.
ALTITUDES, ELEVATIONS AND
HEIGHTS IN METERS.
ALL DISTANCES IN NAUTICAL MILES.

GP INOP	DME (IGY)	2	3	4	5	6	7	8		
	HGT (m)	1329	1426	1523	1620	1717	1814	1911		

MAPt GP INOP
D1.3 IGY
D3.0KWE

GP INOP
D3.2 IGY
D5.0KWE

FAF GP INOP
D9.9 IGY
D11.6KWE

IF
D12.3 IGY
D14.0KWE

THR displaced 300m
DIST to displaced THR

RDH **16.9**

MDA 1440

1900

2100(963)

1850

FAF-MAPt 8.6NM (GP INOP)						
GS kt	80	100	120	140	160	180
min:sec	6:27	5:10	4:18	3:41	3:14	2:52
GP 3°m/s	2.1	2.7	3.3	3.8	4.3	4.9

PALS CAT III
PAPI

1900

205kt
MAX
LT

KWE
114.3

2400

ILS/DME				GP INOP				CIRCLING			ILS CAT II			ILS HUD Special CAT I			
DA(H)	OCA(H)	RVR	VIS	MDA(H)	OCA(H)	RVR	VIS	MDA(H)	OCA(H)	VIS	A,B,C,D	(DH)	(OCH)	(RA)	A,B,C,D		
A								1400(261)	1385(247)	4200	(DH)	(30)			(DH)	(45)	
B								1450(311)	1447(309)	4200	(RA)	(30)			(RA)	(47)	
C	1198(60)	1198(60)	550	800	1265(128)	1265(128)	1600	1600	1580(441)	1579(441)	5000	Autopilot to DH and below RVR	300				
D									1610(471)	1608(470)	5000	Manual operation below DH RVR	300	350		RVR	450

Changes: ATIS FREQ.