

INSTRUMENT APPROACH CHART-ICAO ZUGY/KWE

VAR1.8°W

5V-3

AD ELEV 1138.9
THR ELEV 1137.1

GUIYANG/Longdongbao

VOR/DME RWY19R

D-ATIS(English) 126.825		D-ATIS(Chinese) 127.05		APP01 120.075 (119.45)		APP02 126.05 (119.45)		APP03 119.025 (119.725)		APP04 119.15 (119.725)		Guiyang Tower TWR 118.3 (118.05)	
Guiyang Tower TWR 118.525 (118.05)		VOR KWE 114.3		Final Apch Crs 195°		FAF D11.7 KWE 2100(963)		MISSED APPROACH Climb straight ahead to 1900, turn LEFT to KWE at 2400, contact ATC.					
TL 3600 TA 3000 3300(QNH±1031hPa) 2700(QNH±979hPa)		Notes: RWY19R in the west, RCL offset 3°E to final. Missed approach turn MAX IAS205kt.											
BEARINGS ARE MAGNETIC. ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS. ALL DISTANCES IN NAUTICAL MILES.													

DME (KWE)	5	6	7	8	9	10	11			
HGT (m)	1450	1547	1643	1739	1836	1932	2028			

		FAF-MAPT 7.4NM						PALS CAT III PAPI		CIRCLING	
GS kt	80	100	120	140	160	180			1900	205kt MAX LT	KWE 114.3 & 2400
min:sec	5:33	4:26	3:42	3:10	2:46	2:28					
5.2m/s	2.1	2.7	3.3	3.8	4.3	4.9					

VOR/DME			CIRCLING		
MDA(H)	OCA(H)	VIS	MDA(H)	OCA(H)	VIS
A			1400(261)	1385(247)	4200
B			1450(311)	1447(309)	4200
C	1385(248)	1385(248)	1580(441)	1579(441)	5000
D			1610(471)	1608(470)	5000

Changes: ATIS FREQ.