

INSTRUMENT
APPROACH
CHART-ICAO
ZUUU/CTU

5L-7

AD ELEV 512.4
THR ELEV 496.6

CHENGDU/Shuangliu

RNAV ILS/DME z RWY20L

VAR2.2°W

D-ATIS(Chinese)
126.45

D-ATIS(English)
128.6

APP01
124.85
(127.7)

APP06
126.35
(125.25)

APP07
119.425
(123.825)

APP08
119.25
(123.825)

TWR
130.35
(118.85)

LOC IDE
109.7

Final Apch Crs
204°

FAF D10.3 IDE
1500(1003)

MISSED APPROACH
Climb straight ahead and fly over UU462,
continue to climb to 750,
turn LEFT and direct to BHS at 1500 , contact ATC.

TL 3600
TA 3000
3300(QNH≥1031hPa)
2700(QNH≤979hPa)

Notes:
1. Simultaneously approaches with RW20R, radar vectoring to intercept the localizer course.
2. Speed limits as aircrafts performance allows: keep IAS180kt before final leg until 8NM from the touchdown point,
and then keep IAS 160kt until 6NM from the touchdown point.

2200

090°→CTU

1400

MSA 25NM

BEARINGS ARE MAGNETIC.
ALTITUDES, ELEVATIONS AND
HEIGHTS IN METERS.
ALL DISTANCES IN NAUTICAL MILES.

104° 45'

GP INOP

DME (IDE)

2

3

4

5

6

7

8

ALT (m)

691

788

885

981

1078

1175

1272

MAPt GP INOP D1.7 IDE

GP INOP D4.2 IDE 900(403)

FAF GP INOP D10.3 IDE

IF GP INOP UU623 D15.7 IDE

RDH 15

GP3°

204°

204°

1500(1003)

204°

FAF-MAPt 8.7NM (GP INOP)

GS kt

80

100

120

140

160

180

min:sec

6:32

5:13

4:21

3:44

3:16

2:54

GP 3°m/s

2.1

2.7

3.3

3.8

4.3

4.9

ILS/DME MACG 4% ④

ILS/DME MACG 2.5%

GP INOP

CIRCLING

ILS HUD Special CAT II MACG 4% ④ A,B,C,D

DA(H)

OCA(H)

RVR

VIS

DA(H)

OCA(H)

RVR

VIS

MDA(H)

OCA(H)

VIS

MDA(H)

OCA(H)

VIS

(DH)

(RA)

RVR

A

B

C

D

557(60)

557(60)

800

800

557(60)

557(60)

800

800

562(65)

560(63)

800

800

660(163)

658(162)

2300

700(188)

691(179)

2400

740(228)

728(216)

3200

740(228)

728(216)

3600

(30)

(33)

350

Changes: D-ATIS, OBST.