

INSTRUMENT
APPROACH
CHART-ICAO
ZUUU/CTU

5L-9

AD ELEV 512.4
THR ELEV 495.4

CHENGDU/Shuangliu
RNAV ILS/DME z RWY20R

VAR2.2°W

D-ATIS(Chinese)
126.45

D-ATIS(English)
128.6

APP01
124.85
(127.7)

APP06
126.35
(125.25)

APP07
119.425
(123.825)

APP08
119.25
(123.825)

TWR
123.0
(118.85)

LOC IAA
109.1

Final Apch Crs
204°

FAF D7.3 IAA
1200(705)

MISSED APPROACH
Climb straight ahead and fly over UU425 at 630 or above ,
turn RIGHT to CZH at 1800, contact ATC.

TL TA
3600
3000
3300(QNH≥1031hPa)
2700(QNH≤979hPa)

Notes:
1. Simultaneously approaches with RWY20L, radar vectoring to intercept the localizer course.
2. Speed limits as aircrafts performance allows: keep IAS180kt before final leg until 8NM from the touchdown point,
and then keep IAS 160kt until 6NM from the touchdown point.

2200

1400

CTU

MSA 25NM

BEARINGS ARE MAGNETIC.
ALTITUDES, ELEVATIONS AND
HEIGHTS IN METERS.
ALL DISTANCES IN NAUTICAL MILES.

GP INOP	DME (IAA)	1	2	3	4	5	6	7		
	ALT (m)		687	784	881	978	1075	1172		

MAPt GP INOP
D1.4 IAA
D2.4CTU

GP INOP
D4.2 IAA
D5.4CTU
900(405)

FAF GP INOP
D7.3 IAA
D8.5CTU

IF
UU513
D13.3 IAA
D14.5CTU

CTU IAA

RDH 15

MDA

800

1000

1200(705)

204°

GP3°

FAF-MAPt 5.9NM (GP INOP)							PALS CAT I		GP INOP		CIRCLING		
GS kt	80	100	120	140	160	180	PAPI	630	UU425	RT	CZH 114.5	1800	200kt MAX
min:sec	4:26	3:32	2:57	2:32	2:13	1:58							
GP 3°m/s	2.1	2.7	3.3	3.8	4.3	4.9							
ILS/DME MACS 3% DA(H) OCA(H) RVR VIS							ILS/DME MACS 2.5% DA(H) OCA(H) RVR VIS				CIRCLING MDA(H) OCA(H) VIS		
A	556(60) 555.4(60) 800 800						631(135) 631(135) 1700 1700				700(188) 691(179) 2400		
B													
C	561(65) 560.4(65) 800 800						630(135) 623(128) 1700 1700				740(228) 728(216) 3200		
D											740(228) 728(216) 3600		

Changes: D-ATIS, OBST.