

INSTRUMENT
APPROACH
CHART-ICAO
ZUUU/CTU

VAR2.2°W

5L-10

AD ELEV 512.4
THR ELEV 495.4

CHENGDU/Shuangliu

ILS/DME y RWY20R

D-ATIS(Chinese)
126.45

D-ATIS(English)
128.6

APP01
124.85
(127.7)

APP06
126.35
(125.25)

APP07
119.425
(123.825)

APP08
119.25
(123.825)

TWR
123.0
(118.85)

LOC **IAA**
109.1

Final Apch Crs
204°

FAF **D7.3 IAA**
1200(705)

MISSED APPROACH
Climb straight ahead to 'z'/D1.2CTU(D2.4IAA)
at 630 or above , turn RIGHT to CZH at 1800, contact ATC.

TL 3600
TA 3000
3300(QNH≥1031hPa)
2700(QNH≤979hPa)

Notes:
1. Simultaneously approaches with RWY20L, radar vectoring to intercept the localizer course.
2. Missed approach turning MAX IAS200kt.
3. Speed limits as aircrafts performance allows: keep IAS180kt before final leg until 8NM from the touchdown point,
and then keep IAS 160kt until 6NM from the touchdown point.

2200

090°→CTU

1400

MSA 25NM

BEARINGS ARE MAGNETIC.
ALTITUDES, ELEVATIONS AND
HEIGHTS IN METERS.
ALL DISTANCES IN NAUTICAL MILES.