

**ZUUU AD 2.1 机场地名代码和名称 Aerodrome location indicator(ICA0 / IATA) and name**

ZUUU/CTU-成都/双流 CHENGDU/Shuangliu

**ZUUU AD 2.2 机场地理位置和管理资料 Aerodrome geographical and administrative data**

|   |                                                                                                   |                                                                                                                                                                                                                          |
|---|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | 机场基准点坐标及其在机场的位置<br>ARP coordinates and site at AD                                                 | N30°34.8' E103°56.9'<br>Center of RWY02L/20R                                                                                                                                                                             |
| 2 | 机场基准点与城市的位置关系<br>Direction and distance from city                                                 | 230 °GEO, 16.8km from the Sichuan Science and Technology Museum                                                                                                                                                          |
| 3 | 机场标高、基准温度、低温均值<br>ELEV/Reference temperature/Mean low temperature                                 | 512.4 m/32.1°C(AUG)/4.6°C(JAN)                                                                                                                                                                                           |
| 4 | 机场标高位置的大地水准面波幅<br>Geoid undulation at AD ELEV PSN                                                 |                                                                                                                                                                                                                          |
| 5 | 磁差（测量年份）及年变率<br>VAR(Year)/Annual change                                                           | 2°12'W/-5'00"                                                                                                                                                                                                            |
| 6 | 机场管理部门、地址、电话、传真、AFS 地址、电子邮箱、网址<br>AD administration/Address/Telephone/Telefax/AFS/ E-mail/Website | Southwest Regional Administration of CAAC<br>Chengdu Shuangliu International Airport, Sichuan province, China. Post code:610202<br>TEL:86-28-85206624<br>FAX:86-28-85206124<br>AFS:ZUUUYDYX<br>Website:www.cdairport.com |
| 7 | 允许飞行种类<br>Types of traffic permitted(IFR/VFR)                                                     | IFR-VFR                                                                                                                                                                                                                  |
| 8 | 机场性质/飞行区指标<br>Military or civil airport/Reference code                                            | CIVIL/RWY02R/20L: 4F; RWY02L/20R: 4E                                                                                                                                                                                     |
| 9 | 备注<br>Remarks                                                                                     | Nil                                                                                                                                                                                                                      |

**ZUUU AD 2.3 工作时间 Operational hours**

|   |                                   |     |
|---|-----------------------------------|-----|
| 1 | 机场开放时间<br>AD Operational hours    | H24 |
| 2 | 海关和移民<br>Customs and immigration  | H24 |
| 3 | 卫生健康部门<br>Health and sanitation   | H24 |
| 4 | 航空情报服务讲解室<br>AIS Briefing Office  | H24 |
| 5 | 空中交通服务报告室<br>ATS Reporting Office | H24 |

|    |                                |     |
|----|--------------------------------|-----|
| 6  | 气象服务讲解室<br>MET Briefing Office | H24 |
| 7  | 空中交通服务<br>Air Traffic Service  | H24 |
| 8  | 加油服务<br>Fuelling               | H24 |
| 9  | 地勤服务<br>Handling               | H24 |
| 10 | 安保服务<br>Security               | H24 |
| 11 | 除冰服务<br>De-icing               | H24 |
| 12 | 备注<br>Remarks                  | Nil |

**ZUUU AD 2.4 地勤服务和设施 Handling services and facilities**

|   |                                                       |                                                                                                                                                                                                        |
|---|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | 货物装卸设施<br>Cargo-handling facilities                   | Conveyor truck, platform truck, fork, tow truck, platform lorry, container drum tractor                                                                                                                |
| 2 | 燃油牌号<br>Fuel types                                    | Jet Fuel No.3                                                                                                                                                                                          |
| 3 | 滑油牌号<br>Oil types                                     | Nil                                                                                                                                                                                                    |
| 4 | 加油设施/能力<br>Fuelling facilities & Capacity             | Refueling truck(780L/min), hydrant dispenser(one pipe: 800L/min, double pipe: 2000L/min), apron refueling wells                                                                                        |
| 5 | 除冰设施<br>De-icing facilities                           | 8 de-icers                                                                                                                                                                                             |
| 6 | 过站航空器机库<br>Hangar space for visiting aircraft         | Nil                                                                                                                                                                                                    |
| 7 | 过站航空器的维修设施<br>Repair facilities for visiting aircraft | Maintenance tools and equipment                                                                                                                                                                        |
| 8 | 备注<br>Remarks                                         | Ground air supply unit, ground power unit, passenger stairs, lift truck for disabled, shuttle bus, air condition car, tow tug, potable water supply vehicles, lavatory service vehicles, garbage truck |

**ZUUU AD 2.5 旅客设施 Passenger facilities**

|   |                        |                                                            |
|---|------------------------|------------------------------------------------------------|
| 1 | 宾馆<br>Hotels           | At AD and in the city                                      |
| 2 | 餐饮<br>Restaurants      | At AD and in the city                                      |
| 3 | 交通工具<br>Transportation | Passenger's coaches, taxis, buses, metro, high-speed train |

|   |                               |                                        |
|---|-------------------------------|----------------------------------------|
| 4 | 医疗设施<br>Medical facilities    | First aid at AD, hospitals in the city |
| 5 | 银行和邮局<br>Bank and Post Office | Bank At AD and Post Office in the city |
| 6 | 旅行社<br>Tourist Office         | At AD                                  |
| 7 | 备注<br>Remarks                 | Nil                                    |

**ZUUU AD 2.6 援救与消防服务 Rescue and fire fighting services**

|   |                                                           |                                                                                                                                                                                                                                                                                                                              |
|---|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | 机场消防等级<br>AD category for fire fighting                   | CAT 10                                                                                                                                                                                                                                                                                                                       |
| 2 | 援救设备<br>Rescue equipment                                  | Fire fight facilities: rapid intervention vehicle, primary foam tender, heavy-load foam truck, dry-chemical tender, demolition rescue truck, illumination truck, support vehicle, communication command vehicle;<br>Rescue equipments: uplift air cushion, air pump, towing platform, fork, mobile surface operation devices |
| 3 | 搬移受损航空器的能力<br>Capability for removal of disabled aircraft | MTWA up to B747-800、AN-124                                                                                                                                                                                                                                                                                                   |
| 4 | 备注<br>Remarks                                             | Nil                                                                                                                                                                                                                                                                                                                          |

**ZUUU AD 2.7 可用季节- 扫雪 Seasonal availability-clearing**

|   |                                                                  |                               |
|---|------------------------------------------------------------------|-------------------------------|
| 1 | 可用季节及扫雪设备类型<br>Seasonal availability/Types of clearing equipment | All seasons<br>Not applicable |
| 2 | 扫雪顺序<br>Clearance priorities                                     | Not applicable                |
| 3 | 备注<br>Remarks                                                    | Nil                           |

**ZUUU AD 2.8 停机坪、滑行道及校正位置数据 Aprons, taxiways and check locations data**

|   |                                        |                |                                                                                                                                                                                                                                                                                                                                                                                        |
|---|----------------------------------------|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | 停机坪道面和强度<br>Apron surface and strength | 道面<br>Surface  | CONC                                                                                                                                                                                                                                                                                                                                                                                   |
|   |                                        | 强度<br>Strength | PCR 1440/R/B/W/T : Stands Nr. 101-104, 106-108, 213, 214, 229, 230, 361-365, 361L/R, 362L/R, 364L/R<br>PCR 1350/R/A/W/T : Stands Nr. 113-121<br>PCR 1350/R/B/W/T : Stands Nr. 301-304, 303L/R, 304L/R<br>PCR 1330/R/B/W/T : Stands Nr.122-127<br>PCR 1320/R/B/W/T : Stands Nr.128-132<br>PCR 1290/R/A/W/T : Stands Nr.405, 406, 405L/R, 406L/R<br>PCR 1250/R/A/W/T : Stands Nr.420-422 |

|   |                                                       |             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---|-------------------------------------------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|   |                                                       |             | PCR 1200/R/A/W/T : Stands Nr. 320-322, 324, 326-335, 326L/R<br>PCR 1180/R/A/W/T : Stands Nr.313-317, 410, 313L/R-317L/R<br>PCR 1170/R/A/W/T : Stands Nr.401-404, 401L/R, 403L/R<br>PCR 1160/R/A/W/T : Stands Nr. 318, 319, 318L/R, 319L/R<br>PCR 1150/R/B/W/T : Stands Nr. 201-212, 215-219, 224-228<br>PCR 1140/R/A/W/T : Stands Nr.357-359, 357L/R<br>PCR 1100/R/B/W/T : Stands Nr.305-308, 305L/R, 306L/R, 308L/R<br>PCR 1090/R/A/W/T : Stands Nr. 105, 109-112<br>PCR 1080/R/A/W/T : Stands Nr. 501、502<br>PCR 1070/R/A/W/T : Stands Nr. 168-173<br>PCR 1020/R/B/W/T : Stands Nr. 411, 412<br>PCR 1010/R/A/W/T : Stands Nr. 407-409, 407L/R, 408L/R<br>PCR 940/R/A/W/T : Stands Nr. 161, 162<br>PCR 930/R/A/W/T : Stands Nr. 134, 135, 151-160<br>PCR 920/R/A/W/T : Stands Nr. 146, 147<br>PCR 910/R/A/W/T : Stands Nr.141-145<br>PCR 900/R/A/W/T : Stands Nr. 164, 165<br>PCR 900/R/B/W/T : Stands Nr. 136-140<br>PCR 890/R/A/W/T : Stands Nr. 166, 167<br>PCR 850/R/A/W/T : Stands Nr.149, 150, 503-508, 505L/R-508L/R<br>PCR 840/R/A/W/T : Stands Nr.231-239<br>PCR 770/R/A/W/T : Stands Nr.423, 424, 601-610, 613-619 |
| 2 | 滑行道宽度、道面和强度<br>Taxiway width, surface<br>and strength | 宽度<br>Width | 59m : B1(east of B)<br>57m : C3<br>54m : C2<br>52m : D1-D5, E2(west of E), E8(west of E)<br>50m : A2(east of B), B7(west of B), B10(west of B)<br>49m : B6(west of B), B8(west of B), B9<br>48m : A1(BTN A & B), B1(west of B), B3(east of B), B6-B8(east of B),<br>B10(east of B), C5-C8<br>46m : A8(east of A), A9, B3(west of B), B4, B5<br>44m : B2, E2(east of E), E8(east of E)<br>39m : A1(east of B), A2(west of B), C1<br>34m : E1, E9<br>29m : E3, E6, E7<br>28.5m : A3, A4<br>28m : A1(west of A), A8(west of A)<br>27m : A5, A6, E4, E5<br>25m : B(south of B1), C(BTN A2 & C5), D, E(south of E9), M, N<br>23m : A, A7, B(north of B1), C(north of C5, south of A2), E(north of E9), F,<br>H1-H6, K1, K2, K4, T1, T2(west of stand Nr.319), T3, T4, T8-T10<br>18m : H7, K3, T2(east of stand Nr.319), T6, T7                                                                                                                                                                                                                                                                                                     |
|   |                                                       | 道面          | CONC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

|  |  |                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|--|--|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  |  | Surface        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|  |  | 强度<br>Strength | <p>PCR 1440/R/B/W/T : H5(east of stand Nr.104), H6(BTN stand Nr.229 &amp; Nr.230), T1(west of stand Nr.359), V1, V2</p> <p>PCR 1380/F/A/X/T : B(1270-1490m north of C1, 1715-1910m north of C1)</p> <p>PCR 1370/R/B/W/T : T3(west of stand Nr.304)</p> <p>PCR 1350/R/A/W/T : H3</p> <p>PCR 1350/R/B/W/T : T3(east of stand Nr.304)</p> <p>PCR 1330/R/B/W/T : H2</p> <p>PCR 1320/R/B/W/T : H1</p> <p>PCR 1300/F/A/X/T : C5</p> <p>PCR 1290/R/A/W/T : E8, H5(BTN C &amp; stand Nr.104), K2(BTN stand Nr.405 &amp; Nr.406)</p> <p>PCR 1270/F/A/X/T : C7</p> <p>PCR 1260/R/A/W/T : E9</p> <p>PCR 1250/R/A/W/T : K1</p> <p>PCR 1230/F/A/X/T : C(910-1130m &amp; 1270-1490m &amp; 1715-1910m north of C1)</p> <p>PCR 1200/R/A/W/T : T10(north of stand Nr.412)</p> <p>PCR 1180/R/A/W/T : T2(west of stand Nr.318L)</p> <p>PCR 1170/F/B/X/T : B3(BTN B &amp; C)</p> <p>PCR 1170/R/A/W/T : K4</p> <p>PCR 1160/R/A/W/T : T2(BTN stand Nr.318L &amp; T10)</p> <p>PCR 1150/R/B/W/T : H6(BTN stand Nr.229 &amp; Nr.230 excepted), H7</p> <p>PCR 1140/R/A/W/T : N, T1(BTN T10 &amp; stand Nr.359)</p> <p>PCR 1130/R/A/W/T : E2</p> <p>PCR 1130/R/B/W/T : T4(west of stand Nr.307)</p> <p>PCR 1120/R/A/W/T : D1-D5, M</p> <p>PCR 1110/R/A/W/T : E1</p> <p>PCR 1100/R/A/W/T : B(BTN A2 &amp; 910m north of C1), C2</p> <p>PCR 1100/R/B/W/T : B(BTN B10 &amp; stand Nr.231)</p> <p>PCR 1090/R/A/W/T : H4</p> <p>PCR 1080/R/A/W/T : B(BTN M &amp; A1), C(BTN N &amp; A1), D, T4(stand Nr.304-stand Nr.307)</p> <p>PCR 1070/R/A/W/T : A7</p> <p>PCR 1070/R/B/W/T : A(130-2860m north of A1)</p> <p>PCR 1060/R/A/W/T : T4(east of stand Nr.304)</p> <p>PCR 1050/R/A/W/T : A9, C1</p> <p>PCR 1040/R/A/W/T : A1, C8</p> <p>PCR 1030/R/A/W/T : B(BTN A1&amp; A2)</p> <p>PCR 1020/R/A/W/T : E(south of E9)</p> <p>PCR 1020/R/B/W/T : T10(south of stand Nr.412)</p> <p>PCR 1010/F/A/X/T : C3</p> <p>PCR 1010/R/A/W/T : B6, K2(BTN stand Nr.407 &amp; Nr.409)</p> |

|   |                                             |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---|---------------------------------------------|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|   |                                             |     | <p>PCR 1000/R/A/W/T : A(BTN A1 &amp; 130m north of A1), A3</p> <p>PCR 990/R/A/W/T : A8, B7, E(north of E9)</p> <p>PCR 980/R/A/W/T : A2(east of A), B1, B2, B9</p> <p>PCR 970/R/A/W/T : B8, C6</p> <p>PCR 940/R/A/W/T : B(1490-1715m north of C1), T6(west of stand Nr.160)</p> <p>PCR 940/R/B/W/T : A4(80m east of RWY02L CL to A)</p> <p>PCR 930/R/A/W/T : T6(east of stand Nr.160), T7(east of stand Nr.151), T9(west of stand Nr.136)</p> <p>PCR 920/R/A/W/T : A(BTN 2860m north of A1 &amp; A8), A4(0-80m east of RWY02L CL), B(BTN B6 &amp; B10), B3(BTN A &amp; B), C(BTN 1910m north of C1 &amp; B6, BTN A1 &amp; 910m north of C1, 1490-1715m north of C1), T8(west of stand Nr.145)</p> <p>PCR 910/R/A/W/T : B4, B10, E7, T8(east of stand Nr.145)</p> <p>PCR 900/R/A/W/T : B5, C(1130-1270m north of C1)</p> <p>PCR 900/R/B/W/T : T9(east of stand Nr.136)</p> <p>PCR 890/R/A/W/T : E4</p> <p>PCR 870/R/A/W/T : B(1130-1270m north of C1)</p> <p>PCR 860/R/A/W/T : F</p> <p>PCR 850/R/A/W/T : A(BTN A8 &amp; A9), A2(west of A), B(north of stand Nr.231, BTN 1910m north of C1 &amp; B6), C(B6-B10), T7(west of stand Nr.151)</p> <p>PCR 850/R/B/W/T : A5, A6</p> <p>PCR 830/R/A/W/T : E3</p> <p>PCR 790/R/A/W/T : B(910-1130m north of C1)</p> <p>PCR 770/R/A/W/T : K3</p> <p>PCR 710/R/A/W/T : E5</p> <p>PCR 640/R/A/W/T : E6</p> |
| 3 | 高度表校正点的位置及其标高<br>ACL location and elevation | Nil |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 4 | VOR 校正点<br>VOR checkpoints                  | Nil |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 5 | INS 校正点<br>INS checkpoints                  | Nil |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 6 | 备注<br>Remarks                               | Nil |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## ZUUU AD 2.9 地面活动引导和管制系统与标识

### Surface movement guidance and control system and markings

|   |                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                     |
|---|-----------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | 航空器机位号码标记牌、滑行道引导线、航空器目视停靠引导系统的使用<br>Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands | Taxiing guidance signs at all intersections of TWY and RWY.<br>Taxiing guidance signs at all holding positions.<br>Aircraft stand identification sign boards at all stands.<br>Guide lines at all aprons.<br>Marshalling assistance for all aircraft stands.                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                     |
| 2 | 跑道和滑行道标志及灯光<br>RWY and TWY marking and LGT                                                                                                          | 跑道标志<br>RWY markings                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Pre-threshold area, THR, RWY designation, edge line, RWY center line, TDZ, aiming point                                                             |
|   |                                                                                                                                                     | 跑道灯光<br>RWY lights                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | RTHL, WBAR, REDL, RCLL, RTZL(02L, 02R), RENL                                                                                                        |
|   |                                                                                                                                                     | 滑行道标志<br>TWY markings                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Edge line, center line, TWY shoulder marking, mandatory instruction marking, information signs, RWY holding position, intermediate holding position |
|   |                                                                                                                                                     | 滑行道灯光<br>TWY lights                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Edge line lights, center line lights, No-entry bar , RETILs, intermediate holding position lights                                                   |
| 3 | 停止排灯和跑道警戒灯<br>Stop bars and runway guard lights                                                                                                     | Stop bar lights: A1, A2, A8, E1, E2, E8, E9<br>Operating Rules:<br>(1) Upon receiving ATC instructions to enter or cross a runway, aircraft may proceed to cross the stop bar only after the red stop bar lights are extinguished and the taxiway centerline lights illuminating the entry path to the runway are activated.<br>(2) If the above three conditions cannot be simultaneously met, the aircraft/vehicles/personnel shall reconfirm with the air traffic controller and execute operations strictly in accordance with new instructions issued by the controller after verification.<br>Runway guard lights |                                                                                                                                                     |
| 4 | 其它跑道保护措施<br>Other runway protection measures                                                                                                        | Nil                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                     |
| 5 | 备注<br>Remarks                                                                                                                                       | Retro-reflector marker on the edge of following TWYs straight parts: C(south of A2), D, E, E1-E9, M, N). Road-holding position light.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                     |

## ZUUU AD 2.10 机场障碍物 Aerodrome obstacles

半径 15 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| 1                                           | 2                         | 3                                                                        | 4                                           | 5                                                                       | 6                                                                                    |
| BLDG<br>001                                 | BLDG                      | 012/10601                                                                | 569.6                                       |                                                                         |                                                                                      |
| Antenna<br>002                              | Antenna                   | 014/3743                                                                 | 529                                         |                                                                         | RWY02L Take-off path                                                                 |
| BLDG<br>003                                 | BLDG                      | 015/2527                                                                 | 517.2                                       |                                                                         | RWY02L Take-off path                                                                 |
| BLDG<br>004                                 | BLDG                      | 015/2566                                                                 | 518                                         |                                                                         | RWY02L Take-off path                                                                 |
| Antenna<br>005                              | Antenna                   | 016/4142                                                                 | 535.4                                       |                                                                         | RWY02L Take-off path                                                                 |
| Trees<br>006                                | Trees                     | 017/2443                                                                 | 516                                         |                                                                         | RWY02L Take-off path                                                                 |
| BLDG<br>007                                 | BLDG                      | 026/10462                                                                | 605.9                                       |                                                                         | RWY02L Take-off path                                                                 |
| BLDG<br>008                                 | BLDG                      | 029/4173                                                                 | 547.8                                       | LGT                                                                     | RWY02L departure;<br>RWY02L Take-off path                                            |
| BLDG<br>009                                 | BLDG                      | 032/3965                                                                 | 542                                         | LGT                                                                     |                                                                                      |
| TOWER<br>010                                | TOWER                     | 050/14581                                                                | 645.1                                       |                                                                         |                                                                                      |
| BLDG<br>011                                 | BLDG                      | 053/14776                                                                | 695.9                                       | LGT                                                                     |                                                                                      |
| BLDG<br>012                                 | BLDG                      | 054/4211                                                                 | 553                                         | LGT                                                                     |                                                                                      |
| BLDG<br>013                                 | BLDG                      | 056/3955                                                                 | 551                                         | LGT                                                                     |                                                                                      |
| BLDG<br>014                                 | BLDG                      | 072/11920                                                                | 594.5                                       | LGT                                                                     |                                                                                      |



半径 15 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| BLDG<br>015                                 | BLDG                      | 085/12901                                                                | 593.8                                       | LGT                                                                     |                                                                                      |
| BLDG<br>016                                 | BLDG                      | 086/11499                                                                | 704.4                                       | LGT                                                                     |                                                                                      |
| BLDG<br>017                                 | BLDG                      | 087/11060                                                                | 698.4                                       | LGT                                                                     |                                                                                      |
| Control TWR<br>018                          | Control<br>TWR            | 094/775                                                                  | 558.4                                       | LGT                                                                     |                                                                                      |
| Pole<br>019                                 | Pole                      | 100/11751                                                                | 620.2                                       |                                                                         |                                                                                      |
| BLDG<br>020                                 | BLDG                      | 101/10537                                                                | 673.7                                       | LGT                                                                     |                                                                                      |
| BLDG<br>021                                 | BLDG                      | 102/11768                                                                | 681.2                                       | LGT                                                                     |                                                                                      |
| BLDG<br>022                                 | BLDG                      | 103/3946                                                                 | 544.6                                       | LGT                                                                     |                                                                                      |
| BLDG<br>023                                 | BLDG                      | 103/11439                                                                | 690.1                                       |                                                                         |                                                                                      |
| BLDG<br>024                                 | BLDG                      | 104/11677                                                                | 690.2                                       | LGT                                                                     |                                                                                      |
| BLDG<br>025                                 | BLDG                      | 104/11866                                                                | 628.4                                       |                                                                         |                                                                                      |
| BLDG<br>026                                 | BLDG                      | 105/11275                                                                | 682.2                                       | LGT                                                                     |                                                                                      |
| BLDG<br>027                                 | BLDG                      | 109/11645                                                                | 662.8                                       | LGT                                                                     |                                                                                      |
| BLDG<br>028                                 | BLDG                      | 111/1920                                                                 | 549.6                                       | LGT                                                                     | RWY02R Take-off path                                                                 |
| BLDG<br>029                                 | BLDG                      | 112/12382                                                                | 667.9                                       |                                                                         |                                                                                      |
| BLDG<br>030                                 | BLDG                      | 127/13674                                                                | 577.1                                       | LGT                                                                     |                                                                                      |

半径 15 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| BLDG<br>031                                 | BLDG                      | 132/14179                                                                | 769                                         |                                                                         | Surveillance Vectoring Sector Nr.11                                                  |
| ELECTRICAL_EXIT_LIGHT<br>032                | ELECTRICAL_EXIT_LIGHT     | 134/2228                                                                 | 527.8                                       |                                                                         | RWY02R Take-off path                                                                 |
| BLDG<br>033                                 | BLDG                      | 144/5840                                                                 | 575.8                                       |                                                                         |                                                                                      |
| BLDG<br>034                                 | BLDG                      | 146/6204                                                                 | 575.6                                       |                                                                         |                                                                                      |
| Control TWR<br>035                          | Control TWR               | 152/1080                                                                 | 582.2                                       | LGT                                                                     | RWY02R departure                                                                     |
| Pole<br>036                                 | Pole                      | 152/6792                                                                 | 557.7                                       |                                                                         |                                                                                      |
| BLDG<br>037                                 | BLDG                      | 153/2687                                                                 | 527.1                                       | LGT                                                                     | RWY02R Take-off path                                                                 |
| Microwave TWR<br>038                        | Microwave TWR             | 161/4477                                                                 | 556.8                                       | LGT                                                                     |                                                                                      |
| Microwave TWR<br>039                        | Microwave TWR             | 163/7951                                                                 | 552.2                                       | LGT                                                                     |                                                                                      |
| Microwave TWR<br>040                        | Microwave TWR             | 182/5283                                                                 | 539.7                                       |                                                                         |                                                                                      |
| Microwave TWR<br>041                        | Microwave TWR             | 182/9333                                                                 | 568.9                                       | LGT                                                                     |                                                                                      |
| Trees<br>042                                | Trees                     | 187/6767                                                                 | 532.4                                       |                                                                         |                                                                                      |
| MT<br>043                                   | MT                        | 187/7143                                                                 | 524.1                                       |                                                                         | RWY20L Take-off path                                                                 |
| Trees<br>044                                | Trees                     | 189/7844                                                                 | 547                                         |                                                                         | RWY20L Take-off path                                                                 |
| MT<br>045                                   | MT                        | 189/7910                                                                 | 527.9                                       |                                                                         | RWY20L Take-off path                                                                 |

半径 15 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| MT<br>046                                   | MT                        | 190/7312                                                                 | 528.5                                       |                                                                         | RWY20L Take-off path                                                                 |
| MT<br>047                                   | MT                        | 190/7555                                                                 | 527                                         |                                                                         | RWY20L Take-off path                                                                 |
| Trees<br>048                                | Trees                     | 190/7767                                                                 | 541.5                                       |                                                                         | RWY20L Take-off path                                                                 |
| NATURAL_HIG<br>HPOINT<br>049                | NATURA<br>L_HIGHP<br>OINT | 191/7985                                                                 | 538.6                                       |                                                                         |                                                                                      |
| NATURAL_HIG<br>HPOINT<br>050                | NATURA<br>L_HIGHP<br>OINT | 191/7996                                                                 | 539.3                                       |                                                                         |                                                                                      |
| NATURAL_HIG<br>HPOINT<br>051                | NATURA<br>L_HIGHP<br>OINT | 193/8023                                                                 | 541.1                                       |                                                                         |                                                                                      |
| NATURAL_HIG<br>HPOINT<br>052                | NATURA<br>L_HIGHP<br>OINT | 193/8031                                                                 | 540.8                                       |                                                                         |                                                                                      |
| NATURAL_HIG<br>HPOINT<br>053                | NATURA<br>L_HIGHP<br>OINT | 194/8016                                                                 | 541.3                                       |                                                                         |                                                                                      |
| Pole<br>054                                 | Pole                      | 195/5942                                                                 | 551                                         |                                                                         |                                                                                      |
| Trees<br>055                                | Trees                     | 195/12889                                                                | 600.6                                       |                                                                         | RWY20L Take-off path                                                                 |
| Trees<br>056                                | Trees                     | 195/13179                                                                | 606.2                                       |                                                                         | RWY20L Take-off path                                                                 |
| Trees<br>057                                | Trees                     | 197/12237                                                                | 599.1                                       |                                                                         | RWY20L Take-off path                                                                 |
| BLDG<br>058                                 | BLDG                      | 199/4031                                                                 | 524.2                                       | LGT                                                                     | RWY20R Take-off path                                                                 |

半径 15 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Other<br>059                                | Other                     | 199/9152                                                                 | 562.4                                       |                                                                         |                                                                                      |
| Trees<br>060                                | Trees                     | 201/5791                                                                 | 546.3                                       |                                                                         | RWY20R Take-off path                                                                 |
| Pole<br>061                                 | Pole                      | 201/9252                                                                 | 557.4                                       |                                                                         |                                                                                      |
| STACK<br>062                                | STACK                     | 202/10404                                                                | 567.6                                       |                                                                         |                                                                                      |
| Iron TWR<br>063                             | Iron TWR                  | 204/10544                                                                | 591.1                                       |                                                                         | RWY20R departure                                                                     |
| Iron TWR<br>064                             | Iron TWR                  | 204/10556                                                                | 586.5                                       |                                                                         |                                                                                      |
| BLDG<br>065                                 | BLDG                      | 205/10240                                                                | 571.2                                       |                                                                         |                                                                                      |
| TOWER<br>066                                | TOWER                     | 206/10488                                                                | 585.6                                       |                                                                         |                                                                                      |
| BLDG<br>067                                 | BLDG                      | 207/9162                                                                 | 550                                         |                                                                         |                                                                                      |
| Antenna<br>068                              | Antenna                   | 208/8898                                                                 | 566.8                                       | LGT                                                                     |                                                                                      |
| Pole<br>069                                 | Pole                      | 208/9173                                                                 | 557.1                                       |                                                                         |                                                                                      |
| Antenna<br>070                              | Antenna                   | 208/9223                                                                 | 568.4                                       | LGT                                                                     |                                                                                      |
| BLDG<br>071                                 | BLDG                      | 212/8693                                                                 | 549.7                                       |                                                                         |                                                                                      |
| TOWER<br>072                                | TOWER                     | 212/8793                                                                 | 553.2                                       |                                                                         |                                                                                      |
| BLDG<br>073                                 | BLDG                      | 213/8586                                                                 | 551                                         |                                                                         |                                                                                      |
| BLDG<br>074                                 | BLDG                      | 213/8622                                                                 | 555                                         |                                                                         |                                                                                      |

半径 15 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| BLDG<br>075                                 | BLDG                      | 213/8671                                                                 | 551                                         |                                                                         |                                                                                      |
| TOWER<br>076                                | TOWER                     | 213/8781                                                                 | 555                                         |                                                                         |                                                                                      |
| TOWER<br>077                                | TOWER                     | 214/8639                                                                 | 557                                         |                                                                         |                                                                                      |
| TOWER<br>078                                | TOWER                     | 214/8664                                                                 | 557                                         |                                                                         |                                                                                      |
| Pole<br>079                                 | Pole                      | 218/6593                                                                 | 553.3                                       |                                                                         |                                                                                      |
| BLDG<br>080                                 | BLDG                      | 219/6868                                                                 | 552                                         | LGT                                                                     |                                                                                      |
| BLDG<br>081                                 | BLDG                      | 239/3224                                                                 | 540.4                                       | LGT                                                                     |                                                                                      |
| BLDG<br>082                                 | BLDG                      | 245/3365                                                                 | 541.4                                       | LGT                                                                     |                                                                                      |
| Antenna<br>083                              | Antenna                   | 250/3064                                                                 | 555.4                                       |                                                                         |                                                                                      |
| Antenna<br>084                              | Antenna                   | 251/2147                                                                 | 528.7                                       |                                                                         |                                                                                      |
| BLDG<br>085                                 | BLDG                      | 263/468                                                                  | 530.5                                       | LGT                                                                     |                                                                                      |
| Iron TWR<br>086                             | Iron TWR                  | 263/2423                                                                 | 561.3                                       | LGT                                                                     |                                                                                      |
| Pole<br>087                                 | Pole                      | 265/2462                                                                 | 549.3                                       | LGT                                                                     |                                                                                      |
| TV TWR<br>088                               | TV TWR                    | 266/3186                                                                 | 584.6                                       | LGT                                                                     |                                                                                      |
| Microwave TWR<br>089                        | Microwav<br>e TWR         | 266/13738                                                                | 547.2                                       |                                                                         |                                                                                      |
| Microwave TWR<br>090                        | Microwav<br>e TWR         | 272/11436                                                                | 554.3                                       |                                                                         |                                                                                      |

半径 15 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| BLDG<br>091                                 | BLDG                      | 296/5548                                                                 | 619                                         | LGT                                                                     |                                                                                      |
| Antenna<br>092                              | Antenna                   | 297/7193                                                                 | 609.8                                       |                                                                         |                                                                                      |
| BLDG<br>093                                 | BLDG                      | 322/14848                                                                | 647.2                                       | LGT                                                                     |                                                                                      |
| BLDG<br>094                                 | BLDG                      | 329/13868                                                                | 653.9                                       | LGT                                                                     |                                                                                      |
| MT<br>095                                   | MT                        | 331/13876                                                                | 673                                         |                                                                         |                                                                                      |
| Pole<br>096                                 | Pole                      | 351/705                                                                  | 529.4                                       |                                                                         |                                                                                      |

半径 15 千米-50 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15 to 50km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志、灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| BLDG<br>097                                 | BLDG                      | 001/22615                                                                | 624                                         | LGT                                                                    |                                                                                      |
| BLDG<br>098                                 | BLDG                      | 006/21244                                                                | 610                                         | LGT                                                                    |                                                                                      |
| MT<br>099                                   | MT                        | 007/124304                                                               | 3543                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.01(15m vegetation included)                      |
| MT<br>100                                   | MT                        | 008/98387                                                                | 2517                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.02(15m vegetation included)                      |
| Pole<br>101                                 | Pole                      | 012/15991                                                                | 572                                         | LGT                                                                    |                                                                                      |
| MT<br>102                                   | MT                        | 013/131957                                                               | 2958                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.03(15m vegetation included)                      |

半径 15 千米-50 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15 to 50km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志、灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| MT<br>103                                   | MT                        | 014/133832                                                               | 2506                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.04(15m vegetation included)                      |
| TOWER<br>104                                | TOWER                     | 023/15895                                                                | 618                                         | LGT                                                                    |                                                                                      |
| MT<br>105                                   | MT                        | 024/136098                                                               | 1367                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.05(15m vegetation included)                      |
| BLDG<br>106                                 | BLDG                      | 032/15530                                                                | 630                                         | LGT                                                                    | RWY20L final approach, RWY20R<br>intermediate approach                               |
| BLDG<br>107                                 | BLDG                      | 033/16443                                                                | 603                                         | LGT                                                                    |                                                                                      |
| BLDG<br>108                                 | BLDG                      | 042/17945                                                                | 600                                         | LGT                                                                    |                                                                                      |
| MT<br>109                                   | MT                        | 046/25169                                                                | 592                                         |                                                                        |                                                                                      |
| BLDG<br>110                                 | BLDG                      | 048/15364                                                                | 650                                         | LGT                                                                    |                                                                                      |
| MT<br>111                                   | MT                        | 048/177324                                                               | 927                                         |                                                                        | Surveillance Vectoring Sector<br>Nr.06(15m vegetation included)                      |
| Antenna<br>112                              | Antenna                   | 049/15217                                                                | 662                                         | LGT                                                                    |                                                                                      |
| MT<br>113                                   | MT                        | 051/158428                                                               | 761                                         |                                                                        | Surveillance Vectoring Sector<br>Nr.07(15m vegetation included)                      |
| BLDG<br>114                                 | BLDG                      | 052/15503                                                                | 662                                         | LGT                                                                    |                                                                                      |
| BLDG<br>115                                 | BLDG                      | 059/15182                                                                | 680                                         |                                                                        |                                                                                      |
| Antenna<br>116                              | Antenna                   | 060/16930                                                                | 837                                         |                                                                        | Surveillance Vectoring Sector Nr.08                                                  |
| BLDG<br>117                                 | BLDG                      | 067/16526                                                                | 605                                         | LGT                                                                    |                                                                                      |
| TOWER<br>118                                | TOWER                     | 071/48182                                                                | 793                                         |                                                                        |                                                                                      |

半径 15 千米-50 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15 to 50km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志、灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| BLDG<br>119                                 | BLDG                      | 074/19656                                                                | 708                                         | LGT                                                                    |                                                                                      |
| BLDG<br>120                                 | BLDG                      | 074/41553                                                                | 826                                         |                                                                        |                                                                                      |
| TOWER<br>121                                | TOWER                     | 082/43586                                                                | 1047                                        | LGT                                                                    |                                                                                      |
| BLDG<br>122                                 | BLDG                      | 083/20165                                                                | 995                                         |                                                                        | Surveillance Vectoring Sector Nr.09                                                  |
| MT<br>123                                   | MT                        | 083/43530                                                                | 930                                         |                                                                        |                                                                                      |
| MT<br>124                                   | MT                        | 085/39187                                                                | 854                                         |                                                                        |                                                                                      |
| TOWER<br>125                                | TOWER                     | 095/36633                                                                | 941                                         |                                                                        |                                                                                      |
| TOWER<br>126                                | TOWER                     | 100/34957                                                                | 971                                         |                                                                        |                                                                                      |
| BLDG<br>127                                 | BLDG                      | 104/11644                                                                | 697                                         | LGT                                                                    |                                                                                      |
| MT<br>128                                   | MT                        | 104/34472                                                                | 1057                                        |                                                                        |                                                                                      |
| Iron TWR<br>129                             | Iron TWR                  | 106/33956                                                                | 1066                                        |                                                                        |                                                                                      |
| Antenna<br>130                              | Antenna                   | 107/33925                                                                | 1081                                        |                                                                        | Sector, Surveillance Vectoring<br>Sector Nr.10                                       |
| MT<br>131                                   | MT                        | 113/33367                                                                | 990                                         |                                                                        |                                                                                      |
| BLDG<br>132                                 | BLDG                      | 122/21318                                                                | 605                                         | LGT                                                                    |                                                                                      |
| MT<br>133                                   | MT                        | 125/33093                                                                | 997                                         |                                                                        |                                                                                      |
| BLDG<br>134                                 | BLDG                      | 125/33118                                                                | 1012                                        |                                                                        |                                                                                      |



半径 15 千米-50 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15 to 50km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志、灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Trees<br>135                                | Trees                     | 132/34187                                                                | 972                                         |                                                                        |                                                                                      |
| BLDG<br>136                                 | BLDG                      | 143/19975                                                                | 997                                         |                                                                        | Surveillance Vectoring Sector Nr.13                                                  |
| Antenna<br>137                              | Antenna                   | 143/36703                                                                | 1020                                        | LGT                                                                    | Surveillance Vectoring Sector Nr.12                                                  |
| Iron TWR<br>138                             | Iron TWR                  | 148/38949                                                                | 922                                         |                                                                        |                                                                                      |
| MT<br>139                                   | MT                        | 150/107470                                                               | 692                                         |                                                                        | Surveillance Vectoring Sector<br>Nr.14(15m vegetation included)                      |
| MT<br>140                                   | MT                        | 156/120917                                                               | 925                                         |                                                                        | Surveillance Vectoring Sector<br>Nr.15(15m vegetation included)                      |
| Trees<br>141                                | Trees                     | 158/42781                                                                | 845                                         |                                                                        |                                                                                      |
| BLDG<br>142                                 | BLDG                      | 162/44414                                                                | 859                                         |                                                                        |                                                                                      |
| Microwave TWR<br>143                        | Microwave TWR             | 164/48526                                                                | 942                                         |                                                                        |                                                                                      |
| TOWER<br>144                                | TOWER                     | 164/48534                                                                | 940                                         |                                                                        |                                                                                      |
| MT<br>145                                   | MT                        | 170/56648                                                                | 827                                         |                                                                        | Surveillance Vectoring Sector<br>Nr.16(15m vegetation included)                      |
| Microwave TWR<br>146                        | Microwave TWR             | 198/16663                                                                | 619                                         |                                                                        |                                                                                      |
| Trees<br>147                                | Trees                     | 210/32703                                                                | 711                                         |                                                                        | RWY02L Intermediate approach                                                         |
| Trees<br>148                                | Trees                     | 215/24630                                                                | 632                                         | LGT                                                                    |                                                                                      |
| MT<br>149                                   | MT                        | 221/47218                                                                | 733                                         |                                                                        | Surveillance Vectoring Sector<br>Nr.17(15m vegetation included)                      |
| MT<br>150                                   | MT                        | 221/54302                                                                | 914                                         |                                                                        | Surveillance Vectoring Sector<br>Nr.18(15m vegetation included)                      |

半径 15 千米-50 千米内主要障碍物 (相对 02L/20R 跑道中心)

Obstacles within 15 to 50km of the center of RWY02L/20R

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志、灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| MT<br>151                                   | MT                        | 223/61199                                                                | 1020                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.19(15m vegetation included)                      |
| MT<br>152                                   | MT                        | 228/81087                                                                | 1157                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.20(15m vegetation included)                      |
| MT<br>153                                   | MT                        | 259/72528                                                                | 1438                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.21(15m vegetation included)                      |
| MT<br>154                                   | MT                        | 284/94302                                                                | 5379                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.22(15m vegetation included)                      |
| MT<br>155                                   | MT                        | 287/89618                                                                | 4176                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.23(15m vegetation included)                      |
| Trees<br>156                                | Trees                     | 293/41919                                                                | 813                                         |                                                                        |                                                                                      |
| MT<br>157                                   | MT                        | 297/64552                                                                | 2927                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.24(15m vegetation included)                      |
| MT<br>158                                   | MT                        | 300/56910                                                                | 2235                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.25(15m vegetation included)                      |
| MT<br>159                                   | MT                        | 303/59332                                                                | 2614                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.26(15m vegetation included)                      |
| MT<br>160                                   | MT                        | 318/59010                                                                | 2015                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.27(15m vegetation included)                      |
| BLDG<br>161                                 | BLDG                      | 325/16354                                                                | 645                                         |                                                                        |                                                                                      |
| Antenna<br>162                              | Antenna                   | 343/46956                                                                | 767                                         |                                                                        |                                                                                      |
| MT<br>163                                   | MT                        | 352/89052                                                                | 4131                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.28(15m vegetation included)                      |
| MT<br>164                                   | MT                        | 353/95605                                                                | 4827                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.29(15m vegetation included)                      |
| MT<br>165                                   | MT                        | 355/73908                                                                | 2456                                        |                                                                        | Surveillance Vectoring Sector<br>Nr.30(15m vegetation included)                      |
| Remarks:Nil                                 |                           |                                                                          |                                             |                                                                        |                                                                                      |

## ZUUU AD 2.11 提供的气象情报、气象观测和报告

## Meteorological information provided &amp; meteorological observations and reports

|                                                    |                                                                                                            |                                                                                                                                                                                                           |
|----------------------------------------------------|------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 提供的气象情报<br>Meteorological information provided     |                                                                                                            |                                                                                                                                                                                                           |
| 1                                                  | 相关气象台的名称<br>Associated MET Office                                                                          | Meteorological Center of South-west ATMB of CAAC                                                                                                                                                          |
| 2                                                  | 气象服务时间、服务时间以外的责任气象台<br>Hours of service/MET Office outside hours                                           | H24                                                                                                                                                                                                       |
| 3                                                  | 负责编发 TAF 的气象台、有效时段、发布间隔<br>Office responsible for TAF preparation/Periods of validity/Interval of issuance | Meteorological Center of South-west ATMB of CAAC;9h, 24h;3h, required, 6h, routine                                                                                                                        |
| 4                                                  | 趋势预报及发布间隔<br>Trend forecast/Interval of issuance                                                           | trend (1600-2000UTC 1h) , 30min                                                                                                                                                                           |
| 5                                                  | 所提供的讲解或咨询服务<br>Briefing/Consultation provided                                                              | Briefing provided: P, T, TV                                                                                                                                                                               |
| 6                                                  | 飞行文件及其使用语言<br>Flight documentation/Language(s) used                                                        | Chart, International MET Codes, Abbreviated Plain Language Text;Ch,En                                                                                                                                     |
| 7                                                  | 讲解或咨询服务时可利用的图表和其它信息<br>Charts and other information available for briefing or consultation                 | Synoptic charts, significant weather charts, upper W/T charts, satellite and radar material, AWOS real-time data, significant weather information, low-altitude weather information, data forecast chart. |
| 8                                                  | 提供气象情报的辅助设备<br>Supplementary equipment available for providing information                                 | Nil                                                                                                                                                                                                       |
| 9                                                  | 提供气象情报的空中交通服务单位<br>ATS units provided with information                                                     | ACC, APP, ARO, TWR, flow management officer, operation control office                                                                                                                                     |
| 10                                                 | 其他信息<br>Additional information                                                                             | Tel: 86-28-85702294, 86-28-85701140                                                                                                                                                                       |
| 气象观测和报告<br>Meteorological observations and reports |                                                                                                            |                                                                                                                                                                                                           |
| 1                                                  | 机场观测类型与频率、自动观测设备<br>Type & frequency of observation /Automatic observation equipment                       | Half hourly (1600-2000UTC 1.0h) plus special observation/Yes                                                                                                                                              |
| 2                                                  | 气象报告类型及所包含的补充资料<br>Type of MET Report/Supplementary information included                                   | METAR, SPECI                                                                                                                                                                                              |
| 3                                                  | 观测系统及安装位置<br>Observation system/Site(s)                                                                    | RVR EQPT<br>A: 100m W of RCL, 320m inward THR02L<br>B: 100m W of RCL, 1800m inward THR02L<br>C: 100m W of RCL, 320m inward THR02L<br>D: 100m E of RCL, 350m inward THR02R                                 |

|   |                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---|-----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|   |                                                                       | E: 100m E of RCL, 1790m inward THR02R<br>F: 100m E of RCL, 430m inward THR02R<br>SFC wind sensors<br>02L: 110m W of RCL, 305m inward THR<br>02L/20R: 110m W of RCL, 1800m inward THR02L<br>20R: 110m W of RCL, 305m inward THR<br>02R: 110m E of RCL, 380m inward THR<br>02R/20L: 110m E of RCL, 1800m inward THR02R<br>20L: 110m E of RCL, 410m inward THR<br>Ceilometer<br>02L: 60m W of RCL, 1050m outward THR<br>20R: 60m W of RCL, 270m outward THR<br>02R: 60m E of RCL, 500m outward THR<br>20L: 60m E of RCL, 500m outward THR |
| 4 | 观测系统的工作时间<br>Hours of operation for meteorological observation system | H24                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 5 | 气候资料<br>Climatological information                                    | Climatological tables AVBL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| 6 | 其他信息<br>Additional information                                        | Nil                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

## ZUUU AD 2.12 跑道物理特征 Runway physical characteristics

| 跑道号码<br>RWY<br>Designator | 真方位和<br>磁方位<br>TRUE &<br>MAG BRG | 跑道长宽<br>Dimensions<br>of RWY(m) | 跑道强度、跑道和停<br>止道道面<br>RWY strength/<br>Surface of<br>RWY /SWY                    | 跑道入口坐标、<br>跑道末端坐标、<br>跑道入口大地水<br>准面波幅<br>THR coordinates<br>& RWY end<br>coordinates &<br>THR geoid<br>undulation | 跑道入口标高和<br>精密进近跑道接<br>地带最高标高<br>THR elevation &<br>highest elevation<br>of TDZ of<br>precision APP<br>RWY | 跑道和停止道坡<br>度<br>Slope of<br>RWY/SWY |
|---------------------------|----------------------------------|---------------------------------|---------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-------------------------------------|
| 1                         | 2                                | 3                               | 4                                                                               | 5                                                                                                                 | 6                                                                                                         | 7                                   |
| 02L                       | 022 °GEO<br>024 °MAG             | 3600×45                         | (0-905m)<br>PCR 880/R/A/W/T<br>CONC<br>(905-3600m)<br>PCR 880/R/A/W/T<br>ASPH/- | Nil                                                                                                               | THR 492.9m<br>TDZ 492.9m                                                                                  | 0.08%(1800m)/0.<br>06%(1800m)       |

| 跑道号码<br>RWY<br>Designator                                                                                                                                                                                                                                           | 真方位和<br>磁方位<br>TRUE &<br>MAG BRG  | 跑道长宽<br>Dimensions<br>of RWY(m)   | 跑道强度、跑道和停<br>止道道面<br>RWY strength/<br>Surface of<br>RWY /SWY                      | 跑道入口坐标、<br>跑道末端坐标、<br>跑道入口大地水<br>准面波幅<br>THR coordinates<br>& RWY end<br>coordinates &<br>THR geoid<br>undulation | 跑道入口标高和<br>精密进近跑道接<br>地带最高标高<br>THR elevation &<br>highest elevation<br>of TDZ of<br>precision APP<br>RWY | 跑道和停止道坡<br>度<br>Slope of<br>RWY/SWY |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-----------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-------------------------------------|
| 1                                                                                                                                                                                                                                                                   | 2                                 | 3                                 | 4                                                                                 | 5                                                                                                                 | 6                                                                                                         | 7                                   |
| 20R                                                                                                                                                                                                                                                                 | 202 °GEO<br>204 °MAG              | 3600×45                           | (0-2695m)<br>PCR 880/R/A/W/T<br>ASPH<br>(2695-3600m)<br>PCR 880/R/A/W/T<br>CONC/- | Nil                                                                                                               | THR 495.4m<br>TDZ 495.4m                                                                                  | -0.06%(1800m)/-<br>0.08%(1800m)     |
| 02R                                                                                                                                                                                                                                                                 | 022 °GEO<br>024 °MAG              | 3600×60                           | PCR 1050/R/B/W/T<br>CONC/-                                                        | Nil                                                                                                               | THR 512.4m<br>TDZ 512.4m                                                                                  | -0.44%                              |
| 20L                                                                                                                                                                                                                                                                 | 202 °GEO<br>204 °MAG              | 3600×60                           | PCR 1050/R/B/W/T<br>CONC/-                                                        | Nil                                                                                                               | THR 496.6m<br>TDZ 500.6m                                                                                  | 0.44%                               |
| 跑道号码<br>RWY<br>Designator                                                                                                                                                                                                                                           | 停止道长宽<br>SWY<br>dimensions<br>(m) | 净空道长宽<br>CWY<br>dimensions<br>(m) | 升降带长宽<br>Strip dimensions<br>(m)                                                  | 跑道端安全区<br>长宽<br>RESA<br>dimensions<br>(m)                                                                         | 拦阻系统的<br>位置及描述<br>Location &<br>Description of<br>arresting system                                        | 无障碍物区<br>OFZ                        |
| 1                                                                                                                                                                                                                                                                   | 8                                 | 9                                 | 10                                                                                | 11                                                                                                                | 12                                                                                                        | 13                                  |
| 02L                                                                                                                                                                                                                                                                 | Nil                               | Nil                               | 3720×280                                                                          | 200×120                                                                                                           | Nil                                                                                                       | -                                   |
| 20R                                                                                                                                                                                                                                                                 | Nil                               | Nil                               | 3720×280                                                                          | 200×120                                                                                                           | Nil                                                                                                       | -                                   |
| 02R                                                                                                                                                                                                                                                                 | Nil                               | Nil                               | 3720×280                                                                          | 240×120                                                                                                           | Nil                                                                                                       | -                                   |
| 20L                                                                                                                                                                                                                                                                 | Nil                               | Nil                               | 3720×280                                                                          | 230×120                                                                                                           | Nil                                                                                                       | -                                   |
| Remarks: 02L/20R: RWY shoulder: 7.5m on each side;<br>Blast pad: 60×60m on the both ends.<br>02R/20L: RWY shoulder: 7.5m on each side;<br>Blast pad: 120×75m on the both ends;<br>Distance between RCL02L/20R and RCL02R/20L is 1525m; THR02L is 1040m N of THR20L. |                                   |                                   |                                                                                   |                                                                                                                   |                                                                                                           |                                     |

## ZUUU AD 2.13 公布距离 Declared distances

| 跑道号码<br>RWY Designator | 可用起飞滑跑距离<br>TORA(m) | 可用起飞距离<br>TODA(m) | 可用加速停止距离<br>ASDA(m) | 可用着陆距离<br>LDA(m) | 备注<br>Remarks |
|------------------------|---------------------|-------------------|---------------------|------------------|---------------|
| 1                      | 2                   | 3                 | 4                   | 5                | 6             |
| 02L                    | 3600                | 3600              | 3600                | 3600             | Nil           |

| 跑道号码<br>RWY Designator | 可用起飞滑跑距离<br>TORA(m) | 可用起飞距离<br>TODA(m) | 可用加速停止距离<br>ASDA(m) | 可用着陆距离<br>LDA(m) | 备注<br>Remarks |
|------------------------|---------------------|-------------------|---------------------|------------------|---------------|
| 02L                    | 3200                | 3200              | 3200                | 3600             | FM A2         |
| 20R                    | 3600                | 3600              | 3600                | 3600             | Nil           |
| 02R                    | 3600                | 3600              | 3600                | 3600             | Nil           |
| 02R                    | 3200                | 3200              | 3200                | 3600             | FM E2         |
| 20L                    | 3600                | 3600              | 3600                | 3600             | Nil           |
| 20L                    | 3200                | 3200              | 3200                | 3600             | FM E8         |

## ZUUU AD 2.14 进近和跑道灯光 Approach and runway lighting

| 跑道<br>号码<br>RWY<br>Desig<br>nator | 进近灯<br>类型、长<br>度、强度<br>APCH<br>LGT<br>type/<br>LEN/<br>/INTST | 入口灯<br>颜色、翼<br>排灯<br>THR<br>LGT<br>colour/<br>WBAR | 目视进近坡度<br>指示系统类<br>型、位置、仰<br>角、跑道入口<br>最低眼高<br>Type of<br>VASIS/Position<br>/Angle/MEHT | 接地<br>带<br>灯长<br>度<br>TDZ<br>LGT<br>LEN | 跑道中线灯长度、<br>间隔、颜色、强度<br>RWY center line<br>LGT LEN/Spacing<br>/Colour/INTST                       | 跑道边灯长度、间<br>隔、颜色、强度<br>RWY edge LGT<br>LEN/Spacing<br>/Colour/INTST         | 跑道末端灯<br>颜色<br>RWY end<br>LGT<br>colour | 停止道灯长<br>度、颜色<br>SWY<br>LGT<br>LEN<br>/Colour |
|-----------------------------------|---------------------------------------------------------------|----------------------------------------------------|-----------------------------------------------------------------------------------------|-----------------------------------------|---------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------|-----------------------------------------------|
| 1                                 | 2                                                             | 3                                                  | 4                                                                                       | 5                                       | 6                                                                                                 | 7                                                                           | 8                                       | 9                                             |
| 02L                               | PALS<br>CAT II<br>SFL<br>900 m<br>LIH                         | GREEN<br>Yes                                       | PAPI<br>LEFT<br>426m inward<br>THR02L<br>3°<br>21.1m                                    | 900 m                                   | 3600 m<br>spacing 15m<br>0-2700m, WHITE<br>2700-3300m,<br>RED/WHITE<br>3300-3600m, RED<br>VRB LIH | 3600 m<br>spacing 60m<br>0-3000m, WHITE<br>3000-3600m,<br>YELLOW<br>VRB LIH | RED                                     | Nil                                           |
| 20R                               | PALS<br>CAT I<br>SFL<br>900 m<br>LIH                          | GREEN<br>Yes                                       | PAPI<br>LEFT<br>440m inward<br>THR20R<br>3°<br>20.8m                                    | Nil                                     | 3600 m<br>spacing 15m<br>0-2700m, WHITE<br>2700-3300m,<br>RED/WHITE<br>3300-3600m, RED<br>VRB LIH | 3600 m<br>spacing 60m<br>0-3000m, WHITE<br>3000-3600m,<br>YELLOW<br>VRB LIH | RED                                     | Nil                                           |
| 02R                               | PALS<br>CAT III<br>SFL<br>900 m<br>LIH                        | GREEN<br>Yes                                       | PAPI<br>LEFT<br>432m inward<br>THR02R<br>3°<br>18.7m                                    | 900 m                                   | 3600 m<br>spacing 15m<br>0-2700m, WHITE<br>2700-3300m,<br>RED/WHITE<br>3300-3600m, RED<br>VRB LIH | 3600 m<br>spacing 60m<br>0-3000m, WHITE<br>3000-3600m,<br>YELLOW<br>VRB LIH | RED                                     | Nil                                           |

| 跑道<br>号码<br>RWY<br>Desig<br>nator | 进近灯<br>类型、长<br>度、强度<br>APCH<br>LGT<br>type/<br>LEN/<br>/INTST | 入口灯<br>颜色、翼<br>排灯<br>THR<br>LGT<br>colour/<br>WBAR | 目视进近坡度<br>指示系统类<br>型、位置、仰<br>角、跑道入口<br>最低眼高<br>Type of<br>VASIS/Position<br>/Angle/MEHT | 接地<br>带<br>灯长<br>度<br>TDZ<br>LGT<br>LEN | 跑道中线灯长度、<br>间隔、颜色、强度<br>RWY center line<br>LGT LEN/Spacing<br>/Colour/INTST                       | 跑道边灯长度、间<br>隔、颜色、强度<br>RWY edge LGT<br>LEN/Spacing<br>/Colour/INTST         | 跑道末端灯<br>颜色<br>RWY end<br>LGT<br>colour | 停止道灯长<br>度、颜色<br>SWY<br>LGT<br>LEN<br>/Colour |
|-----------------------------------|---------------------------------------------------------------|----------------------------------------------------|-----------------------------------------------------------------------------------------|-----------------------------------------|---------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------|-----------------------------------------------|
| 20L                               | PALS<br>CAT I<br>SFL<br>900 m<br>LIH                          | GREEN<br>Yes                                       | PAPI<br>LEFT<br>359m inward<br>THR20L<br>3°<br>19.0m                                    | Nil                                     | 3600 m<br>spacing 15m<br>0-2700m, WHITE<br>2700-3300m,<br>RED/WHITE<br>3300-3600m, RED<br>VRB LIH | 3600 m<br>spacing 60m<br>0-3000m, WHITE<br>3000-3600m,<br>YELLOW<br>VRB LIH | RED                                     | Nil                                           |
| Remarks:                          |                                                               |                                                    |                                                                                         |                                         |                                                                                                   |                                                                             |                                         |                                               |

**ZUUU AD 2.15 其它灯光,备份电源 Other lighting, secondary power supply**

|   |                                                                                    |                                                                                                                                                                                                              |
|---|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | 机场灯标或识别灯标位置、特性和工作时间<br>ABN/IBN location, characteristics and hours<br>of operation | Nil                                                                                                                                                                                                          |
| 2 | 着陆方向标和风向标位置和灯光<br>LDI/ WDI location and LGT                                        | WDI:<br>02L:126.6m W of RCL, 352m inward THR02L, LGT;<br>20R:125.26m W of RCL, 358.36m inward THR20R, LGT;<br>02R:105.5m E of RCL, 437m inward THR02R, LGT;<br>20L:117.5m E of RCL, 355m inward THR20L, LGT. |
| 3 | 滑行道边灯和滑行道中线灯<br>TWY edge and center line lighting                                  | All TWYs: yellow center line lights, green center line lights, blue edge line<br>lights                                                                                                                      |
| 4 | 备份电源及转换时间<br>Secondary power supply/Switch-over time                               | Secondary power supply available, diesel motor /<br>CAT I: 15 s, CAT II: 1s, CAT III: 1s                                                                                                                     |
| 5 | 备注<br>Remarks                                                                      | Nil                                                                                                                                                                                                          |

**ZUUU AD 2.16 直升机着陆区域 Helicopter landing area**

|   |                                                                                        |     |
|---|----------------------------------------------------------------------------------------|-----|
| 1 | TLOF 坐标或 FATO 入口坐标及大地水准<br>面波幅<br>Coordinates TLOF or THR of FATO, Geoid<br>undulation | Nil |
| 2 | TLOF 和 (或) FATO 标高<br>TLOF and/or FATO elevation                                       | Nil |

|   |                                                                                       |     |
|---|---------------------------------------------------------------------------------------|-----|
| 3 | TLOF 和 FATO 区域范围、道面、强度和标志<br>TLOF and FATO area dimensions,surface, strength, marking | Nil |
| 4 | FATO 的真方位和磁方位<br>True and MAG BRG of FATO                                             | Nil |
| 5 | 公布距离<br>Declared distance available                                                   | Nil |
| 6 | 进近灯光和 FATO 灯光<br>APP and FATO lighting                                                | Nil |
| 7 | 备注<br>Remarks                                                                         | Nil |

## ZUUU AD 2.17 空中交通服务空域 ATS airspace

| 空域名称和水平范围<br>Designation and lateral limits |                                                                                                                           | 垂直范围<br>Vertical limits                                                       | 空域分类<br>Airspace class | 空中交通服务单位<br>呼号和使用语言<br>ATS unit callsign<br>Language | 工作时间<br>Hours of applicability | 备注<br>Remarks                                                                                                             |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|------------------------|------------------------------------------------------|--------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| 1                                           | 2                                                                                                                         | 3                                                                             | 4                      | 5                                                    | 6                              | 7                                                                                                                         |
| Tower Control Area                          | A circuit, all arcs with radius 13km centered at centers of all RWY THRs and all lines tangential to the adjacent 2 arcs. | 1200m(QNH) and below                                                          |                        |                                                      |                                |                                                                                                                           |
| Fuel Dumping Area                           | N291035E1031147 -<br>N291044E1034847 -<br>N282726E1034853 -<br>N282717E1031208 -<br>N291035E1031147                       | QNE5000m and above                                                            |                        |                                                      |                                | Flight method:<br>1. After approval, enter from JYA to N290512E1 031759, exit from N290518E1 034238 to JYA;<br>2. By ATC. |
| Altimeter setting region and TL/TA          | Same as Chengdu APP area                                                                                                  | TL 3600m<br>TA 3000m<br>3300m(QNH $\geq$ 1031hPa)<br>2700m(QNH $\leq$ 979hPa) |                        |                                                      |                                |                                                                                                                           |



## ZUUU AD 2.18 空中交通服务通信设施 ATS communication facilities

| 服务名称<br>Service<br>designation | 呼号<br>Callsign        | 频率<br>Frequency (MHz)         | 卫星话音通信<br>号码<br>SATVOICE<br>number | 登录地址<br>Logon address | 工作时间<br>Hours of<br>operation | 备注<br>Remarks       |
|--------------------------------|-----------------------|-------------------------------|------------------------------------|-----------------------|-------------------------------|---------------------|
| 1                              | 2                     | 3                             | 4                                  | 5                     | 6                             | 7                   |
| ATIS                           |                       | 126.45 (Chinese)              |                                    |                       | H24                           | D-ATIS available    |
|                                |                       | 128.6 (English)               |                                    |                       | H24                           | D-ATIS available    |
| APP                            | Chengdu<br>Approach   | APP01:124.85<br>(127.7)       |                                    |                       | H24                           |                     |
|                                |                       | APP06:126.35<br>(125.25)      |                                    |                       | 0030-130<br>0                 |                     |
|                                |                       | APP07:119.425<br>(123.825)    |                                    |                       | 0030-190<br>0                 |                     |
|                                |                       | APP08:119.25<br>(123.825)     |                                    |                       | 0030-190<br>0                 |                     |
| TWR                            | Shuangliu<br>Tower    | 123.0 (118.85)                |                                    |                       | H24                           | Used for RWY02L/20R |
|                                |                       | 130.35 (118.85)               |                                    |                       | 2200-140<br>0(next<br>day)    | Used for RWY02R/20L |
| GND                            | Shuangliu<br>Delivery | 121.6 (121.7)                 |                                    |                       | 0100-130<br>0                 | DCL available       |
|                                | Shuangliu<br>Ground   | 121.75 (121.7)                |                                    |                       | by ATC                        | Used for RWY02R/20L |
|                                |                       | 121.85 (121.7)                |                                    |                       | 2200-180<br>0(next<br>day)    | Used for RWY02L/20R |
| APN                            | Shuangliu<br>Apron    | APN01:121.9<br>(121.65/121.8) |                                    |                       | by ATC                        |                     |
|                                |                       | APN02:121.8<br>(121.65/121.9) |                                    |                       | H24                           |                     |
|                                |                       | APN03:121.65<br>(121.8/121.9) |                                    |                       | by ATC                        |                     |

## ZUUU AD 2.19 无线电导航和着陆设施 Radio navigation and landing aids

| 设施名称及类型、磁差、支持运行类别、VOR/ILS 磁偏角<br>Name and type of aid, VAR, Type of supported OPS, Declination of VOR/ILS | 识别<br>ID | 频率、波道<br>Frequency/<br>Channel<br>number | 工作<br>时间<br>Hours of<br>operation | 发射天线坐标<br>及相对位置<br>Coordinates of<br>transmitting antenna/<br>Position  | DME 发射<br>天线标高<br>Elevation of<br>DME<br>transmitting<br>antenna | 备注<br>Remarks                                                                                                                                                                                                                                                  |
|-----------------------------------------------------------------------------------------------------------|----------|------------------------------------------|-----------------------------------|-------------------------------------------------------------------------|------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1                                                                                                         | 2        | 3                                        | 4                                 | 5                                                                       | 6                                                                | 7                                                                                                                                                                                                                                                              |
| Baihesi<br>VOR/DME                                                                                        | BHS      | 117.9 MHz<br>CH 126X                     | H24                               | N30°30.7'<br>E104°12.0'                                                 |                                                                  | For VOR: Beyond<br>20NM on R219 °for<br>STAR U/S;<br>For DME: Beyond<br>24NM on R082 °for<br>STAR U/S.                                                                                                                                                         |
| Chongzhou<br>VOR/DME                                                                                      | CZH      | 114.5 MHz<br>CH 92X                      | H24                               | N30°38.7'<br>E103°41.2'                                                 |                                                                  |                                                                                                                                                                                                                                                                |
| Dexin<br>VOR/DME                                                                                          | CDX      | 116.35 MHz<br>CH 110Y                    | H24                               | N31°15.0'<br>E104°22.8'                                                 | 540 m                                                            | R255 °R360 °<br>clockwise U/S.                                                                                                                                                                                                                                 |
| Huilong<br>VOR/DME                                                                                        | HLC      | 115.95 MHz<br>CH 106Y                    | H24                               | N30°18.1'<br>E103°41.7'                                                 | 567 m                                                            |                                                                                                                                                                                                                                                                |
| Jintang<br>VOR/DME                                                                                        | JTG      | 115.4 MHz<br>CH 101X                     | H24                               | N30°52.3'<br>E104°23.4'                                                 |                                                                  | For VOR: Beyond<br>24NM on R029 °for<br>STAR, beyond 37NM<br>on R068 °for SID,<br>R170 °R205 °<br>clockwise, beyond<br>20NM on R206 °for<br>SID, R320 °R360 °<br>clockwise U/S;<br>For DME: Beyond<br>40NM on R068 °for<br>SID, R170 °R205 °<br>clockwise U/S. |
| Mianyang<br>VOR/DME                                                                                       | MYG      | 114.8 MHz<br>CH 95X                      | H24                               | N31°26.0'<br>E104°44.0'                                                 | 538 m                                                            | Coverage 200km                                                                                                                                                                                                                                                 |
| Shuangliu<br>VOR/DME                                                                                      | CTU      | 115.7 MHz<br>CH 104X                     | H24                               | N30°34.4'<br>E103°56.6'<br>219 °MAG/827m FM the<br>Center of RWY02L/20R | 505 m                                                            | For DME: BTN<br>12-14NM on R290 °for<br>ENR/SID U/S.                                                                                                                                                                                                           |

| 设施名称及类型、磁差、支持运行类别、VOR/ILS 磁偏角<br>Name and type of aid, VAR, Type of supported OPS, Declination of VOR/ILS | 识别<br>ID | 频率、波道<br>Frequency/<br>Channel<br>number | 工作<br>时间<br>Hours of<br>operation | 发射天线坐标<br>及相对位置<br>Coordinates of<br>transmitting antenna/<br>Position | DME 发射<br>天线标高<br>Elevation of<br>DME<br>transmitting<br>antenna | 备注<br>Remarks                                                                                                    |
|-----------------------------------------------------------------------------------------------------------|----------|------------------------------------------|-----------------------------------|------------------------------------------------------------------------|------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| Wufengxi<br>VOR/DME                                                                                       | WFX      | 117.1 MHz<br>CH 118X                     | H24                               | N30°36.4'<br>E104°29.5'                                                |                                                                  |                                                                                                                  |
| Jingyan<br>VOR/DME                                                                                        | JYA      | 114.65 MHz<br>CH 93Y                     | H24                               | N29°46.4'<br>E104°02.9'                                                | 467 m                                                            |                                                                                                                  |
| Zhugao<br>VOR/DME                                                                                         | ZGA      | 115.25 MHz<br>CH 99Y                     | H24                               | N30°35.5'<br>E104°43.9'                                                | 563 m                                                            |                                                                                                                  |
| Ziyang<br>VOR/DME                                                                                         | ZYG      | 112.1 MHz<br>CH 58X                      | H24                               | N29°56.4'<br>E104°44.3'                                                | 427 m                                                            |                                                                                                                  |
| Chengdu<br>NDB                                                                                            | ZW       | 260 kHz                                  | H24                               | N30°30.0'<br>E103°54.5'                                                |                                                                  | Beyond 30NM on<br>BRG122 °, beyond<br>10NM on BRG260 °for<br>SID, beyond 10NM on<br>BRG269 °for<br>STAR/SID U/S. |
| LMM 02L                                                                                                   | Z        | 396 kHz                                  | H24                               | 204 °MAG/1050m FM<br>THR02L                                            |                                                                  | Marker coverage<br>300 ±100m<br>NDB coverage 11NM                                                                |
| OM 02L                                                                                                    |          | 75 MHz                                   |                                   | 204 °MAG/7750m FM<br>THR02L                                            |                                                                  | Coverage 600 ±200m<br>Co-located with<br>Chengdu NDB 'ZW'                                                        |
| IM 02L                                                                                                    |          | 75 MHz                                   |                                   | 204 °MAG/280m FM<br>THR02L                                             |                                                                  | Coverage 150 ±50m                                                                                                |
| LOC 02L<br>ILS CAT II                                                                                     | IZW      | 111.1 MHz                                |                                   | 024 °MAG/260m FM<br>RWY02L end                                         |                                                                  | Coverage 25NM                                                                                                    |
| GP 02L                                                                                                    |          | 331.7 MHz                                |                                   | 120m W of RCL, 310m<br>inward THR02L                                   |                                                                  | Angle 3 °, RDH 15 m<br>Coverage 10 NM                                                                            |
| DME 02L                                                                                                   | IZW      | CH 48X<br>(111.1 MHz)                    |                                   |                                                                        | 498m                                                             | Co-located with GP<br>02L<br>13.5NM-13.9NM U/S.                                                                  |
| LOC 20R<br>ILS CAT I                                                                                      | IAA      | 109.1 MHz                                |                                   | 204 °MAG/260m FM<br>RWY20R end                                         |                                                                  | Coverage 25NM                                                                                                    |
| GP 20R                                                                                                    |          | 331.4 MHz                                |                                   | 120m W of RCL, 319m<br>inward THR20R                                   |                                                                  | Angle 3 °, RDH 15 m<br>Coverage 10NM                                                                             |

| 设施名称及类型、磁差、支持运行类别、VOR/ILS 磁偏角<br>Name and type of aid, VAR, Type of supported OPS, Declination of VOR/ILS | 识别<br>ID | 频率、波道<br>Frequency/<br>Channel<br>number | 工作<br>时间<br>Hours of<br>operation | 发射天线坐标<br>及相对位置<br>Coordinates of<br>transmitting antenna/<br>Position | DME 发射<br>天线标高<br>Elevation of<br>DME<br>transmitting<br>antenna | 备注<br>Remarks                        |
|-----------------------------------------------------------------------------------------------------------|----------|------------------------------------------|-----------------------------------|------------------------------------------------------------------------|------------------------------------------------------------------|--------------------------------------|
| DME 20R                                                                                                   | IAA      | CH 28X<br>(109.1 MHz)                    |                                   |                                                                        | 500m                                                             | Co-located with GP 20R               |
| IM 02R                                                                                                    |          | 75 MHz                                   |                                   | 325m outward THR02R                                                    |                                                                  | Coverage 150 ±50m                    |
| LOC 02R<br>ILS CAT II                                                                                     | ICR      | 108.7 MHz                                |                                   | 290m outward RWY02R end                                                |                                                                  | Coverage 25NM                        |
| GP 02R                                                                                                    |          | 330.5 MHz                                |                                   | 125m E of RCL, 342m inward THR02R                                      |                                                                  | Angle 3 °, RDH 15 m<br>Coverage 12NM |
| DME 02R                                                                                                   | ICR      | CH 24X<br>(108.7 MHz)                    |                                   |                                                                        | 519m                                                             | Co-located with GP 02R               |
| LOC 20L<br>ILS CAT I                                                                                      | IDE      | 109.7 MHz                                |                                   | 305m outward RWY20L end                                                |                                                                  | Coverage 25NM                        |
| GP 20L                                                                                                    |          | 333.2 MHz                                |                                   | 120m E of RCL, 288m inside THR20L                                      |                                                                  | Angle 3 °, RDH 15 m<br>Coverage 16NM |
| DME 20L                                                                                                   | IDE      | CH 34X<br>(109.7 MHz)                    |                                   |                                                                        | 506m                                                             | Co-located with GP 20L               |

ZUUA AD 2.20 本场规定

ZUUA AD 2.20 Local aerodrome regulations

1. 机场使用规定

1.Airport operations regulations

1.1 禁止未安装二次雷达应答机的航空器起降；

1.1 Takeoff/landing of aircraft without SSR transponder are forbidden;

1.2 地面运行时二次雷达应答机操作程序：离场，收到同意推出或开车指令时，选择 XPNDR 或 AUTO 模式；进场，脱离跑道后，选择 XPNDR 或 AUTO 模式，进入停机位后，选择 STBY 模式；其余运行阶段，按照公司或管制单位要求设置应答机模式。

1.2 SSR transponder operating procedures on ground: for departure aircraft, when flight crew obtain push-back or start-up clearance, select XPNDR or AUTO mode; for arrival aircraft, after vacating the runway, select XPNDR or AUTO mode ,after parking the stand, select STBY mode.Other stage flight crew shall select mode by ATC or airlines.

1.3 对所有无 ACAS II, 最大起飞重量大于 15000 公斤或批准的旅客座位数量超过 30 的民用固定翼涡轮发动机航空器, 0000 至 1400(UTC)不得在本场起降。

#### 1.4 平行跑道同时仪表运行规定

1.4.1 本场可以实施三种运行模式: 独立平行离场、相关平行仪表进近、隔离平行运行。运行模式、运行时间及使用跑道听从 ATC 指令。

1.4.2 当出现风切变, 颠簸, 下降气流或强侧风等可能加大航空器偏离仪表着陆系统航向道的程度时, 航空器驾驶员应立即向管制员报告, 根据收到的机组报告和气象信息, 空中交通管制部门可依据平行跑道实施方案中的有关程序, 及时终止相关平行进近模式或完全终止平行跑道同时仪表运行。

#### 1.5 双流机坪 (APN) 范围:

滑行道: A2 (不含) 以北的 C 滑, B10 以北的 B 滑, B10(A 和 C 滑之间)。

机坪: 所有机坪区域。

## 2. 跑道和滑行道的使用

2.1 可以通过塔台管制室或双流机坪申请拖车、引导车服务, 引导车引导方式如下:

1.3 For fixed wing turbine engine aircraft (ACAS II not equipped and MTOW more than 15000 kg or approved passenger seat number more than 30), departure and landing are forbidden during 0000-1400(UTC).

#### 1.4 Simultaneous operations on parallel runways

1.4.1 Three operation modes can be implemented:

independent parallel departures, dependent parallel ILS approaches, and segregated parallel approaches/departures. Follow ATC instructions for the specific operation mode, operation time and the runway in use.

1.4.2 Under certain adverse weather conditions(e.g. wind shear, turbulence, down drafts or crosswind) which might increase ILS localizer course deviations to the extent that safety may be impaired, report the situation to controller immediately. According to the reports and weather information, ATC unit will decide the necessity to terminate the dependent parallel approaches or independent parallel ILS operations completely.

#### 1.5 Range of APN(Shuangliu Apron) :

TWYs: TWY C(north of A2(excluded)), TWY B(north of B10), TWY B10(BTN TWY A and C).

Apron: All aprons.

## 2. Use of runways and taxiways

2.1 Follow-me vehicle service and towing service are available via Tower Control or Shuangliu Apron. The guidance instructions of follow-me vehicle is shown below:

|                          |                                                          |
|--------------------------|----------------------------------------------------------|
| Instructions of guidance | Follow-me vehicle lights; Display information            |
| Arrival guidance         | Emergency flashers ON; information of the parking stand. |
| Departure guidance       | Emergency flashers ON.                                   |
| Stop taxiing             | Emergency flashers ON; 'STOP'.                           |
| Termination of guidance  | Emergency flashers OFF. .No information.                 |

2.2 禁止航空器在滑行道上做 180 转弯。

2.2 180 turnaround on TWY is strictly forbidden for all aircrafts.

2.3 滑行道使用原则:

2.3 General rules for the use of taxiways:

拖行航空器穿越 RWY02L/20R 时, 使用 A3, A4 滑行道。

TWY A3,A4 are available for towing aircraft across the RWY02L/20R.

2.4 当 20L 跑道使用 HUD 特殊 II 类运行标准时, 禁止高度 $\geq 20\text{m}$ 的航空器在 E 滑及 E 滑以东的区域运行。

2.4 When HUD Special CAT II operation standard implemented on RWY20L, aircraft altitude above 20m is forbidden to taxi on TWY E and the area east of TWY E.

2.5 机动区冲突多发地带运行要求

2.5 Operating requirements of hot spots procedure

为减少跑道侵入事件发生, 保障跑道安全, 航空器进入 HS 时注意以下事项:

For the purpose of reducing errors that lead to ground conflicts and runway incursions, aircraft operating within the maneuvering area of Chengdu airport must follow the requirements below.

2.5.1 HS1/HS2:

2.5.1 HS1/HS2:

此区域设有 I 类和 II 类等待线, I、II 类运行时, 如未收到进一步管制指令, 禁止航空器穿越等待线。

Hold position for ILS CAT I and II established in the area, wait for clearance from ATC to cross.

2.5.2 HS3/HS4:

2.5.2 HS3/HS4:

此区域设有 I 类等待线, 在实施 I 类运行时, 未收

Hold position for ILS CAT I established in the area, wait

到进一步管制指令，严禁航空器越过等待线。

for clearance from ATC to cross.

#### 2.5.3 HS5:

#### 2.5.3 HS5:

进入该区域前，有 4 个等待标志 HP1-HP4，飞行员应根据管制员指令进入等待。

Four hold positions (HP1-HP4) established before the area, hold according to ATC instruction.

#### 2.5.4 HS6:

#### 2.5.4 HS6:

进入该区域前，有 4 个等待标志 HP5-HP8，其中“HP8”为强制位置报告点，飞行员应根据管制员指令进行等待。

Four hold positions including one compulsory reporting position “HP8” established before the area, hold according to ATC instruction.

#### 2.5.5 HS7:

#### 2.5.5 HS7:

2.5.5.1 此区域有地面等待标志 HP9、HP10。HP9 为强制位置报告点。

2.5.5.1 Two hold positions (HP9, HP10 )including one compulsory reporting position “HP9” established in the area, hold according to ATC instruction;

2.5.5.2 此区域设有 I 类和 II 类等待线，I、II 类运行时，需等待管制员指令，进行穿越。

2.5.5.2 Hold positions for ILS CAT I and II established, wait for clearance from ATC to cross.

#### 2.5.6 HS8:

#### 2.5.6 HS8:

此区域设有 I 类等待线，I 类运行时，需等待管制员指令，进行穿越。

Hold position for ILS CAT I established in the area, wait for clearance from ATC to cross.

#### 2.5.7 HS9:

#### 2.5.7 HS9:

此区域设有 I 类和 II 类等待线，I、II 类运行时，需等待管制员指令，进行穿越。

Hold positions for ILS CAT I and II established, wait for clearance from ATC to cross.

#### 2.5.8 HS10、HS11、HS12:

#### 2.5.8 HS10, HS11, HS12:

为供车辆进入跑道的通行道路。

For vehicle to enter runway

#### 2.6 地面常规滑行路线

#### 2.6 Routine Taxiing Route,

不同运行模式对应不同标准滑行路线，除管制员特别要求外，进离场航空器使用地面常规滑行路线滑行。

different modes of operations require different taxiing route. Routine Taxiing Routes are established in the aerodrome. Aircraft shall taxi along the Routine Taxiing Route except receiving the specific instruction from

controller.

| Operation type      | Used for                 | Route ID | Taxiing direction                                  |
|---------------------|--------------------------|----------|----------------------------------------------------|
| RWY 02L             | Runway 02L for departure | Route 1  | BX(X=1-6)/B-B6-A-RWY<br>02L hold position          |
|                     | Runway 02L for arrival   | Route 2  | A-BX(X=1-10)-B-stands                              |
| RWY 02R             | Runway 02R for departure | Route 3  | BX(X=1-10)/H7-B-M-D-<br>E1-RWY02R hold<br>position |
|                     |                          | Route 4  | E-E9-N-C-B10-B-stands                              |
|                     | Runway 02R for arrival   | Route 12 | D-T10-(K1/K3/K2/T1/T2)<br>-stands                  |
| RWY 02L and RWY 02R | Runway 02L for departure | Route 5  | BX(X=1-10)/A7-A-RWY0<br>2L hold position           |
|                     | Runway 02R for arrival   | Route 6  | E-E8-N-B/C-B10-B-stand<br>s                        |
|                     |                          | Route 12 | D-T10-(K1/K3/K2/T1/T2)<br>-stands                  |
| RWY 02L and RWY 02R | Runway 02L for departure | Route 5  | BX(X=1-10)/A7-A-RWY0<br>2L hold position           |
|                     | Runway 02R for departure | Route 3  | BX(X=1-10)/H7-B-M-D-<br>E1-RWY02R hold<br>position |
|                     | Runway 02R for arrival   | Route 4  | E-E9-N-C-B10-B-stands                              |
|                     |                          | Route 12 | D-T10-(K1/K3/K2/T1/T2)<br>-stands                  |
| RWY 02L and RWY 02R | Runway 02L for departure | Route 1  | BX(X=1-6)/B-B6-A-RWY                               |



|                    |                          |          |                                      |
|--------------------|--------------------------|----------|--------------------------------------|
|                    |                          |          | 02L hold position                    |
|                    | Runway 02L for arrival   | Route 2  | A-BX(X=1-10)-B-stands                |
|                    | Runway 02R for arrival   | Route 4  | E-E9-N-C-B10-B-stands                |
|                    |                          | Route 12 | D-T10-(K1/K3/K2/T1/T2)-stands        |
| RWY 20L            | Runway 20L for departure | Route 7  | B-B10-C-N-E9-RWY20L hold position    |
|                    | Runway 20L for arrival   | Route 8  | E-E8-M-B-stands                      |
| RWY 20R            | Runway 20R for departure | Route 9  | BX(X=4-10)/A7-A-RWY20R hold position |
|                    | Runway 20R for arrival   | Route 10 | A-BX(X=1-10)/A7-stands               |
| RWY 20L and RWY20R | Runway 20L for departure | Route 7  | B-B10-C-N-E9-RWY20L hold position    |
|                    |                          | Route 11 | T10-D-E9-RWY20L hold position        |
|                    | Runway 20R for arrival   | Route 10 | A-BX(X=1-10)/A7-stands               |
| RWY 20L and RWY20R | Runway 20L for departure | Route 7  | B-B10-C-N-E9-RWY20L hold position    |
|                    | Runway 20R for departure | Route 9  | BX(X=4-10)/A7-A-RWY20R hold position |
|                    | Runway 20R for arrival   | Route 10 | A-BX(X=1-10)/A7-stands               |
| RWY 20L and RWY20R | Runway 20L for departure | Route 7  | B-B10-C-N-E9-RWY20L hold position    |
|                    | Runway 20L for arrival   | Route 8  | E-E8-M-B-stands                      |
|                    | Runway 20R for arrival   | Route 10 | A-BX(X=1-10)/A7-stands               |

## 2.7 滑行道使用限制

## 2.7 Taxiway limitation

| TWY                                                                                                                                                                                             | Wing span limits for aircraft                                                                                                                                                                                                                                                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| B(BTN B1 & M), B1, C(BTN C2 & C5), C2, E, E1-E3, E7-E9, M, N, T2                                                                                                                                | 80m                                                                                                                                                                                                                                                                                 |
| A,A1-A9, B(BTN B1 & B10, north of stand Nr.212), B2-B10,C(others), C1, C3, C5-C8, D, D1-D5, E(BTN E9 & F), E4-E6, F, H3, H4, H5, H6(south of stand Nr.215), K1, K2, K4, T1, T3, T4, T10, V1, V2 | 65m                                                                                                                                                                                                                                                                                 |
| H1(west of stand Nr.131), H2(west of stand Nr.123), T7(west of stand Nr.151), T8(west of stand Nr.145), T9(west of stand Nr.136)                                                                | 61m                                                                                                                                                                                                                                                                                 |
| H2(east of stand Nr.123)                                                                                                                                                                        | 52m                                                                                                                                                                                                                                                                                 |
| B(BTN B10 & stand Nr.212)                                                                                                                                                                       | 39m                                                                                                                                                                                                                                                                                 |
| H1(east of stand Nr.131), H7, K3, T6, T7(east of stand Nr.151), T8(east of stand Nr.145), T9(east of stand Nr.136)                                                                              | 36m                                                                                                                                                                                                                                                                                 |
| B1(BTN B & C),C3                                                                                                                                                                                | <p>1.Allow aircraft on B1(BTN B &amp; C)and aircraft on C3 to operate independently while: both<math>\leq</math>53m.</p> <p>2. When one of the two TWYs occupied by ACFT with wing span more than 53m, the other TWY only available for ACFT with wing span not exceeding 36m.</p>  |
| B3(BTN B & C), C5                                                                                                                                                                               | <p>1.Allow aircraft on B3(BTN B &amp; C)and aircraft on C5 to operate independently while: both<math>\leq</math>53m..</p> <p>2. When one of the two TWYs occupied by ACFT with wing span more than 53m, the other TWY only available for ACFT with wing span not exceeding 36m.</p> |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                    |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| C6, C7                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | <p>1.Allow aircraft on C6 and aircraft on C7 to operate independently while: both<math>\leq</math>53m.</p> <p>2.When one of the two TWYs occupied by ACFT with wing span more than 53m, the other TWY only available for ACFT with wing span not exceeding 36m.</p>                |
| B6(BTN B & C), C8                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <p>1.Allow aircraft on B6 (BTN B &amp; C)and aircraft on C8 to operate independently while: both<math>\leq</math>53m.</p> <p>2.When one of the two TWYs occupied by ACFT with wing span more than 53m, the other TWY only available for ACFT with wing span not exceeding 36m.</p> |
| T10(north of T4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | $\leq$ 36m (when aircraft with wingspan $\geq$ 36m parking on stand Nr.326)                                                                                                                                                                                                        |
| H1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | $\leq$ 36m (when aircraft with wingspan $>$ 52m enter/exit stand Nr.123)                                                                                                                                                                                                           |
| H2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | $\leq$ 36m (when aircraft with wingspan $>$ 52m parking on or enter/exit stand Nr.123)                                                                                                                                                                                             |
| H6(north of stand Nr.215)                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | $\leq$ 36m (except for the aircraft pushed back,start up and taxi out of stands Nr.213, 214, 229, 230)                                                                                                                                                                             |
| <p>1. While an aircraft holding at TWY A2(BTN A &amp; RWY02L/20R),other aircraft are forbidden to taxi across TWY A2 along TWY A or taxi to TWY A via TWY A2.</p> <p>2. While an aircraft holding at TWY E2(BTN E &amp; RWY02R/20L),other aircraft are forbidden to taxi across TWY E2 along TWY E or taxi to TWY E via TWY E2.</p> <p>3. While an aircraft holding at TWY E8(BTN E &amp; RWY02R/20L)),other aircraft are forbidden to taxi across TWY E8 along TWY E or taxi to TWY E via TWY E8.</p> |                                                                                                                                                                                                                                                                                    |

2.8 F 滑和 E9 滑以北的 E 滑运行限制

2.8 Operation limitation for TWY F and TWY E(north of TWY E9)

2.8.1 当有航空器在 20L 跑道 I 类着陆或 02R 跑道 II

2.8.1 When an aircraft operates CAT I landing on

- 类运行时，在 G1 等待点以北的 E 滑以及 G2 和 G3 等待点之间的 F 滑上不能有航空器运行。当有航空器在 20L 跑道 HUD 特殊 II 类着陆时，F 滑和 E9 滑以北的 E 滑不能有航空器运行。

RWY20L or CAT II on RWY02R, other aircraft are forbidden to taxi on TWY E (north of holding point G1), or TWY F(BTN holding point G2 G3). When an aircraft operates HUD special CAT II landing on RWY20L, other aircraft are forbidden to taxi on TWY F or TWY E(north of TWY E9).
- 2.8.2 在对 02R 跑道航向台进行飞行校验时，F 滑及 G1 等待点以北的 E 滑不能有航空器运行。

2.8.2 When LOC flight inspection is carried out on RWY02R, aircraft is forbidden to taxi on TWY F or TWY E(north of holding point G1).
- 2.8.3 当有航空器在 02R 跑道起飞时,在 G1 等待点以北的 E 滑以及 G3 等待点以北的 F 滑上不能有航空器运行。G3 以南的 F 滑上不能有机高超过 10.46m（不含）的航空器运行。

2.8.3 When an aircraft takes off on RWY02R, other aircraft are forbidden to taxi on TWY E(north of holding point G1) and TWY F(north of holding point G3). Aircraft with height more than 10.46m(exclusive) is forbidden to taxi on TWY F(south of G3).
- 2.9 滑行道运行限制

2.9 Operation limitation for TWYs
- 2.9.1 V1、V2 滑

2.9.1 TWY: V1、V2

| TWY in use                                                                     | TWYs forbidden to use                                                       |
|--------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| TWY V1                                                                         | TWY T1(BTN stands Nr.365-364L), TWY T2(BTN TWY C and stand Nr.315L), TWY V2 |
| TWY V2                                                                         | TWY T1(BTN stands Nr.365-364L), TWY T2(BTN TWY C and stand Nr.315L), TWY V1 |
| It is forbidden to use TWY V1 and V2 when conducting low visibility operation. |                                                                             |

- 2.10 B747-8 航空器运行规则

2.10 Operation rules for B747-8
- 2.10.1 跑道: RWY02R/20L(主用),RWY02L/20R。

2.10.1 RWY: RWY02R/20L(main),RWY02L/20R.
- 2.10.2 滑行道:A、A1-A6、A8、A9、B(B3 以南)、B1、

2.10.2 TWYs: A, A1-A6, A8, A9, B(south of B3), B1,

B3、C(B3 以南)、C2、D、D1-D5、E、E1-E9、F、M、N、T2。

2.10.3 停机位:162、313、505-508 号停机位, B747-8 在本场运行时由引导车提供引导。

2.10.4 当使用 02L/20R 跑道起飞时,须在跑道 B 型等待位置前等待。

2.10.5 不能同时运行的滑行道

B3, C(south of B3), C2, D, D1-D5, E, E1-E9, F, M, N, T2.

2.10.3 Stands: Nr.162, 313, 505-508, B747-8 shall be guided by follow-me vehicle.

2.10.4 When taking off on RWY02L/20R, aircraft shall hold at type B holding position.

2.10.5 TWYs cannot be used simultaneously

|                            |                                                                                        |
|----------------------------|----------------------------------------------------------------------------------------|
| B747-8 on TWYs             | TWYs forbidden to use                                                                  |
| TWY A (north of TWY B1)    | aircraft with wingspan>65m on lateral TWY B(north of TWY B1)                           |
| TWY B (north of TWY B1)    | aircraft with wingspan>65m on lateral TWY A (north of TWY B1)or TWY C(north of TWY B1) |
| TWY B1(BTN TWY B & TWY C)  | aircraft with wingspan>36m on lateral TWY C3                                           |
| TWY B3(BTN TWY B & TWY C)  | aircraft with wingspan>36m on lateral TWY C5                                           |
| TWY C(BTN TWY B1 & TWY B3) | aircraft with wingspan>65m on lateral TWY B(BTN TWY B1&TWY B3)                         |
| TWY C2                     | aircraft with wingspan>65m on lateral TWY A2(BTN TWY B&TWY C)                          |
| TWY T2                     | aircraft with wingspan>65m on lateral TWY T1                                           |

2.10.6 B747-8 航空器滑行路线

2.10.6 Taxiing route for B747-8

|                      |                                          |                                  |                                  |
|----------------------|------------------------------------------|----------------------------------|----------------------------------|
|                      | Parking on stand Nr.162                  | Parking on stand Nr.313          | Parking on stand Nr.505-508      |
| RWY02R for departure | C-B3-A-A1-B-M-D-E1-02<br>R holding point | T2-C-M-D-E1-02R<br>holding point | F-E-E9-D-E1-02R holding<br>point |

|                                                        |                                    |                                            |                                                       |
|--------------------------------------------------------|------------------------------------|--------------------------------------------|-------------------------------------------------------|
| RWY02R for arrival                                     | E-E9-N-C to enter parking stand    | E-E9-N-C-T2 to enter parking stand         | E-F to enter parking stand                            |
| RWY20L for departure                                   | C-B3-A-A1-C-N-E9-20L holding point | T2-C-N-E9-20L holding point                | F-E-E9-20L holding point                              |
| RWY20L for arrival                                     | D-M-C to enter parking stand       | D-M-C-T2 to enter parking stand            | E-F to enter parking stand                            |
| RWY02L for departure                                   | C-B3-A-A1-02L holding point        | T2-C-A1-02L holding point                  | F-E-E9-N-C-A1-02L holding point                       |
| RWY02L for arrival                                     | A-B3-C to enter parking stand      | A-B1-C-T2/A-B3-C-T2 to enter parking stand | A-B1-B-M-E9-E-F to enter parking stand                |
| RWY20R for departure                                   | C-B3-A-A8-20R holding point        | T2-C-B3-A-A8-20R holding point             | F-E-E9-M-B-B3-A-20R holding point                     |
| RWY20R for arrival                                     | A-A1-C to enter parking stand      | A-A1-C-T2 to enter parking stand           | A1-B-M-E9-E-F or B1-B-M-E9-E-F to enter parking stand |
| Remarks: Actual taxiing route follow ATC instructions. |                                    |                                            |                                                       |

## 2.11 A380 航空器运行规则

## 2.11 Operation rules for A380

## 2.11.1 跑道: RWY02R/20L。

## 2.11.1 RWY: RWY02R/20L.

2.11.2 滑行道: B (B1 以南)、B1、C (C2 和 B3 之间)、C2、D、E、E1、E2、E8、E9、M、N、T2。

2.11.2 TWTs: B(south of B1), B1, C(BTN C2&C3), C2, D, E, E1, E2, E8, E9, M, N, T2.

2.11.3 停机位: 162、313 号停机位, A380 在本场运行时由引导车提供引导。

2.11.3 Stands: Nr.162, 313, A380 shall be guided by follow-me vehicle.

## 2.11.4 不能同时运行的滑行道

## 2.11.4 TWYs cannot be used simultaneously

|                        |                                                      |
|------------------------|------------------------------------------------------|
| A380 on TWYs           | TWYs forbidden to use                                |
| TWY B(south of TWY B1) | aircraft with wingspan>65m on lateral TWY C(south of |

|                          |                                                                 |
|--------------------------|-----------------------------------------------------------------|
|                          | TWY B1)                                                         |
| TWY B1(btn TWY B&TWY C)  | aircraft with wingspan>36m on lateral TWY C3 (BTN TWY B&TWY C)  |
| TWY C(btn TWY C2&TWY B1) | aircraft with wingspan>65m on lateral TWY B (BTN TWY C2&TWY B1) |
| TWY C(btn TWY B1&TWY B3) | aircraft with wingspan>52m on lateral TWY B (BTN TWY B1&TWY B3) |
| TWY C2                   | aircraft with wingspan>61m on lateral TWY A2 (BTN TWY B&TWY C)  |
| TWY T2                   | aircraft with wingspan>61m on lateral TWY T1                    |

## 2.11.5 A380 航空器滑行路线

## 2.11.5 Taxiing route for A380

| Parking on stand Nr.162                                |                                      | Parking on stand Nr.313 |                                       |
|--------------------------------------------------------|--------------------------------------|-------------------------|---------------------------------------|
| RWY02R for departure                                   | C-C2-B-N-E9-E-E1-02R holding point   | RWY02R for departure    | T2-C2-B-N-E9-E-E1-02R holding point   |
| RWY02R for arrival                                     | E-E9-N-B-C2-C to enter parking stand | RWY02R for arrival      | E-E9-N-B-C2-T2 to enter parking stand |
| RWY20L for departure                                   | C-C2-B-N-E9-20L holding point        | RWY20L for departure    | T2-C2-B-N-E9-20L holding point        |
| RWY20L for arrival                                     | E-E8-M-B-C2-C to enter parking stand | RWY20L for arrival      | E-E8-M-B-C2-T2 to enter parking stand |
| Remarks: Actual taxiing route follow ATC instructions. |                                      |                         |                                       |

## 2.12 AN124 航空器运行规则

## 2.12 Operation rules for AN124

2.12.1 跑道: RWY02R/20L(主用)、RWY02L/20R。

2.12.1 RWY:RWY02R/20L(main), RWY02L/20R.

2.12.2 滑行道: A、A1-A6、A8、B (B1 以南)、B1、

2.12.2 TWYs:A, A1-A6, A8, B(south of B1), B1, B3,

B3、C (B3 以南)、C2、D、E、E1-E9、M、N、T2。

C(north of B3), C2, D, E, E1-E9, M, N, T2.

2.12.3 停机位：313 号停机位，AN124 在本场运行时  
由引导车提供引导位。

2.12.3 Stands: Nr.313, AN124 shall be guided by  
follow-me vehicle.

2.12.4 AN124 航空器滑行路线

2.12.4 Taxiing route for AN124

|                                                        |                                            |
|--------------------------------------------------------|--------------------------------------------|
| Parking on stand Nr.313                                |                                            |
| RWY02R for departure                                   | T2-C2-B-N-E9-E-E1-02R holding point        |
| RWY02R for arrival                                     | E-E9-N-B-C2-T2 to enter parking stand      |
| RWY20L for departure                                   | T2-C2-B-N-E9-20L holding point             |
| RWY20L for arrival                                     | E-E8-M-B-C2-T2 to enter parking stand      |
| RWY02L for departure                                   | T2-C-A1-02L holding point                  |
| RWY02L for arrival                                     | A-B1-C-T2/A-B3-C-T2 to enter parking stand |
| RWY20R for departure                                   | T2-C-B3-A-A8-20R holding point             |
| RWY20R for arrival                                     | A-A1-C-T2 to enter parking stand           |
| Remarks: Actual taxiing route follow ATC instructions. |                                            |

2.12.5 不能同时运行的滑行道

2.12.5 TWYs cannot be used simultaneously

|                          |                                                                 |
|--------------------------|-----------------------------------------------------------------|
| AN124 on TWYs            | TWYs forbidden to use                                           |
| TWY A(north of TWY B1)   | aircraft with wingspan>61m on lateral TWY B(north of TWY B1)    |
| TWY B1(BTN TWY B&TWY C)  | aircraft with wingspan>36m on lateral TWY C3                    |
| TWY B3(BTN TWY B&TWY C)  | aircraft with wingspan>36m on lateral TWY C5                    |
| TWY C(BTN TWY B1&TWY B3) | aircraft with wingspan>61m on lateral TWY B (BTN TWY B1&TWY B3) |
| TWY C2                   | aircraft with wingspan>65m on lateral TWY A2 (BTN               |



|        |                                              |
|--------|----------------------------------------------|
|        | TWY B&TWY C)                                 |
| TWY T2 | aircraft with wingspan>65m on lateral TWY T1 |

|                                                                         |                                                                                                                                                                                    |
|-------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2.13 对机组的要求                                                             | 2.13 Requirements for pilots                                                                                                                                                       |
| 2.13.1 在塔台管制室管制范围内，由塔台管制室发布滑行指令，在双流机坪管制范围内，由双流机坪发布滑行指令。                 | 2.13.1 Tower Control and Shuangliu Apron shall issue taxiing instructions in their own control areas only.                                                                         |
| 2.13.2 在脱离跑道首次与地面管制联系时，尤其是在地面能见度较差的情况下，必须向地面管制员报告脱离的跑道和所使用的滑行道。         | 2.13.2 Pilot shall report the designation of the RWY having been vacated and TWY designation being in use on initial contact with GND, especially under low visibility conditions. |
| 2.13.3 专机滑行路线以管制员通知为准。                                                  | 2.13.3 The taxiing routes of special flight shall be instructed by ATC.                                                                                                            |
| 2.13.4 申请正在使用跑道以外的跑道起降，必须征得 ATC 的许可方能使用。                                | 2.13.4 Pilot shall obtain the clearance from controller before changing the RWY in use.                                                                                            |
| 2.13.5 在 ATC 的许可下，由机组根据短距起飞工作程序及机型翼展、机高的限制，自行决定是否使用非全跑道起飞。              | 2.13.5 With ATC clearance, flight crew can conduct the Shortened Distance Taking-off Procedures.                                                                                   |
| 2.13.6 进出货机坪停机位 501-503 的航空器应在 180s（含）以内滑行通过 G1 与 G2 之间的滑行道，否则应提前告知管制员。 | 2.13.6 Aircraft enter/exit from stands Nr.501-503 shall pass the TWY between TWY G1&G2 within 180s. Otherwise, pilot shall inform ATC in advance.                                  |
| 2.13.7 进出货机坪停机位 504-508 的航空器应在 180s（含）以内滑行通过 G1 与 G3 之间的滑行道，否则应提前告知管制员。 | 2.13.7 Aircraft enter/exit from stands Nr.504-508 shall pass the TWY between TWY G1&G3 within 180s. Otherwise, pilot shall inform ATC in advance.                                  |
| 2.14 满足下列条件之一时，须启动跑道方向转换：                                               | 2.14 When any of the following conditions are met, the runway direction conversion shall be initiated:                                                                             |
| 2.14.1 干跑道条件下，当跑道顺风分量达到 3.5m/s，                                         | 2.14.1 Dry runway conditions: When the tailwind                                                                                                                                    |

且有继续增大趋势时；

component reaches 3.5 m/s and shows a continuing increasing trend.

2.14.2 湿跑道或者污染跑道条件下(跑道表面状况代码为 5)，当跑道顺风分量达到 3.5m/s，且有继续增大趋势时。

2.14.2 Wet runway or contaminated runway (surface condition code 5): When the tailwind component reaches 3.5 m/s and shows a continuing increasing trend.

2.15 转换跑道运行方向过程中，干跑道条件下跑道顺风分量超过 3.5m/s 但不大于 5m/s 时；湿跑道或者污染跑道(跑道表面状况代码为 5)顺风分量超过 3.5m/s 但不大于 5m/s 时，管制员应当通知航空器驾驶员，航空器驾驶员根据飞机性能或航空公司运行手册决定是否使用管制员安排的顺风跑道起降。

2.15 During runway direction conversion: On a dry runway, if the tailwind component exceeds 3.5m/s but does not exceed 5 m/s; On a wet runway or contaminated runway (surface condition code 5), if the tailwind component exceeds 3.5 m/s but does not exceed 5 m/s: The controller shall notify the pilot. The pilot may decide whether to use the assigned tailwind runway for takeoff/landing based on aircraft performance or airline operations manual.

### 3. 机坪和机位的使用

### 3. Use of aprons and parking stands

3.1 离场飞行的航空器，在计划起飞(ETD)前 30min 根据通播(ATIS)公布的初始联系频率可向双流塔台管制室申请放行许可；收到放行许可后，应立即与放行席位确认抄收并脱波，转频至双流机坪建立联系并保持长守，由双流机坪负责离港航班的推出开车顺序。

3.1 Departure aircraft shall contact the initial contact frequency issued by ATIS to obtain delivery clearance, but shall be no earlier than 30 minutes of the ETD then change frequency to contact Shuangliu APN Control and keep listening the frequency. Shuangliu Apron is responsible for push-back and start-up sequence.

3.2 双流机坪发布的推出开车许可指令，机组必须在 3min 内执行，否则，需要重新申请。

3.2 The clearance of push-back and start-up issued by Shuangliu Apron shall be performed within 3 minutes, otherwise, the clearance will be cancelled automatically and a new clearance shall be applied.

3.3 起飞及着陆航空器占用跑道时间要求：

起飞航空器从等待位置到对正跑道时间应在 60 秒内，着陆航空器从接地到滑出跑道时间应该在 50 秒内，

3.3 Time requirement of occupying runway for departure and landing aircraft: Departure aircraft shall finish RWY alignment within 60 seconds after leaving

运行中航空器不能满足上述跑道占用时间要求的，应当及时通知管制单位。

hold position, landing aircraft shall fully vacate RWY within 50 seconds after touch down.If pilot consider that they can not fulfill the time requirement, they shall inform ATC controller as soon as possible.

3.4 发动机试车，需经运控中心许可，并在指定地点进行。严禁在廊桥附近、客机坪和滑行道上试大车。

3.4 Engine run-ups are subject to AOC clearance, and shall be carried out at a designated location. Fast engine run-ups near boarding bridges, or on apron or TWYs are strictly forbidden.

| Engine run-up stands     | Engine run-up location        | Operating Regulations                                                                                                                                                                                                                                                |
|--------------------------|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Nr.1 engine run-up stand | TWY B (north of stand Nr.239) | 1. Nose to south.<br>2. Available for aircrafts with wingspan≤65m(B747 series not included).<br>3. While engine run-up, aircraft push-back via stand Nr.237 is forbidden, aircraft taxi in/push-back via stands Nr.238 and 239 is forbidden.<br>4. Apply in advance. |
| Nr.2 engine run-up stand | TWY K1(west of stand Nr.422)  | 1. Nose to northeast.<br>2. Available for aircrafts with wingspan≤65m.<br>3. While engine run-up, aircraft taxi in/push-back via stands Nr.420 and 424 is forbidden.<br>4. Apply in advance.                                                                         |

3.5 停机位翼展限制

3.5 Wing span limits for aircraft

| 停机位编号/Stands Nr. | 翼展限制（m）/Wing span limits(m) | 机身长度限制（m）/Fuselage limits(m) |
|------------------|-----------------------------|------------------------------|
|------------------|-----------------------------|------------------------------|

|                                                                                                                                                                                                                                         |       |       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------|
| 162, 313                                                                                                                                                                                                                                | 80    |       |
| 505-508                                                                                                                                                                                                                                 | 68.5  | 76.3  |
| 167-171                                                                                                                                                                                                                                 | 65    | 76    |
| 420-422                                                                                                                                                                                                                                 | 65    | 75.5  |
| 231-235                                                                                                                                                                                                                                 | 65    | 73.9  |
| 301-306, 308, 401-403, 405-410                                                                                                                                                                                                          | 65    | 71    |
| 503, 504                                                                                                                                                                                                                                | 65    | 70.7  |
| 357, 358, 501, 502                                                                                                                                                                                                                      | 65    | 70.66 |
| 114                                                                                                                                                                                                                                     | 65    | 67    |
| 103, 104, 106, 112, 132, 134, 147,<br>149, 164, 172, 314-319, 326,<br>362-364                                                                                                                                                           | 65    |       |
| 321, 322, 361                                                                                                                                                                                                                           | 61    | 74    |
| 230                                                                                                                                                                                                                                     | 61    | 65    |
| 121, 123, 146, 229                                                                                                                                                                                                                      | 61    | 64    |
| 131                                                                                                                                                                                                                                     | 61    | 63.7  |
| 102, 107, 135, 150, 165, 213, 214                                                                                                                                                                                                       | 61    |       |
| 404                                                                                                                                                                                                                                     | 47.57 | 55    |
| 423, 424                                                                                                                                                                                                                                | 38.05 | 47.32 |
| 110, 111, 113, 115, 116, 119, 120,<br>122, 124, 166, 303L, 303R, 304L,<br>304R, 305L, 305R, 306L, 306R,<br>307, 308L, 308R, 320, 324, 401L,<br>401R, 405L, 405R, 406L, 406R,<br>407L, 407R, 408L, 408R, 508L,<br>508R, 601-610, 614-619 | 36    | 45    |

|                                                                                                                                                                                                                                                                                                       |    |      |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|------|
| 126-128, 139-141, 154-157, 225-227                                                                                                                                                                                                                                                                    | 36 | 40   |
| 101, 125, 129, 130, 137, 138, 142,<br>152, 153, 158, 159                                                                                                                                                                                                                                              | 36 | 39   |
| 236-239                                                                                                                                                                                                                                                                                               | 36 | 37.6 |
| 108, 109, 117, 118, 411, 412                                                                                                                                                                                                                                                                          | 36 | 34   |
| 613                                                                                                                                                                                                                                                                                                   | 36 | 29   |
| 105, 136, 143-145, 151, 160, 161,<br>173, 201-208, 211, 212, 215-218,<br>224, 313L, 313R, 314L, 314R,<br>315L, 315R, 316L, 316R, 317L,<br>317R, 318L, 318R, 319L, 319R,<br>326L, 326R, 327-334, 357L, 357R,<br>359, 361L, 361R, 362L, 362R,<br>364L, 364R, 365, 505L, 505R,<br>506L, 506R, 507L, 507R | 36 |      |
| 210, 219                                                                                                                                                                                                                                                                                              | 35 |      |
| 335                                                                                                                                                                                                                                                                                                   | 30 |      |
| 403L, 403R                                                                                                                                                                                                                                                                                            | 28 | 45   |
| 209, 228                                                                                                                                                                                                                                                                                              | 23 |      |

## 3.6 航空器进出停机位的滑行限制

## 3.6 Limits for aircraft entering /exiting stands

| 停机位/Stand             | 进入滑行道/Enter into<br>stand by | 滑出滑行道/Exit stand by | 顶推出机头方向/Nose<br>direction after push-back |
|-----------------------|------------------------------|---------------------|-------------------------------------------|
| Nr.101                | H5                           | H5                  | Nose to West                              |
| Nr.213, 214, 229, 230 | H5-H6                        | H6-H5               | Nose to South                             |
| Nr.102-104            | H5                           | H5                  | Push back to H6(south of                  |

|                                |          |                                                       |                                              |
|--------------------------------|----------|-------------------------------------------------------|----------------------------------------------|
|                                |          |                                                       | stand Nr.215), nose to South                 |
| Nr.105, 113, 122               | C        | C                                                     | Follow ATC instructions                      |
| Nr.106-112                     | H4       | H4                                                    | Nose to West                                 |
| Nr.115-121                     | H3       | H3                                                    | Nose to West                                 |
| Nr.114                         | H3       | C (wingspan $\geq$ 36m)<br>H3 or C (wingspan $<$ 36m) | Follow ATC instructions                      |
| Nr.123                         | H2       | C                                                     | Follow ATC instructions                      |
| Nr.124,125                     | H1 or H2 | H2                                                    | Nose to North                                |
| Nr.126-130                     | H1       | H2                                                    | Nose to North(126,127),Nose to East(128-130) |
| Nr.131                         | H1       | C                                                     | Follow ATC instructions                      |
| Nr.132, 134, 147, 149, 162,164 | C        | C                                                     | Follow ATC instructions                      |
| Nr.135                         | C-T9     | C                                                     | Follow ATC instructions                      |
| Nr.150                         | C-T7     | C                                                     | Follow ATC instructions                      |
| Nr.136-138                     | T8 or T9 | T9                                                    | Nose to West(136)Nose to North(137,138)      |
| Nr.139-145                     | T8       | T9                                                    | Nose to North(139,140),Nose to East(141-145) |
| Nr.146                         | T8       | C                                                     | Follow ATC instructions                      |
| Nr.151-153                     | T6 or T7 | T7                                                    | Nose to West(151)Nose to North(152,153)      |
| Nr.154-161                     | T6       | T7                                                    | Nose to North(154,155),Nose to               |

|                                                                                |                |                |                                                                                                              |
|--------------------------------------------------------------------------------|----------------|----------------|--------------------------------------------------------------------------------------------------------------|
|                                                                                |                |                | East(156-161)                                                                                                |
| Nr.165-173                                                                     | T4             | T4             | Nose to<br>West(165-172),Nose to<br>Southwest(173)                                                           |
| Nr.201-212                                                                     | B              | B              | Nose to South                                                                                                |
| Nr.215-218                                                                     | H5-H6 or H7-H6 | H6-H7 or H6-H5 | Follow ATC instructions                                                                                      |
| Nr.219, 224                                                                    | H5-H6 or H7-H6 | H6-H7          | Nose to North                                                                                                |
| Nr.225, 226                                                                    | H7 or H6       | H7 or H6       | Follow ATC instructions                                                                                      |
| Nr.227, 228                                                                    | H7             | H7             | Nose to West                                                                                                 |
| Nr.231-239                                                                     | B              | B              | Nose to South                                                                                                |
| Nr.301-308, 303L/R,<br>304L/R, 305L/R,<br>306L/R,308L/R                        | T3 or T4       | T3 or T4       | Follow ATC<br>instructions,Nose to<br>West(308, 308L/R) while<br>ACFT taxiing at TWYC<br>(BTN TWY T2 and T4) |
| Nr.313-319(include<br>combined stands)                                         | T2             | T2             | Nose to<br>West(313-319(include<br>combined stands))                                                         |
| Nr.320-322, 324                                                                | T10            | T10            | Follow ATC instructions                                                                                      |
| Nr.326(include combined<br>stands),327                                         | T10            | T10            | Nose to North                                                                                                |
| Nr.328-335                                                                     | T10            | T10            | Follow ATC instructions                                                                                      |
| Nr.411, 412                                                                    | T10            | T10            | Nose to North                                                                                                |
| Nr.357-359(include<br>combined stands),<br>361-365(include combined<br>stands) | T1             | T1             | Nose to West (357-359<br>(include combined stands),<br>361-365(include combined<br>stands))                  |

|                                                                 |           |           |                                                                                                                                                |
|-----------------------------------------------------------------|-----------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Nr.401, 401L/R, 402,<br>407-408, 407L/R,<br>408L/R、410          | K2 or K4  | K2 or K4  | Follow ATC instructions                                                                                                                        |
| Nr.403, 403L, 403R, 404,<br>405, 405L, 405R, 406,<br>406L, 406R | K2        | K4        | Follow ATC instructions                                                                                                                        |
| Nr.409                                                          | K2 or T10 | K2 or T10 | Follow ATC instructions                                                                                                                        |
| Nr.420                                                          | T10       | K1        | Nose to Northeast                                                                                                                              |
| Nr.421-424                                                      | K1        | K1        | Nose to Northeast                                                                                                                              |
| Nr.501,502                                                      | E-F       | F-E       | Nose to South                                                                                                                                  |
| Nr.503                                                          | F         | F         | Nose to South                                                                                                                                  |
| Nr.504, 505-507(include<br>combined stands)                     | F         | F         | Nose to North                                                                                                                                  |
| Nr.508                                                          | F         | F         | Follow ATC instructions,<br>for parking A340, B777,<br>B747 or aircraft that need<br>to start one engine on the<br>stand should nose to south. |
| Nr.508L                                                         | F         | F         | Nose to north                                                                                                                                  |
| Nr.508R                                                         | F         | F         | Follow ATC instructions,<br>aircraft that need to start<br>one engine on the stand<br>should nose to south.                                    |
| Nr.601-609, 613-619                                             | K3        | K3        | Nose to Northeast                                                                                                                              |
| Nr.610                                                          | K3        | K3        | Nose to northeast (Aircraft<br>parking at stand Nr.610<br>with the distance between                                                            |



|                                       |  |  |                                                                                                                                                        |
|---------------------------------------|--|--|--------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                       |  |  | the nose gear and the tail≤26.5m), nose to southwest ( Aircraft parking at stand Nr.610 with the distance between the nose gear and the tail > 26.5m). |
| Follow ATC instructions in operation. |  |  |                                                                                                                                                        |

3.7 不能同时使用的机位

3.7 Stands forbidden to be used simultaneously

| The stand in use                                                                                                                                                                                                                                                                                                                                                                                   | The stands forbidden to be used |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| Nr.162(wingspan>65m)                                                                                                                                                                                                                                                                                                                                                                               | Nr.164(wingspan>52m)            |
| Nr.164(wingspan>52m)                                                                                                                                                                                                                                                                                                                                                                               | Nr.162(wingspan>65m)            |
| Nr.361(wingspan≥52m)                                                                                                                                                                                                                                                                                                                                                                               | Nr.362L                         |
| Nr.303-308, 313-319, 326, 357, 361, 362, 364, 401, 403, 405-408, 505-508 are combined stands. When an aircraft is parked at any of these combined stands, no aircraft shall be parked at their corresponding L (Left) or R (Right) stands; in turn, if an aircraft is parked at the corresponding L or R stand of any of these combined stands,no aircraft shall be parked at that combined stand. |                                 |

3.8 当 107 机位停放翼展 52m(含)至 61m(含)的航空器且 108 机位、109 机位都停有航空器时，若 108 机位的航空器早于 107 机位的航空器推出，须沿 H4 顶推至 C 滑滑出，机头朝向听从管制员指挥。

3.8 When aircrafts parking on stands Nr.107-109(aircraft with wingspan 52-61m(included) parking on stand Nr.107), if aircraft on stand Nr.108 is pushed back earlier than aircraft on stand Nr.107, the aircraft on stand Nr.108 should be pushed to TWY C via TWY H4 and nose direction should follow ATC instructions.

3.9 APU 替代设备方面，101-125 廊桥机位（T1），126-173 廊桥机位（T2），配备有 400Hz 电源和空调系统，桥位可提供允许停放的全部机型使用地面电源和空调。(134、149 桥位电源不满足 B787 机型)。为降低碳排放及噪音，成都双流国际机场所有停靠廊桥机位的航空器必须接驳航空地面静变电源和航空器地面空调，关闭 APU。(除 134、149 桥位停靠 B787 机型外)。

3.9 Alternative Measure of APU:Boarding bridge stands Nr.101-125 (TML Nr.1) and Nr.126-173 (TML Nr.2) are equipped with 400Hz power units and air supply units,which are available for all types of aircrafts that are allowed to park here.(The bridge power units at Stands Nr.134 and 149 are not available for B787 aircraft). For the purpose of reducing carbon emissions and noise, at CHENGDU/Shuangliu International Airport, all aircraft parked at boarding bridge stands must connect to ground static inverter power units (i.e., ground power units) and ground air supply units, and shut down the APU (except for B787 aircraft parked at Stands Nr.134 and 149).

| Boarding bridge                                                                   | Ground air supply unit |
|-----------------------------------------------------------------------------------|------------------------|
| Nr.129, 130, 136-145, 151-160, 166, 173                                           | AC215X                 |
| Nr.118-120, 122, 124-125, 132, 134, 147, 149, 161,162<br>(main bridge) , 164, 172 | AC315X                 |
| Nr.121, 123, 135, 150, 162(auxiliary bridge), 165                                 | AC385X                 |
| Nr.126-128                                                                        | JDFX160                |
| Nr.101, 105, 108-111, 113, 115-117                                                | JDFX210-V              |
| Nr.102-104, 106-107, 112, 114, 131, 146, 167-171                                  | JDFX320                |

3.10 滑入及滑出停机位的规定

3.10 Rules for entering/exiting stands

| 机位/Stands | 滑入方式/Enter by | 滑出方式/Exit by | 航空器翼展限制/Wing span limits for aircraft |
|-----------|---------------|--------------|---------------------------------------|
|-----------|---------------|--------------|---------------------------------------|

|                                                                                                               |         |                    |       |
|---------------------------------------------------------------------------------------------------------------|---------|--------------------|-------|
| Nr.320                                                                                                        | Taxi-in | Push-out/ taxi-out | ≤24m  |
|                                                                                                               | Taxi-in | Push-out           | > 24m |
| Nr.324                                                                                                        | Taxi-in | Push-out/ taxi-out | ≤24m  |
|                                                                                                               | Taxi-in | Push-out           | > 24m |
| 1.ACFT are forbidden to taxi out to north from stand Nr.313 by own power while stands Nr.308,308L/R occupied. |         |                    |       |

3.10.1 停放于 364 和 364R 机位的航空器须顶推过 HP14，机头方向向西；停放于 314 和 314R 机位的航空器须顶推过 HP15，机头方向向西。

3.10.1 Aircrafts paking on stands Nr.364 and Nr.364R should be pushed back through HP14, nose to west.  
Aircrafts parking on stands Nr.314 and Nr.314R should be pushed back through HP15, nose to west.

3.10.2 610 机位机头向东北推开及 609、613、614 停机位推开时，到位前不允许开车。

3.10.2 When the aircraft at stand Nr.610 is pushed back with nose towards northeast, and when the aircraft at stands Nr.609, 613 and 614 are pushed back, these aircrafts are not allowed to start up before they are in position.

3.10.3 停放 171、172 停机位的航空器向西推出至 T4 滑行道时，326、326L/R、327、328 停机位不允许航空器进出，停放 329 停机位的航空器不允许向南推出。

3.10.3 When the aircraft at stand Nr.171 and 172 is pushed back with nose towards west to TWY T4, aircraft are not allowed to taxi into/out to parking stands Nr.326, 326L/R, 327 and Nr.328, and aircraft parking at stand Nr.329 not allowed to push back with nose towards south.

3.11 航空器除冰/雪规定

3.11 Deicing/snow clearing rules

3.11.1 一般要求

3.11.1 General rules

驻场航空公司、地服公司应做好航空器除冰、防冰工作，地面除冰人员应向机组确认航空器是否处于适当的除冰、防冰构型，向机组通报使用除冰液的类型、浓缩比例和使用防冰液的开始时间，应安排放行人员

Airlines and ground service department are responsible for deicing/anti-icing tasks.Ground service staff shall confirm with flight crew to guarantee aircraft is in proper deicing/anti-icing configuration, and notify the

监控航空器在除冰雪过程中的安全。

type of deicing fluid, the concentration ratio and the time to use it. Staff responsible for Delivery shall monitor the deicing process to ensure the safety of aircraft.

### 3.11.2 响应程序

### 3.11.2 Response program

3.11.2.1 三级响应（预除冰/雪）：气象预报次日本场可能出现降雪或霜降天气导致航空器积冰/雪，机场发布灾害性天气预警并启动三级响应，各基地航空公司、机场地服做好预除冰工作。

3.11.2.1 Response Level 3(pre-deicing/snow clearing): when weather forecast predict it may snow or frost tomorrow and lead to the aircraft covered by ice/snow, airport shall give early warning of disaster weather and start Response Level 3. Airlines and airport shall be prepared for the pre-deicing work.

3.11.2.2 二级响应（机位除冰/雪）：实施预除冰/雪后，若国航及其代理、川航、机场地服代理三家代理中，任意一家航司代理的航班出现机位上等待除冰/雪情况，且一小时内等待除冰/雪航班数量未超过其最大小时除冰/雪容量时，升级除冰/雪响应等级为二级。

3.11.2.2 Response Level 2(deicing/snow clearing at parking stands): After pre-deicing/snow clearing work, if aircraft of one of the AIR CHINA and its agency, Sichuan Airline or aerodrome ground agency waits for deicing/snow clearing on the parking stands and the amount of flight waiting for deicing/snow clearing within 1h is not exceed the maximum volume, upgrade the response level to level 2.

3.11.2.3 一级响应（定点除冰/雪）：国航及其代理、川航、机场地服代理中任意一家航司代理预计一小时等待除冰/雪航班数量超过最大小时除冰/雪容量时，超容的航司或代理可向运控中心申请定点除冰/雪，运控中心评估后根据实际运行情况决定是否实施定点除冰。确定实施定点除冰则启动一级响应。

3.11.2.3 Response Level 1(deicing/snow clearing at designated location): one of the AIR CHINA and its agency, Sichuan Airline or aerodrome ground agency predict the amount of flight waiting for deicing/snow clearing within 1h would exceed the maximum volume, the excess airlines or agencies could apply to AOC for designated deicing/snow clearing. AOC evaluate and decide whether implement designated deicing according to the actual operation condition. If implement

|                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                                                                                                                                  | designated deicing, start response Level 1.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 3.11.3 除冰雪区域                                                                                                                                                                                                     | 3.11.3 De-icing Areas                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| 3.11.3.1 1 号除冰雪区域: 105 机位后方 C 滑设置 1 号除冰雪区域, 可供翼展<65m 的航空器停放, 主用于川航航空器定点除冰雪指定区域, 航空器自滑入机位后机头朝南停放。                                                                                                                 | 3.11.3.1 De-icing Area Nr.1: Located behind Stand Nr.105 on TWY C, De-icing Area Nr.1 is designated for aircraft with wing span less than 56m. It primarily serves as a dedicated de-icing zone for Sichuan Airlines aircraft. After taxiing into the stand, aircraft shall park nose to south.                                                                                                                                                                                                                                                                                       |
| 3.11.3.2 2 号除冰雪区域: 313 停机位、308 停机位区域设置为 2 号除冰雪区域。同时启用时, 313 机位可停放翼展<36m 的航空器, 308 机位可停放翼展<65m 的航空器。拆分单独使用时, 优先启用 313 机位, 可停放翼展<65m 的航空器。2 号除冰雪作为各航司通用定点除冰雪指定区域, 主用于起飞跑道为西跑道时使用, 两架航空器依次自滑至 313、308 机位区域, 机头朝南停放。 | 3.11.3.2 De-icing Area Nr.2: Comprises stands Nr.313 and 308. When both stands are activated, stand Nr.313 is available for aircraft with wing span less than 36m, stand Nr.308 is available for aircraft with wing span less than 65m. When operated separately, priority is given to stand Nr.313, and stand Nr.313 is available for aircraft with wing span less than 65m. This area serves as a general de-icing zone for all airlines, primarily used when the departure runway is RWY02L/20R. Aircraft shall taxi sequentially to Stands Nr.313 and 308 and park nose to south. |
| 3.11.3.3 3 号除冰雪区域: T2 与 T3 间 C 滑上设置 3 号除冰雪区域, 可供翼展<65m 的航空器停放, 备用起飞跑道为西跑道时使用, 航空器自滑到位后机头朝南停放。                                                                                                                    | 3.11.3.3 De-icing Area Nr.3: Located on TWY C between TWYs T2 and T3, De-icing Area Nr.3 is a backup zone for aircraft with wing span less than 65m, primarily used when the departure runway is RWY02L/20R. Aircraft shall park nose to south after taxiing into the area.                                                                                                                                                                                                                                                                                                           |
| 3.11.3.4 4 号除冰雪区域: 位于 K1 滑行道对应的 T10 滑行道附近, 供翼展<65m 的航空器停放, 为各航司通用定点除冰雪指定区域, 主用于起飞跑道为东跑道                                                                                                                          | 3.11.3.4 De-icing Area Nr.4: Situated near TWY T10 adjacent to TWY K1, De-icing Area 4 is available for aircraft with wing span less than 65m. It serves as a                                                                                                                                                                                                                                                                                                                                                                                                                         |

时使用，航空器自滑到位后机头朝南停放。

general de-icing zone for all airlines, primarily used when the departure runway is 02R/20L. Aircraft shall park nose to south after taxiing into the area.

3.11.4 国航配备有除冰车 3 台，川航配备有除冰车 2 台，地服配备有除冰车 3 台。

3.11.4 Air China: 3 De-icing trucks. Sichuan Airlines: 2 De-icing trucks. Ground Service Provider: 3 De-icing trucks.

#### 4. 低能见度运行

#### 4. Low visibility operation

4.1 成都/双流机场 02L 号跑道装有 II 类仪表着陆系统，02R 号跑道装有 III 类仪表着陆系统。

4.1 RWY02L of CHENGDU/Shuangliu Airport is equipped with ILS CAT II, RWY02R of CHENGDU/Shuangliu Airport is equipped with ILS CAT III.

4.2 使用 02L/20R 离场航空器通常自 A 滑行道进入跑道。

4.2 Departing aircraft using RWY02L/20R shall normally enter RWY from TWY A.

#### 4.3 低能见度运行

#### 4.3 Low Visibility Operation(LVO)

##### 4.3.1 跑道的使用

##### 4.3.1 Use of RWYs

02L、02R 跑道满足 II 类及 HUD 特殊 I 类运行标准，20L 跑道满足 HUD 特殊 II 类运行标准；02L、02R 跑道允许使用 HUD 实施 RVR150m 起飞。

RWY 02L/R is satisfied with CAT II and HUD Special CAT I operation standard; RWY 20L is satisfied with HUD Special CAT II operation standard; RWY 02L/R is available for HUD RVR150m take-off.

##### 4.3.2 低能见度运行程序的准备、实施和结束

##### 4.3.2 Preparation, implementation and termination of Low Visibility Operation Procedures

4.3.2.1 当机场能见度为 1000m 或云高 90m 并呈下降趋势时，西南空管局管制中心将发布准备实施低能见度运行程序的指令；

4.3.2.1 When VIS=1000m or ceiling=90m and forecast shows a decreasing trend, ATC will instruct the preparation of Low Visibility Operation Procedures.

4.3.2.2 当机场能见度降至 800m、或跑道视程降至 550m 或云高降至 60m 时，西南空管局管制中心将发布开始实施低能见度运行程序的指令；

4.3.2.2 When VIS descend to 800m or RVR descend to 550m or ceiling descend to 60m, ATC will instruct the implementation of Low Visibility Operation Procedures.

|                                                                                     |                                                                                                                                                                                                                                              |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4.3.2.3 当机场跑道视程达到 550m 且云高达到 60m 并呈上升趋势时,西南空管局管制中心将发布结束低能见度运行程序的指令。                 | 4.3.2.3 When RVR $\geq$ 550m and ceiling $\geq$ 60m and forecast shows a increasing trend, ATC will instruct the termination of Low Visibility Operation Procedures.                                                                         |
| 4.3.2.4 当天气状况满足任一条跑道实施低能见度运行程序条件时,西南空管局管制中心可决定该条跑道实施低能见度起飞、CAT II 类或 HUD 特殊 II 类运行。 | 4.3.2.4 When weather condition is satisfied for any one of RWYs to implement Low Visibility Operation Procedure, the implementation of low visibility take-off or CAT II or HUD Special CAT II operation shall follow ATC instructions.      |
| 4.3.3 航空器引导                                                                         | 4.3.3 Aircraft guidance                                                                                                                                                                                                                      |
| 4.3.3.1 双流机场实施低能见度运行程序时,所有进港航空器由引导车引导,出港航空器由机组或管制提出申请后,引导车按需引导。                     | 4.3.3.1 During the implementation of Low Visibility Operation Procedures, arrival aircraft shall be guided by follow-me vehicle; departure aircraft shall be guided if necessary after applying for follow-me vehicle by flight crew or ATC. |
| 4.3.3.2 引导车在引导航空器时行驶速度不超过 20km/h。                                                   | 4.3.3.2 The speed of follow-me vehicle shall not exceed 20km/h in service.                                                                                                                                                                   |
| 4.3.3.3 引导路线局部能见度低于 100m 或者在难以保证安全的情况下,不提供引导服务。                                     | 4.3.3.3 If partial visibility is less than 100m or it's hard to ensure safety along guiding route, guidance U/S.                                                                                                                             |
| 4.3.4 实施低能见度运行程序时的注意事项                                                              | 4.3.4 Notice for implementing Low Visibility Operation Procedure                                                                                                                                                                             |
| 4.3.4.1 禁止出港航空器经 A2 滑 (02L/20R 跑道与 A 滑之间)、E2 或 E8 进入跑道直接起飞。                         | 4.3.4.1 Departure aircraft is forbidden to enter RWY to take off via TWY A2(BTN RWY 02L/20R TWY A), E2 or E8.                                                                                                                                |
| 4.3.4.2 注意观察停止排灯。                                                                   | 4.3.4.2 Pay attention to stop bars.                                                                                                                                                                                                          |
| 5. 直升机飞行限制,直升机停靠区                                                                   | 5. Helicopter operation restrictions and helicopter parking/docking area                                                                                                                                                                     |
| 无                                                                                   | Nil                                                                                                                                                                                                                                          |
| 6. 警告                                                                               | 6. Warning                                                                                                                                                                                                                                   |

激光设备发出绿色光束，夜间光束醒目，不穿越跑道，提醒机组注意。

Laser bird dispersal equipments transmitting green light, flight crew should pay exercise caution while taking off and landing.

## ZUUU AD 2.21 减噪程序

### 1 噪音限制规定

1.1 航空器起飞减噪操作程序，用于起飞爬升阶段，在确保飞行安全的前提下，尽量减少噪音对地面的影响。

1.2 在保证安全超障和飞行程序最低爬升梯度的条件下，要求所有飞行员执行以下减噪飞行操作程序，由于非管制原因不执行减噪飞行操作程序，飞行员须在起飞前告知空管并说明理由(校验飞行等特殊飞行除外)。

### 2 减噪程序

2.1 在航空器起飞性能允许情况下，尽可能使用减推力起飞。

2.2 在到达场压高 1500ft 时，起始爬升速度  $V_2+20\text{km/h}(10\text{kt})$ ，开始减功率/推力，减小机身角/俯仰角，保持可靠上升率和起飞襟翼/缝翼继续爬升。

2.3 保持减功率/推力和可靠的上升率，场压高 3000ft 以上时，平稳加速至航路爬升速度，按规定收襟翼/缝翼。

## ZUUU AD 2.21 Noise abatement procedures

### 1 Noise restrictions

1.1 Noise abatement departure procedure is used while climbing. Under condition of insuring flight safety, reduce the impact of noise on ground.

1.2 Under condition of complying with the requirements of obstacle clearance and climb gradient required by flight procedure, the following noise abatement procedures shall be implemented by pilots. If the procedures can not be implemented due to any reason except ATC, pilot shall inform the controller with a reasonable explanation (except for flight check and other special flight ).

### 2 Noise abatement procedures

2.1 Use the reduced thrust to take off if aircraft performance permits.

2.2 At flight height of 1500ft (QFE), with a climb speed of  $V_2$  plus 20km/h(10kt), reduce engine power/thrust and angle of fuselage/pitch, maintain a positive rate of climb and flaps/slats in the take-off configuration.

2.3 Maintain reduced engine power/thrust and positive rate of climb. While flight height is more than 3000ft (QFE), accelerate smoothly to en-route climb speed and retract flaps/slats on schedule.



**ZUUU AD 2.22 飞行政程序****1. 总则**

使用 02L/20R 号跑道进近时，未经 ATC 许可禁止偏向五边西侧；使用 02L 跑道离场时，未经 ATC 许可禁止偏向一边西侧。

**2. 起落航线**

通常，起落航线在跑道两侧均可，高度为修正海压 1200m。

**3. 仪表飞行政序**

3.1 严格按照航图中公布的进、离场程序飞行。如果需要，航空器可在空中交通管制部门指定的航路、导航台或定位点上空等待或做机动飞行。

3.2 前往双流机场落地的航空器，除 ATC 有特殊要求外，飞行员应严格执行程序图公布的速度。如机组因机型性能等原因不能执行此速度限制时，应提前报告 ATC。为保证运行效率，ATC 将对未提前报告不能执行公布速度的航空器重新安排落地次序。

**4. 雷达程序和/或 ADS-B 程序**

4.1 成都进近管制区域内实施雷达管制。航空器最小水平间隔为 5.6km，最小垂直间隔为 300m。

**ZUUU AD 2.22 Flight procedures****1. General**

When approaching to RWY02L/RWY20R, deviation to the west of the final approach course is forbidden without ATC permission; when departing from RWY02L, deviation to the west of the up wind course is forbidden without ATC permission.

**2. Traffic circuits**

Usually, traffic circuits can be made to both sides of RWY, at the altitude 1200m (QNH) .

**3. IFR flight procedures**

3.1 Strict adherence is required to the relevant arrival/departure procedures published in the aeronautical charts. Aircraft may, if necessary, hold or maneuver on an airway, over a navigation facility or a fix designated by ATC.

3.2 Aircraft landing at Shuangliu airport shall abide by the rules about the IAS limitation except special limitation required by ATC. If flight crew can not implement the speed limitations due to aircraft performance, flight crew shall inform ATC in advance, otherwise, ATC will rearrange landing sequence.

**4. Radar procedures and/or ADS-B procedures**

4.1 Radar control within Chengdu APP has been implemented. The minimum horizontal radar separation is 5.6km, the minimum vertical radar separation is 300m.

4.2 在最后进近航段距跑道末端 18.5km (10NM) 范围内, 满足尾流间隔标准的前提下 ATC 可向两架跟进落地的航空器提供 5km 的最小雷达间隔。

4.2 Within 18.5km(10NM) from approaching RWY END, under the standard of wake intervals, minimum radar separation between two following approaching aircrafts can be reduced to 5km by ATC.

#### 4.3 最低监视引导高度扇区

#### 4.3 Surveillance Minimum Altitude Sectors

|                                                                                                                                                                                 |                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| Sector 1                                                                                                                                                                        | ALT limit: 4150m or above |
| N313119E1041418-N313647E1040556-N314459E1041238-N314528E1041623-N313119E1041418                                                                                                 |                           |
| Sector 2                                                                                                                                                                        | ALT limit: 3150m or above |
| N311637E1041227-N312822E1041846-N313119E1041418-N311550E1035554-N311637E1041227                                                                                                 |                           |
| Sector 3                                                                                                                                                                        | ALT limit: 3600m or above |
| N314528E1041623-N314557E1042002-N313208E1042048-N312822E1041846-N313119E1041418-N314528E1041623                                                                                 |                           |
| Sector 4                                                                                                                                                                        | ALT limit: 3150m or above |
| N314557E1042002-N313208E1042048-N314712E1044817-N314648E1043818-N314604E1042059-N314557E1042002                                                                                 |                           |
| Sector 5                                                                                                                                                                        | ALT limit: 2000m or above |
| N311637E1041227-N312822E1041846-N313208E1042048-N314712E1044817-N314739E1045941-N313641E1044255-N311637E1041227                                                                 |                           |
| Sector 6                                                                                                                                                                        | ALT limit: 1550m or above |
| N314739E1045941-N313641E1044255-N312924E1051058-N312932E1051602-N314112E1051218-N314803E1051006-N314739E1045941                                                                 |                           |
| Sector 7                                                                                                                                                                        | ALT limit: 1200m or above |
| N311637E1041227-N313641E1044255-N312924E1051058-N312932E1051602-N312518E1051723-N311360E1052126-N310317E1052507-N305852E1044356-N310660E1043919-N310713E1042233-N311637E1041227 |                           |
| Sector 8                                                                                                                                                                        | ALT limit: 1150m or above |

|                                                                                                                                                                                                                                                 |                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| N304242E1040723-N304259E1040322-N303931E1040144-N303751E1040233-N303612E1040409-N304242E1040723                                                                                                                                                 |                           |
| Sector 9                                                                                                                                                                                                                                        | ALT limit: 1300m or above |
| N303744E1041336-N304030E1041104-N304242E1040723-N303612E1040409-N303331E1040646-N303202E1041045-N303744E1041336                                                                                                                                 |                           |
| Sector 10                                                                                                                                                                                                                                       | ALT limit: 1400m or above |
| N305852E1044356-N310660E1043919-N310713E1042233-N305512E1042223-N303744E1041336-N303202E1041045-N302821E1040856-N302458E1042242-N302830E1042534-N304311E1043804-N305852E1044356                                                                 |                           |
| Sector 11                                                                                                                                                                                                                                       | ALT limit: 1100m or above |
| N303202E1041045-N303331E1040646-N303612E1040409-N303751E1040233-N303931E1040144-N302414E1035618-N302252E1035958-N302620E1035912-N302752E1035950-N302904E1040121-N303005E1040418-N302821E1040856-N303202E1041045                                 |                           |
| Sector 12                                                                                                                                                                                                                                       | ALT limit: 1350m or above |
| N302821E1040856-N302055E1040515-N300338E1035645-N300038E1040440-N300427E1040942-N301357E1041543-N302458E1042242-N302821E1040856                                                                                                                 |                           |
| Sector 13                                                                                                                                                                                                                                       | ALT limit: 1300m or above |
| N302055E1040515-N302821E1040856-N303005E1040418-N302904E1040121-N302752E1035950-N302620E1035912-N302252E1035958-N302055E1040515                                                                                                                 |                           |
| Sector 14                                                                                                                                                                                                                                       | ALT limit: 1000m or above |
| N310317E1052507-N305852E1044356-N304311E1043804-N302830E1042534-N302458E1042242-N301357E1041543-N300551E1041036-N300017E1041237-N295307E1041945-N295231E1042021-N295011E1050712-N302949E1051847-N303841E1052157-N305035E1052511-N310317E1052507 |                           |
| Sector 15                                                                                                                                                                                                                                       | ALT limit: 1300m or above |
| N295218E1042458-N294127E1041819-N293722E1041205-N291614E1041238-N291619E1041543-N291835E1043601-N292003E1045127-N292034E1045808-N293012E1050125-N295011E1050712-N295218E1042458                                                                 |                           |
| Sector 16                                                                                                                                                                                                                                       | ALT limit: 1150m or above |
| N292323E1040160-N293102E1035542-N293711E1035039-N293923E1034851-N295812E1033318-N295945E10                                                                                                                                                      |                           |

|                                                                                                                                                                                                                                                                                                 |                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| 33160-N300017E1033302-N300311E1033850-N300648E1034057-N301050E1034139-N301559E1034236-N300338E1035645-N300038E1040440-N300427E1040942-N300551E1041036-N300017E1041237-N295307E1041945-N295231E1042021-N295218E1042458-N294127E1041819-N293722E1041205-N291614E1041238-N292323E1040160           |                           |
| Sector 17                                                                                                                                                                                                                                                                                       | ALT limit: 1050m or above |
| N311637E1041227-N310929E1040539-N310130E1035910-N303845E1034107-N302042E1033333-N301559E1034236-N300338E1035645-N302055E1040515-N302252E1035958-N302414E1035618-N303931E1040144-N304259E1040322-N304242E1040723-N304030E1041104-N303744E1041336-N305512E1042223-N310713E1042235-N311637E1041227 |                           |
| Sector 18                                                                                                                                                                                                                                                                                       | ALT limit: 1250m or above |
| N301752E1033222-N301413E1033816-N301050E1034139-N301559E1034236-N302042E1033333-N301752E1033222                                                                                                                                                                                                 |                           |
| Sector 19                                                                                                                                                                                                                                                                                       | ALT limit: 1350m or above |
| N300017E1033302-N300311E1033850-N300648E1034057-N301050E1034139-N301413E1033816-N301752E1033222-N300741E1032807-N300017E1033302                                                                                                                                                                 |                           |
| Sector 20                                                                                                                                                                                                                                                                                       | ALT limit: 1600m or above |
| N310130E1035910-N303845E1034107-N303103E1033753-N302042E1033333-N301752E1033222-N300741E1032807-N300017E1033302-N295945E1033160-N301534E1031840-N305756E1034702-N310130E1035910                                                                                                                 |                           |
| Sector 21                                                                                                                                                                                                                                                                                       | ALT limit: 2100m or above |
| N305520E1033806-N305756E1034702-N301534E1031840-N301941E1031512-N302444E1031801-N303636E1032723-N304604E1033343-N305520E1033806                                                                                                                                                                 |                           |
| Sector22                                                                                                                                                                                                                                                                                        | ALT limit: 6000m or above |
| N304841E1031121-N303339E1030325-N303631E1030060-N304822E1030101-N304841E1031121                                                                                                                                                                                                                 |                           |
| Sector 23                                                                                                                                                                                                                                                                                       | ALT limit: 4800m or above |
| N304860E1032225-N302708E1030856-N303339E1030325-N304841E1031121-N304860E1032225                                                                                                                                                                                                                 |                           |
| Sector 24                                                                                                                                                                                                                                                                                       | ALT limit: 3550m or above |
| N304860E1032225-N302708E1030856-N302529E1031019-N304031E1032443-N305149E1032938-N304908E103                                                                                                                                                                                                     |                           |

|                                                                                                                                                                 |                           |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|
| 32729-N304860E1032225                                                                                                                                           |                           |
| Sector 25                                                                                                                                                       | ALT limit: 2850m or above |
| N301941E1031512-N302320E1031208-N302916E1031812-N305451E1033631-N305520E1033806-N304604E103343-N303636E1032723-N302444E1031801-N301941E1031512                  |                           |
| Sector 26                                                                                                                                                       | ALT limit: 3250m or above |
| N305149E1032938-N305949E1033603-N310000E1033660-N310115E1034044-N305451E1033631-N302916E1031812-N302320E1031208-N302529E1031019-N304031E1032443-N305149E1032938 |                           |
| Sector 27                                                                                                                                                       | ALT limit: 2650m or above |
| N310115E1034044-N310929E1040539-N310130E1035910-N305756E1034702-N305520E1033806-N305451E1033631-N310115E1034044                                                 |                           |
| Sector 28                                                                                                                                                       | ALT limit: 4800m or above |
| N311550E1035554-N310000E1033660-N305949E1033603-N311537E1034845-N311550E1035554                                                                                 |                           |
| Sector 29                                                                                                                                                       | ALT limit: 5500m or above |
| N311550E1035554-N313119E1041418-N313647E1040556-N311537E1034845-N311550E1035554                                                                                 |                           |
| Sector 30                                                                                                                                                       | ALT limit: 3100m or above |
| N310929E1040539-N310115E1034044-N310000E1033660-N311550E1035554-N311637E1041227-N310929E1040539                                                                 |                           |

**5. 无线电通信失效程序**

参见 AIP GEN3.4.5 中的仪表飞行规则航空器地空双向无线电通信失效通用程序。

**5. Radio communication failure procedures**

Refer to AIP GEN3.4.5 general procedures for aircraft under instrument flight rule with air-ground two-way radio communication failure.

**6. 目视飞程序**

无

**6. Procedures for VFR flights**

Nil

**7. 目视飞行航线**

无

**7. VFR route**

Nil

8. 其它规定

无

8. Other regulations

Nil

ZUUU AD 2.23 其它资料

鸟情资料

双流机场处四川盆地西缘-横断山区过渡带，属于国内西线鸟类迁徙通道，也是世界鸟类九大迁徙路线之一的东亚—澳大利西亚鸟类迁徙路线。全年鸟类活动频繁，尤其在每年3-5月、9-11月的春、秋季迁徙期，本场及周边有大量迁徙鸟和候鸟活动。3-5月春季迁徙期，夏候鸟和迁徙鸟类沿岷江、沱江河谷及凉山山系由南向北进入盆地，再沿成都平原向北部或西北部进入高原或高纬度地区；9-11月冬候鸟和迁徙鸟类陆续从西北和北部地区由北向南进入成都平原，途经龙门山山脉，一支经龙泉山向东南迁徙，一支经成都平原、凉山山系向南迁徙。

ZUUU AD 2.23 Other information

Bird's information

Shuangliu International Airport is located in the transition zone between the western edge of the Sichuan Basin and the Hengduan Mountains. It lies along the western bird migration route in China and is part of the East Asian–Australasian Flyway, one of the world's nine major bird migration routes. Bird activity is frequent throughout the year, especially during the spring and autumn migration periods from March to May and September to November, when a large number of migratory birds are active at and around the airport. During the spring migration period(March–May), summer residents enter the basin from the south along the Minjiang and Tuojiang River Valleys and the Liangshan Mountain Range, then proceed northward or northwestward across the Chengdu Plain into plateaus or high-latitude regions. During the autumn migration period(September–November), winter residents successively enter the Chengdu Plain from the northwest and north areas via the Longmen Mountains: one branch migrates southeastward via the Longquan Mountains,

and the other migrates southward via the Chengdu Plain  
and the Liangshan Mountain Range.

| Major Species |                       | Residential Type                    | Time of major activity             | Major Area                               | Major Activity Altitude | Max Migration/Flight Altitude |
|---------------|-----------------------|-------------------------------------|------------------------------------|------------------------------------------|-------------------------|-------------------------------|
| Charadriidae  | Kentish Plover        | Winter residents,some are residents | September to next May              | The whole airport                        | 0-100 m                 | 500 m                         |
|               | Pacific Golden Plover | Winter residents,some are residents | March to May、September to November | The whole airport                        | 0-100 m                 |                               |
|               | Grey Plover           | Traveler                            | March to May、September to November | The whole airport                        | 0-100 m                 | 1000 m                        |
|               | Northern Lapwing      | Winter resident                     | September to next May              | North end of Runway 02R/20L, Taxiway MN  | 0-100 m                 |                               |
|               | Grey-headed Lapwing   | Traveler                            | March to May、September to November | West end of Runway 02L/20R ,north end of | 0-100 m                 |                               |

|              |                          |                         |                             |                                   |         |        |
|--------------|--------------------------|-------------------------|-----------------------------|-----------------------------------|---------|--------|
|              |                          |                         |                             | Runway<br>02R/20L                 |         |        |
| Accipitridae | Eurasian<br>Sparrowhawk  | Winter<br>resident      | September<br>to next<br>May | Whole airport                     | 0-500 m | 1500 m |
|              | Eastern<br>Buzzard       |                         |                             |                                   |         |        |
|              | Mountain<br>Hawk-Eagle   | Resident                | Whole year                  | North end of<br>Runway<br>02R/20L |         |        |
| Falconidae   | Common<br>Kestrel        | Winter<br>resident      | September to<br>next May    | Whole airport                     |         |        |
| Tytonidae    | Eastern<br>Grass Owl     | Resident                | Whole year                  | Whole airport                     | 0-500 m | 1500 m |
| Strigidae    | Oriental<br>Scops Owl    | Resident                | Whole year                  |                                   |         |        |
|              | Asian<br>Barred<br>Owlet | Resident                | Whole year                  |                                   |         |        |
|              | Long-eared<br>Owl        | Winter<br>resident      | September<br>to next<br>May |                                   |         |        |
|              | Short-eared<br>Owl       | Winter<br>resident      | September<br>to next<br>May |                                   |         |        |
| Ardeidae     | Little<br>Egret          | Summer<br>residents,som | Mainly from<br>March to     | Whole<br>airport,                 | 0-500 m | 1000 m |



|              |                                     |                                  |                                                                                |                                                                                                                                                              |         |        |
|--------------|-------------------------------------|----------------------------------|--------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|--------|
|              |                                     | e are<br>residents               | November,<br>some<br>residents are<br>found<br>throughout<br>the whole<br>year | with higher<br>concentration<br>s at west side,<br>south end and<br>north end of<br>Runway<br>02L/20R,<br>north end and<br>south end of<br>Runway<br>02R/20L |         |        |
|              | Chinese<br>Pond<br>Heron            | Summer<br>resident               | March to<br>November(at<br>night)                                              |                                                                                                                                                              |         |        |
|              | Eastern<br>Cattle<br>Egret          |                                  |                                                                                |                                                                                                                                                              |         |        |
|              | Cinnamon<br>Bittern                 |                                  |                                                                                |                                                                                                                                                              |         |        |
|              | Yellow<br>Bittern                   |                                  |                                                                                |                                                                                                                                                              |         |        |
|              | Black-crowne<br>d<br>Night<br>Heron |                                  |                                                                                |                                                                                                                                                              |         |        |
| Anatidae     | Mallard                             | Winter<br>resident               | September<br>to next<br>May                                                    | North<br>end,south end<br>and east side<br>of Runway<br>02R/20L,nort<br>h end and<br>south end of<br>Runway<br>02L/20R                                       | 0-500 m | 1000 m |
|              | Eurasian<br>Teal                    |                                  |                                                                                |                                                                                                                                                              |         |        |
| Hirundinidae | Barn<br>Swallow                     | Summer<br>residents,<br>some are | Mainly from<br>March to<br>November,                                           | South end,<br>west side and<br>north end                                                                                                                     | 0-200 m | 1000 m |

|                       |                            |                    |                                              |                                                |         |        |
|-----------------------|----------------------------|--------------------|----------------------------------------------|------------------------------------------------|---------|--------|
|                       |                            | residents          | some                                         | of Runway                                      |         |        |
|                       | Sand                       | Summer<br>resident | residents                                    | 02L/20R,                                       |         |        |
|                       | Martin                     |                    | are found                                    | Taxiway MN,                                    |         |        |
|                       | Red-rumped<br>Swallow      |                    | throughout<br>the whole<br>year              | south and<br>north end of<br>Runway<br>02R/20L |         |        |
| Apodidae              | House<br>Swift             |                    |                                              |                                                |         |        |
|                       | Pacific<br>Swift           |                    |                                              |                                                |         |        |
| Glareolidae           | Oriental<br>Pratincole     | Traveler           | March to<br>May,<br>September to<br>November | Whole airport                                  | 0-100 m | 1000 m |
| Vespertilioni-<br>dae | Harlequin Bat              | -                  | March to<br>November                         | Whole airport                                  | 0-200 m | 1500 m |
|                       | Chinese<br>Noctule         |                    |                                              |                                                |         |        |
|                       | Japanese<br>Pipistrelle    |                    |                                              |                                                |         |        |
|                       | Pipistrellus<br>pulveratus |                    |                                              |                                                |         |        |
|                       | Pipistrellus<br>abramus    |                    |                                              |                                                |         |        |
| Columbidae            | Spotted<br>Dove            | Resident           | Whole year                                   |                                                |         |        |
|                       | Oriental<br>Turtle<br>Dove | Resident           | March to<br>November                         | Whole airport                                  | 0-100 m | 300 m  |

|              |                             |                    |                                              |                                                                                                                 |         |        |
|--------------|-----------------------------|--------------------|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------|---------|--------|
|              | Red<br>Collared<br>Dove     | Traveler           | March to<br>May、<br>September to<br>November |                                                                                                                 |         | 500 m  |
|              | Rock<br>Dove                | -                  | Whole year                                   | Whole<br>airport, with<br>higher<br>concentration<br>s at north<br>end and<br>west side of<br>Runway<br>02L/20R |         | 300 m  |
| Passeridae   | Eurasian<br>Tree<br>Sparrow | Resident           | Whole year                                   | Whole airport                                                                                                   | 0-100 m | 200 m  |
| Fringillidae | Grey-capped<br>Greenfinch   | Resident           | Whole year                                   | Whole<br>airport, with<br>higher<br>concentration<br>s at east side<br>of Runway<br>02R/20L                     | 0-100 m | 200 m  |
| Alaudidae    | Eurasian<br>Skylark         | Winter<br>resident | September to<br>next May                     | Whole airport                                                                                                   | 0-100 m | 1000 m |
|              | Oriental<br>Skylark         | Resident           | Whole year                                   |                                                                                                                 |         |        |

|               |                          |                    |                                              |               |         |       |
|---------------|--------------------------|--------------------|----------------------------------------------|---------------|---------|-------|
| Emberizidae   | Little<br>Bunting        | Resident           | Whole year                                   | Whole airport | 0-100 m | 500 m |
| Motacillidae  | Grey<br>Wagtail          | Resident           | Whole year                                   | Whole airport | 0-100 m | 200 m |
|               | White<br>Wagtail         |                    |                                              |               |         |       |
|               | Rosy<br>Pipit            |                    |                                              |               |         | 500 m |
|               | Paddyfield<br>Pipit      | Winter<br>resident | September to<br>next May                     |               |         | 500 m |
|               | Olive-backed<br>Pipit    |                    |                                              |               |         |       |
|               | Red-throated<br>Pipit    | Traveler           | March to<br>May、<br>September to<br>November |               |         |       |
| Laniidae      | Brown<br>Shrike          | Summer<br>resident | March to<br>November                         | Whole airport | 0-100 m | 500 m |
|               | Long-tailed<br>Shrike    | Resident           | Whole year                                   |               |         | 200 m |
| Upupidae      | Eurasian<br>Hoopoe       | Summer<br>resident | March to<br>November                         | Whole airport | 0-100 m | 200 m |
| Rostratulidae | Greater<br>Painted-snipe | Summer<br>resident | March to<br>November                         | Whole airport | 0-100 m | 200 m |
| Scolopacidae  | Eurasian<br>Woodcock     | Resident           | Whole year                                   | Whole airport | 0-100 m | 500 m |

|              |                        |                 |                                        |                     |         |       |
|--------------|------------------------|-----------------|----------------------------------------|---------------------|---------|-------|
|              | Pin-tailed Snipe       | Traveler        | March to May、<br>September to November |                     |         |       |
|              | Common Snipe           | Traveler        | March to May、<br>September to November |                     |         |       |
| Pycnonotidae | Light-vented Bulbul    | Resident        | Whole year                             | Whole airport       | 0-100 m | 200 m |
|              | Sooty-headed Bulbul    |                 |                                        |                     |         |       |
| Sturnidae    | Crested Myna           | Resident        | Whole year                             | Whole airport       | 0-100 m | 200 m |
|              | Red-billed Starling    | Resident        |                                        | West side of Runway |         | 500 m |
|              | White-cheeked Starling | Winter resident | September to next May                  | 02L/20R, Taxiway MN |         |       |
| Turdidae     | Chinese Blackbird      | Resident        | Whole year                             | Whole airport       | 0-100 m | 200 m |
|              | Blue Whistling Thrush  | Summer resident | March to November                      |                     |         | 500 m |
|              | Dusky Thrush           | Winter resident | September to next May                  |                     |         |       |
|              | Scaly                  | Traveler        | March to                               |                     |         |       |

|              |                      |          |                                              |               |         |       |
|--------------|----------------------|----------|----------------------------------------------|---------------|---------|-------|
|              | Thrush               |          | May、<br>September to<br>November             |               |         |       |
| Cisticolidae | Zitting<br>Cisticola | Resident | Whole year                                   | Whole airport | 0-100 m | 200 m |
| Muscicapidae | Taiga<br>Flycatcher  | Traveler | March to<br>May、<br>September to<br>November | Whole airport | 0-100 m | 500 m |

针对本场鸟类活动情况，机场采取了以下多种措施，保障航空器正常运行：

1. 机场有飞行活动期间，持续开展人员巡视驱赶，并根据鸟情、鸟击变化持续调整巡视重点时间和重点区域；
2. 飞行区内安装布设有全向声波驱鸟器、定向声波驱鸟器、拦鸟网等多种驱鸟设备设施，并持续开展驱鸟设备设施维护保养和动态管理工作，确保驱鸟设备设施完好适用，降低鸟类对设备设施的适应性；
3. 持续清理草坪小动物，定期开展飞行区及周边鸟类巢穴清理，土质区平整碾压，破坏场内野生动物生存、栖息环境，驱赶野生动物离场；

Given the bird activity around the airport, Shuangliu International Airport has taken the following measures to ensure the normal operation of aircraft:

1. During flight operations, continuous patrols are conducted for bird dispersal, with focus times and areas adjusted based on bird activity and bird strike trends.
2. Various bird dispersal devices and facilities are installed in the airfield area, including omnidirectional and directional acoustic bird repellers, and bird nets.Maintenance and dynamic management of these devices are carried out continuously to ensure they remain operational and effective, reducing bird adaptation to the equipment.
3. Continuous removal of small animals from grassy areas, regular clearing of bird nests in the airfield area and surrounding zones, and leveling and compacting of soil areas are implemented as key preventive measures to disrupt wildlife habitats and nesting environments,

4. 开展土面区草坪筛草构建狗牙根草坪，洒布驱鸟剂、除虫剂、筛草剂、鼠药等驱鸟药物开展生态治理，切断本场野生动物食物链，减少野生动物来场活动频次；

5. 根据生态调研情况优化除虫剂配方、调整化学防治措施，保证驱鸟药物使用的有效性。

6. 机场邻近区域已协调地方政府及相关单位开展生态环境治理，组织进行鸟巢排查清理、鸽害调查宣传等生态治理工作。

and drive wildlife away from the airport.

4. Ecological control measures, including turf management in soil areas (through the establishment of Cynodon grass lawns) and the distribution of bird repellents, insecticides, herbicides, and rodenticides, are carried out to disrupt the food chain of wildlife within the airport and reduce the frequency of wildlife activities at the airport.

5. Optimization of insecticide formulations and adjustment of chemical control measures, based on ecological research, are carried out to ensure the effectiveness of bird repellent applications at the airport.

6. Regarding the areas adjacent to the airport, coordination has been conducted with the local government and relevant units to carry out ecological environment inspections and management within their areas. Additionally, airport personnel have been organized to conduct bird nest inspections and clearance, pigeon hazard investigations and publicity.