

**ZWSH AD 2.1 机场地名代码和名称 Aerodrome location indicator(ICAO / IATA) and name**

ZWSH/KHG-喀什/徕宁 KASHI/Laining

**ZWSH AD 2.2 机场地理位置和管理资料 Aerodrome geographical and administrative data**

|   |                                                                                                   |                                                                                                                                                                                                              |
|---|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | 机场基准点坐标及其在机场的位置<br>ARP coordinates and site at AD                                                 | N39°32.7' E076°01.3'<br>Center of RWY                                                                                                                                                                        |
| 2 | 机场基准点与城市的位置关系<br>Direction and distance from city                                                 | 019° GEO, 8.8km from city center                                                                                                                                                                             |
| 3 | 机场标高、基准温度、低温均值<br>ELEV/Reference temperature/Mean low temperature                                 | 1380.0 m/33.6°C(JUL)/-7.9°C(JAN)                                                                                                                                                                             |
| 4 | 机场标高位置的大地水准面波幅<br>Geoid undulation at AD ELEV PSN                                                 |                                                                                                                                                                                                              |
| 5 | 磁差（测量年份）及年变率<br>VAR(Year)/Annual change                                                           | 4°7'E(2021)/-                                                                                                                                                                                                |
| 6 | 机场管理部门、地址、电话、传真、AFS 地址、电子邮箱、网址<br>AD administration/Address/Telephone/Telefax/AFS/ E-mail/Website | Kashi Laining International Airport, Xinjiang Airport (Group) CO. Ltd.<br>Airport Street 473, Kashi Post code:844001<br>TEL:86-998-5856055<br>FAX:86-998-5856049<br>AFS:ZWSHZPZX<br>E-mail:zwshzpzx@sina.com |
| 7 | 允许飞行种类<br>Types of traffic permitted(IFR/VFR)                                                     | IFR-VFR                                                                                                                                                                                                      |
| 8 | 机场性质/飞行区指标<br>Military or civil airport/Reference code                                            | CIVIL/4E                                                                                                                                                                                                     |
| 9 | 备注<br>Remarks                                                                                     | Nil                                                                                                                                                                                                          |

**ZWSH AD 2.3 工作时间 Operational hours**

|   |                                   |     |
|---|-----------------------------------|-----|
| 1 | 机场开放时间<br>AD Operational hours    | H24 |
| 2 | 海关和移民<br>Customs and immigration  | HO  |
| 3 | 卫生健康部门<br>Health and sanitation   | H24 |
| 4 | 航空情报服务讲解室<br>AIS Briefing Office  | H24 |
| 5 | 空中交通服务报告室<br>ATS Reporting Office | H24 |

|    |                                |     |
|----|--------------------------------|-----|
| 6  | 气象服务讲解室<br>MET Briefing Office | H24 |
| 7  | 空中交通服务<br>Air Traffic Service  | H24 |
| 8  | 加油服务<br>Fuelling               | H24 |
| 9  | 地勤服务<br>Handling               | H24 |
| 10 | 安保服务<br>Security               | H24 |
| 11 | 除冰服务<br>De-icing               | H24 |
| 12 | 备注<br>Remarks                  | Nil |

**ZWSH AD 2.4 地勤服务和设施 Handling services and facilities**

|   |                                                       |                                                                                                                                                                                                                                                                                                                                        |
|---|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | 货物装卸设施<br>Cargo-handling facilities                   | Baggage transporter, fork(3.5t), dolly(14t), luggage towing vehicle, baggage trailer vehicle                                                                                                                                                                                                                                           |
| 2 | 燃油牌号<br>Fuel types                                    | Jet A-1                                                                                                                                                                                                                                                                                                                                |
| 3 | 滑油牌号<br>Oil types                                     | Nil                                                                                                                                                                                                                                                                                                                                    |
| 4 | 加油设施/能力<br>Fuelling facilities & Capacity             | Refueling trucks(45000L, 35000L, 20000L): 17L/s                                                                                                                                                                                                                                                                                        |
| 5 | 除冰设施<br>De-icing facilities                           | 3 De-icers; deicing fluid: FCY-1Bio+; anti-icing fluid: FCY9311; de-icing apron(Stands Nr. 214, 216)                                                                                                                                                                                                                                   |
| 6 | 过站航空器机库<br>Hangar space for visiting aircraft         | Nil                                                                                                                                                                                                                                                                                                                                    |
| 7 | 过站航空器的维修设施<br>Repair facilities for visiting aircraft | Line maintenance available for B737-700/800, A319/320/321.<br>General maintenance.                                                                                                                                                                                                                                                     |
| 8 | 备注<br>Remarks                                         | Towing vehicle, power supply unit, air supply unit, water vehicle, sewage disposal vehicle, aircraft-warming machine, tow-bar(for B737-700/800, B757-200, A319/320/321, B747, B767, B777, B787, A330/340, IL76, EMB190, CRJ900, C919, ARJ21-700), passenger stairs, bridge power supply equipment and air conditioner(Stands Nr.01-11) |

**ZWSH AD 2.5 旅客设施 Passenger facilities**

|   |                   |                       |
|---|-------------------|-----------------------|
| 1 | 宾馆<br>Hotels      | At AD and in the city |
| 2 | 餐饮<br>Restaurants | At AD and in the city |

|   |                               |                                        |
|---|-------------------------------|----------------------------------------|
| 3 | 交通工具<br>Transportation        | Buses, airport buses, taxis            |
| 4 | 医疗设施<br>Medical facilities    | First aid at AD, hospitals in the city |
| 5 | 银行和邮局<br>Bank and Post Office | In the city                            |
| 6 | 旅行社<br>Tourist Office         | In the city                            |
| 7 | 备注<br>Remarks                 | Nil                                    |

**ZWSH AD 2.6 援救与消防服务 Rescue and fire fighting services**

|   |                                                           |                                                                                                                                                                                                                                                                                                                                     |
|---|-----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | 机场消防等级<br>AD category for fire fighting                   | CAT 9                                                                                                                                                                                                                                                                                                                               |
| 2 | 援救设备<br>Rescue equipment                                  | Fire fighting facilities: rapid intervention vehicle, primary foam tender, heavy-load foam tender, illumination truck, rescue vehicle, command car, logistics truck;<br>Rescue equipment: lifesaving air-cushion, hydraulic spreader, hydraulic cutting pliers, hydraulic jack, toothless cutter, smoke exhaust pressurization fan. |
| 3 | 搬移受损航空器的能力<br>Capability for removal of disabled aircraft | MTWA up to B747-400 and equal<br>Removal EQPT: mobile surface operation devices, undercarriage rack, rubber crosstie, lifting EQPT, tractor, uplift air cushion.                                                                                                                                                                    |
| 4 | 备注<br>Remarks                                             | Crane can be callable                                                                                                                                                                                                                                                                                                               |

**ZWSH AD 2.7 可用季节- 扫雪 Seasonal availability-clearing**

|   |                                                                  |                                                                               |
|---|------------------------------------------------------------------|-------------------------------------------------------------------------------|
| 1 | 可用季节及扫雪设备类型<br>Seasonal availability/Types of clearing equipment | All seasons<br>Multifunctional removal vehicle, snow blower, snow fluid truck |
| 2 | 扫雪顺序<br>Clearance priorities                                     | RWY, TWY, Apron                                                               |
| 3 | 备注<br>Remarks                                                    | Nil                                                                           |

**ZWSH AD 2.8 停机坪、滑行道及校正位置数据 Aprons, taxiways and check locations data**

|   |                                        |                |                                                                           |
|---|----------------------------------------|----------------|---------------------------------------------------------------------------|
| 1 | 停机坪道面和强度<br>Apron surface and strength | 道面<br>Surface  | CONC                                                                      |
|   |                                        | 强度<br>Strength | PCR 750/R/A/W/T : Stands Nr. 07-11<br>PCR 730/R/A/W/T : Stands Nr. 01, 02 |

|   |                                                    |                |                                                                                                                                      |
|---|----------------------------------------------------|----------------|--------------------------------------------------------------------------------------------------------------------------------------|
|   |                                                    |                | PCR 710/R/A/W/T : Stands Nr. 201-213, 215, 214, 216<br>PCR 680/R/A/W/T : Stands Nr. 301, 302<br>PCR 330/R/A/W/T : Stands Nr. 03-06   |
| 2 | 滑行道宽度、道面和强度<br>Taxiway width, surface and strength | 宽度<br>Width    | 38m : B1-B3, B5<br>30m : A3, A7, A8, B4<br>26.5m : A1<br>23m : A, H, T                                                               |
|   |                                                    | 道面<br>Surface  | CONC                                                                                                                                 |
|   |                                                    | 强度<br>Strength | PCR 840/R/A/W/T : T<br>PCR 800/R/A/W/T : A1, A3, A7<br>PCR 780/R/A/W/T : B4<br>PCR 730/R/A/W/T : A, B1-B3, B5<br>PCR 710/R/A/W/T : H |
| 3 | 高度表校正点的位置及其标高<br>ACL location and elevation        | Nil            |                                                                                                                                      |
| 4 | VOR 校正点<br>VOR checkpoints                         | Nil            |                                                                                                                                      |
| 5 | INS 校正点<br>INS checkpoints                         | Nil            |                                                                                                                                      |
| 6 | 备注<br>Remarks                                      | A8: TWY U/S    |                                                                                                                                      |

### ZWSH AD 2.9 地面活动引导和管制系统与标识

#### Surface movement guidance and control system and markings

|   |                                                                                                                                                     |                                                                                                                                                                                                                                      |                                                                                                                |
|---|-----------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| 1 | 航空器机位号码标记牌、滑行道引导线、航空器目视停靠引导系统的使用<br>Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands | Taxiing guidance signs at all intersections of TWY and RWY.<br>Aircraft stand identification sign boards at all stands.<br>Guide lines at all TWYs.<br>Guide lines at all aprons.<br>Marshalling assistance for all aircraft stands. |                                                                                                                |
| 2 | 跑道和滑行道标志及灯光<br>RWY and TWY marking and LGT                                                                                                          | 跑道标志<br>RWY markings                                                                                                                                                                                                                 | THR, RWY designation, edge line, RWY center line, TDZ, aiming point, Center circle                             |
|   |                                                                                                                                                     | 跑道灯光<br>RWY lights                                                                                                                                                                                                                   | RTHL, WBAR, REDL, RCLL, RENL                                                                                   |
|   |                                                                                                                                                     | 滑行道标志<br>TWY markings                                                                                                                                                                                                                | Edge line, center line, No-entry(A3), RWY holding position, intermediate holding position, runway turn pad(26) |
|   |                                                                                                                                                     | 滑行道灯光<br>TWY lights                                                                                                                                                                                                                  | Edge line lights, center line lights , intermediate holding position lights                                    |

|   |                                                 |                                                                                                                                                          |
|---|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| 3 | 停止排灯和跑道警戒灯<br>Stop bars and runway guard lights | Stop bar lights: CAT II, located on TWYs A7, H at 97m FM RCL<br>Runway guard lights: Located on TWYs A1, A7, A8, H at both sides of RWY holding position |
| 4 | 其它跑道保护措施<br>Other runway protection measures    | Nil                                                                                                                                                      |
| 5 | 备注<br>Remarks                                   | BLUE apron edge line lights                                                                                                                              |

**ZWSH AD 2.10 机场障碍物 Aerodrome obstacles**

半径 15 千米内主要障碍物 (相对 08/26 跑道中心)

Obstacles within 15km of the center of RWY08/26

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| 1                                           | 2                         | 3                                                                        | 4                                           | 5                                                                       | 6                                                                                    |
| BLDG<br>001                                 | BLDG                      | 074/1324                                                                 | 1378.4                                      |                                                                         |                                                                                      |
| BLDG<br>002                                 | BLDG                      | 118/2628                                                                 | 1439.7                                      | Light:RED                                                               |                                                                                      |
| BLDG<br>003                                 | BLDG                      | 119/4159                                                                 | 1430.6                                      | Light:RED                                                               |                                                                                      |
| Antenna<br>004                              | Antenna                   | 160/1447                                                                 | 1421.6                                      | Light:RED                                                               |                                                                                      |
| BLDG<br>005                                 | BLDG                      | 226/2234                                                                 | 1436.2                                      | Light:RED                                                               |                                                                                      |
| MT<br>006                                   | MT                        | 267/4400                                                                 | 1396                                        |                                                                         | RWY08 VSS                                                                            |
| TRANSMISSION<br>_LINE<br>007                | TRANSMISSION_LINE         | 273/3605                                                                 | 1421.9                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>008                | TRANSMISSION_LINE         | 273/3639                                                                 | 1421.9                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>009                | TRANSMISSION_LINE         | 275/3617                                                                 | 1426.4                                      | Light:RED                                                               |                                                                                      |
| MT<br>010                                   | MT                        | 275/7562                                                                 | 1492                                        |                                                                         |                                                                                      |

半径 15 千米内主要障碍物 (相对 08/26 跑道中心)

Obstacles within 15km of the center of RWY08/26

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类<br>型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|-------------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| TRANSMISSION<br>_LINE<br>011                | TRANSM<br>SSION_L<br>INE      | 276/2998                                                                 | 1422.0                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>012                | TRANSM<br>SSION_L<br>INE      | 276/3139                                                                 | 1423.9                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>013                | TRANSM<br>SSION_L<br>INE      | 276/3144                                                                 | 1424.1                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>014                | TRANSM<br>SSION_L<br>INE      | 276/3300                                                                 | 1424.4                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>015                | TRANSM<br>SSION_L<br>INE      | 276/3402                                                                 | 1423.5                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>016                | TRANSM<br>SSION_L<br>INE      | 276/3447                                                                 | 1426.7                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>017                | TRANSM<br>SSION_L<br>INE      | 276/3653                                                                 | 1428.0                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>018                | TRANSM<br>SSION_L<br>INE      | 277/2873                                                                 | 1422.7                                      | Light:RED                                                               |                                                                                      |
| NATURAL_HIG<br>HPOINT<br>019                | NATURA<br>L_HIGHP<br>OINT     | 278/2762                                                                 | 1400                                        |                                                                         |                                                                                      |
| Antenna<br>020                              | Antenna                       | 279/1973                                                                 | 1421.1                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>021                | TRANSM<br>SSION_L<br>INE      | 279/2832                                                                 | 1421.2                                      | Light:RED                                                               |                                                                                      |

半径 15 千米内主要障碍物 (相对 08/26 跑道中心)

Obstacles within 15km of the center of RWY08/26

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| TRANSMISSION<br>_LINE<br>022                | TRANSMISSION<br>_LINE     | 283/2898                                                                 | 1429.7                                      | Light:RED                                                               |                                                                                      |
| Antenna<br>023                              | Antenna                   | 285/2651                                                                 | 1434.9                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>024                | TRANSMISSION<br>_LINE     | 285/2931                                                                 | 1432.2                                      | Light:RED                                                               |                                                                                      |
| MT<br>025                                   | MT                        | 286/13600                                                                | 1887                                        |                                                                         |                                                                                      |
| TRANSMISSION<br>_LINE<br>026                | TRANSMISSION<br>_LINE     | 287/3012                                                                 | 1435.2                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>027                | TRANSMISSION<br>_LINE     | 288/3023                                                                 | 1445.2                                      | Light:RED                                                               |                                                                                      |
| Antenna<br>028                              | Antenna                   | 290/1754                                                                 | 1430.1                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>029                | TRANSMISSION<br>_LINE     | 291/2956                                                                 | 1449.0                                      | Light:RED                                                               |                                                                                      |
| MT<br>030                                   | MT                        | 292/11700                                                                | 1829                                        |                                                                         | RWY08 VOR/DME arrival and<br>holding                                                 |
| BLDG<br>031                                 | BLDG                      | 293/5456                                                                 | 1491.8                                      | Light:RED                                                               |                                                                                      |
| MT<br>032                                   | MT                        | 296/3400                                                                 | 1429                                        |                                                                         |                                                                                      |
| MT<br>033                                   | MT                        | 302/8600                                                                 | 1613                                        |                                                                         |                                                                                      |
| BLDG<br>034                                 | BLDG                      | 303/310                                                                  | 1390.7                                      |                                                                         |                                                                                      |

半径 15 千米内主要障碍物 (相对 08/26 跑道中心)

Obstacles within 15km of the center of RWY08/26

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|---------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Pole<br>035                                 | Pole                      | 304/1782                                                                 | 1425.6                                      | Light:RED                                                               |                                                                                      |
| MT<br>036                                   | MT                        | 305/5800                                                                 | 1502                                        |                                                                         |                                                                                      |
| Pole<br>037                                 | Pole                      | 311/1584                                                                 | 1427.1                                      | Light:RED                                                               |                                                                                      |
| TRANSMISSION<br>_LINE<br>038                | TRANSMISSION_LINE         | 312/2697                                                                 | 1447.3                                      | Light:RED                                                               |                                                                                      |
| Antenna<br>039                              | Antenna                   | 317/1222                                                                 | 1424.7                                      | Light:RED                                                               |                                                                                      |
| Antenna<br>040                              | Antenna                   | 318/4906                                                                 | 1520.8                                      | Light:RED                                                               |                                                                                      |
| Antenna<br>041                              | Antenna                   | 320/5118                                                                 | 1508.9                                      | Light:RED                                                               |                                                                                      |
| Pole<br>042                                 | Pole                      | 323/1033                                                                 | 1426.1                                      | Light:RED                                                               |                                                                                      |
| Pole<br>043                                 | Pole                      | 323/1457                                                                 | 1428.3                                      | Light:RED                                                               |                                                                                      |
| Pole<br>044                                 | Pole                      | 324/1506                                                                 | 1428.5                                      | Light:RED                                                               |                                                                                      |
| Pole<br>045                                 | Pole                      | 326/1156                                                                 | 1426.8                                      | Light:RED                                                               |                                                                                      |
| Pole<br>046                                 | Pole                      | 332/963                                                                  | 1424.5                                      | Light:RED                                                               |                                                                                      |
| Pole<br>047                                 | Pole                      | 334/1090                                                                 | 1424.9                                      | Light:RED                                                               |                                                                                      |
| MT<br>048                                   | MT                        | 336/8000                                                                 | 1722                                        |                                                                         | RWY08 VOR/DME arrival                                                                |
| Pole<br>049                                 | Pole                      | 338/1175                                                                 | 1421.2                                      | Light:RED                                                               |                                                                                      |

半径 15 千米内主要障碍物 (相对 08/26 跑道中心)

Obstacles within 15km of the center of RWY08/26

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类<br>型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|-------------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Pole<br>050                                 | Pole                          | 340/1321                                                                 | 1423.8                                      | Light:RED                                                               |                                                                                      |

半径 15 千米-50 千米内主要障碍物 (相对 08/26 跑道中心)

Obstacles within 15 to 50km of the center of RWY08/26

| 障碍物名称<br>或编号<br>Obstacle ID/<br>Designation | 障碍物类<br>型<br>Obstacle<br>type | 障碍物位置<br>磁方位(°)/距离(m)<br>Obstacle position<br>MAG<br>BRG(degree)/DIST(m) | 标高或<br>(高)<br>Elevation<br>/(Height)<br>(m) | 障碍物标志, 灯光<br>类型及颜色<br>Obstacle<br>marking<br>/Lighting Type<br>& Colour | 影响的飞行程序及<br>起飞航径区/备注<br>Flight procedure/take-off<br>path area affected<br>& Remarks |
|---------------------------------------------|-------------------------------|--------------------------------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| MT<br>051                                   | MT                            | 004/38000                                                                | 2532                                        |                                                                         | Sector                                                                               |
| MT<br>052                                   | MT                            | 242/39000                                                                | 1872                                        |                                                                         |                                                                                      |
| MT<br>053                                   | MT                            | 274/25400                                                                | 2107                                        |                                                                         | RWY26 departure; RWY08<br>VOR/DME base turn and<br>intermediate approach             |
| MT<br>054                                   | MT                            | 276/33000                                                                | 2434                                        |                                                                         | RWY26 VOR/DME arrival                                                                |
| MT<br>055                                   | MT                            | 283/43500                                                                | 3244                                        |                                                                         | Sector                                                                               |
| MT<br>056                                   | MT                            | 287/48000                                                                | 3300                                        |                                                                         |                                                                                      |

Remarks: within 15km: No TKOF path OBST for RWY08/26.

15km-50km: Nil

**ZWSH AD 2.11 提供的气象情报、气象观测和报告****Meteorological information provided & meteorological observations and reports**

提供的气象情报

Meteorological information provided

|   |                                   |                                                  |
|---|-----------------------------------|--------------------------------------------------|
| 1 | 相关气象台的名称<br>Associated MET Office | Kashi Laining International Aerodrome MET Office |
|---|-----------------------------------|--------------------------------------------------|

|                                                    |                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                             |
|----------------------------------------------------|------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2                                                  | 气象服务时间、服务时间以外的责任气象台<br>Hours of service/MET Office outside hours                                           | H24<br>--                                                                                                                                                                                                                                                                                                                                                                                   |
| 3                                                  | 负责编发 TAF 的气象台、有效时段、发布间隔<br>Office responsible for TAF preparation/Periods of validity/Interval of issuance | Kashi Laining International Aerodrome MET Office;9h, 30h;3h, 6h                                                                                                                                                                                                                                                                                                                             |
| 4                                                  | 趋势预报及发布间隔<br>Trend forecast/Interval of issuance                                                           | trend 1h                                                                                                                                                                                                                                                                                                                                                                                    |
| 5                                                  | 所提供的讲解或咨询服务<br>Briefing/Consultation provided                                                              | Briefing provided: P, T, TV<br>Consultation provided: P, T, TV                                                                                                                                                                                                                                                                                                                              |
| 6                                                  | 飞行文件及其使用语言<br>Flight documentation/Language(s) used                                                        | Chart, International MET Codes, Abbreviated Plain Language Text;Ch, En                                                                                                                                                                                                                                                                                                                      |
| 7                                                  | 讲解或咨询服务时可利用的图表和其它信息<br>Charts and other information available for briefing or consultation                 | Synoptic charts, significant weather charts, upper W/T charts, satellite material, AWOS real-time data, SIGMET, aerodrome alerting data                                                                                                                                                                                                                                                     |
| 8                                                  | 提供气象情报的辅助设备<br>Supplementary equipment available for providing information                                 | Internet information, Tel, MET service terminal, Fax, satellite cloud monitor, AWOS data monitor                                                                                                                                                                                                                                                                                            |
| 9                                                  | 提供气象情报的空中交通服务单位<br>ATS units provided with information                                                     | TWR, ARO, Xinjiang ATMB ATC center MET center                                                                                                                                                                                                                                                                                                                                               |
| 10                                                 | 其他信息<br>Additional information                                                                             | MET FCST TEL: 86-998-5856049<br>MET OBS TEL: 86-998-5856045                                                                                                                                                                                                                                                                                                                                 |
| 气象观测和报告<br>Meteorological observations and reports |                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                             |
| 1                                                  | 机场观测类型与频率、自动观测设备<br>Type & frequency of observation<br>/Automatic observation equipment                    | Hourly plus special observation plus accident observation/Yes                                                                                                                                                                                                                                                                                                                               |
| 2                                                  | 气象报告类型及所包含的补充资料<br>Type of MET Report/Supplementary information included                                   | METAR, SPECI                                                                                                                                                                                                                                                                                                                                                                                |
| 3                                                  | 观测系统及安装位置<br>Observation system/Site(s)                                                                    | RVR EQPT<br>A: 100m N of RCL, 320m inward THR08;<br>B: 100m N of RCL, 1600m inward THR08;<br>C: 100m N of RCL, 340m inward THR26.<br>SFC wind sensors<br>08: 120m N of RCL, 310m inward THR08;<br>08/26 Center: 120m N of RCL, 1600m inward THR08;<br>26: 120m N of RCL, 340m inward THR26.<br>Ceilometer<br>08: 110m N of RCL, 300m inward THR08;<br>26: 105m N of RCL, 340m inward THR26. |
| 4                                                  | 观测系统的工作时间                                                                                                  | H24                                                                                                                                                                                                                                                                                                                                                                                         |

|   |                                                          |                            |
|---|----------------------------------------------------------|----------------------------|
|   | Hours of operation for meteorological observation system |                            |
| 5 | 气候资料<br>Climatological information                       | Climatological tables AVBL |
| 6 | 其他信息<br>Additional information                           | Nil                        |

ZWSH AD 2.12 跑道物理特征 Runway physical characteristics

| 跑道号码<br>RWY<br>Designator                                                                                                                            | 真方位和<br>磁方位<br>TRUE &<br>MAG BRG  | 跑道长宽<br>Dimensions<br>of RWY(m)   | 跑道强度、跑道和停<br>止道道面<br>RWY strength/<br>Surface of<br>RWY /SWY | 跑道入口坐标、<br>跑道末端坐标、<br>跑道入口大地水<br>准面波幅<br>THR coordinates<br>& RWY end<br>coordinates &<br>THR geoid<br>undulation | 跑道入口标高和<br>精密进近跑道接<br>地带最高标高<br>THR elevation &<br>highest elevation<br>of TDZ of<br>precision APP<br>RWY | 跑道和停止道坡<br>度<br>Slope of<br>RWY/SWY |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-----------------------------------|--------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-------------------------------------|
| 1                                                                                                                                                    | 2                                 | 3                                 | 4                                                            | 5                                                                                                                 | 6                                                                                                         | 7                                   |
| 08                                                                                                                                                   | 085.99° GEO<br>082° MAG           | 3200×45                           | PCR 810/R/A/W/T<br>CONC/CONC                                 | Nil                                                                                                               | THR 1378.6m                                                                                               | 0.24%(592m)/-0.<br>36%(2608m)       |
| 26                                                                                                                                                   | 265.99° GEO<br>262° MAG           | 3200×45                           | PCR 810/R/A/W/T<br>CONC/CONC                                 | Nil                                                                                                               | THR 1370.6m                                                                                               | 0.36%(2608m)/-0.<br>.24%(592m)      |
| 跑道号码<br>RWY<br>Designator                                                                                                                            | 停止道长宽<br>SWY<br>dimensions<br>(m) | 净空道长宽<br>CWY<br>dimensions<br>(m) | 升降带长宽<br>Strip dimensions<br>(m)                             | 跑道端安全区<br>长宽<br>RESA<br>dimensions<br>(m)                                                                         | 拦阻系统的<br>位置及描述<br>Location&<br>Description of<br>arresting system                                         | 无障碍物区<br>OFZ                        |
| 1                                                                                                                                                    | 8                                 | 9                                 | 10                                                           | 11                                                                                                                | 12                                                                                                        | 13                                  |
| 08                                                                                                                                                   | 60×45                             | 300×150                           | 3500×280                                                     | 240×120                                                                                                           | Nil                                                                                                       | -                                   |
| 26                                                                                                                                                   | 60×45                             | 300×150                           | 3500×280                                                     | 240×120                                                                                                           | Nil                                                                                                       | -                                   |
| Remarks: 08/26: RWY shoulder: 7.5m on each side;<br>RWY grooved(6mm*6mm*32mm) at full length. RWY turn pad located at THR26. No forced landing area. |                                   |                                   |                                                              |                                                                                                                   |                                                                                                           |                                     |

ZWSH AD 2.13 公布距离 Declared distances

| 跑道号码<br>RWY Designator | 可用起飞滑跑距离<br>TORA(m) | 可用起飞距离<br>TODA(m) | 可用加速停止距离<br>ASDA(m) | 可用着陆距离<br>LDA(m) | 备注<br>Remarks |
|------------------------|---------------------|-------------------|---------------------|------------------|---------------|
| 1                      | 2                   | 3                 | 4                   | 5                | 6             |
| 08                     | 3200                | 3500              | 3260                | 3200             | Nil           |
| 26                     | 3200                | 3500              | 3260                | 3200             | Nil           |

**ZWSH AD 2.14 进近和跑道灯光 Approach and runway lighting**

| 跑道<br>号码<br>RWY<br>Designator | 进近灯<br>类型、长<br>度、强度<br>APCH<br>LGT<br>type/<br>LEN/<br>/INTST | 入口灯<br>颜色、翼<br>排灯<br>THR<br>LGT<br>colour/<br>WBAR | 目视进近坡度<br>指示系统类<br>型、位置、仰<br>角、跑道入口<br>最低眼高<br>Type of<br>VASIS/Position<br>/Angle/MEHT | 接地<br>带<br>灯长<br>度<br>TDZ<br>LGT<br>LEN | 跑道中线灯长度、<br>间隔、颜色、强度<br>RWY center line<br>LGT LEN/Spacing<br>/Colour/INTST                       | 跑道边灯长度、间<br>隔、颜色、强度<br>RWY edge LGT<br>LEN/Spacing<br>/Colour/INTST         | 跑道末端灯<br>颜色<br>RWY end<br>LGT<br>colour | 停止道灯长<br>度、颜色<br>SWY<br>LGT<br>LEN<br>/Colour |
|-------------------------------|---------------------------------------------------------------|----------------------------------------------------|-----------------------------------------------------------------------------------------|-----------------------------------------|---------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------|-----------------------------------------------|
| 1                             | 2                                                             | 3                                                  | 4                                                                                       | 5                                       | 6                                                                                                 | 7                                                                           | 8                                       | 9                                             |
| 08                            | PALS<br>CAT I<br>SFL<br>720 m<br>VRB<br>LIH                   | GREEN<br>Yes                                       | PAPI<br>LEFT<br>375m inward<br>THR08<br>3°<br>18.5m                                     | Nil                                     | 3200 m<br>spacing 30m<br>0-2300m, WHITE<br>2300-2900m,<br>RED/WHITE<br>2900-3200m, RED<br>VRB LIH | 3200 m<br>spacing 60m<br>0-2600m, WHITE<br>2600-3200m,<br>YELLOW<br>VRB LIH | RED                                     | Nil                                           |
| 26                            | PALS<br>CAT I<br>SFL<br>900 m<br>VRB<br>LIH                   | GREEN<br>Yes                                       | PAPI<br>LEFT<br>375m inward<br>THR26<br>3°<br>17.7m                                     | Nil                                     | 3200 m<br>spacing 30m<br>0-2300m, WHITE<br>2300-2900m,<br>RED/WHITE<br>2900-3200m, RED<br>VRB LIH | 3200 m<br>spacing 60m<br>0-2600m, WHITE<br>2600-3200m,<br>YELLOW<br>VRB LIH | RED                                     | Nil                                           |
| Remarks:                      |                                                               |                                                    |                                                                                         |                                         |                                                                                                   |                                                                             |                                         |                                               |

**ZWSH AD 2.15 其它灯光,备份电源 Other lighting, secondary power supply**

|   |                                                                                    |                                                                                              |
|---|------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| 1 | 机场灯标或识别灯标位置、特性和工作时间<br>ABN/IBN location, characteristics and hours<br>of operation | Nil                                                                                          |
| 2 | 着陆方向标和风向标位置和灯光<br>LDI/ WDI location and LGT                                        | WDI:<br>08: 130m N of RCL, 370m inward THR, LGT;<br>26: 135m S of RCL, 360m inward THR, LGT. |
| 3 | 滑行道边灯和滑行道中线灯<br>TWY edge and center line lighting                                  | All TWYs: green center line lights, blue edge line lights                                    |
| 4 | 备份电源及转换时间<br>Secondary power supply/Switch-over time                               | Secondary power supply available/1s, diesel motor available/<15s                             |
| 5 | 备注<br>Remarks                                                                      | Nil                                                                                          |

**ZWSH AD 2.16 直升机着陆区域 Helicopter landing area**

|   |                                                                                       |     |
|---|---------------------------------------------------------------------------------------|-----|
| 1 | TLOF 坐标或 FATO 入口坐标及大地水准面波幅<br>Coordinates TLOF or THR of FATO, Geoid undulation       | Nil |
| 2 | TLOF 和 (或) FATO 标高<br>TLOF and/or FATO elevation                                      | Nil |
| 3 | TLOF 和 FATO 区域范围、道面、强度和标志<br>TLOF and FATO area dimensions,surface, strength, marking | Nil |
| 4 | FATO 的真方位和磁方位<br>True and MAG BRG of FATO                                             | Nil |
| 5 | 公布距离<br>Declared distance available                                                   | Nil |
| 6 | 进近灯光和 FATO 灯光<br>APP and FATO lighting                                                | Nil |
| 7 | 备注<br>Remarks                                                                         | Nil |

**ZWSH AD 2.17 空中交通服务空域 ATS airspace**

| 空域名称和水平范围<br>Designation and lateral limits |                                               | 垂直范围<br>Vertical limits                                                                               | 空域分类<br>Airspace class | 空中交通服务单位呼号和使用语言<br>ATS unit callsign Language | 工作时间<br>Hours of applicability | 备注<br>Remarks |
|---------------------------------------------|-----------------------------------------------|-------------------------------------------------------------------------------------------------------|------------------------|-----------------------------------------------|--------------------------------|---------------|
| 1                                           | 2                                             | 3                                                                                                     | 4                      | 5                                             | 6                              | 7             |
| Tower Control area                          | A circle with radius of 50km centered at ARP. | SFC to 6000m (QNE)                                                                                    |                        | Kashi Tower/En,Ch                             | H24                            |               |
| Altimeter setting region and TL/TA/TH       |                                               | TL 4800m<br>TA 4200m<br>4500m(QNH $\geq$ 1031hPa)<br>3900m(QNH $\leq$ 979hPa)<br>TH (3000)m or by ATC |                        |                                               |                                |               |

**ZWSH AD 2.18 空中交通服务通信设施 ATS communication facilities**

| 服务名称<br>Service designation | 呼号<br>Callsign | 频率<br>Frequency (MHz) | 卫星话音通信<br>号码<br>SATVOICE number | 登录地址<br>Logon address | 工作时间<br>Hours of operation | 备注<br>Remarks |
|-----------------------------|----------------|-----------------------|---------------------------------|-----------------------|----------------------------|---------------|
| 1                           | 2              | 3                     | 4                               | 5                     | 6                          | 7             |
| ATIS                        |                | 126.2                 |                                 |                       | H24                        |               |
| TWR                         | Kashi Tower    | 118.5 (130.0)         | 17400012252                     |                       | H24                        |               |
| EMG                         |                | 121.5                 |                                 |                       | H24                        |               |

**ZWSH AD 2.19 无线电导航和着陆设施 Radio navigation and landing aids**

| 设施名称及类型、磁差、支持运行类别、VOR/ILS 磁偏角<br>Name and type of aid, VAR, Type of supported OPS, Declination of VOR/ILS | 识别<br>ID | 频率、波道<br>Frequency/<br>Channel number | 工作时间<br>Hours of operation | 发射天线坐标及相对位置<br>Coordinates of transmitting antenna/<br>Position | DME 发射天线标高<br>Elevation of DME transmitting antenna | 备注<br>Remarks                             |
|-----------------------------------------------------------------------------------------------------------|----------|---------------------------------------|----------------------------|-----------------------------------------------------------------|-----------------------------------------------------|-------------------------------------------|
| 1                                                                                                         | 2        | 3                                     | 4                          | 5                                                               | 6                                                   | 7                                         |
| Kashi VOR/DME                                                                                             | KHG      | 115.7 MHz<br>CH 104X                  | H24                        | N39°32.8'<br>E076°01.4'<br>022°MAG/260m FM<br>RWY center        | 1401 m                                              |                                           |
| LMM 08                                                                                                    | X        | 223 kHz                               |                            | 262°MAG/1050m<br>FM THR08                                       |                                                     |                                           |
| LOC 08<br>ILS CAT I                                                                                       | IXX      | 109.9 MHz                             |                            | 082°MAG/295m FM<br>RWY08 end                                    |                                                     | Beyond 008° leftside of front course U/S. |
| GP 08                                                                                                     |          | 333.8 MHz                             |                            | 120m N of RCL,<br>283m inward THR08                             |                                                     | Angle 3°<br>RDH 15m                       |
| DME 08                                                                                                    | IXX      | CH 36X<br>(109.9 MHz)                 |                            |                                                                 | 1388m                                               | Co-located with GP 08                     |
| LMM 26                                                                                                    | L        | 210 kHz                               |                            | 082°MAG/1050m<br>FM THR26                                       |                                                     |                                           |
| LOC 26<br>ILS CAT I                                                                                       | ILL      | 111.1 MHz                             |                            | 262°MAG/314m FM<br>RWY26 end                                    |                                                     |                                           |
| GP 26                                                                                                     |          | 331.7 MHz                             |                            | 120m N of RCL,<br>307m inward THR26                             |                                                     | Angle 3°<br>RDH 15m                       |
| DME 26                                                                                                    | ILL      | CH 48X<br>(111.1 MHz)                 |                            |                                                                 | 1385m                                               | Co-located with GP 26                     |

**ZWSH AD 2.20 本场规定****1. 机场使用规定**

1.1 本场多大风，停场过夜的航空器，要认真做好防风准备。

1.2 本场距备降机场远，在天气复杂情况下，要考虑增加适当的备份油量。

1.3 本场可供 B747-400 及同类以下机型使用。

1.4 本场进离场航空器严格按管制指令飞行，服从管制指挥。

**2. 跑道和滑行道的使用**

2.1 未经塔台许可，禁止航空器在跑道上 180°掉头。

**2.2 跑道运行规定**

2.2.1 满足下列条件之一时，须转换跑道方向：

(1) 无污染跑道地面顺风分量达到风量大于 3.5m/s。

(2) 污染跑道条件下，跑道顺风分量为顺风时。

2.2.2 当转换使用跑道方向时，使用跑道顺风分量大于 3.5m/s，小于 5m/s 时，如航空器性能限制等原因无法接受时，航空器驾驶员应及时通告塔台管制员。

**2.3 跑道等待位置及使用规定**

2.3.1 航空器在进入跑道前应在指定的跑道等待位置等待，并向塔台报告等待位置，得到塔台进入跑道许

**ZWSH AD 2.20 Local aerodrome regulations****1. Airport operations regulations**

1.1 Overnight flight shall take some measures on wind protection due to strong wind in this airport.

1.2 The alternate airport is far away from this airport. It's advised that aircraft shall take appropriate fuel under complex weather.

1.3 Maximum aircraft to be available: B747-400.

1.4 Departure and arrival aircraft shall strictly follow ATC instructions.

**2. Use of runways and taxiways**

2.1 Without TWR ATC clearance, 180° turnaround on RWY is strictly forbidden for all aircrafts.

**2.2 Rules for the use of RWY**

2.2.1 The direction of RWY in use shall be changed if one of the following conditions is met:

(1) Under dry RWY conditions, downwind speed is more than 3.5m/s.

(2) Under contaminated RWY condition, RWY is shown downwind.

2.2.2 During changing the direction of RWY in use, when downwind speed is more than 3.5m/s and less than 5m/s, if aircraft performance limit or other reasons cannot sustained, pilot shall inform TWR ATC in time.

**2.3 RWY holding positions and requirements**

2.3.1 Aircraft shall stop at the designated RWY holding positions before enter the RWY, report the position to

|                                                                          |                                                                                                                                                                                                                                                                                                                                                                       |
|--------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 可后方可进入跑道，跑道等待位置详见机场图；                                                    | TWR, then enter the RWY with TWR clearance.(RWY holding positions refer to aerodrome chart)                                                                                                                                                                                                                                                                           |
| 2.3.2 航空器在跑道等待位置等待时，机头应尽量靠近跑道等待位置标志，但不能超过此标志。如机头超过跑道等待位置标志，应立即向塔台报告。     | 2.3.2 The nose of aircraft shall get close to the RWY holding position marking without exceeding it when aircraft is waiting at the RWY holding position. Report to TWR immediately if the nose of aircraft exceeds the marking.                                                                                                                                      |
| 2.4 滑行道使用规定                                                              | 2.4 Use of TWY                                                                                                                                                                                                                                                                                                                                                        |
| 2.4.1 航空器可通过塔台管制室申请引导车服务。                                                | 2.4.1 Follow-me vehicle service are available via TWR Control.                                                                                                                                                                                                                                                                                                        |
| 2.4.2 B747、B777、B787、A330、A340、A350 系列机型在 A1、A3、A7、B1-B5 滑行道运行时，需采用偏置转弯。 | 2.4.2 Offset turn is requested on TWY A1, A3, A7, B1-B5 for aircraft type B747, B777, B787, A330, A340, A350.                                                                                                                                                                                                                                                         |
| 2.4.3 B5 联络道为单向使用通道，仅限航空器由机坪滑行进入 A 滑行道，严禁航空器由 A 滑行道经 B5 联络道进入机坪。         | 2.4.3 TWYL B5 only for aircraft taxiing FM APN to TWY A; entering APN via TWYL B5 is forbidden.                                                                                                                                                                                                                                                                       |
| 2.5 发出着陆许可后，着陆许可条件发生变化时，应立即通知航空器复飞，并简要说明复飞原因；着陆航空器驾驶员认为有必要时，应立即复飞，并报告塔台。 | 2.5 After issuing the landing clearance, if TWR ATC observes any change in the release conditions of the landing clearance, TWR ATC shall notify the pilot to go around immediately and explain the reason briefly.<br><br>Under such situation, pilot shall make a missed approach at any moment if it is considered to be necessary and notify TWR ATC immediately. |
| 2.6 对机组的要求                                                               | 2.6 Requirements for pilots                                                                                                                                                                                                                                                                                                                                           |
| 2.6.1 听清并重复塔台的滑行指令，尤其是限制性指令，发现疑问及时证实。                                    | 2.6.1 Repeat TWR Control's taxiing instructions, especially the limitations, and verify any questions immediately.                                                                                                                                                                                                                                                    |
| 2.6.2 地面滑行期间，机组应密切关注相关活动，及                                               | 2.6.2 Flight crew shall follow TWR instructions to taxi,                                                                                                                                                                                                                                                                                                              |

时依照塔台的活动通报观察或将观察到的不明活动情况通报给塔台。

keep watching ATC-related activities and report the observed activities to TWR in time.

### 3. 机坪和机位的使用

### 3. Use of aprons and parking stands

#### 3.1 停机位使用限制:

#### 3.1 Limits of parking stands:

| 停机位编号/Stands Nr. | 翼展限制 (m) /Wing span limits(m) | 机身长度限制 (m) /Fuselage limits(m) | 进出方式/Enter or Exit |
|------------------|-------------------------------|--------------------------------|--------------------|
| 01, 212, 301     | <65                           | ≤80                            | Taxi in, Push back |
| 11               | <65                           | ≤75                            | Taxi in, Push back |
| 215, 216         | <65                           | ≤75.5                          | Taxi in, Taxi out  |
| 02, 302          | <52                           | ≤80                            | Taxi in, Push back |
| 214              | <52                           | ≤75.5                          | Taxi in, Taxi out  |
| 213              | <52                           | ≤68                            | Taxi in, Push back |
| 03, 04           | <48.5                         | ≤80                            | Taxi in, Push back |
| 05, 06           | <36                           | ≤66                            | Taxi in, Push back |
| 07-10, 201-204   | <36                           | ≤50                            | Taxi in, Push back |
| 210              | <36                           | ≤45                            | Taxi in, Taxi out  |
| 205-209          | <36                           | ≤44.5                          | Taxi in, Taxi out  |
| 211              | <24                           | ≤46                            | Taxi in, Taxi out  |

3.2 停机位 214 和 216 为除冰机位。

3.2 Stands Nr.214 and 216 are de-icing stands.

3.3 为降低碳排放及噪音, 所有停放本场廊桥停机位的航空器必须关闭 APU, 使用 400Hz 桥载电源及航空器专用空调设备, 以下特殊情况除外:

3.3 Aircraft parking at boarding bridge stands shall turn off APU, use bridge power supply equipment(400Hz) and special air conditioner. Aircraft can use APU as the following situations:

3.3.1 机场不能提供有效的桥载设备服务;

3.3.1 Bridge equipment is unserviceable;

|                                                                           |                                                                                                                                                                                                                                                                                                    |
|---------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 3.3.2 航空器因启动发动机而需开启 APU;                                                  | 3.3.2 Aircraft needs APU to start up engine;                                                                                                                                                                                                                                                       |
| 3.3.3 航空器进行 APU 的维修检测;                                                    | 3.3.3 APU is under maintained;                                                                                                                                                                                                                                                                     |
| 3.3.4 遇到影响航空器安全、正常运行的特殊情况。<br>例如：极端天气、重要保障、航空器过站时间不足等有关情况。                | 3.3.4 In case of exceptional circumstance influencing the regularity and safty of operation, such as extreme weather, special plane support, and insufficient flight transtion time, aircraft can use APU.                                                                                         |
| 3.4 航空器除冰规则                                                               | 3.4 Aircraft deicing rules                                                                                                                                                                                                                                                                         |
| 3.4.1 一般要求                                                                | 3.4.1 General rules                                                                                                                                                                                                                                                                                |
| 需除冰的航空器，在关舱门前向塔台申请；自滑至除冰坪；除冰完毕后，向塔台申请开车滑出。滑出除冰坪时，机组应注意控制油门，以防尾流影响附近人员和设备。 | Apply to TWR for deicing before closing the hatch; taxi to deicing apron; after deicing, apply to TWR for start-up and taxi out. Aircrew shall control the throttle carefully, avoiding the exhausted gas causing damage to support personnel and equipment, when aircraft exit the deicing apron. |
| 3.4.2 除冰程序                                                                | 3.4.2 Deicing procedures                                                                                                                                                                                                                                                                           |
| 3.4.2.1 航空器除冰应在关舱门前向塔台申请；                                                 | 3.4.2.1 Apply to TWR for deicing before closing the hatch;                                                                                                                                                                                                                                         |
| 3.4.2.2 航空器自滑至除冰坪；                                                        | 3.4.2.2 Taxi to deicing apron;                                                                                                                                                                                                                                                                     |
| 3.4.2.3 机组确认满足除冰条件后通知地面机务进行除冰；                                            | 3.4.2.3 Confirm the deicing condition and contact gound personnel to deice;                                                                                                                                                                                                                        |
| 3.4.2.4 机组与地面机务确认除冰完毕后，向塔台申请开车滑出，并由塔台管制员指挥航空器进入跑道。                        | 3.4.2.4 Confirm deicing complete with gound personnel, then apply to TWR for start-up and taxi out, and follow ATC instructions to enter RWY.                                                                                                                                                      |
| <b>4. 低能见度运行</b>                                                          | <b>4. Low visibility operation</b>                                                                                                                                                                                                                                                                 |
| 无                                                                         | Nil                                                                                                                                                                                                                                                                                                |

**5. 直升机飞行限制, 直升机停靠区**

无

**5. Helicopter operation restrictions and helicopter parking/docking area**

Nil

**6. 警告**

6.1 进出本机场的航空器, 严格保持航迹和高度, 准确控制落地时间, 并听从 ATC 指挥。

6.2 在机场上空或进近时有 TCAS 告警时, 应及时联系 ATC 确认。

6.3 本场实行 ADS-B 监视下的程序管制, 所用间隔标准为程序管制间隔。

6.4 本场夏季(6月-8月)午后常出现对流性天气, 易造成短时大风、风切变、雷暴天气, 飞行机组需注意其影响。

**6. Warning**

6.1 The departing and landing aircraft shall strictly keep the flight track and altitudes, accurately control the landing time, and follow ATC instructions.

6.2 If TCAS alert above the airport or in approach, pilot shall confirm to ATC in time.

6.3 Implement procedure control under ADS-B monitoring, using procedure control interval.

6.4 In summer(JUN to AUG), convective weather often occurs in the afternoon, which is easy to cause short-term wind, wind shear, thunderstorm weather. Pilots should pay attention to its influence.

**ZWSH AD 2.21 减噪程序**

无

**ZWSH AD 2.21 Noise abatement procedures**

Nil

**ZWSH AD 2.22 飞行程序****1. 总则**

除经喀什徕宁国际机场塔台特殊许可外机场管制地带内的飞行, 必须按照仪表飞行规则进行, 除非特殊情况, 本场进出港航空器优先使用传统飞行程序。

**2. 起落航线**

起落航线通常在跑道南侧进行, 高(QFE)400m-600m。

**ZWSH AD 2.22 Flight procedures****1. General**

Flights within Aerodrome Control Zone shall operate under IFR unless special clearance has been obtained from TWR. Traditional procedure is primary use for all departure/arrival aircraft.

**2. Traffic circuits**

Traffic circuits shall be made to the south of RWY, at

使用 26 跑道为左起落, 使用 08 跑道为右起落。

QFE 400m-600m. RWY26 in use is LEFT traffic circuits; RWY08 in use is RIGHT traffic circuits.

### 3. 仪表飞行程序

严格按照航图中公布的进、离场程序和进近程序飞行。如果需要, 航空器可在空中交通管制部门指定的航路、导航台或定位点上空等待或做机动飞行。

### 3. IFR flight procedures

Strict adherence is required to the relevant arrival/departure and approach procedures published in the aeronautical charts. Aircraft may, if necessary, hold or maneuver on an airway, over a navigation facility or a fix designated by ATC.

### 4. 雷达程序和/或 ADS-B 程序

无

### 4. Radar procedures and/or ADS-B procedures

Nil

### 5. 无线电通信失效程序

5.1 当发生通信失效时, 航空器机组可使用卫星电话或通过航空公司签派拨打 86-998-5856051 或 86-998-5856054 作为喀什塔台紧急通信联络手段。

5.1 In case of radio failure, the crew contact with TWR by satellite phones. TWR phones:

86-998-5856051/86-998-5856054.

5.2 参见 AIP GEN3.4.5 中的仪表飞行规则航空器地空双向无线电通信失效通用程序。

5.2 Refer to AIP GEN3.4.5 general procedures for aircraft under instrument flight rule with air-ground two-way radio communication failure.

### 6. 目视飞行程序

机场塔台管制区范围内, 符合目视气象条件, 经飞行员申请, 管制员批准, 方可进行目视飞行, 但应接受空中交通管制服务, 服从管制员的调配。

### 6. Procedures for VFR flights

Under visual meteorological condition within TWR Control area, pilot can apply to ATC for VFR flight, then implement with ATC clearance and follow ATC instructions.

### 7. 目视飞行航线

无

### 7. VFR route

Nil

### 8. 其它规定

无

### 8. Other regulations

Nil

## ZWSH AD 2.23 其它资料

## ZWSH AD 2.23 Other information

## 鸟情资料

## Bird's information

机场配备了驱鸟设备，机场当局采取了驱赶措施，以减少鸟群活动。

Aerodrome is equipped with bird dispersal equipments, and Aerodrome Authority resorts to dispersal methods to reduce bird activities.

| Migratory Season          |     | Direction of ACT            | FLT HGT WI AD<br>(m)  | Characteristic              |
|---------------------------|-----|-----------------------------|-----------------------|-----------------------------|
| Spring(MAR-MAY)           | Day | Near the AP                 | 0-100                 | Small size group            |
|                           |     | Migrate S to N              | 0-150                 | Medium and small size       |
|                           | NGT | Near the AP                 | 0-100                 | Medium and small size       |
| Summer(JUN-AUG)           | Day |                             |                       | Migrate S to N              |
|                           |     | Large and medium size group |                       |                             |
|                           | NGT | Near the AP                 | 0-100                 | Large size                  |
| Autumn(SEP-NOV)           | Day |                             |                       | 0-150                       |
|                           |     |                             | Medium and small size |                             |
|                           | NGT |                             | 0-100                 | Large size                  |
| Winter(DEC-FEB(NXT year)) | Day |                             |                       | 0-150                       |
|                           |     |                             | Medium and small size |                             |
|                           | NGT |                             | 0-100                 | Medium and small size group |