

May 25, 2016

1 Notes

- A configuration $e \mid \varepsilon$ is well-typed if the expression e is closed under the empty context, and we have $\vdash e : \tau$ **with** ε according to some derivation.

2 Progress

2.1 Statement

For any well-typed configuration $e \mid \varepsilon$ either:

- e is a value.
- $\mu \mid e \mid \varepsilon \longrightarrow \mu' \mid e' \mid \varepsilon'$, for some configuration $\mu' \mid e' \mid \varepsilon'$.

3 Preservation

3.1 Statement

Suppose the following:

- $\mu \mid e \mid \varepsilon$ is a well-typed configuration.
- $\mu \mid e \mid \varepsilon \longrightarrow \mu' \mid e' \mid \varepsilon'$

Then $\mu' \mid e' \mid \varepsilon'$ is well-typed.

4 Soundness Of Terminating Programs

4.1 Statement

Suppose the following:

- $\mu_1 \mid e \mid \varepsilon_1$ is well-typed.
- $e : \tau$ **with** ε
- $\mu_1 \mid e \mid \varepsilon_1 \longrightarrow_* \mu_2 \mid v \mid \varepsilon_2$

Then $\varepsilon_2 \subseteq \varepsilon$.

5 Soundness Of All Programs

5.1 Statement

Suppose the following:

- $\mu_1 \mid e \mid \varepsilon_1$ is well-typed.
- $e : \tau$ **with** ε
- $\mu_1 \mid e \mid \varepsilon_1 \longrightarrow_* \mu_2 \mid e_2 \mid \varepsilon_2$

Then $\varepsilon_2 \subseteq \varepsilon$.