



SCLAIRPIPE®
IPS PIPE SIZES AND PRESSURE
RATINGS PE4710

PRODUCT BULLETIN

| | | DR32.5 (64 psi) | | | DR26 (80 psi) | | | DR21 (100 psi) | | | DR17 (125 psi) | | | |
|-----|-------------------|-------------------|---------------------|---------------------------|-------------------|---------------------|---------------------------|-------------------|---------------------|---------------------------|-------------------|---------------------|---------------------------|-----|
| NPS | Avg OD (in) | Avg ID (in) | Min Wall (in) | Avg Weight (lbs/ft) | NPS |
| 3 | 3.50 | 3.27 | 0.108 | 0.51 | 3.21 | 0.135 | 0.63 | 3.15 | 0.167 | 0.77 | 3.06 | 0.206 | 0.94 | 3 |
| 4 | 4.50 | 4.21 | 0.138 | 0.84 | 4.13 | 0.173 | 1.03 | 4.05 | 0.214 | 1.27 | 3.94 | 0.265 | 1.55 | 4 |
| 5 | 5.56 | 5.20 | 0.171 | 1.28 | 5.11 | 0.214 | 1.58 | 5.00 | 0.265 | 1.94 | 4.87 | 0.327 | 2.36 | 5 |
| 6 | 6.63 | 6.19 | 0.204 | 1.81 | 6.08 | 0.255 | 2.24 | 5.96 | 0.315 | 2.75 | 5.80 | 0.390 | 3.35 | 6 |
| 7 | 7.13 | 6.66 | 0.219 | 2.09 | 6.54 | 0.274 | 2.59 | 6.41 | 0.339 | 3.18 | 6.24 | 0.419 | 3.88 | 7 |
| 8 | 8.63 | 8.06 | 0.265 | 3.07 | 7.92 | 0.332 | 3.80 | 7.75 | 0.411 | 4.66 | 7.55 | 0.507 | 5.68 | 8 |
| 10 | 10.75 | 10.05 | 0.331 | 4.77 | 9.87 | 0.413 | 5.91 | 9.66 | 0.512 | 7.24 | 9.41 | 0.632 | 8.83 | 10 |
| 12 | 12.75 | 11.92 | 0.392 | 6.70 | 11.71 | 0.490 | 8.31 | 11.46 | 0.607 | 10.18 | 11.16 | 0.750 | 12.42 | 12 |
| 13 | 13.38 | 12.50 | 0.412 | 7.38 | 12.28 | 0.514 | 9.14 | 12.02 | 0.637 | 11.21 | 11.71 | 0.787 | 13.67 | 13 |
| 14 | 14.00 | 13.09 | 0.431 | 8.08 | 12.86 | 0.538 | 10.02 | 12.59 | 0.667 | 12.28 | 12.25 | 0.824 | 14.98 | 14 |
| 16 | 16.00 | 14.96 | 0.492 | 10.56 | 14.70 | 0.615 | 13.08 | 14.38 | 0.762 | 16.04 | 14.00 | 0.941 | 19.56 | 16 |
| 18 | 18.00 | 16.83 | 0.554 | 13.36 | 16.53 | 0.692 | 16.56 | 16.18 | 0.857 | 20.29 | 15.76 | 1.059 | 24.76 | 18 |
| 20 | 20.00 | 18.70 | 0.615 | 16.49 | 18.37 | 0.769 | 20.44 | 17.98 | 0.952 | 25.06 | 17.51 | 1.176 | 30.56 | 20 |
| 22 | 22.00 | 20.56 | 0.677 | 19.96 | 20.21 | 0.846 | 24.74 | 19.78 | 1.048 | 30.32 | 19.26 | 1.294 | 36.98 | 22 |
| 24 | 24.00 | 22.43 | 0.738 | 23.75 | 22.04 | 0.923 | 29.44 | 21.58 | 1.143 | 36.08 | 21.01 | 1.412 | 44.01 | 24 |
| 26 | 26.00 | 24.30 | 0.800 | 27.87 | 23.88 | 1.000 | 34.55 | 23.38 | 1.238 | 42.34 | 22.76 | 1.529 | 51.65 | 26 |
| 28 | 28.00 | 26.17 | 0.862 | 32.33 | 25.72 | 1.077 | 40.07 | 25.17 | 1.333 | 49.11 | 24.51 | 1.647 | 59.90 | 28 |
| 30 | 30.00 | 28.04 | 0.923 | 37.11 | 27.55 | 1.154 | 46.00 | 26.97 | 1.429 | 56.37 | 26.26 | 1.765 | 68.77 | 30 |
| 32 | 32.00 | 29.91 | 0.985 | 42.22 | 29.39 | 1.231 | 52.34 | 28.77 | 1.524 | 64.14 | 28.01 | 1.882 | 78.24 | 32 |
| 36 | 36.00 | 33.65 | 1.108 | 53.44 | 33.06 | 1.385 | 66.24 | 32.37 | 1.714 | 81.18 | 31.51 | 2.118 | 99.02 | 36 |
| 40 | 40.00 | 37.39 | 1.231 | 65.98 | 36.74 | 1.538 | 81.77 | 35.96 | 1.905 | 100.22 | 35.01 | 2.353 | 122.25 | 40 |
| 42 | 42.00 | 39.26 | 1.292 | 72.74 | 38.58 | 1.615 | 90.16 | 37.76 | 2.000 | 110.49 | 36.76 | 2.471 | 134.78 | 42 |
| 48 | 48.00 | 44.87 | 1.477 | 95.01 | 44.09 | 1.846 | 117.76 | 43.15 | 2.286 | 144.32 | 42.01 | 2.824 | 176.04 | 48 |
| 54 | 54.00 | 50.48 | 1.662 | 120.24 | 49.60 | 2.077 | 149.03 | 48.55 | 2.571 | 182.65 | 47.27 | 3.176 | 222.81 | 54 |
| 63 | 63.00 | 58.89 | 1.938 | 163.66 | 57.86 | 2.423 | 202.85 | 56.64 | 3.000 | 248.61 | | | | 63 |

Pipe dimensions are in accordance with ASTM F714 and AWWA C906. Pressure Ratings are for water at 73°F. Ratings will vary for other fluids and temperatures. Some of the pipe sizes and DR's above are available only on request. Check with your representative for availability. Other dimensions and DR's not listed may be available upon special request. Weights are calculated by the methodology established in PPI's TR-7. Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. As conditions of use may vary and are beyond the control of Uponor Infra Ltd., no representations or warranty, express or implied, are made with respect to the accuracy, reliability, or completeness of the this information.



| | | DR13.5 (160 psi) | | | DR11 (200 psi) | | | DR9 (250 psi) | | | DR7.3 (317 psi) | | | |
|-----|-------------------|-------------------|---------------------|---------------------------|-------------------|---------------------|---------------------------|-------------------|---------------------|---------------------------|-------------------|---------------------|---------------------------|-----|
| NPS | Avg OD (in) | Avg ID (in) | Min Wall (in) | Avg Weight (lbs/ft) | NPS |
| 3 | 3.50 | 2.95 | 0.259 | 1.16 | 2.83 | 0.318 | 1.39 | 2.68 | 0.389 | 1.66 | 2.48 | 0.479 | 1.99 | 3 |
| 4 | 4.50 | 3.79 | 0.333 | 1.91 | 3.63 | 0.409 | 2.30 | 3.44 | 0.500 | 2.75 | 3.19 | 0.616 | 3.28 | 4 |
| 5 | 5.56 | 4.69 | 0.412 | 2.93 | 4.49 | 0.506 | 3.52 | 4.25 | 0.618 | 4.20 | 3.95 | 0.762 | 5.02 | 5 |
| 6 | 6.63 | 5.58 | 0.491 | 4.15 | 5.35 | 0.602 | 4.99 | 5.06 | 0.736 | 5.96 | 4.70 | 0.908 | 7.12 | 6 |
| 7 | 7.13 | 6.01 | 0.528 | 4.80 | 5.75 | 0.648 | 5.78 | 5.45 | 0.792 | 6.89 | 5.06 | 0.976 | 8.23 | 7 |
| 8 | 8.63 | 7.27 | 0.639 | 7.03 | 6.96 | 0.784 | 8.47 | 6.59 | 0.958 | 10.10 | 6.12 | 1.182 | 12.07 | 8 |
| 10 | 10.75 | 9.06 | 0.796 | 10.93 | 8.68 | 0.977 | 13.15 | 8.22 | 1.194 | 15.69 | 7.63 | 1.473 | 18.75 | 10 |
| 12 | 12.75 | 10.75 | 0.944 | 15.37 | 10.29 | 1.159 | 18.50 | 9.75 | 1.417 | 22.08 | 9.05 | 1.747 | 26.37 | 12 |
| 13 | 13.38 | 11.27 | 0.991 | 16.92 | 10.80 | 1.216 | 20.36 | 10.22 | 1.486 | 24.29 | 9.49 | 1.832 | 29.02 | 13 |
| 14 | 14.00 | 11.80 | 1.037 | 18.53 | 11.30 | 1.273 | 22.31 | 10.70 | 1.556 | 26.62 | 9.93 | 1.918 | 31.79 | 14 |
| 16 | 16.00 | 13.49 | 1.185 | 24.21 | 12.92 | 1.455 | 29.13 | 12.23 | 1.778 | 34.76 | 11.35 | 2.192 | 41.53 | 16 |
| 18 | 18.00 | 15.17 | 1.333 | 30.64 | 14.53 | 1.636 | 36.87 | 13.76 | 2.000 | 44.00 | 12.77 | 2.466 | 52.56 | 18 |
| 20 | 20.00 | 16.86 | 1.481 | 37.82 | 16.15 | 1.818 | 45.52 | 15.29 | 2.222 | 54.32 | 14.19 | 2.740 | 64.89 | 20 |
| 22 | 22.00 | 18.55 | 1.630 | 45.77 | 17.76 | 2.000 | 55.08 | 16.82 | 2.444 | 65.72 | 15.61 | 3.014 | 78.51 | 22 |
| 24 | 24.00 | 20.23 | 1.778 | 54.47 | 19.37 | 2.182 | 65.55 | 18.35 | 2.667 | 78.22 | 17.03 | 3.288 | 93.44 | 24 |
| 26 | 26.00 | 21.92 | 1.926 | 63.92 | 20.99 | 2.364 | 76.93 | 19.88 | 2.889 | 91.80 | | | | 26 |
| 28 | 28.00 | 23.60 | 2.074 | 74.13 | 22.60 | 2.545 | 89.22 | 21.40 | 3.111 | 106.46 | | | | 28 |
| 30 | 30.00 | 25.29 | 2.222 | 85.10 | 24.22 | 2.727 | 102.42 | 22.93 | 3.333 | 122.22 | | | | 30 |
| 32 | 32.00 | 26.97 | 2.370 | 96.83 | 25.83 | 2.909 | 116.53 | | | | | | | 32 |
| 36 | 36.00 | 30.35 | 2.667 | 122.55 | 29.06 | 3.273 | 147.49 | | | | | | | 36 |
| 40 | 40.00 | 33.72 | 2.963 | 151.29 | | | | | | | | | | 40 |
| 42 | 42.00 | 35.40 | 3.111 | 166.80 | | | | | | | | | | 42 |
| 48 | 48.00 | | | | | | | | | | | | | 48 |
| 54 | 54.00 | | | | | | | | | | | | | 54 |
| 63 | 63.00 | | | | | | | | | | | | | 63 |

Pipe dimensions are in accordance with ASTM F714 and AWWA C906. Pressure Ratings are for water at 73°F. Ratings will vary for other fluids and temperatures. Some of the pipe sizes and DR's above are available only on request. Check with your representative for availability. Other dimensions and DR's not listed may be available upon special request. Weights are calculated by the methodology established in PPI's TR-7. Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. As conditions of use may vary and are beyond the control of Uponor Infra Ltd., no representations or warranty, express or implied, are made with respect to the accuracy, reliability, or completeness of the this information.

Uponor Infra

6507 Mississauga Road Mississauga, ON L5N 1A6 CANADA

Tel: 866.594.7473 Fax: 905.858.0208 **Web: www.uponor.ca**