






Classification: Public

PIPE TYPE	6" OD	8" ID	10" OD	12" OD	14" ID	16"ID	18" ID
SDR-26 (D3034)	6.28	7.75	10.75	12.50			16.62
SDR-35 (D3034)	6.28	7.92	10.75	12.50			17.63
SCH.40	6.63	7.94	10.75	12.75	13.07	14.94	16.81
SCH.80	6.63	7.57	10.75	12.75	12.41	14.21	16.01
HDPE	6.92	7.90	11.75	14.45			18.07
C900 (DR 18)	6.90	7.98	11.10	13.20	13.50	15.35	17.20
IPS (DR 32.5)	6.63	8.06	10.75	12.75	13.09	14.96	16.83
DIP (UL CLASS 56)	6.90	8.15	11.10	13.20	14.26	16.66 (CLASS 51)	18.44

Side Plate Pipe Port	Pipe Connector 8"	Pipe Connector 10"	Pipe Connector 12"	Top Adapter 12"	Top Adapter 16"	Side Plate Pipe Port
Max. 6.4" Open	8" Spigot = 7.9" OD	10" OD < 12.4"	12" Spigot = 12.4" OD	12" Spigot = 12.4" OD	16" Spigot = 16.64" OD	Max. 13.4" Open
						
Field Core Hole to Size	Bell End Connection Over 8" Spigot	Cut 8" Spigot | Core (Expand) Hole to 10" OD	Gasketed Bell End Over 12" Spigot	Gasketed Bell End Over 12" Spigot	Bell End Connection Over 16" Spigot	Field Core Hole to Size
2476600003 (Part #)	2476631200 (Part #)	2476631200 (Part #)	2476631200 (Part #)	3085857 (Part #)	2476842000 (Part #)	2476600003 (Part #)



***Rubber Couplers can also be used in the field installed over the spigot end of 8-12" Pipe (Provided by others)**

wavin

Classification: Public