






PIPE TYPE	6" OD	8" ID	10" OD	12" OD	14" ID	16"ID	18" ID
SDR-26 (D3034)	6.28	7.75	10.75	12.50			16.62
SDR-35 (D3034)	6.28	7.92	10.75	12.50			17.63
SCH.40	6.63	7.94	10.75	12.75	13.07	14.94	16.81
SCH.80	6.63	7.57	10.75	12.75	12.41	14.21	16.01
HDPE	6.92	7.90	11.75	14.45			18.07
C900 (DR 18)	6.90	7.98	11.10	13.20	13.50	15.35	17.20
IPS (DR 32.5)	6.63	8.06	10.75	12.75	13.09	14.96	16.83
DIP (UL CLASS 56)	6.90	8.15	11.10	13.20	14.26	16.66 (CLASS 51)	18.44

Side Plate Pipe Port	Pipe Connector 8"	Pipe Connector 8"-12"	Pipe Connector 8"-12"	Top Adapter 12"	Top Adapter 16"	Side Plate Pipe Port
Max. 6.4" Open	8" Spigot = 7.9" OD	10" OD < 12.4"	12" Spigot = 12.4" OD	12" Spigot = 12.4" OD	16" Spigot = 16.64" OD	Max. 13.4" Open
						
Field Core Hole to Size	Bell End Connection Over 8" Spigot	Cut 8" Spigot | Core (Expand) Hole to 10" OD	Gasketed Bell End Over 12" Spigot	Gasketed Bell End Over 12" Spigot	Bell End Connection Over 16" Spigot	Field Core Hole to Size
2476600003 (Part #)	2476631200 (Part #)	2476631200 (Part #)	2476631200 (Part #)	3085857 (Part #)	2476842000 (Part #)	2476600003 (Part #)

Managing water better since 1955.
950 Winter Street
Waltham, MA 02451
wavin.us.com
wavintechsupport@orbia.com

Title: AquaCell Compatible Pipe Connections

The design details/specifications presented in this document are for informational & reference purposes only and are subject to change without notice. Responsibility for design of any AquaCell system rests solely with the original design engineer of record. For questions, contact: wavintechsupport@orbia.com.

Drawn by: HJD	Approved by:
Scale: NTS	Revision: 3
AQ-200-1	Date: 10/27/2026