




Core Design Concepts Discussed:



Recursive Functions and their Evaluation

Harley Eades III

Recursive Functions in OCaml

Syntax

```
# let rec f x = e;;
```

Recursive Functions in OCaml

Syntax

function
name



```
# let rec f x = e;;
```

Recursive Functions in OCaml

Syntax

function
name
↓
let rec f x = e;;
↑
argument


Recursive Functions in OCaml

Syntax

function
name
↓
let rec f x = e;;
↑
argument

Can call
f.
↓

Core Design Concepts:



But, what about performance?

The Function Call Stack

Activation Record:

The location in memory where an executing function stores its bindings.

Activation records are sometimes referred to as frames.

Consider evaluating the following function:

```
1: let cube n =  
2:   let c = n*n*n in  
3:     c;;  
4: let main =  
5:   let n = 5 in  
6:   let ans = cube n in  
7:     ans;;  
8: main;;
```

The Function Call Stack

Activation Record:


The location in memory where an executing function stores its binding.

Activation records are sometimes referred to as frames.

Consider evaluating the following function:

```
1: let cube n =  
2:   let c = n*n*n in  
3:     c;;  
4: let main =  
5:   let n = 5 in  
6:   let ans = cube n in  
7:     ans;;  
8: main;;
```

Core Design Concepts:



Activation Record: program initialization

Frame	Symbol	Value
init line: 8	cube main	<fun> <fun>

The Function Call Stack

Activation Record:


The location in memory where an executing function stores its binding.

Activation records are sometimes referred to as frames.

Consider evaluating the following function:

```
1: let cube n =
2:   let c = n*n*n in
3:     c;;
4: let main =
5:   let n = 5 in
6:   let ans = cube n in
7:     ans;;
8: main;;
```

Core Design Concepts:



Activation Record: program initialization


Frame	Symbol	Value
init line: 8	cube main	<fun> <fun>

Activation Record: after calling `main`

Frame	Symbol	Value
init line: 8	cube main	<fun> <fun>
main line: 6	n ans	5 ?

The Function Call Stack

Core Design Concepts:



Activation Record:

The location in memory where an executing function stores its binding.


Activation records are sometimes referred to as frames.

Consider evaluating the following function:

```
1: let cube n =
2:   let c = n*n*n in
3:     c;;
4: let main =
5:   let n = 5 in
6:   let ans = cube n in
7:     ans;;
8: main;;
```


Activation Record: after calling main

Frame	Symbol	Value
init line: 8	cube main	<fun> <fun>
main line: 6	n ans	5 ?
cube line: 2	n c	5 125



The Function Call Stack

Core Design Concepts:



Activation Record:

The location in memory where an executing function stores its binding.


Activation records are sometimes referred to as frames.

Consider evaluating the following function:

```
1: let cube n =
2:   let c = n*n*n in
3:     c;;
4: let main =
5:   let n = 5 in
6:   let ans = cube n in
7:     ans;;
8: main;;
```

Activation Record: after calling main

Frame	Symbol	Value
init line: 8	cube main	<fun> <fun>
main line: 6	n ans	5 125
cube line: 2	n c	5 125



Evaluating Recursive Functions

Core Design Concepts:


Evaluation

Consider evaluating the following recursive function:

```
1. let rec ackermann m n =  
2.   if m == 0  
3.   then let ret = n + 1 in ret  
4.   else if n == 0  
5.       then let ack  = ackermann (m - 1) 1 in ack  
6.       else let ack1 = ackermann m (m - 1) in  
7.           let ack2 = ackermann (m - 1) ack1 in  
8.               ack2  
9.  
10. let main =  
11.   let m = 1 in  
12.   let n = 0 in  
13.   let ans1 = ackermann m n in  
14.   let ans2 = ackermann m m in  
15.   ans1 + ans2  
16.  
17. main;;
```

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.     let ans1 = ackermann m n in
14.     let ans2 = ackermann m m in
15.       ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
init line: 17	ackermann main	<fun> <fun>

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.   let ans1 = ackermann m n in
14.   let ans2 = ackermann m m in
15.   ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
init line: 17	ackermann main	<fun> <fun>
main line: 14	m n ans1 ans2	1 0 ? ?

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.   let ans1 = ackermann m n in
14.   let ans2 = ackermann m m in
15.   ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
init line: 17	ackermann main	<fun> <fun>
main line: 14	m n ans1 ans2	1 0 ? ?
ackermann line: 5	m n ack	1 0 ?

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.     let ans1 = ackermann m n in
14.     let ans2 = ackermann m m in
15.       ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
init line: 17	ackermann main	<fun> <fun>
main line: 13	m n ans1 ans2	1 0 ? ?
ackermann line: 5	m n ack	1 0 ?
ackermann line: 3	m n ret	0 1 2

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.     let ans1 = ackermann m n in
14.     let ans2 = ackermann m m in
15.       ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
init line: 17	ackermann main	<fun> <fun>
main line: 13	m n ans1 ans2	1 0 ? ?
ackermann line: 5	m n ack	1 0 2
ackermann line: 3	m n ret	0 1 2

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.     let ans1 = ackermann m n in
14.     let ans2 = ackermann m m in
15.       ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
init line: 17	ackermann main	<fun> <fun>
main line: 14	m n ans1 ans2	1 0 2 ?
ackermann line: 5	m n ack	1 0 2
ackermann line: 3	m n ret	0 1 2

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.     let ans1 = ackermann m n in
14.     let ans2 = ackermann m m in
15.       ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
main line: 14	m	1
	n	0
	ans1	2
	ans2	?
ackermann line: 7	m	1
	n	1
	ack1	?
	ack2	?

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.       then let ack  = ackermann (m - 1) 1 in ack
6.       else let ack1 = ackermann m (m - 1) in
7.           let ack2 = ackermann (m - 1) ack1 in
8.               ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.   let ans1 = ackermann m n in
14.   let ans2 = ackermann m m in
15.   ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
main line: 14	m	1
	n	0
	ans1	2
	ans2	?
ackermann line: 7	m	1
	n	1
	ack1	?
	ack2	?
ackermann line: 5	m	1
	n	0
	ack	?

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.     let ans1 = ackermann m n in
14.     let ans2 = ackermann m m in
15.       ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
main line: 14	m	1
	n	0
	ans1	2
	ans2	?
ackermann line: 7	m	1
	n	1
	ack1	?
	ack2	?
ackermann line: 5	m	1
	n	0
	ack	?
ackermann line: 3	m	0
	n	1
	ret	2

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.     let ans1 = ackermann m n in
14.     let ans2 = ackermann m m in
15.       ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
main line: 14	m	1
	n	0
	ans1	2
	ans2	?
ackermann line: 7	m	1
	n	1
	ack1	?
	ack2	?
ackermann line: 5	m	1
	n	0
	ack	2
ackermann line: 3	m	0
	n	1
	ret	2

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.     let ans1 = ackermann m n in
14.     let ans2 = ackermann m m in
15.       ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
main line: 14	m	1
	n	0
	ans1	2
	ans2	?
ackermann line: 7	m	1
	n	1
	ack1	2
	ack2	?
ackermann line: 5	m	1
	n	0
	ack	2
ackermann line: 3	m	0
	n	1
	ret	2

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.     let ans1 = ackermann m n in
14.     let ans2 = ackermann m m in
15.       ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
main line: 14	m	1
	n	0
	ans1	2
	ans2	?
ackermann line: 7	m	1
	n	1
	ack1	2
	ack2	?
ackermann line: 5	m	1
	n	0
	ack	2
ackermann line: 3	m	0
	n	1
	ret	2
ackermann line: 3	m	0
	n	2
	ret	3

Evaluating Recursive Functions

Core Design Concepts:




Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.     let ans1 = ackermann m n in
14.     let ans2 = ackermann m m in
15.       ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
main line: 14	m	1
	n	0
	ans1	2
	ans2	?
ackermann line: 7	m	1
	n	1
	ack1	2
	ack2	3
ackermann line: 5	m	1
	n	0
	ack	2
ackermann line: 3	m	0
	n	1
	ret	2
ackermann line: 3	m	0
	n	2
	ret	3

Evaluating Recursive Functions

Core Design Concepts:



Consider evaluating the following recursive function:

```
1. let rec ackermann m n =
2.   if m == 0
3.   then let ret = n + 1 in ret
4.   else if n == 0
5.         then let ack  = ackermann (m - 1) 1 in ack
6.         else let ack1 = ackermann m (m - 1) in
7.               let ack2 = ackermann (m - 1) ack1 in
8.                 ack2
9.
10. let main =
11.   let m = 1 in
12.   let n = 0 in
13.     let ans1 = ackermann m n in
14.     let ans2 = ackermann m m in
15.       ans1 + ans2
16.
17. main;;
```

Frame	Symbol	Value
main line: 14	m	1
	n	0
	ans1	2
	ans2	3
ackermann line: 7	m	1
	n	1
	ack1	2
	ack2	3
ackermann line: 5	m	1
	n	0
	ack	2
ackermann line: 3	m	0
	n	1
	ret	2
ackermann line: 3	m	0
	n	2
	ret	3