

BOE Costing Portal

Technical Whitepaper

The system module by module: access, the import register, ingestion, the costing engine, simulation and export.

Source: docs/WHITEPAPER.md

CONTENTS

- | | |
|-----------------------------------|------------------------------------|
| 1. The system in one view | 6. Module 4 — Costing engine |
| 2. Architecture | 7. Module 5 — Simulation workbench |
| 3. Module 1 — Access and identity | 8. Module 6 — Export |
| 4. Module 2 — Import register | 9. Data model |
| 5. Module 3 — Ingestion | 10. Operations |


The BOE Costing Portal is a web application that turns an ICEGATE Bill of Entry into a structured import record, computes the landed cost of every line item on it, and lets that costing be re-run under hypothetical inputs without disturbing the record it came from.

It answers one question, repeatedly and exactly: **what did this item cost me, landed, per piece?**

The output format is the C-SHEET workbook the business has always costed against. What the portal changes is that nobody transcribes figures into it by hand, and the arithmetic behind it is pinned by tests.

1. The system in one view

The portal is built as six modules. Each owns one part of the journey from a government PDF to a defensible cost per piece, and each is described in its own section below.




Six modules, and the gate they sit behind.

#	MODULE	OWNS	STATUS
1	Access and identity	who may open the portal at all	in development
2	Import register	the list of records, filtering, retrieval	live
3	Ingestion	PDF upload, extraction, document storage	live
4	Costing engine	the landed-cost model	live
5	Simulation workbench	scenarios and their comparison	live; per-scenario password in development
6	Export	the C-SHEET workbook, actual and simulated	live

Status is given once, here, so the rest of this document can describe the system as a whole rather than annotating every paragraph.

2. Architecture

Two deployable services and one database.



Two deployable services and one database. Only the parser can write.

2.1 Why the work is split in two

The portal is TypeScript and cannot read a PDF. The extraction is positional — `pdfplumber`, by x-coordinate — which is what lets it survive watermark bleed, OCR spelling variants and multi-invoice numbering. Rewriting that in TypeScript would mean re-deriving every one of those cases in a language with no comparable PDF layout library.

So one Python process exists, and it is needed for exactly two actions:

ACTION	NEEDS THE PARSER SERVICE
PDF upload	yes
Excel download, actual and simulated	yes
Records list, filters, sorting	no
Costing, simulations, comparisons	no

Everything else is Postgres reads plus arithmetic in the browser.

2.2 Two deployments, not one

The two services deploy as separate Vercel projects from the same repository. A Next.js app and a Python function both claim `/api/*`, and inside a single project Next answers first — requests never reach Python. The parser therefore needs a project with **no framework**. A `vercel.json` at the repository root is also applied to the portal whatever root directory it is configured with, so `parser/` is entirely self-contained and nothing sits at the repository root. Neither project can affect the other.

They are joined by one variable, `NEXT_PUBLIC_API_BASE_URL`, which can point at localhost, a container, or a deployment; the portal does not care which. `NEXT_PUBLIC_*` values are compiled in at build time, so changing one requires a redeploy rather than a restart.

2.3 One source of truth for the model

`frontend/src/lib/costing.ts` is the single implementation of the costing model. It is pure and dependency-free: no Supabase, no React, no clock. The same inputs always give the same outputs, which is what makes it fully unit-testable in isolation.

The simulation export does not redo the arithmetic server-side. The portal posts the costing result it is already displaying and the parser service lays it into the workbook template. Two implementations of one model, shown to the same user from the same page, would eventually disagree; this way there is only one.

3. Module 1 — Access and identity

Access is the first module because it is the gate every other module sits behind. Nothing else in the system can make a distinction it does not make.

3.1 Sign-in

The portal is entered through Supabase Auth. Every page requires a session; without one the request is redirected to sign-in. The anon key compiled into the client bundle stops being a key to the data and becomes only the key that lets a browser ask to sign in — the Postgres policies behind it grant to *authenticated*, not to *anyone*.

This distinction is the whole point of the module. Data access is decided by policies at the database, not by which screen the interface chooses to render, so a route that forgets to check is not a way in.

3.2 What each credential can do

Three credentials exist, and they are deliberately unequal.

CREDENTIAL	HELD BY	CAN
anon key	the browser, in the client bundle	read the import tables for a signed-in session; write nothing
service_role key	the parser service only, server-side	read and write everything; bypasses RLS; never reaches a browser
PARSER_ADMIN_TOKEN	operators	the parser's administrative routes — record listing, retrieval, deletion, supporting-document upload

Writes to the import tables are closed to the browser entirely. The parser service performs them with the `service_role` key, which is why ingestion is the only path that can create or change a Bill of Entry.

The administrative routes **fail closed**: with no token configured they return 503 rather than opening, so an unset variable in a new environment cannot quietly reopen the door.

3.3 Identity downstream

A session gives the rest of the system something it otherwise lacks — a person to attribute an action to.

- **Scenarios acquire an owner.** `boe_scenarios` carries a `created_by` referencing the authenticated user, which is what makes a per-scenario password (§7.6) meaningful and what any future revision history will key on.
- **The parser's browser-facing routes verify a session.** Upload and the two Excel routes are reached from the browser; with a session they can check a token, leaving `PARSER_ADMIN_TOKEN` as a break-glass key rather than the only guard.
- **Excel download moves off a plain link.** An `<a href>` carries no Authorization header, so the export is fetched with the session attached, or issued as a short-lived signed URL.

4. Module 2 — Import register

The register is the front door: every Bill of Entry on file, in one list.

Records are fetched once per page load and filtered, sorted and paged in the browser. For a few hundred records that is instant and avoids a round trip per keystroke; `LIST_LIMIT` is the guard on that choice.

CONTROL	BEHAVIOUR
Supplier, BOE number	substring match, case-insensitive
Date range, value range	either end may be left open
Sorting	any column, ascending or descending; undated records sort last in both directions
Paging	ten rows per page, most recent first

Filters combine, and the record count reads *n of m* whenever any is active, so the amount of hidden data is always on screen.

Opening a record shows the shipment facts — supplier, invoice number and date, BE date, AWB/HAWB, importer — the costing table, the licence rows, and the indexed documents. Six headline tiles carry exchange


rate, invoice value, freight, expenses, duty in cost and average cost per piece.

Provisional and confirmed figures are distinguished on sight. Exchange rate and freight are routinely estimated at costing time and settle weeks later. Each carries a status, shown green when confirmed and red while still provisional, and anything never marked confirmed counts as provisional: silence is not confirmation. A system that stored only the latest value could not make this distinction at all.

5. Module 3 — Ingestion

Ingestion converts a printed government form into rows.

An ICEGATE Bill of Entry is a fixed-layout form, typically 7–30 pages, printed to PDF. It has no data layer — no XML, no embedded metadata. Every stored field is recovered from the printed page.



The parse pipeline, from PDF bytes to stored record.

Two reading strategies are used deliberately. Parts I and II print a label beside each value, so a regex anchored on the label finds it. Parts III and IV are dense grids where one row carries BCD, SWS and IGST as bare numbers under column headers printed pages earlier — there, the x-coordinate is the only thing that says which number is which.

Page furniture is removed before words are assembled rather than after. The form sets its content between 7pt and 14pt; the diagonal *ASSESSED COPY* watermark and the sideways section labels fall outside that band and fuse with real tokens when they are not filtered out. Filtering by character size removes them at source, so nothing downstream has to guess which letters are real.

[docs/PARSER.md](#) is the field-by-field reference for this module: every field, where on the form it comes from, and the circumstances that change the answer.

Ingestion also owns the document store. The uploaded PDF is written to a private Storage bucket and indexed in `boe_documents`; the record page signs a fresh link per render, expiring an hour later. Supporting documents — invoice, packing list, certificate of origin — are extracted heuristically, so their output is treated as a hint and the raw text is always retained.

Re-uploading a Bill of Entry replaces its items and licences wholesale rather than duplicating them, and brings any field still marked provisional back in line with the new parse. Fields confirmed by a person are never overwritten, and every change is logged to `boe_field_history`.

6. Module 4 — Costing engine

Landed cost is **value-proportional apportionment of a single expense pool**. For each item i :

```
declared INR    Fi = unit_price_usd x qty x exchange_rate
value share     si = Fi / SUM(F)
expense share    Hi = expense_pool x si
duty in cost     Gi = BCD + SWS
cost per piece  Ii = (Fi + Gi + Hi) / qty
selling price    Ji = Ii x (1 + margin%)
```

and, separately, a reconciliation of computed against assessed value:

```
assess computed Oi = Fi + freight_i + misc_i + insurance_i
assess actual   Pi = boe_items.assess_value
difference       Qi = Oi - Pi
```

Change any expense and every item's slice moves in proportion. Change an item's price and the shares are recomputed before the split.

6.1 The expense pool

The pool is the sum of every cost of getting the consignment onto the shelf: freight, insurance, clearance, misc charges (freight 2), supplier freight, bank charges, own bank charges, and others. All eight are apportioned.


Costings produced here read higher than the legacy spreadsheet on any consignment where the last four are non-zero: the template captured and displayed them but did not sum them into cost per piece. The Excel export writes the corrected total, so workbook and screen agree, and the C-SHEET formulas are evaluated by hand in `costing.test.ts` and checked against the engine to keep them that way.

6.2 IGST is excluded from cost

IGST is a creditable input tax: it is recovered, so it is cash flow rather than cost. Duty in cost is BCD plus SWS. IGST is reported separately as part of the cyber-receipt outflow.

6.3 Cash BCD versus licence-paid BCD

An item's BCD may be paid in cash or met by debiting an export-incentive licence, and the form records these in different places.



An item's real BCD comes from one of two places, never both.


On a fully licence-paid Bill of Entry, page 1 shows **BCD 0** while SWS and IGST are non-zero — SWS being 10% of a BCD never paid in cash. Section G is then the only source of the real figure. A cross-check that holds on real forms: Section G's per-item duty foregone equals the sum of that item's Section F licence debits, and the total is exactly 10× the SWS on page 1.

6.4 Duty amounts, not duty rates

The Bill of Entry records duty *amounts*, never *rates*. Effective rates are back-computed from what customs actually charged, which is what allows duty to respond to a change in value in a simulation. Where an item has no assessable value to back-compute from, the engine holds it at its actual duty and flags it rather than multiplying by a zero rate and reporting nil duty.

6.5 Where an input comes from

An expense figure is resolved in a fixed order.



Where an expense figure comes from, in fixed order.

An operator-maintained value wins over what the parser read, which wins over zero. This is why a corrected parse does not silently override a figure a person has already confirmed.

7. Module 5 — Simulation workbench

A scenario is a saved what-if against one Bill of Entry.

7.1 Null means inherit

Every adjustable column on a scenario is nullable, and null means *inherit the actual*. A new scenario reproduces the actual costing exactly until something is deliberately changed, so any difference on screen is a difference the user made. This is what makes a scenario diffable against the record rather than a disconnected copy.

Per-item overrides are sparse for the same reason: a row exists only for an item actually touched, null columns within it still inherit, and an override carrying no change is discarded on save.

7.2 Scenario inputs

INPUT	BEHAVIOUR
Duty mode	fixed holds duty at what customs charged; float recomputes it from the BOE's effective rates
Exchange rate	INR per USD, with a confirmed / provisional status
Freight	typed as a total, or computed as rate × weight, volume or containers; also status-carrying
Freight mode	Air / Sea / Road / Courier / Other — a label; it changes no figure
Expenses	insurance, clearance, misc, supplier freight, bank charges, own bank charges, others
Margin	drives the selling-price columns of the export

A half-filled freight calculator never wins: a partially configured basis must not silently zero out freight, and choosing a basis is not itself a freight figure, so it must not drop the inherited actual either.

7.3 Per-item adjustment

Price and quantity may be overridden per item. An empty box shows the actual as its placeholder, so an untouched row still reads as the number it will use.

FOC items keep their declared value in the apportionment base. The goods still ship and are still assessed, so removing their value would shift freight onto the paid items and overstate their cost. A separate toggle decides whether duty applies.

Duplicated items are extra rows existing only in the scenario, carrying their own description, price and quantity. They always derive duty from their source's *rates*, even when duty is fixed: locking a copy to the source's actual amounts would charge the same customs payment twice. Duplicating a copy points at the same original, so the chain cannot go stale.

7.4 Keyed by (invsno, itemsn)

Scenario rows key on the natural key rather than a row id. Re-ingesting a Bill of Entry deletes and reinserts its items wholesale, which would strand every id-based reference. The natural key survives it, and it is the same key Parts III and IV of the form use.

7.5 Comparison

Every scenario on a record is costed on every render, in the browser — pure arithmetic over a few dozen rows, which is what makes the controls respond as they are typed. The comparison strip shows the active scenario against the actual, and a table lists the actual and every scenario side by side. Unsaved edits are included in both, so a comparison always reflects what is on screen.

7.6 Scenario locking

A scenario may carry a password. Once it is set and the scenario saved, opening that scenario — its inputs, its item adjustments, its costed rows — requires the password; without it the scenario is listed by name and nothing more is shown.

Enforcement is at the data layer, not in the interface. The portal reads scenario tables directly from Postgres, so a lock that only hides a panel is a curtain rather than a lock — the row is one query away, and it is a query the client is otherwise entitled to make. The password is stored as an Argon2id hash that is never selectable; verification runs as a `security definer` function returning a short-lived grant, and the row-level policy releases the scenario body only against that grant. The owner can clear the lock, so a forgotten password costs a reset rather than the costing.

Three consequences follow from the rest of the design:

- **The lock is on the scenario, never on the record.** The actual costing must stay readable; the value of a scenario is being diffable against it, and locking the record would break the comparison for every scenario on that Bill of Entry, including unlocked ones.
- **The comparison table degrades honestly.** A locked scenario appears as a named row with its figures withheld — not omitted, which would misstate how many scenarios exist, and not costed-but-hidden, which would leak the answer through the comparison.
- **A password takes effect on save,** consistent with everything else in the workbench: what is on screen is what is being compared, saved or not.

A scenario password is a sharing control between people who are already signed in. It is not a second factor and not a substitute for Module 1.

8. Module 6 — Export

Both exports produce the same C-SHEET workbook with live formulas, so a recipient can trace any figure through the sheet rather than receiving a flat dump.

A simulation exports through the same template, filled with the scenario's figures, with a red banner naming the scenario so a what-if cannot be mistaken for the actual record. Three inputs a scenario needs that an actual record does not:

INPUT	PURPOSE
<code>margin_pct</code>	column J, in place of the actual's fixed 102%
<code>other_charges</code>	I8 , which an actual record has no field for
<code>foc_keys</code>	switches those rows to $=(G+H)/C$, dropping the goods value while leaving it in F so the row still absorbs freight and duty

Duty foregone is deliberately not passed to the export. The engine has already resolved each item's BCD to whichever of cash or licence applies, and letting the workbook substitute a foregone amount for a zero BCD would overwrite duty a scenario waived on purpose.

Row numbering is contiguous `1..n` in display order, because the C-SHEET reads one sheet's row `10+i` from another's row `12+i` ; a gap shifts every duty reference below it.

9. Data model

TABLE	HOLDS	WRITTEN BY
boes	one row per Bill of Entry, keyed by BE number	parser service
boe_items	line items, keyed <code>(be_no, invsno, itemsn)</code> , plus a document-wide <code>global_sno</code>	parser service
boe_licences	licence debits per item; reference only	parser service
boe_documents	index of the private Storage bucket	parser service
boe_variable_fields	the cost figures estimated at costing time, each with a provisional / confirmed status	parser service
boe_field_history	audit trail of changes to those figures	parser service
boe_scenarios	one saved what-if; every input nullable	portal
boe_scenario_items	sparse per-item overrides and added rows	portal
document_extractions	heuristic fields from supporting documents	parser service

Migrations run in numeric order and every statement is `if not exists` , so re-running one changes nothing. Two constraints carry meaning rather than hygiene. Two scenarios on the same record may not share a name, because the comparison identifies columns by name and the same name twice is unreadable. And `global_sno` must be contiguous in display order, for the workbook reason in §8.

A Bill of Entry carries IEC, GSTIN, supplier identities and unit prices, so sample documents are kept out of version control.

10. Operations

10.1 Configuration

SETTING	SERVICE	PURPOSE
<code>SUPABASE_URL</code> , <code>SUPABASE_KEY</code>	parser	<code>service_role</code> credentials for writing
<code>NEXT_PUBLIC_SUPABASE_*</code>	portal	project URL and anon key
<code>NEXT_PUBLIC_API_BASE_URL</code>	portal	where the parser service answers
<code>ALLOWED_ORIGINS</code>	parser	which origins may call it
<code>PARSER_ADMIN_TOKEN</code>	parser	administrative routes; unset means closed

Both services point at the same Supabase project.

10.2 Verification

Three independent checks, each catching a different class of error.

The document reconciles against itself. The form states its own assessable value; the parser computes one independently as `inv_value × exchange_rate + freight + insurance + misc` . The two agree to the paisa on a correct parse, and a gap means an input is in the wrong unit — the single most useful diagnostic in the system.

BOE	COMPUTED	FORM STATES	GAP
3168452	4,204,710.42	4,204,710.41	+0.01
2898472	616,041.60	616,041.60	0.00

Screen and workbook agree. The C-SHEET formulas are evaluated by hand in the test suite and checked against the engine.

Invariants hold. Switching duty mode with nothing else changed moves no number; a new scenario reproduces the actual costing exactly. Both are tests, not conventions.

`npm test` runs the engine tests and needs no database.

10.3 Deployment

COMPONENT	ADDRESS	RUNTIME
Portal	<code>https://boe-costing-portal.vercel.app</code>	Next.js 16 on Vercel
Parser service	<code>https://boe-costing-portal-backend.vercel.app</code>	FastAPI on Vercel
Database, auth, storage	Supabase, project <code>1qur1ldfpesbjhrkkczv</code>	Postgres 17

Two Vercel projects from one repository: the portal with root directory `frontend` and zero configuration, the parser with root directory `parser` , framework **Other**, and its own `vercel.json` . Set the portal's API base URL to the parser's address and the parser's allowed origins to the portal's.

They are two projects rather than one because a single project cannot serve both a Next.js app and a Python function under one `/api` namespace: the runtimes contend for the same routes, and the request reaches whichever the platform resolves first.

Sign-in is Google OAuth through Supabase Auth, so the portal's callback (`/auth/callback`) must appear in the Supabase redirect allowlist for **every** origin it is served from — production and local alike. An origin that is missing completes the whole round trip at Google and only then fails, on the way back, which makes it look like a credentials problem rather than a configuration one.

The parser also ships a Dockerfile and runs as a container anywhere, which is the route to take when a Bill of Entry is large enough to press against a serverless time limit.