



HeuristicLab

A Paradigm-Independent and Extensible
Environment for Heuristic Optimization

Algorithm and Experiment Design with HeuristicLab

An Open Source Optimization Environment for
Research and Education

S. Wagner, G. Kronberger

Heuristic and Evolutionary Algorithms Laboratory (HEAL)

School of Informatics/Communications/Media, Campus Hagenberg

University of Applied Sciences Upper Austria



HEAL

Heuristic and Evolutionary
Algorithms Laboratory



Josef Ressel-Zentrum
HEUREKA!

Instructor Biographies



- Stefan Wagner
 - Full professor for complex software systems (since 2009)
University of Applied Sciences Upper Austria
 - Co-founder of the HEAL research group
 - Project manager and chief architect of HeuristicLab
 - PhD in technical sciences (2009)
Johannes Kepler University Linz, Austria
 - Associate professor (2005 – 2009)
University of Applied Sciences Upper Austria
 - <http://heal.heuristiclab.com/team/wagner>



- Gabriel Kronberger
 - Full professor for business intelligence (since 2011)
University of Applied Sciences Upper Austria
 - Member of the HEAL research group
 - Architect of HeuristicLab
 - PhD in technical sciences (2010)
Johannes Kepler University Linz, Austria
 - Research assistant (2005 – 2011)
University of Applied Sciences Upper Austria
 - <http://heal.heuristiclab.com/team/kronberger>



Agenda

- Objectives of the Tutorial
- Introduction
- Where to get HeuristicLab?
- Plugin Infrastructure
- Graphical User Interface
- Available Algorithms & Problems
- **Demonstration Part I: Working with HeuristicLab**
- **Demonstration Part II: Data-based Modeling**
- Some Additional Features
- Planned Features
- Team
- Suggested Readings
- Bibliography
- Questions & Answers

Objectives of the Tutorial




- Introduce general motivation and design principles of HeuristicLab
- Show where to get HeuristicLab
- Explain basic GUI usability concepts
- Demonstrate basic features
- Demonstrate editing and analysis of optimization experiments
- Demonstrate custom algorithms and graphical algorithm designer
- Demonstrate data-based modeling features
- Outline some additional features

Introduction



- Motivation and Goals
 - graphical user interface
 - paradigm independence
 - multiple algorithms and problems
 - large scale experiments and analyses
 - parallelization
 - extensibility, flexibility and reusability
 - visual and interactive algorithm development
 - multiple layers of abstraction

- Facts
 - development of HeuristicLab started in 2002
 - based on Microsoft .NET and C#
 - used in research and education
 - second place at the *Microsoft Innovation Award 2009*
 - open source (GNU General Public License)
 - version 3.3.0 released on May 18th, 2010
 - latest version 3.3.9 released on October 11th, 2013



Where to get HeuristicLab?





- Download binaries
 - deployed as ZIP archives
 - latest stable version 3.3.9
 - released on October 11th, 2013
 - daily trunk builds
 - <http://dev.heuristiclab.com/download>
- Check out sources
 - SVN repository
 - HeuristicLab 3.3.9 tag
 - <http://dev.heuristiclab.com/svn/hl/core/tags/3.3.9>
 - current development trunk
 - <http://dev.heuristiclab.com/svn/hl/core/trunk>
- License
 - GNU General Public License (Version 3)
- System requirements
 - Microsoft .NET Framework 4.0 Full Version
 - enough RAM and CPU power ;-)


A screenshot of the HeuristicLab Development Homepage. The page features a header with the HeuristicLab logo and navigation links for Home, Status Board, View Tickets, Timeline, Browse Source, and Search. Below the header is a search bar and a link to the WikiStart. The main content area has a yellow banner at the top with the text "Welcome to the HeuristicLab Development Homepage". It includes sections for "At a glance", "Getting Started", "Developers", "Publications and Projects", and "Citation". There are also three boxes labeled "Users", "Developers", and "Download" with their respective icons and links. At the bottom, there is an "Imprint" section and a "Download in other formats" link.

Plugin Infrastructure

- HeuristicLab consists of many assemblies
 - 132 plugins in HeuristicLab 3.3.9
 - plugins can be loaded or unloaded at runtime
 - plugins can be updated via internet
 - application plugins provide GUI frontends
- Extensibility
 - developing and deploying new plugins is easy
 - dependencies are explicitly defined, automatically checked and resolved
 - automatic discovery of interface implementations (service locator pattern)
- Plugin Manager
 - GUI to check, install, update or delete plugins



Plugin Architecture




Graphical User Interface




- HeuristicLab GUI is made up of views
 - views are visual representations of content objects
 - views are composed in the same way as their content
 - views and content objects are loosely coupled
 - multiple different views may exist for the same content
- Drag & Drop
 - views support drag & drop operations
 - content objects can be copied or moved (shift key)
 - enabled for collection items and content objects

Graphical User Interface



Graphical User Interface

- ViewHost
 - control which hosts views
 - right-click on windows icon to switch views
 - double-click on windows icon to open another view
 - drag & drop windows icon to copy contents



Available Algorithms & Problems

Algorithms

- Evolution Strategy
- Genetic Algorithm
- Genetic Programming
- Hungarian Algorithm
- Island Genetic Algorithm
- Island Offspring Selection Genetic Algorithm
- LM-BFGS
- Local Search
- NSGA-II
- Offspring Selection Genetic Algorithm
- Particle Swarm Optimization
- Relevant Alleles Preserving GA (RAPGA)
- Robust Taboo Search
- SASEGASA
- Scatter Search
- Simulated Annealing
- Tabu Search
- User-defined Algorithm
- Variable Neighborhood Search
- Performance Benchmarks
- Cross Validation
- Gaussian Process Regression and Least-Squares Classification
- k-Means
- Linear Discriminant Analysis
- Linear Regression
- Multinomial Logit Classification
- Nearest Neighbor Regression and Classification
- Neural Network Regression and Classification
- Random Forest Regression and Classification
- Support Vector Regression and Classification

Problems

- Artificial Ant
- Classification
- Clustering
- External Evaluation Problem
- Job Shop Scheduling
- Knapsack
- Lawn Mower
- Linear Assignment
- OneMax
- Quadratic Assignment
- Regression
- Single-Objective Test Function
- Symbolic Classification
- Symbolic Regression
- Symbolic Time-Series Prognosis
- Traveling Salesman
- User-defined Problem
- Vehicle Routing

Agenda


- Objectives of the Tutorial
- Introduction
- Where to get HeuristicLab?
- Plugin Infrastructure
- Graphical User Interface
- Available Algorithms & Problems
- **Demonstration Part I: Working with HeuristicLab**
- **Demonstration Part II: Data-based Modeling**
- Some Additional Features
- Planned Features
- Team
- Suggested Readings
- Bibliography
- Questions & Answers

Demonstration Part I: Working with HeuristicLab



- Create, Parameterize and Execute Algorithms
- Save and Load Items
- Create Batch Runs and Experiments
- Multi-core CPUs and Parallelization
- Analyze Runs
- Analyzers
- Building User-Defined Algorithms

HeuristicLab Optimizer



The screenshot shows the HeuristicLab Optimizer 3.3.3.5448 application window. The title bar reads "HL HeuristicLab Optimizer 3.3.3.5448". The menu bar includes File, Edit, View, and Help. A toolbar with various icons is visible above the main content area. The left sidebar has a tree view with "Clipboard" selected. The main content area is titled "Start Page" and displays the following text:

HeuristicLab Optimizer 3.3.3.5448

Follow these steps to start working with HeuristicLab Optimizer:



- 1. Open an algorithm**
 - click (New Item) in the toolbar and select an algorithm or click (Open File) in the toolbar and load an algorithm from a file
- 2. Open a problem in the algorithm**
 - in the Problem tab of the algorithm click (New Problem) and select a problem or click (Open Problem) and load a problem from a file
- 3. Set parameters**
 - set problem parameters in the Problem tab of the algorithm
 - set algorithm parameters in the Parameters tab of the algorithm

Below this, there is a "Samples" section with a red box around it. It contains a table with two columns: "Name" and "Description". The "Name" column lists "Evolution Strategy - Griewank", "Genetic Algorithm - TSP", and "Genetic Algorithm - ...". The "Description" column provides details for each sample.


| Name | Description |
|-------------------------------|--|
| Evolution Strategy - Griewank | An evolution strategy which solves the 10-dimensional Griewank test function |
| Genetic Algorithm - TSP | A genetic algorithm which solves the "ch130" traveling salesman problem (imported from "http://www.math.uwaterloo.ca/tsp/world/ch130.tsp") |
| Genetic Algorithm - ... | A genetic algorithm which solves the "kroA100" quadratic assignment problem (imported from "http://www.math.uwaterloo.ca/tsp/world/kroA100.tsp") |

**double-click to open
sample algorithms and problems**


Create Algorithm




Create or Load Problem




Import or Parameterize Problem Data




Parameterize Algorithm



Start, Pause, Resume, Stop and Reset




Inspect Results




Compare Runs

- A run is created each time when the algorithm is stopped
 - runs contain all results and parameter settings
 - previous results are not forgotten and can be compared



Save and Load


- Save to and load from disk
 - HeuristicLab items (i.e., algorithms, problems, experiments, ...) can be saved to and loaded from a file
 - algorithms can be paused, saved, loaded and resumed
 - data format is custom compressed XML
 - saving and loading files might take several minutes
 - saving and loading large experiments requires some memory




Create Batch Runs and Experiments




- Batch runs
 - execute the same optimizer (e.g. algorithm, batch run, experiment) several times
- Experiments
 - execute different optimizers
 - suitable for large scale algorithm comparison and analysis
- Experiments and batch runs can be nested
- Generated runs can be compared afterwards



Create Batch Runs and Experiments




Clipboard




Clipboard

- Store items
 - click on the buttons to add or remove items
 - drag & drop items on the clipboard
 - use the menu to add a copy of a shown item to the clipboard




- Show items
 - double-click on an item in the clipboard to show its view
- Save and restore clipboard content
 - click on the save button to write the clipboard content to disk
 - clipboard is automatically restored when HeuristicLab is started the next time

Start, Pause, Resume, Stop, Reset




Compare Runs




Analyze Runs

- HeuristicLab provides interactive views to analyze and compare all runs of a run collection
 - textual analysis
 - RunCollection Tabular View
 - graphical analysis
 - RunCollection BubbleChart
 - RunCollection BoxPlots
- Filtering is automatically applied to all open run collection views



RunCollection Tabular View



The screenshot shows the HeuristicLab Optimizer interface with the title bar "HL HeuristicLab Optimizer 3.3.3.5837 [Unsaved]". The main window is titled "Genetic Algorithm / RunCollection Tabular View". On the left, there is a sidebar with tabs for "Clipboard" and "RunCollection Tabular View". The "RunCollection Tabular View" tab is selected, showing the following configuration:

- Rows: 30
- Columns: 48

The table displays 30 rows of data, each representing a run of a Genetic Algorithm. The columns are:


| | BestKnownQuality | Best Known Solution | BestQuality | Coordinates | Crossover | CurrentAverageQuality |
|---|------------------|---------------------------|-------------|-------------------|----------------|-----------------------|
| ▶ Genetic Algorithm (Mutation Rate 1%) Run 13 | 5110 | [0:40:38;116;111;114;...] | 16405 | [[334,5909245...] | OrderCrosso... | 16543,13 |
| Genetic Algorithm (Mutation Rate 1%) Run 14 | 5110 | [0:40:38;116;111;114;...] | 14783 | [[334,5909245...] | OrderCrosso... | 15029,02 |
| Genetic Algorithm (Mutation Rate 1%) Run 15 | 5110 | [0:40:38;116;111;114;...] | 14252 | [[334,5909245...] | OrderCrosso... | 14282,89 |
| Genetic Algorithm (Mutation Rate 1%) Run 16 | 5110 | [0:40:38;116;111;114;...] | 13243 | [[334,5909245...] | OrderCrosso... | 13245,95 |
| Genetic Algorithm (Mutation Rate 1%) Run 17 | 5110 | [0:40:38;116;111;114;...] | 13703 | [[334,5909245...] | OrderCrosso... | 13749,98 |
| Genetic Algorithm (Mutation Rate 1%) Run 18 | 5110 | [0:40:38;116;111;114;...] | 13564 | [[334,5909245...] | OrderCrosso... | 13951,09 |
| Genetic Algorithm (Mutation Rate 1%) Run 19 | 5110 | [0:40:38;116;111;114;...] | 15421 | [[334,5909245...] | OrderCrosso... | 15431,74 |
| Genetic Algorithm (Mutation Rate 1%) Run 20 | 5110 | [0:40:38;116;111;114;...] | 14409 | [[334,5909245...] | OrderCrosso... | 15147 |
| Genetic Algorithm (Mutation Rate 1%) Run 21 | 5110 | [0:40:38;116;111;114;...] | 13771 | [[334,5909245...] | OrderCrosso... | 13954,56 |
| Genetic Algorithm (Mutation Rate 1%) Run 22 | 5110 | [0:40:38;116;111;114;...] | 14529 | [[334,5909245...] | OrderCrosso... | 14532,3 |
| Genetic Algorithm (Mutation Rate 5%) Run 13 | 5110 | [0:40:38;116;111;114;...] | 13095 | [[334,5909245...] | OrderCrosso... | 13642,7 |
| Genetic Algorithm (Mutation Rate 5%) Run 14 | 5110 | [0:40:38;116;111;114;...] | 12403 | [[334,5909245...] | OrderCrosso... | 12818,09 |
| Genetic Algorithm (Mutation Rate 5%) Run 15 | 5110 | [0:40:38;116;111;114;...] | 14091 | [[334,5909245...] | OrderCrosso... | 14653,98 |
| Genetic Algorithm (Mutation Rate 5%) Run 16 | 5110 | [0:40:38;116;111;114;...] | 12595 | [[334,5909245...] | OrderCrosso... | 13297,99 |
| Genetic Algorithm (Mutation Rate 5%) Run 17 | 5110 | [0:40:38;116;111;114;...] | 12792 | [[334,5909245...] | OrderCrosso... | 13264,38 |
| Genetic Algorithm (Mutation Rate 5%) Run 18 | 5110 | [0:40:38;116;111;114;...] | 12711 | [[334,5909245...] | OrderCrosso... | 13151,19 |
| Genetic Algorithm (Mutation Rate 5%) Run 19 | 5110 | [0:40:38;116;111;114;...] | 12326 | [[334,5909245...] | OrderCrosso... | 12625,78 |
| Genetic Algorithm (Mutation Rate 5%) Run 20 | 5110 | [0:40:38;116;111;114;...] | 13346 | [[334,5909245...] | OrderCrosso... | 13777,85 |
| Genetic Algorithm (Mutation Rate 5%) Run 21 | 5110 | [0:40:38;116;111;114;...] | 12807 | [[334,5909245...] | OrderCrosso... | 13284,81 |
| Genetic Algorithm (Mutation Rate 5%) Run 22 | 5110 | [0:40:38;116;111;114;...] | 12741 | [[334,5909245...] | OrderCrosso... | 13113,18 |
| Genetic Algorithm (Mutation Rate 10%) Run 13 | 5110 | [0:40:38;116;111;114;...] | 15921 | [[334,5909245...] | OrderCrosso... | 18084,04 |
| Genetic Algorithm (Mutation Rate 10%) Run 14 | 5110 | [0:40:38;116;111;114;...] | 16384 | [[334,5909245...] | OrderCrosso... | 19609,36 |

RunCollection Tabular View



- Sort columns
 - click on column header to sort column
 - Ctrl-click on column header to sort multiple columns
- Show or hide columns
 - right-click on table to open dialog to show or hide columns
- Compute statistical values
 - select multiple numerical values to see count, sum, minimum, maximum, average and standard deviation
- Select, copy and paste into other applications

RunCollection BubbleChart




RunCollection BubbleChart



- Choose values to plot
 - choose which values to show on the x-axis, the y-axis and as bubble size
 - possible values are all parameter settings and results
- Add jitter
 - add jitter to separate overlapping bubbles
- Zoom in and out
 - click on Zoom and click and drag in the chart area to zoom in
 - double click on the chart area background or on the circle buttons beside the scroll bars to zoom out
- Color bubbles
 - click on Select, choose a color and click and drag in the chart area to select and color bubbles
 - apply coloring automatically by clicking on the axis coloring buttons
- Show runs
 - double click on a bubble to open its run
- Export image
 - right-click to open context menu to copy or save image
 - save image as pixel (BMP, JPG, PNG, GIF, TIF) or vector graphics (EMF)
- Show box plots
 - right-click to open context menu to show box plots view

RunCollection BoxPlots




RunCollection BoxPlots



- Choose values to plot
 - choose which values to show on the x-axis and y-axis
 - possible values are all parameter settings and results
- Zoom in and out
 - click on Zoom and click and drag in the chart area to zoom in
 - double click on the chart area background or on the circle buttons beside the scroll bars to zoom out
- Show or hide statistical values
 - click on the lower left button to show or hide statistical values
- Export image
 - right-click to open context menu to copy or save image
 - save image as pixel (BMP, JPG, PNG, GIF, TIF) or vector graphics (EMF)

Filter Runs




Multi-core CPUs and Parallelization




- Parallel execution of optimizers in experiments
 - optimizers in an experiment are executed sequentially from top to bottom per default
 - experiments support parallel execution of their optimizers
 - select a not yet executed optimizer and start it manually to utilize another core
 - execution of one of the next optimizers is started automatically after an optimizer is finished
- Parallel execution of algorithms
 - HeuristicLab provides special operators for parallelization
 - engines decide how to execute parallel operations
 - sequential engine executes everything sequentially
 - parallel engine executes parallel operations on multiple cores
 - Hive engine (under development) executes parallel operations on multiple computers
 - all implemented algorithms support parallel solution evaluation

Parallel Execution of Experiments




Parallel Execution of Algorithms




Analyzers

- Special operators for analysis purposes
 - are executed after each iteration
 - serve as general purpose extension points of algorithms
 - can be selected and parameterized in the algorithm
 - perform algorithm-specific and/or problem-specific tasks
 - some analyzers are quite costly regarding runtime and memory
 - implementing and adding custom analyzers is easy
- Examples
 - TSPAlleleFrequencyAnalyzer
 - TSPPopulationDiversityAnalyzer
 - SuccessfulOffspringAnalyzer
 - SymbolicDataAnalysisVariableFrequencyAnalyzer
 - SymbolicRegressionSingleObjectiveTrainingBestSolutionAnalyzer
 - ...


Analyzers



TSPAlleleFrequencyAnalyzer




TSPPopulationDiversityAnalyzer




Building User-Defined Algorithms

- Operator graphs
 - algorithms are represented as operator graphs
 - operator graphs of user-defined algorithms can be changed
 - algorithms can be defined in the graphical algorithm designer
 - use the menu to convert a standard algorithm into a user-defined algorithm




- Operators sidebar
 - drag & drop operators into an operator graph
- Programmable operators
 - add programmable operators in order to implement custom logic in an algorithm
 - no additional development environment needed
- Debug algorithms
 - use the debug engine to obtain detailed information during algorithm execution


Building User-Defined Algorithms




Building User-Defined Algorithms



Programmable Operators



Debugging Algorithms



Agenda

- Objectives of the Tutorial
- Introduction
- Where to get HeuristicLab?
- Plugin Infrastructure
- Graphical User Interface
- Available Algorithms & Problems
- **Demonstration Part I: Working with HeuristicLab**
- **Demonstration Part II: Data-based Modeling**
- Some Additional Features
- Planned Features
- Team
- Suggested Readings
- Bibliography
- Questions & Answers

Demonstration Part II: Data-based Modeling



- Introduction
- Regression with HeuristicLab
- Model simplification and export
- Variable relevance analysis
- Classification with HeuristicLab

Introduction to Data-based Modeling



- Dataset: Matrix $(x_{i,j})_{i=1..N, j=1..K}$
 - N observations of K input variables
 - $x_{i,j}$ = i-th observation of j-th variable
 - Additionally: Vector of labels $(y_1 \dots y_N)^T$
- Goal: learn association of input variable values to labels
- Common tasks
 - Regression (real-valued labels)
 - Classification (discrete labels)
 - Clustering (no labels, group similar observations)




Data-based Modeling Algorithms in HeuristicLab



- Symbolic regression and classification based on genetic programming
- External Libraries:
 - Support Vector Machines for Regression and Classification
 - Linear Regression
 - Linear Discriminate Analysis
 - K-Means clustering

Case Studies

- Demonstration
 - problem configuration
 - data import
 - target variable
 - input variables
 - data partitions (training and test)
 - analysis of results
 - accuracy metrics
 - visualization of model output




Case Study: Regression


- Poly-10 benchmark problem dataset
 - 10 input variables $x_1 \dots x_{10}$
 - $y = x_1 \cdot x_2 + x_3 \cdot x_4 + x_5 \cdot x_6 + x_1 \cdot x_7 \cdot x_9 + x_3 \cdot x_6 \cdot x_{10}$
 - non-linear modeling approach necessary
 - frequently used in GP literature
 - download
<http://dev.heuristiclab.com/AdditionalMaterial#GECCO2012>

Linear Regression


- Create new algorithm




Import Data from CSV-File




Inspect and Configure Dataset




Inspect Imported Data




Set Target Variable




Select Input Variables




Configure Training and Test Partitions




Run Linear Regression




Inspect Results




Inspect Scatterplot of Predicted and Target Values



Inspect Linechart



Inspect the Model



The screenshot shows the HeuristicLab Optimizer interface. The window title is "HL HeuristicLab Optimizer 3.3.3.5837 [Unsaved]". The menu bar includes File, Edit, View, Services, and Help. The toolbar has icons for New, Open, Save, and Run. The tabs at the top are Start Page, Linear Regression, and Model, with Model selected. On the left, there's a vertical clipboard pane labeled "Clipboard" with the "HL" logo. The main area displays the following information:

Name: Model
Data Type: SymbolicRegressionModel


Value

$Result = (c_0 \cdot x_1 + c_1 \cdot x_2 + c_2 \cdot x_3 + c_3 \cdot x_4 + c_4 \cdot x_5 + c_5 \cdot x_6 + c_6 \cdot x_7 + c_7 \cdot x_8 + c_8 \cdot x_9 + c_9 \cdot x_{10} + c_{10})$

| | |
|------------|-----------|
| $c_0 =$ | 0.081337 |
| $c_1 =$ | 0.19906 |
| $c_2 =$ | -0.029881 |
| $c_3 =$ | 0.078892 |
| $c_4 =$ | -0.010307 |
| $c_5 =$ | 0.031685 |
| $c_6 =$ | -0.047071 |
| $c_7 =$ | -0.029194 |
| $c_8 =$ | 0.0015768 |
| $c_9 =$ | 0.10525 |
| $c_{10} =$ | 0.020099 |

Symbolic Regression with HeuristicLab



- Linear regression produced an inaccurate model.
- Next: produce a nonlinear symbolic regression model using genetic programming
- Genetic programming
 - evolve variable-length models
 - model representation: symbolic expression tree
 - structure and model parameters are evolved side-by-side
 - white-box models




Symbolic Regression with HeuristicLab




- Demonstration
 - problem configuration
 - function set and terminal set
 - model size constraints
 - Evaluation
- Algorithm configuration
 - selection
 - Mutation
- Analysis of results
 - model accuracy
 - model structure and parameters




Create New Genetic Algorithm




Create New Symbolic Regression Problem




Import Data




Inspect Data and Configure Dataset




Set Target and Input Variables




Configure Maximal Model Depth and Length




Configure Function Set (Grammar)




Configure Function Set (Grammar)




Configure Algorithm Parameters




Configure Mutation Operator




Configure Selection Operator




Configure Tournament Group Size




Start Algorithm and Inspect Results




Inspect Quality Chart




Inspect Best Model on Training Partition



Inspect Linechart of Best Model on Training Partition




Inspect Structure of Best Model on Training Partition



Model Simplification and Export



- Demonstration
 - automatic simplification
 - visualization of node impacts
 - manual simplification
 - online update of results
 - model export
 - MATLAB
 - LaTeX




$$Result = x4(t) \cdot x3(t) \cdot c_{20} \quad (13)$$


$$\cdot \left(x_6(t) \cdot x_5(t) \cdot c_4 + x_4(t) \cdot x_3(t) \cdot c_7 + x_4(t) \cdot x_3(t) \cdot c_{10} + \frac{c_{11}x_1(t)}{x_4(t) \cdot x_3(t) \cdot \left(c_{14}x_4(t) + c_{15}x_5(t) + \frac{1}{c_{17}x_2(t)} \right) \cdot c_{18}} + c_{19} \right) + c_{21}$$

(14)

Detailed Model Analysis and Simplification



Symbolic Simplification and Node Impacts




Manual Simplification

HL HeuristicLab Optimizer 3.3.3.5837 [Unsaved]

File Edit View Services Help

Start Page Genetic Algorithm Interactive Regression Solution

Simplify



Details

Regression Solution

- Average relative error (test): 497.347029771583 %
- Average relative error (training): 210.827113981827 %
- Mean squared error (test): 0.16222671796286908
- Mean squared error (training): 0.1407763050506841

Model: SymbolicRegressionModel

- ModelDepth: 11
- ModelLength: 41
- Pearson's R² (test): 0.50720401737421239
- Pearson's R² (training): 0.66645660997240819

ProblemData: Data imported from multivariate poly-10


Regression Solution ScatterPlot
Regression Solution LineChart
Regression Solution EstimatedValues

Clipboard

Simplify


double-click nodes

Automatic Symbolic Simplification




Textual Representations Are Also Available

- Use *ViewHost* to switch to textual representation view.



Default Textual Representation for Model Export



Textual Representation for Export to LaTeX



HL HeuristicLab Optimizer 3.3.3.5837 [Unsaved]

File Edit View Services Help

Start Page Linear Regression Model

Name: Model

Data Type: SymbolicRegressionModel

Value

Formatter: **LaTeX String Formatter**

```
% needs \usepackage{amsmath}
\begin{aligned}
Result &= \left( c_{(0)} x_1(t) + c_{(1)} x_2(t) + c_{(2)} x_3(t) + c_{(3)} x_4(t) + c_{(4)} x_5(t) + c_{(5)} x_6(t) + c_{(6)} x_7(t) + c_{(7)} x_8(t) + c_{(8)} x_9(t) + c_{(9)} x_{10}(t) + c_{(10)} \right) \\
c_{(0)} &= 0.0813371220642195 \\
c_{(1)} &= 0.199055016563887 \\
c_{(2)} &= -0.0298811744629839 \\
c_{(3)} &= 0.078891883541302 \\
c_{(4)} &= -0.0103065273366223 \\
c_{(5)} &= 0.0316849536396099 \\
c_{(6)} &= -0.0470707585925129 \\
c_{(7)} &= -0.0291939124032144 \\
c_{(8)} &= 0.00157679665070775 \\
c_{(9)} &= 0.105250443686677 \\
c_{(10)} &= 0.0200987846293256
\end{aligned}
```

Result = $(c_0 x_1(t) + c_1 x_2(t) + c_2 x_3(t) + c_3 x_4(t) + c_4 x_5(t) + c_5 x_6(t) + c_6 x_7(t) + c_7 x_8(t) + c_8 x_9(t) + c_9 x_{10}(t) + c_{10})$

(1)

$c_0 = 0.0813371220642195$

(2)

$c_1 = 0.199055016563887$

(3)

$c_2 = -0.0298811744629839$

(4)

$c_3 = 0.078891883541302$

(5)

$c_4 = -0.0103065273366223$

(6)

$c_5 = 0.0316849536396099$

(7)

$c_6 = -0.0470707585925129$

(8)

$c_7 = -0.0291939124032144$

(9)

$c_8 = 0.00157679665070775$

(10)

$c_9 = 0.105250443686677$

(11)

$c_{10} = 0.0200987846293256$

(12)

LaTeX Export



HL HeuristicLab Optimizer 3.3.3.5837 [Unsaved]

File Edit View Services Help

Start Page Genetic Algorithm Interactive Regression Solution S... Model

Name: Model

Data Type: SymbolicRegressionModel

Value

Formatter: LaTeX String Formatter

```
% needs \usepackage{amsmath}
\begin{aligned}
Result &= \left( c_{(0)} x_4(t) \cdot c_1 x_3(t) \cdot c_2 x_6(t) \cdot c_3 x_5(t) \cdot c_4 x_4(t) + c_5 x_4(t) \cdot c_6 x_3(t) \cdot c_7 x_4(t) + c_8 x_4(t) \cdot c_9 x_3(t) \cdot c_{10} \right. \\
&\quad \left. + \frac{c_{11}}{c_{12} x_4(t)} \cdot c_{13} x_3(t) \cdot c_{14} x_4(t) + c_{15} x_5(t) + \frac{c_{16}}{c_{17} x_2(t)} \right) \cdot c_{18} \\
&\quad + c_{19} \\
c_{(4)} &= -1.57302367616477 \\
c_{(7)} &= -0.867137925013337 \\
c_{(10)} &= -0.867137925013337 \\
c_{(11)} &= 1.27519978915975 \\
c_{(14)} &= -0.017064976517855 \\
c_{(15)} &= 0.00314376988160885 \\
c_{(17)} &= -3.00832012161288 \\
c_{(18)} &= 0.867137925013337 \\
c_{(19)} &= -5.45190909899249 \\
c_{(20)} &= -0.204498330755849 \\
c_{(21)} &= -0.0465339907207764
\end{aligned}
```

Result = $x_4(t) \cdot x_3(t) \cdot c_{20}$ (13)

$$\cdot \left(x_6(t) \cdot x_5(t) \cdot c_4 + x_4(t) \cdot x_3(t) \cdot c_7 + x_4(t) \cdot x_3(t) \cdot c_{10} + \frac{c_{11} x_1(t)}{x_4(t) \cdot x_3(t) \cdot \left(c_{14} x_4(t) + c_{15} x_5(t) + \frac{1}{c_{17} x_2(t)} \right) \cdot c_{18}} + c_{19} \right) + c_{21}$$
 (14)

$c_4 = -1.57302367616477$ (15)

$c_7 = -0.867137925013337$ (16)

$c_{10} = -0.867137925013337$ (17)

$c_{11} = 1.27519978915975$ (18)

$c_{14} = -0.017064976517855$ (19)

$c_{15} = 0.00314376988160885$ (20)

$c_{17} = -3.00832012161288$ (21)

$c_{18} = 0.867137925013337$ (22)


$c_{19} = -5.45190909899249$ (23)

$c_{20} = -0.204498330755849$ (24)

$c_{21} = -0.0465339907207764$ (25)


Variable Relevance Analysis

- Which variables are important to predict classes correctly?
- Demonstration
 - Variable frequency analyzer
 - symbol frequency analyzer
 - variable impacts




| | Relative variable relevance |
|-----|-----------------------------|
| x4 | 0.302803869106054 |
| x3 | 0.241170172985569 |
| x1 | 0.179112369714678 |
| x10 | 0.0589664719249172 |
| x2 | 0.0544635184742382 |
| x6 | 0.0446774403657897 |
| x8 | 0.0436011597048278 |
| x7 | 0.0331173502974243 |
| x5 | 0.0226252246461621 |
| x9 | 0.01946242278034 |

Inspect Variable Frequency Chart



Inspect Variable Impacts



The screenshot shows the HeuristicLab Optimizer interface version 3.3.3.5837 [Unsaved]. The main window title is "HL HeuristicLab Optimizer 3.3.3.5837 [Unsaved]". The menu bar includes File, Edit, View, Services, and Help. The toolbar has icons for New, Open, Save, and Run. The tabs at the top are Start Page (selected) and Genetic Algorithm.

The "Results" tab is selected. On the left, there is a tree view with the following items:


- Evaluated Solutions: 43957
- Generations: 43
- Symbol frequencies: Symbol frequencies
- Variable frequencies: Variable frequencies
- Variable impacts: [[0.302803869106054][0.24]]
- Symbolic expression tree length: Values
- Best training solution: SymbolicRegressionSolu
- Best training solution quality: 0.500629316831
- CurrentBestQuality: 0.50062931683180834
- CurrentAverageQuality: 0.2875027821157774
- CurrentWorstQuality: 0
- BestQuality: 0.50062931683180834
- BestKnownQuality: 0
- Absolute Difference Best Known To Best: 0.5006
- Relative Difference Best Known To Best: NaN
- Qualities: Qualities

To the right of the tree view is a "Details" section with "Rows: 10" and "Columns: 1". Below this is a table titled "Relative variable relevance" with 10 rows, indexed x4 through x9. The first row (x4) is highlighted in blue, showing a value of 0.302803869106054.

| | Relative variable relevance |
|-----|-----------------------------|
| x4 | 0.302803869106054 |
| x3 | 0.241170172985569 |
| x1 | 0.179112369714678 |
| x10 | 0.0589664719249172 |
| x2 | 0.0544635184742382 |
| x6 | 0.0446774403657897 |
| x8 | 0.0436011597048278 |
| x7 | 0.0331173502974243 |
| x5 | 0.0226252246461621 |
| x9 | 0.01946242278034 |

At the bottom of the window, there are buttons for Run, Stop, and Save, and the text "Execution Time: 00:01:30.9862041".



Inspect Symbol Frequencies



Classification with HeuristicLab



- Symbolic classification
 - evolve discriminating function using GP
 - find thresholds to assign classes
- Demonstration
 - real world medical application
 - model accuracy
 - visualization of model output
 - discriminating function output
 - ROC-curve
 - confusion matrix



| | Actual Class 0 | Actual Class 1 |
|-------------------|----------------|----------------|
| Predicted Class 0 | 197 | 29 |
| Predicted Class 1 | 64 | 190 |

Case Study: Classification

- Real world medical dataset (*Mammographic Mass*) from UCI Machine Learning Repository
 - data from non-invasive mammography screening
 - variables:
 - patient age
 - visual features of inspected mass lesions: shape, margin, density
 - target variable: severity (malignant, benign)
 - download
<http://dev.heuristiclab.com/AdditionalMaterial#GECCO2012>

Open Sample

HeuristicLab Optimizer 3.3.3.5837

Follow these steps to start working with HeuristicLab Optimizer:

1. Open an algorithm
 - click  (New Item) in the toolbar and select an algorithm or click  (Open File) in the toolbar and load an algorithm from a file
2. Open a problem in the algorithm
 - in the Problem tab of the algorithm click  (New Problem) and select a problem or click  (Open Problem) and load a problem from a file
3. Set parameters
 - set problem parameters in the Problem tab of the algorithm
 - set algorithm parameters in the Parameters tab of the algorithm
4. Run the algorithm
 - click  (Start/Resume Algorithm) to execute the algorithm (if the button is grayed out some parameters of the algorithm or the problem still have to be set)
 - wait for the algorithm to terminate or click  (Pause Algorithm) to interrupt its execution or click  (Stop Algorithm) to stop its execution
5. Check results
 - check the results on the Results tab of the algorithm
 - click  (Start/Resume Algorithm) to continue the algorithm or click  (Reset Algorithm) to prepare a new run


Looking for predefined algorithms which can be executed immediately?

- check out the **sample algorithms** below


| Samples | |
|---|--|
| Name | Description |
|  Evolution Strategy - Griewank | An evolution strategy which solves the 10-dimensional Griewank test function |
|  Genetic Algorithm - TSP | A genetic algorithm which solves the "ch130" traveling salesman problem (imported from TSPLIB) |
|  Genetic Algorithm - VRP | A genetic algorithm which solves the "C101" vehicle routing problem (imported from Solomon) |
|  Genetic Programming - Artificial Ant | A standard genetic programming algorithm to solve the artificial ant problem (Santa-Fe trail) |
|  Genetic Programming - Symbolic Classification | A standard genetic programming algorithm to solve a classification problem (Mammographic+Mass dataset) |
|  Genetic Programming - Symbolic Regression | A standard genetic programming algorithm to solve a symbolic regression problem (tower dataset) |
|  Island Genetic Algorithm - TSP | An island genetic algorithm which solves the "ch130" traveling salesman problem (imported from TSPLIB) |
|  Local Search - Knapsack | A local search algorithm that solves a randomly generated Knapsack problem |

Show Start Page on Startup


Configure and Run Algorithm




Inspect Quality Linechart




Inspect Best Training Solution



Inspect Model Output and Thresholds




Inspect Confusion Matrix



The screenshot shows the HeuristicLab Optimizer interface with the title "HL HeuristicLab Optimizer 3.3.3.5837 [Unsaved]". The main window displays a "Best training solution" under the "Genetic Algorithm" tab. The "Details" pane on the right shows a confusion matrix for "Training" samples. The matrix is as follows:


| | Actual Class 0 | Actual Class 1 |
|-------------------|----------------|----------------|
| Predicted Class 0 | 197 | 29 |
| Predicted Class 1 | 64 | 190 |

Inspect ROC Curve




Validation of Results

- Overfitting = memorizing data






- Strategies to reduce overfitting
 - validation partition
 - cross-validation




Validation of Results


- Demonstration
 - Configuration of a validation set
 - Inspection of best solution on validation set
 - Analysis of training- and validation fitness correlation
 - Cross-validation
 - Configuration
 - Analysis of results




Configuration of Validation Partition



Inspect Best Model on Validation Partition



Inspect Linechart of Correlation of Training and Validation Fitness



Agenda

- Objectives of the Tutorial
- Introduction
- Where to get HeuristicLab?
- Plugin Infrastructure
- Graphical User Interface
- Available Algorithms & Problems
- **Demonstration Part I: Working with HeuristicLab**
- **Demonstration Part II: Data-based Modeling**
- Some Additional Features
- Planned Features
- Team
- Suggested Readings
- Bibliography
- Questions & Answers

Some Additional Features

- HeuristicLab Hive
 - parallel and distributed execution of algorithms and experiments on many computers in a network
- Optimization Knowledge Base (OKB)
 - database to store algorithms, problems, parameters and results
 - open to the public
 - open for other frameworks
 - analyze and store characteristics of problem instances and problem classes
- External solution evaluation and simulation-based optimization
 - interface to couple HeuristicLab with other applications (MATLAB, AnyLogic, ...)
 - supports different protocols (command line parameters, TCP, ...)
- Parameter grid tests and meta-optimization
 - automatically create experiments to test large ranges of parameters
 - apply heuristic optimization algorithms to find optimal parameter settings for heuristic optimization algorithms



Planned Features

- Algorithms & Problems
 - steady-state genetic algorithm
 - unified tabu search for vehicle routing
 - estimation of distribution algorithms
 - evolution of Robocode bots
 - ...
- Cloud Computing
 - port HeuristicLab Hive to Windows Azure
- Statistics
 - implement statistical tests and automated statistical analysis
- Have a look at the HeuristicLab roadmap
 - <http://dev.heuristiclab.com/trac/hl/core/roadmap>
- Any other ideas, requests or recommendations?
 - join our HeuristicLab Google group heuristiclab@googlegroups.com
 - write an e-mail to support@heuristiclab.com

HeuristicLab Team



Heuristic and Evolutionary Algorithms Laboratory (HEAL)
School of Informatics, Communications and Media
University of Applied Sciences Upper Austria

Softwarepark 11
A-4232 Hagenberg
AUSTRIA


WWW: <http://heal.heuristiclab.com>




Suggested Readings



- S. Voß, D. Woodruff (Edts.)
Optimization Software Class Libraries
Kluwer Academic Publishers, 2002



- M. Affenzeller, S. Winkler, S. Wagner, A. Beham
**Genetic Algorithms and Genetic Programming
Modern Concepts and Practical Applications**
CRC Press, 2009



Bibliography

- S. Wagner, M. Affenzeller
HeuristicLab: A generic and extensible optimization environment
Adaptive and Natural Computing Algorithms, pp. 538-541
Springer, 2005
- S. Wagner, S. Winkler, R. Braune, G. Kronberger, A. Beham, M. Affenzeller
Benefits of plugin-based heuristic optimization software systems
Computer Aided Systems Theory - EUROCAST 2007, Lecture Notes in Computer Science, vol. 4739, pp. 747-754
Springer, 2007
- S. Wagner, G. Kronberger, A. Beham, S. Winkler, M. Affenzeller
Modeling of heuristic optimization algorithms
Proceedings of the 20th European Modeling and Simulation Symposium, pp. 106-111
DIPTEM University of Genova, 2008
- S. Wagner, G. Kronberger, A. Beham, S. Winkler, M. Affenzeller
Model driven rapid prototyping of heuristic optimization algorithms
Computer Aided Systems Theory - EUROCAST 2009, Lecture Notes in Computer Science, vol. 5717, pp. 729-736
Springer, 2009
- S. Wagner
Heuristic optimization software systems - Modeling of heuristic optimization algorithms in the HeuristicLab software environment
Ph.D. thesis, Johannes Kepler University Linz, Austria, 2009.
- S. Wagner, A. Beham, G. Kronberger, M. Kommenda, E. Pitzer, M. Kofler, S. Vonolfen, S. Winkler, V. Dorfer, M. Affenzeller
HeuristicLab 3.3: A unified approach to metaheuristic optimization
Actas del séptimo congreso español sobre Metaheurísticas, Algoritmos Evolutivos y Bioinspirados (MAEB'2010), 2010
- S. Wagner, G. Kronberger, A. Beham, M. Kommenda, A. Scheibenpflug, E. Pitzer, S. Vonolfen, M. Kofler, S. Winkler, V. Dorfer, M. Affenzeller
Architecture and Design of the HeuristicLab Optimization Environment
Advanced Methods and Applications in Computational Intelligence, vol. 6, pp. 197-261, Springer, 2014
- Detailed list of all publications of the HEAL research group: <http://research.fh-ooe.at/de/orgunit/detail/356#showpublications>

Questions & Answers



<http://dev.heuristiclab.com>

heuristiclab@googlegroups.com

<http://www.youtube.com/heuristiclab>

<http://www.facebook.com/heuristiclab>