

DEV BRIEF — Dynamic “Upcoming Workshops” on Homepage (Astro) via Cloudflare Worker Cache

Objective

Display the “Upcoming Workshops” section on the homepage without triggering a rebuild of 5,000 recipes,

without global SSR, and using a lightweight edge caching layer.

Workshops are managed on:

<https://atelier-lacuisinedebernard.com/>

1) Target Architecture (Locked)

Data Flow

1. Source of truth (workshops backend) exposes JSON:

<https://atelier-lacuisinedebernard.com/api/upcoming-workshops>

- 1.

2. A Cloudflare Worker on the public domain exposes:

<https://www.lacuisinedebernard.com/api/workshops-cache>

- 2.

3. The Astro homepage performs a server-side fetch to:

/api/workshops-cache

3.

4. The “Upcoming Workshops” block is rendered in HTML at page render time.

Key Principles

- No global rebuild
- No full SSR architecture
- Only a small edge endpoint with short TTL
- SEO-safe (HTML rendered server-side)

2) Cloudflare Worker Requirements

Route

/api/workshops-cache

Responsibilities

The Worker must:

- Fetch JSON from:

<https://atelier-lacuisinedebernard.com/api/upcoming-workshops>

-

- Return the JSON response unchanged

- Apply edge caching (300 seconds / 5 minutes)
- Handle upstream errors gracefully

Caching Rules

Use:

```
cf: {  
  cacheEverything: true,  
  cacheTtl: 300  
}
```

Response headers must include:

Content-Type: application/json; charset=utf-8
Cache-Control: public, max-age=60, s-maxage=300

Error Handling (Mandatory)

If the upstream endpoint fails:

- Return cached version if available
- Otherwise return:

```
{  
  "items": [],  
  "error": "upstream_unavailable"  
}
```

Status: 200

The homepage must never break if the workshops API is down.

3) Upstream JSON Contract (Workshops API)

The endpoint:

/api/upcoming-workshops

Must return stable JSON in this structure:

```
{
  "updatedAt": "2026-02-13T12:00:00Z",
  "items": [
    {
      "id": "wk_123",
      "title": "Chinese Cooking Workshop",
      "startAt": "2026-03-09T18:30:00+01:00",
      "durationMin": 240,
      "location": "Paris",
      "price": 85,
      "capacity": 8,
      "spotsLeft": 2,
      "status": "LIMITED",
      "bookingUrl": "https://atelier-lacuisinedebernard.com/booking/wk_123",
      "image": {
        "src": "https://.../image.webp",
        "alt": "Chinese Cooking Workshop"
      }
    }
  ]
}
```

Requirements

- status must be one of:
 - OPEN
 - LIMITED
 - SOLD_OUT
- spotsLeft must be computed server-side

- bookingUrl must be directly usable

No business logic should be required inside Astro.

4) Astro Homepage Integration

4.1 Server-side Fetch (No Client-side Fetch Required)

On the Astro homepage:

- Perform a server-side fetch to:

/api/workshops-cache

-
- Render the workshops section in HTML
- Do not rely on client-side hydration

4.2 Timeout & Stability

- Fetch timeout recommended: 1–2 seconds
- If fetch fails:
 - Render fallback UI
 - Do not crash page render

4.3 UI Rules

- Display maximum 3 workshops
- Badge logic:
 - SOLD_OUT → “Fully booked”
 - LIMITED → “Last spots”
- CTA button → bookingUrl
- Images must respect portrait format (no aggressive cropping)

5) QA & Acceptance Criteria

Functional

1. GET /api/workshops-cache returns valid JSON
2. Edge caching works (same response served within ~300 seconds)
3. If upstream is down:
 - Homepage remains functional
 - Workshops block shows fallback state
4. No full rebuild required to update workshops
5. No client-side JS required for rendering

6) Deliverables

- Cloudflare Worker implementation
- Route configuration on public domain

- Astro homepage component integration
- QA evidence:
 - curl output for endpoint
 - screenshot homepage
 - cache validation proof

Result

This implementation ensures:

- Zero rebuild impact on 5,000 recipes
- No global SSR architecture
- Stable performance
- SEO-friendly homepage rendering
- Controlled workshop freshness (max 5-minute delay)
-