

NATIONAL UNIVERSITY OF SINGAPORE

Semester 2, 2016/2017

CS1010S — Programming Methodology

Time Allowed: 2 hours

INSTRUCTIONS TO STUDENTS

1. Please write your Student Number only. Do not write your name.
2. The assessment paper contains **FIVE (5) questions** and comprises **TWENTY-TWO (22) pages** including this cover page.
3. Weightage of questions is given in square brackets. The maximum attainable score is 100.
4. This is a **CLOSED** book assessment, but you are allowed to bring **ONE** double-sided A4 sheet of notes for this assessment.
5. Write all your answers in the space provided in this booklet.
6. You are allowed to write with pencils, as long as it is legible.
7. **Please write your student number below.**

STUDENT NO: _____

(this portion is for the examiner's use only)

Question	Marks	Remark
Q1	/ 30	
Q2	/ 28	
Q3	/ 26	
Q4	/ 12	
Q5	/ 4	
Total	/ 100	

This page is intentionally left blank.

It may be used as scratch paper.

Question 1: Python Expressions [30 marks]

There are several parts to this problem. Answer each part **independently and separately**. In each part, one or more Python expressions are entered into the interpreter (Python shell). Determine the response printed by the interpreter for the final expression entered and **write the exact output in the answer box**. If the interpreter produces an error message, or enters an infinite loop, **briefly explain why**. You may show your workings **outside the answer box** in the space beside the code. Partial marks will be awarded for workings if the final answer is wrong.

A. `s = "Lillypilly"`
`d = {}`
`for i in range(len(s)):`
 `d[s[i]] = i%5`
`print(d)`

[5 marks]


B. `a = [1, 2]`
`b = [a, a]`
`c = a.copy()`
`c[0], a[1] = b[1], c[0]`
`print(a)`
`print(b)`
`print(c)`

[5 marks]

C. `def f(x):`
 `return lambda y: (x, y(x))`
`def g(y):`
 `return lambda x: x(y)`
`print(g(2)(f)(lambda x:x+1))`

[5 marks]

D. `lst = [4, 3, 2, 1]` [5 marks]
`for i in lst.copy():`
 `lst.append(i + 1)`
 `lst.pop(i)`
`print(lst)`



E. `n = 10` [5 marks]
`while n:`
 `if n % 5:`
 `n //= 2`
 `if n > 10:`
 `break`
 `else:`
 `n += 6`
`print(n)`



F. `def t(x, y):` [5 marks]
 `try:`
 `x[1] = x[0] + y`
 `except TypeError:`
 `print("This")`
 `except IndexError:`
 `print("is")`
 `except NameError:`
 `print("Sparta!")`
 `finally:`
 `return x[1]`
`print(t([1, "Madness"], "Blasphemy"))`



Question 2: Bingo! [28 marks]

Bingo is a card game of chance where players match numbers on a given card. In the United States, Bingo is played using a 5x5 square grid of unique numbers on a card, like so:

3	23	39	56	64
2	20	35	50	72
14	27	41	52	70
8	16	45	53	61
7	30	36	47	71

Numbers will be drawn at random and matching numbers on the card will be marked, usually by crossing out. A player wins when a **complete row or column** of numbers have been crossed out. For simplicity, we **do not consider completing the diagonals as a win**.

Also note that though US Bingo is played on a 5x5 grid, your **implementations should work with a square bingo grid of any size**.

A. [Warm up] The function `make_card` takes as input a list of lists. Each element in the list represents a row of the bingo card as another list of numbers. `make_card` returns a data type that represents a card. A card can also be represented as a list of lists, like the dense matrix representation discussed in class.

For example, the card illustrated above is denoted as:

```
>>> card = make_card([[3, 23, 39, 56, 64],
                      [2, 20, 35, 50, 72],
                      [14, 27, 41, 52, 70],
                      [8, 16, 45, 53, 61],
                      [7, 30, 36, 47, 71]])
```

Provide an implementation of the function `make_card`.

[4 marks]

```
def make_card(seq):
```

B. Whenever a number is drawn, the player will cross out the number if found on his card. The function `cross_out` takes as inputs a card and a number, and modifies the state of the card to reflect the crossing out of the number.

One possibility is to replace the matching number in the card with an `'X'` to indicate that it has been crossed out.

Provide an implementation for the function `cross_out`.

[4 marks]

```
def cross_out(card, num):
```

C. To win the game, a player has to have one complete row or column crossed out. The functions `check_rows` and `check_cols` takes as input a card, and returns `True` if the card has at least one row, or one column respectively, crossed out. Otherwise, the functions return `False`.

Example:

```
>>> card = make_card([[4, 10], [3, 11]]) # create a 2x2 card
>>> cross_out(card, 4) # [[X, 10], [3, 11]]
>>> check_rows(card)
False

>>> cross_out(card, 10) # [[X, X], [3, 11]]
>>> check_rows(card) # First row is crossed out
True

>>> check_cols(card)
False
```

```
>>> cross_out(card, 11) # [[X, X], [3, X]]
>>> check_cols(card)    # Second column is crossed out
True
```

Provide an implementation for `check_rows` and `check_cols`. *Hint: Recall that you can multiply lists with an integer. It might be helpful to use as a comparison if your representation of a card contains a list.* [8 marks]

```
def check_rows(card):
```

```
def check_cols(card):
```

D. Your friend Chelsea thinks that it is redundant to write the `check_cols` function if you are able to transpose the card like a matrix. Her rationale is that after the transposition, the columns will become rows after which she can then use the `check_rows` function.

Chelsea wants to have an “in-place” transpose function, i.e., it takes constant space ($O(1)$) and does not require creating any new objects. Her idea is that since the card is always a square, she can simply swap the elements diagonally like so:

```
def transpose(card):  
    for row in range(len(card)):  
        for col in range(len(card)):  
            card[row][col], card[col][row] = card[col][row], card[row][col]
```

She then uses a function `print_card` that displays the card in a human-readable form to test her function:

```
>>> print_card(card)  
3, 23, 39, 56, 64  
2, 20, 35, 50, 72  
14, 27, 41, 52, 70  
8, 16, 45, 53, 61  
7, 30, 36, 47, 71
```

```
>>> transpose(card)
```

```
>>> print_card(card)  
3, 23, 39, 56, 64  
2, 20, 35, 50, 72  
14, 27, 41, 52, 70  
8, 16, 45, 53, 61  
7, 30, 36, 47, 71
```

Oh no! Her card did not end up getting transposed. Please explain what is wrong with Chelsea's transpose function? [4 marks]

E. Help Chelsea fix her code by providing a correct implementation of `transpose` that still fulfills her requirement of being in-place. [4 marks]

```
def transpose(card):
```

F. Chelsea also wrote this simple function to draw the numbers for her bingo game:

```
from random import *
def draw_number(n):
    return randint(1, n) # Draws a number between 1 and n (inclusive)
```

However, her players complained that the numbers already drawn should not be drawn a second time. In other words, the function should not produce repeated numbers for each bingo game.

You know this can be done by creating a class which can store a list of numbers from which to draw. Each draw will only choose from the numbers in the list and then the chosen number is removed, thus ensuring that no repeated numbers will be drawn. When all possible numbers have been drawn, the draw will always return 0.

A class `Drawer` may be implemented and used like so:

```
>>> drawer = Drawer(75) # valid numbers are from 1 to 75 inclusive.
>>> drawer.draw()
42

>>> drawer.draw()
37

>>> for i in range(73):
...     drawer.draw()
# 73 unique numbers are printed

>>> drawer.draw()
0 # all numbers have been drawn
```

Provide an implementation of the class `Drawer`.

Hint: The random package contains the function `randint(a, b)` which returns a random integer N such that $a \leq N \leq b$. You may assume it has been imported for your use. [4 marks]

```
from random import *  
  
class Drawer:
```


Thus, an empty playing grid is created with the following function:

```
def make_empty_grid():  
    return ({}, {})
```

A. Rachel thinks this will not work because the grid is represented using a tuple, and since tuples are immutable, we will not be able to add points and ships to the grid. She believes we should use a list instead.

Explain why her thinking is right or wrong.

[2 marks]

B. Since Battleship is also played using a grid like Bingo, give one reason why do we not use the same list-of-lists representation of a Bingo board to represent the Battleship grid? [2 marks]

C. The function `add_ship` takes as inputs a grid, a name of a ship, and one or many points (which are strings), and adds the ship into the grid at the given points.

Example:

```
>>> grid = make_empty_grid()

>>> add_ship(grid, "Battleship", "D2", "E2", "F2", "G2")
>>> add_ship(grid, "Destroyer", "F6", "F7")
```

Complete the implementation of the function `add_ship`. You may assume at least one point is given and all given points are valid. [6 marks]

```
def add_ship(grid, name, *coords): # Assume coordinates are correct
    points, ships = grid
```

D. The function `remove_ship` takes as input a grid and a ship name, and removes the ship from the grid. If the ship does not exist in the grid, `NameError` is raised with the message "No such ship".

Complete the implementation for the function `remove_ship` [6 marks]

```
def remove_ship(grid, name):
    points, ships = grid
```

E. The function `is_sunk` takes as input a ship (which is a dictionary) and returns `True` if the ship is sunk, i.e., all its occupied points has been destroyed, and `False` otherwise.

Provide an implementation for the function `is_sunk`. [3 marks]

```
def is_sunk(ship):
```

F. Provide an implementation for the function `ships_left` takes as input a grid, and returns the number of ships that are not sunk. [3 marks]

```
def ships_left(grid):
```

G. The function `attack` takes as inputs a grid and a coordinate point on the grid. If no ship is present at that point, the string `'Miss!'` is returned. Otherwise, the occupying point of the ship is destroyed.

If the ship has sunk, the string `'<name of ship> sunk'` is returned and the ship is removed from the grid. Otherwise, the grid will be updated to reflect the ship's state and the string `'Hit!'` will be returned.

Example:

```
>>> grid = make_empty_grid()
>>> add_ship(grid, "Destroyer", "F6", "F7")
>>> attack(grid, "E5")
'Miss!'

>>> attack(grid, "F6" )
'Hit!'


>>> attack(grid, "F6") # repeated shots will produce the same effect
'Hit!'

>>> attack(grid, "F7")
'Destroyer sunk'
```

Complete the implementation for the function `attack`.

[4 marks]

```
def attack(grid, coord):
    points, ships = grid
    if coord in points:
```



```
else:
    return "Miss!"
```

Question 4: Trains II [12 marks]

Note: Please read this question carefully as it is not the same as the re-midterm question.

Consider the following implementation where we model trains using Python classes.

```
class Car:
    def __init__(self, weight):
        self.weight = weight

    def get_weight(self):
        return self.weight

class PassengerCar(Car):
    def __init__(self, weight):
        self.passengers = 0
        super().__init__(weight)

    def get_weight(self):
        return self.passengers * 100 + super().get_weight()
```

A `Car` models a carriage that moves on tracks and it has a weight. A `PassengerCar` is a `Car` that can take on passengers, and each passenger is assumed to add 100 units to the car's weight.

Mr. Conductor wrote some code to create a passenger car:

```
>>> p1 = PassengerCar(25_000)
>>> print(p1.weight)
25000

>>> p1.passengers = 100
>>> print(p1.weight)
25000
```

“Something’s not right,” he exclaims. “The weight should be 35,000 because I have added 100 passengers who weight 100 units each. Why does it show 25,000?”

A. Please explain how the incorrect value was given and how Mr. Conductor can get the correct weight of the railcar. [3 marks]

An `Engine` is also a `Car`, but has two additional properties: `power` and `cars`. It's partial implementation is as given:

```
class Engine(Car):
    def __init__(self, power):
        self.power = power
        self.cars = []
        super().__init__(0)

    def add_car(self, car):
        self.cars.append(car)

    def get_weight(self):
        pass # to be implemented in 4B

    def move(self):
        return self.power >= self.get_weight()
```

An `Engine` contains a sequence of cars which it is pulling. The weight of an `Engine` is the sum total of the weights of all the cars it is pulling. The weight of an `Engine` without any cars is 0.

As can be seen from the current implementation, an `Engine` can only move if its power is greater or equal to its weight. Thus, its method `get_weight` should return its combined weight, which is the sum total of all its cars.

Example:

```
>>> thomas = Engine(100_000)
>>> thomas.get_weight()
0
```

```
>>> p1 = PassengerCar(25_000)
>>> thomas.add_car(p1)
>>> thomas.get_weight()
25000
```

```
>>> p1.passengers = 100 # passengers add 100×100 = 10,000 to the weight
>>> thomas.get_weight()
35000
```

B. Provide an implementation of the `get_weight`. You may assume that an Engine will not have another Engine in its cars. [3 marks]

```
def get_weight(self):
```

C. A `RailCar` is a self-powered passenger car. In other words, it is both an `Engine` and a `PassengerCar`. Thus, it is able to both pull cars as well as take on passengers.

A `RailCar`'s own weight is 0 and is determined by the sum total of all its cars (like an `Engine`), as well as by the number of passengers it has (like a `PassengerCar`). It is initialized with one input: power.

One interesting issue with Railcars is that if its power is less than its weight, `RailCar.move()` raises a `SignalFault` error.

Example:

```
>>> mrt = RailCar(50_000)
>>> p2 = PassengerCar(15_000)
>>> p3 = PassengerCar(15_000)
>>> mrt.get_weight()      # mrt has no weight on its own
0

>>> mrt.add_car(p2)
>>> mrt.add_car(p3)
>>> mrt.get_weight()
30000                      # mrt weight now includes its cars

>>> mrt.passengers = 50    # adds 5,000 weight
```

```
>>> p2.passengers = 60    # adds 6,000 weight
>>> p3.passengers = 70    # adds 7,000 weight

>>> mrt.get_weight()
48000                      # = 30,000 + 5,000 + 6,000 + 7,000
>>> mrt.move()
True

>>> mrt.passengers = 100   # increases weight by 5,000
>>> mrt.get_weight()
53000

>>> mrt.move()
SignalFault
```

Provide an implementation for the class `RailCar`. You may assume that the Exception class `SignalFault` is given. [6 marks]

Question 5: 42 and the Meaning of Life [4 marks]

Either: (a) explain how you think some of what you have learnt in CS1010S will be helpful for you for the rest of your life and/or studies at NUS; or (b) tell us an interesting story about your experience with CS1010S this semester. [4 marks]

— END OF PAPER —

Scratch Paper

Scratch Paper

– H A P P Y H O L I D A Y S ! –