

CS1010S Programming Methodology

Lecture 7

Searching & Sorting

7 Oct 2020

Saying of the Wise

I hear and I forget.

I see and I remember.

I do and I understand.

- Xun Zi

不聞不若聞之
聞之不若見之
見之不若知之
知之不若行之
學至于行之而止矣




Some Philosophy

Python is like chess

- Easy to learn, hard to master

Levels of learning

- Knowledge
- Understanding
- Application



Secret Recipe for Success in CS1010S


- DOING IT (Getting hands dirty and writing code)!

Lots of Optional
Trainings


Remedial

Check Announcements

Expected Level Progression



Difficulty Curve



Plagiarism

The act of presenting another's work or idea that as your own.



Today's Agenda

- Python Lists
- Searching
 - Linear search
 - Binary search
- Sorting
 - Basic sorting algorithms
 - Properties of sorting

Why Lists?

- Recall: tuples are **immutable**.

```
int_tuple = (1, 2, 3)
```

```
int_tuple[0] = 5
```

TypeError: 'tuple' object does not support item assignment

- What about lists?

```
int_list = [1, 2, 3] # this is a list
```

```
int_list[0] = 5      # [5, 2, 3]
```

Mutable!!

a.k.a. Arrays

Lists are sequences
So are tuples and strings

Sequence Operations

Tuple

```
()  
(1, 2, 3)  
type((1, 2, 3))  
<class 'tuple'>
```

```
t = tuple(range(5))  
→ (0, 1, 2, 3, 4)  
t[4] → 4  
t[2:] → (2, 3, 4)
```

List

```
[]  
[1, 2, 3]  
type([1, 2, 3])  
<class 'list'>
```

```
l = list(range(5))  
→ [0, 1, 2, 3, 4]  
l[4] → 4  
l[2:] → [2, 3, 4]
```

Sequence Operations

Tuple

a = (1, 2, 3, 4)

b = (5, 6, 7, 8)

c = a + b

c → (1, 2, 3, 4, 5, 6, 7, 8)

List

a = [1, 2, 3, 4]

b = [5, 6, 7, 8]


c = a + b

c → [1, 2, 3, 4, 5, 6, 7, 8]

Appending element to list

With Tuples, we can only create new tuples


```
tp1 = (1, 2, 3)
tp1 = tp1 + (4,)
```



With Lists, we can directly append to the list

```
>>> lst = [1, 2, 3]
>>> lst.append(4)
>>> lst
[1, 2, 3, 4]
```

element



No reassignment necessary

Extending list with list

We can also directly **extend** an existing list

```
lst = [1, 2, 3]      list
lst.extend([4, 5, 6])
lst                  → [1, 2, 3, 4, 5, 6]
```

This is **equivalent** to the following

```
lst = [1, 2, 3]
lst += [4, 5, 6]
lst                  → [1, 2, 3, 4, 5, 6]
```

Mutable versus Immutable

```
lst = [1, 2, 3]
```

```
lst2 = lst
```

```
lst == lst2
```

→ True

```
lst is lst2
```

→ True

```
lst += [4, 5, 6]
```

```
lst
```

→ [1, 2, 3, 4, 5, 6]

```
lst2
```

→ [1, 2, 3, 4, 5, 6]

```
lst == lst2
```

→ True

```
lst is lst2
```

→ True

Mutable versus Immutable

```
tup = (1, 2, 3)
```

```
tup2 = tup
```

```
tup == tup2
```

→ True

```
tup is tup2
```

→ True

```
tup += (4, 5, 6)
```

```
tup
```

(1, 2, 3, 4, 5, 6)

```
tup2
```

(1, 2, 3)

```
tup == tup2
```

→ False

```
tup is tup2
```

→ False

Deleting Elements

```
>>> a = [-1, 1, 66.25, 333, 333, 1234.5]
```

```
>>> del a[0]
```

```
>>> a
```

```
[1, 66.25, 333, 333, 1234.5]
```

```
>>> del a[2:4]
```

```
>>> a
```

```
[1, 66.25, 1234.5]
```

```
>>> del a[:]
```

```
>>> a
```

```
[]
```

What if we do `del a`?

Sequence Operations

Some other handy functions that will work on sequences

<code>len([1, 2, 3, 4])</code>	<code>→ 4</code>
<code>min([1, 2, 3, 4])</code>	<code>→ 1</code>
<code>max([1, 2, 3, 4])</code>	<code>→ 4</code>
<code>1 in [1, 2, 3]</code>	<code>→ True</code>
<code>5 not in [1, 2, 3]</code>	<code>→ True</code>
<code>[1, 2, 3] * 2</code>	<code>→ [1, 2, 3, 1, 2, 3]</code>

List Operations

```
lst = [1, 2, 3, 4]
```

```
lst.copy()
```

returns a shallow copy of a list

```
lst.insert(<pos>, <element>)
```

inserts `element` into position `pos`

List Operations

`lst.pop(<pos>)`

returns and remove element at position `pos`. If `pos` is omitted, removes the last element

`lst.remove(<element>)`

removes first occurrence of `element` from list, error if `element` is not in the list.

`lst.clear()`

clears the list

List Operations

```
s = [1, 2, 3, 4, 5]
t = s.copy()      # t = [1, 2, 3, 4, 5]
s.reverse()       # s = [5, 4, 3, 2, 1]
                  # t = [1, 2, 3, 4, 5]
s.insert(0, 1)     # s = [1, 5, 4, 3, 2, 1]
s.pop()            # 1
                  # s = [1, 5, 4, 3, 2]
s.pop(1)           # 5
                  # s = [1, 4, 3, 2]
s.insert(2, 2)     # s = [1, 4, 2, 3, 2]
s.remove(4)        # s = [1, 2, 3, 2]
s.clear()          # s = []
```

Iterating on Lists

We can iterate through lists using `for` operator

```
>>> s = [1, 2, 3, 4, 5]
```

```
>>> for element in s:  
    print(element)
```

1

2

3

4

5

List Comprehension

We can iterate also generate new lists

```
>>> s = [1, 2, 3, 4, 5]
>>> t = [n**2 for n in s]
[1, 4, 9, 16, 25]
```

Does this look familiar?

It should. This is equivalent to:

```
t = list(map(lambda n: n**2, s))
```


List Comprehension

Together with a filter

```
>>> s = [1, 2, 3, 4, 5]
>>> t = [n**2 for n in s if n%2]
[1, 9, 25]
```

This is equivalent to:

```
t = list(map(lambda n: n**2,
             filter(lambda n: n%2), s))
```

Python Lists: Summary

- Lists are **sequences**
 - can be used with all the sequence operations
- Lists are **mutable**
 - has mutable operations which are not common to tuples and strings

Searching

Searching

- You have a list.
- How do you find something in the list?
- **Basic idea:** go through the list from start to finish one element at a time.

Linear Search

- Idea: go through the list from start to finish

5	2	3	4
---	---	---	---

- Example: Search for 3

5	2	3	4
---	---	---	---

3 not found, move on

5	2	3	4
---	---	---	---

3 not found, move on

5	2	3	4
---	---	---	---

Found 3.

Linear Search

Idea: go through the list from start to finish

```
# equivalent code
for i in [5, 2, 3, 4]:
    if i == 3:
        return True
```

Linear Search

Implemented as a function:

```
def linear_search(value, lst):  
    for i in lst:  
        if i == value:  
            return True  
    return False
```

What kind of performance can we expect?

Large vs small lists?

Sorted vs unsorted lists?

$O(n)$

Can we do better?

Of course Ia!

Searching

IDEA:

If the elements in the list were sorted in order, life would be much easier.


Why?




IDEA

If list is sorted, we can
“divide-and-conquer”

Assuming a list is sorted in ascending order:





if the k^{th} element is larger than what we are looking for, then we only need to search in the indices $< k$

Binary Search

1. Find the middle element.
2. If it is what we are looking for (key), return **True**.
3. If our key is smaller than the middle element, repeat search on the left of the list.
4. Else, repeat search on the right of the list.

Binary Search

Looking for 25 (key)

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

Find the middle element: 34

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

Not the thing we're looking for: $34 \neq 25$

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

$25 < 34$, so we repeat our search on the left half:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

Binary Search

Find the middle element: 12

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

$25 > 12$, so we repeat the search on the right half:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

Find the middle element: 25

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

Great success: 25 is what we want

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

Binary Search

“Divide and Conquer”

In large sorted lists, performs much better than linear search on average.

Binary Search

Algorithm (assume sorted list):

1. Find the middle element.
2. If it is we are looking for (key), return True.
3. A) If our key is **smaller** than the middle element, repeat search on the left of the element.
B) Else, repeat search on the right of the element.

Binary Search

```
def binary_search(key, seq):  
    if seq == []:  
        return False  
    mid = len(seq) // 2  
    if key == seq[mid]:  
        return True  
    elif key < seq[mid]:  
        return binary_search(key, seq[:mid])  
    else:  
        return binary_search(key, seq[mid+1:])
```

Binary Search

```
def binary_search(key, seq): # seq is sorted
    def helper(low, high):
        if low > high:
            return False
        mid = (low + high) // 2 # get middle
        if key == seq[mid]:
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
    return helper(0, len(seq)-1)
```

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):  
    def helper(low, high):  
        if low > high:  
            return False  
        mid = (low + high) // 2  
        if key == seq[mid]:  
            return True  
        elif key < seq[mid]:  
            return helper(low, mid-1)  
        else:  
            return helper(mid+1, high)  
    return helper(0, len(seq)-1)
```

Step 1. Find the
middle element.

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):  
    def helper(low, high):  
        if low > high:  
            return False  
        mid = (low + high) // 2  
        if key == seq[mid]:  
            return True  
        elif key < seq[mid]:  
            return helper(low, mid-1)  
        else:  
            return helper(mid+1, high)  
    return helper(0, len(seq)-1)
```

key → 11

helper(0, 10-1)

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):  
    def helper(low, high): # 0, 9  
        if low > high:  
            return False  
        mid = (low + high) // 2 # mid=4  
        if key == seq[mid]:  
            return True  
        elif key < seq[mid]:  
            return helper(low, mid-1)  
        else:  
            return helper(mid+1, high)  
    return helper(0, len(seq)-1)
```

Step 1. Find the
middle element.

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):  
    def helper(low, high): # 0, 9  
        if low > high:  
            return False  
        mid = (low + high) // 2 # mid=4  
        if key == seq[mid]: # 11 == 25  
            return True  
        elif key < seq[mid]:  
            return helper(low, mid-1)  
        else:  
            return helper(mid+1, high)  
    return helper(0, len(seq)-1)
```

Step 2. If it is
what we are
looking for,
return True

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):
    def helper(low, high): # 0, 9
        if low > high:
            return False
        mid = (low + high) // 2 # mid=4
        if key == seq[mid]: # 11 == 25
            return True
        elif key < seq[mid]: # 11 < 25
            return helper(low, mid-1) # helper(0, 4-1)
        else:
            return helper(mid+1, high)
    return helper(0, len(seq)-1)
```

Step 3a. If key is
smaller, look at
left side

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):
    def helper(low, high): # 0, 3
        if low > high:
            return False
        mid = (low + high) // 2 # mid=4
        if key == seq[mid]: # 11 == 25
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
    return helper(0, len(seq)-1)
```

Step 3a. If key is
smaller, look at
left side

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):  
    def helper(low, high): # 0, 3  
        if low > high:  
            return False  
        mid = (low + high) // 2 # mid=1  
        if key == seq[mid]:  
            return True  
        elif key < seq[mid]:  
            return helper(low, mid-1)  
        else:  
            return helper(mid+1, high)  
    return helper(0, len(seq)-1)
```

Step 1. Find the
middle element

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):
    def helper(low, high): # 0, 3
        if low > high:
            return False
        mid = (low + high) // 2 # mid=1
        if key == seq[mid]: # 11 == 9
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
    return helper(0, len(seq)-1)
```

Step 2. If it is
what we are
looking for,
return True

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):
    def helper(low, high): # 0, 3
        if low > high:
            return False
        mid = (low + high) // 2 # mid=1
        if key == seq[mid]: # 11 == 9
            return True
        elif key < seq[mid]: # 11 < 9
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
    return helper(0, len(seq)-1)
```

Step 3a. If key
is smaller, look
at left side

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):  
    def helper(low, high): # 0, 3  
        if low > high:  
            return False  
        mid = (low + high) // 2 # mid=1  
        if key == seq[mid]: # 11 == 9  
            return True  
        elif key < seq[mid]: # 11 < 9  
            return helper(low, mid-1)  
        else:  
            return helper(mid+1, high) # helper(1+1, 3)  
    return helper(0, len(seq)-1)
```

Step 3b. Else
look at right
side

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):  
    def helper(low, high): # 2, 3  
        if low > high:  
            return False  
        mid = (low + high) // 2  
        if key == seq[mid]:  
            return True  
        elif key < seq[mid]:  
            return helper(low, mid-1)  
        else:  
            return helper(mid+1, high)  
    return helper(0, len(seq)-1)
```

Step 3b. Else
look at right
side

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):  
    def helper(low, high): # 2, 3  
        if low > high:  
            return False  
        mid = (low + high) // 2  
        if key == seq[mid]:  
            return True  
        elif key < seq[mid]:  
            return helper(low, mid-1)  
        else:  
            return helper(mid+1, high)  
    return helper(0, len(seq)-1)
```

Step 3b. Else
look at right
side

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):
    def helper(low, high): # 2, 3
        if low > high:
            return False
        mid = (low + high) // 2 # mid=2
        if key == seq[mid]:
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
    return helper(0, len(seq)-1)
```

Step 1. Find
the middle
element

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):
    def helper(low, high): # 2, 3
        if low > high:
            return False
        mid = (low + high) // 2 # mid=2
        if key == seq[mid]: # 11 == 12
            return True
        elif key < seq[mid]:
            return helper(low, mid-1)
        else:
            return helper(mid+1, high)
    return helper(0, len(seq)-1)
```

Step 2. If it is
what we are
looking for,
return True

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):
    def helper(low, high): # 2, 3
        if low > high:
            return False
        mid = (low + high) // 2 # mid=2
        if key == seq[mid]: # 11 == 12
            return True
        elif key < seq[mid]: # 11 < 12
            return helper(low, mid-1) # helper(2, 2-1)
        else:
            return helper(mid+1, high)
    return helper(0, len(seq)-1)
```

Step 3a. If key
is smaller, look
at left side

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):  
    def helper(low, high): # 2, 1  
        if low > high:  
            return False  
        mid = (low + high) // 2  
        if key == seq[mid]:  
            return True  
        elif key < seq[mid]:  
            return helper(low, mid-1)  
        else:  
            return helper(mid+1, high)  
    return helper(0, len(seq)-1)
```

Step 3a. If key
is smaller, look
at left side

Binary Search

Now let's try searching for 11:

5	9	12	18	25	34	85	100	123	345
---	---	----	----	----	----	----	-----	-----	-----

```
def binary_search(key, seq):  
    def helper(low, high): # 2, 1  
        if low > high: # 2 > 1  
            return False  
        mid = (low + high) // 2  
        if key == seq[mid]:  
            return True  
        elif key < seq[mid]:  
            return helper(low, mid-1)  
        else:  
            return helper(mid+1, high)  
    return helper(0, len(seq)-1)
```

Key cannot be
found. Return
False

Binary Search

- Each step eliminates the problem size by half.
 - The problem size gets reduced to 1 very quickly
- This is a simple yet powerful strategy, of halving the solution space in each step
- What is the order of growth?

$$O(\log n)$$

Wishful Thinking

We assumed the list was sorted.

Now, let's deal with this assumption!

Sorting

Sorting

- High-level idea:
 1. some objects
 2. function that can order two objects


⇒ order all the objects

How Many Ways to
Sort?

Too many. 😊

Example

Let's sort some playing cards?




What do you do when
you play cards?

Obvious Way

Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.


Unsorted



Sorted




Smallest



Obvious Way


Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Sorted


Smallest



Obvious Way


Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Sorted


Smallest



Obvious Way


Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Sorted


Smallest



Obvious Way


Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Sorted


Smallest



Obvious Way


Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Sorted


Smallest



Obvious Way


Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Sorted


Smallest



Obvious Way


Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Sorted



Smallest




Obvious Way

Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Sorted




Smallest


Obvious Way

Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.


Unsorted




Repeat



Sorted





Smallest



Obvious Way



Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted



Repeat

Sorted




Smallest

Obvious Way

Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.



Unsorted




Repeat



Sorted



Smallest




Obvious Way

Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.



Unsorted



Repeat



Sorted



Smallest

Obvious Way

Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.




Unsorted



Repeat



Sorted



Smallest



Obvious Way

Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.


Unsorted



Repeat



Sorted



Smallest


Obvious Way

Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.


Unsorted



Repeat



Sorted



Smallest



Obvious Way

Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.




Unsorted



Repeat



Sorted



Smallest

Obvious Way

Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.



Unsorted



Repeat



Sorted



Smallest



Obvious Way


Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted

Repeat



Sorted



Smallest

Obvious Way


Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted

Repeat



Sorted



Smallest



Obvious Way


Find the smallest card not in hand (SCNIH), and put it at the end of your hand. Repeat.

Unsorted

Done

Sorted

Smallest



There is actually a name for this:

Selection Sort!

Let's Implement it!

```
a = [4,12,3,1,11]
```

```
sort = []
```

```
while a:    # a is not []
    smallest = a[0]
    for element in a:
        if element < smallest:
            smallest = element
    a.remove(smallest)
    sort.append(smallest)
print(a)
```

Output

```
[4, 12, 3, 11]
```

```
[4, 12, 11]
```

```
[12, 11]
```

```
[12]
```

```
[]
```

```
print(a)
```

```
[]
```

```
print(sort)
```

```
[1, 3, 4, 11, 12]
```

Order of Growth?

- Time: Worst $O(n^2)$
 Average $O(n^2)$
 Best $O(n^2)$
- Space: ~~$O(n)$~~ $O(1)$


Let's try something
else...

suppose you have a
friend

Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.


Split into halves



Doing it with a friend




- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.

Split into halves





Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.






Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.





Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.





Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.





Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.






Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.






Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.






Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.





Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.





Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.



Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.




How to combine the 2 sorted halves?

Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.



Compare first elements



Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.




Compare first elements



Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.



Compare first elements



Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.


Compare first elements



Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.


Compare first elements



Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.

Compare first elements



Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.


Compare first elements



Doing it with a friend

- Split cards into two halves and sort. Combine halves afterwards. Repeat with each half.

Compare first elements




There is also a name for this:

Merge Sort!

Let's Implement It!

First observation: **RECURSION!**

- Base case: $n < 2$, return list
- Otherwise:



- Divide list into two
- Sort each of them
- Merge!

Merge Sort

```
def merge_sort(lst):  
    if len(lst) < 2:  # Base case!  
        return lst  
    mid = len(lst) // 2  
    left = merge_sort(lst[:mid])  #sort left  
    right = merge_sort(lst[mid:]) #sort right  
    return merge(left, right)
```

How to merge?

How to merge?

- Compare first element
- Take the smaller of the two
- Repeat until no more elements

Merging

```
def merge(left, right):  
    results = []  
    while left and right:  
        if left[0] < right[0]:  
            results.append(left.pop(0))  
        else:  
            results.append(right.pop(0))  
    results.extend(left)  
    results.extend(right)  
    return results
```

Order of Growth?

- Time:

Worst	$O(n \log n)$
Average	$O(n \log n)$
Best	$O(n \log n)$
- Space: $O(n)$

No need to memorize

Sort Properties

In-place: uses a small, constant amount of extra storage space, i.e., $O(1)$ space

Selection Sort: No (Possible)

Merge Sort: No (Possible)

Sort Properties

Stability: maintains the relative order of items with equal keys (i.e., values)

Selection Sort: Yes (maybe)

Merge Sort: Yes

How Many Ways to
Sort?

Too many. 😊

How Many Sort Must You Learn?

None (sort of) 😊

`list.sort()`

No need to remember the
time/space complexity

list.sort

- `sort(*, key=None, reverse=None)`
 - This method sorts the list in place, using only < comparisons
 - Exceptions are not suppressed - if any comparison operations fail, the entire sort operation will fail (and the list will likely be left in a partially modified state).
 - `key` specifies a function of one argument that is used to extract a comparison key from each list element
 - `reverse` is a boolean value. If set to `True`, then the list elements are sorted as if each comparison were reversed.
 - This method modifies (mutates) the sequence in place.
 - The `sort()` method is guaranteed to be stable

Example

```
>>> a = [4, 32, 3, 34, 7, 31, 2, 1]
```

```
>>> a.sort()
```

```
>>> print(a)
```

```
[1, 2, 3, 4, 7, 31, 32, 34]
```

```
>>> a.sort(key=lambda x: x%5)
```

```
>>> print(a)
```

```
[1, 31, 2, 7, 32, 3, 4, 34]
```

Sorting Records

Mostly not entirely too useful to sort values.
Typically, we sort records using a key.

Example

```
students = [  
    ('john', 'A', 15),  
    ('jane', 'B', 10),  
    ('ben', 'C', 8),  
    ('simon', 'A', 21),  
    ('dave', 'B', 12)]
```

Example

```
students.sort()  
print(students)  
[('ben', 'C', 8),  
 ('dave', 'B', 12),  
 ('jane', 'B', 10),  
 ('john', 'A', 15),  
 ('simon', 'A', 21)]
```

Example

```
students.sort(key=lambda x: x[2], reverse=True)
print(students)
[('simon', 'A', 21),
 ('john', 'A', 15),
 ('dave', 'B', 12),
 ('jane', 'B', 10),
 ('ben', 'C', 8)]
```

Example

```
students.sort(key=lambda x: x[1])  
print(students)  
[('simon', 'A', 21),  
 ('john', 'A', 15),  
 ('dave', 'B', 12),  
 ('jane', 'B', 10),  
 ('ben', 'C', 8)]
```

Example

```
students = [  
    ('john', 'A', 15),  
    ('jane', 'B', 10),  
    ('ben', 'C', 8),  
    ('simon', 'A', 21),  
    ('dave', 'B', 12)]
```

Example

```
students.sort(key=lambda x: x[1])  
print(students)  
[('john', 'A', 15),  
 ('simon', 'A', 21),  
 ('jane', 'B', 10),  
 ('dave', 'B', 12),  
 ('ben', 'C', 8)]
```

Scipy

Numpy

Summary

- Python Lists are mutable data structures
- Searching
 - Linear Search
 - Binary Search: Divide-and-conquer
- Sorting
 - Selection Sort
 - Merge Sort: Divide-and-conquer + recursion
 - Properties: In-place & Stability