


I. Instruction Set

Instruction Set	Instruction	B	C	Opcode	Operand 1	Operand 2
AND -> A	ANL A, Rn	1	1	01011111	<direct>	
	ANL A, direct	2	1	01010101	<direct>	
	ANL A, @Ri	1	1	01010111	<data>	
	ANL A, #<data>	2	1	01010100	<data>	
	ANL direct, A	2	1	01010010	<direct>	<data>
OR -> A	ORL A, Rn	1	1	01011111	<direct>	
	ORL A, direct	2	1	01000101	<direct>	
	ORL A, @Ri	1	1	01000111	<data>	
	ORL A, #<data>	2	1	01000100	<data>	
	ORL direct, A	2	1	01000010	<direct>	<data>
XOR -> A	XRL A, Rn	1	1	01101111	<direct>	
	XRL A, direct	2	1	01100101	<direct>	
	XRL A, @Ri	1	1	01100111	<data>	
	XRL A, #<data>	2	1	01100100	<data>	
	XRL direct, A	2	1	01100010	<direct>	<data>
rotate ACC right	RR A	1	1	00000011		
	rotate ACC left	1	1	00100011		
	rotate ACC right through C	1	1	00010011		
	rotate ACC left through C	1	1	00110011		
	swap low and high nibbles in ACC	1	1	10001000		
set bit low	CLR C	1	1	11000011	<bit address>	
	CPL C	1	1	10110011	<bit address>	
	CPL, <bit>	2	1	10110100	<bit address>	
	SETB C	1	1	11010011	<bit address>	
	SETB, <bit>	2	1	11010010	<bit address>	
single-bit logic	ANL C, <bit>	2	2	10000010	<bit address>	
	ANL C, /<bit>	2	2	10110000	<bit address>	
	ORL C, <bit>	2	2	01110010	<bit address>	
	ORL C, /<bit>	2	2	01010000	<bit address>	
	MOV C, <bit>	1	1	11010001	<bit address>	
hitwise move	MOV, <bit>, C	2	2	10010010	<bit address>	
	JC, <offset>	2	2	01000000	<offset>	
	JNC, <offset>	2	2	01010000	<offset>	
	JB, <bit>, <offset>	3	2	00100000	<bit address>	<offset>
	JNB, <bit>, <offset>	3	2	00110000	<bit address>	<offset>
Jump and clear bit if bit set	JBC, <bit>, <offset>	3	2	00010000	<bit address>	<offset>
	ADD A, Rn	1	1	00101111	<direct>	
	ADD A, @Ri	1	1	00100111	<data>	
	ADD A, #<data>	2	1	00100100	<data>	
	ADDC A, Rn	1	1	00111111	<direct>	
A + val -> A	ADDC A, <direct>	2	1	00110101	<direct>	
	ADDC A, @Ri	1	1	00110111	<data>	
	ADDC A, #<data>	2	1	00110100	<data>	
	SUBB A, Rn	1	1	10011111	<direct>	
	SUBB A, @Ri	1	1	10010111	<data>	
A - val -> A	SUBB A, #<data>	2	1	10010100	<data>	
	INC A	1	1	00000100		
	INC Rn	1	1	00001111	<direct>	
	INC, <direct>	2	1	00000101	<direct>	
	INC @Ri	1	1	00000111	<data>	
Increment	INC DPTR	1	2	10100011		
	DEC A	1	1	00010100		
	DEC Rn	1	1	00011111	<direct>	
	DEC, <direct>	2	1	00010101	<direct>	
	DEC @Ri	1	1	00010111	<data>	
Decrement	MUL AB	1	4	10101000		
	DIV AB	1	4	10001000		
	MOV @Ri, #<data>	2	1	01101111	<data>	
	MOV @Ri, A	1	1	11101111	<src>	
	MOV @Ri, <direct>	2	1	10101111	<data>	
dest <- src	MOV A, #<data>	2	1	01101000	<data>	
	MOV A, @Ri	1	1	11100111	<src>	
	MOV A, <direct>	2	1	11100101	<src>	
	MOV A, Rn	1	1	11101111	<src>	
	MOV, <direct>, <direct>	1	1	11101111	<dest>	<src>
no fucking clue	MOV, <direct>, #<data>	3	2	01101011	<dest>	<data>
	MOV, <direct>, @Ri	1	1	10001111	<dest>	<data>
	MOV, <direct>, A	2	1	11101011	<dest>	<data>
	MOV, <direct>, Rn	2	2	10001111	<dest>	<data>
	MOV DPTR, #<data>	2	2	10010000	<data>	<data>
stack operations	MOV Rn, #<data>	2	1	11111111	<data>	
	MOV Rn, A	1	1	11111111	<data>	
	MOV Rn, <direct>	2	2	10101111	<src>	
	MOV Rn, @Ri	1	1	11001111	<src>	
	MOV Rn, #<data>	2	2	11011111	<src>	
exchange A and src	MOVC A, @A+DPTR	1	2	10010011		
	MOVC A, @A+PC	1	2	10000011		
	MOVX @Ri, A	1	2	11100111		
	MOVX A, @DPTR	1	2	11100000		
	MOVX A, @Ri	1	2	11100011		
calling subroutines	PUSH <direct>	2	2	11000000	<src>	
	POP <direct>	2	2	11000000	<dest>	
	XCH A, @Ri	1	1	11001111	<src>	
	XCH A, <direct>	2	1	11001011	<src>	
	XCH A, Rn	1	1	11001111	<src>	
jumping and branching	XCHD A, @Ri	1	1	11010111	<src>	
	ACALL <direct(11b)>	2	2	aaa10001	<addr/low>	<addr/high>
	LCALL <direct(16b)>	3	2	00010010	<addr/low>	<addr/high>
	RET	1	2	00100010	<addr/low>	<addr/high>
	RETI	1	2	00110010	<addr/low>	<addr/high>
do nothing	AJMP <direct(11b)>	2	2	aaa00001	<addr/low>	<addr/high>
	LJMP <direct(16b)>	3	2	00000010	<addr/low>	<addr/high>
	SJMP <offset(8b)>	2	2	10000000	<offset>	
	JMP @A+DPTR	1	2	01110011	<offset>	
	JZ <offset(8b)>	2	2	01100000	<offset>	
jumping and branching	JNC <offset(8b)>	2	2	01110000	<offset>	
	CJNE @Ri, #<data>, <offset(8b)>	3	2	10110111	<data>	<offset>
	CJNE A, #<data>, <offset(8b)>	3	2	10110100	<data>	<offset>
	CJNE A, <direct>, <offset(8b)>	3	2	10110101	<data>	<offset>
	CJNE Rn, #<data>, <offset(8b)>	3	2	10111111	<data>	<offset>
do nothing	DJNZ <direct>, <offset(8b)>	3	2	11010101	<src>	<offset>
	DJNZ Rn, <offset(8b)>	2	2	11011111	<src>	<offset>
	NO	1	1	00000000		

B. Memory Organization



II. 8051 Organization

Programs can be in either "absolute form", or "relocatable form". If they are in relocatable form, linking is required to set the absolute addresses for execution.


ROM	4K
RAM	128B
Address Bus	16b
I/O	4x 8b parallel ports, 1x serial port (all bit-addressable)

PSW.7	CY	0xD7
PSW.6	AC	0xD6
PSW.5	F0	0xD5
PSW.4	RS1	0xD4
PSW.3	RS0	0xD3
PSW.2	OV	0xD2
PSW.1	0xD1	
PSW.0	P	0xD0

C. Program Flow

1	program & data read in and stored in main memory
2	Instruction Fetch Cycle
3	Instruction fetched from main memory
4	Instruction Execution Cycle
5	Operand(s) fetched
6	Operation performed
	GOTO 1

A. Components



1) Embedded System Advantages:

- low power consumption
- small size
- ugged operating ranges
- low unit cost


D. Addressing Modes

Implied Mode	operands are specified implicitly
Immediate Mode	operands evaluate to values
Index Mode	effective address determined by both the contents of the index register and a displacement
Register Mode	operand is a register containing wanted value
Direct Mode	operands are addresses pointing to wanted value
Indirect Register Mode	operand is either R0 or R1, which contains an address pointing to wanted value

III. I/O

D. Interrupts

A. Pinout



B. Serial Port Operation

1) Modes:

Mode	Description	Baud Rate
0	Shift register	Fixed(freq/12)
1	8-bit UART	Variable(T1)
2	9-bit UART	Fixed(freq/12 16)
3	9-bit UART	Variable(T1)

2) Baud Rate:

Baud Rate	Crystal Freq	SMOD	TH1	Actual	Error
9600	12,000 MHz	1	-7(0xF9)	8923	7%
2400	12,000 MHz	0	-13(0xF3)	2404	.16%
1200	12,000 MHz	0	-26(0xE6)	1202	.16%
19200	11,059 MHz	1	-3(0xFD)	19200	0
9600	1,059 MHz	0	-3(0xFD)	9600	0
2400	11,059 MHz	0	-12(0xF4)	2400	0
1200	11,059 MHz	0	-24(0xE8)	1200	0

C. Timer Operation

Mode	Description	Max Interval
0	13-bit	
1	16-bit	65536μs
2	8-bit auto-reload	256μs
3	Split-timer mode	256μs

1) Interval Timing v. Event Counting: Interval timing works as one would expect, where the timer is started, and then stopped either by overflow or manually. Event counting works by pulsing the timer when an external source pulses, effectively counting external pulses. This is set by setting 'C/T' high.

2) 13-bit Timer:

3) 16-bit Timer: In 16-bit timer mode, THx and TLx hold the high and low bytes, respectively.

4) 8-bit Auto-Reload Timer: In auto-reload mode, TLx acts as an 8-bit timer, while THx holds a reload value. When TLx overflows, it is reloaded with the value in THx.

5) Split-Timer Mode: In split-timer mode, T0 is split into two 8-bit timers. Consequently, TL0 and TH0 act as separate timers, using TF1 for TH0, rather than for T1.

Since T1 is stopped in split-timer mode, but can be reactivated by switching to its own mode 3, split-timer mode is common for generating baud-rates, since T1 can be switched on and off at arbitrary intervals.

INTERRUPT	FLAG	bit position	Vector address
External0	IE0	TCON.1	0x03
External1	IE1	TCON.3	0x13
Timer1	TF1	TCON.7	0x1B
Timer0	TF0	TCON.5	0x0B
Transmit	TI	SCON.1	0x23
Receive	RI	SCON.0	0x23

1) Interrupt and Priority Bits:

BIT	Symbol	Bit address	Semantics 1 = Enable, 0 = Disable	BIT	Symbol	Bit address	Semantics 1 = Higher level, 0 = Lower level
IE.7	EA	A8H	Global enable/disable interrupt	IP.7	-	-	Unused
IE.6	-	AEH	Unused	IP.6	-	-	Unused
IE.5	ET2	ADH	Enable timer2 interrupt(8052)	IP.5	PT2	0BDH	Priority for timer2 interrupt(8052)
IE.4	ES	ACH	Enable Serial port interrupt	IP.4	PS	0BCH	Priority for Serial port interrupt
IE.3	ET1	ABH	Enable timer1 interrupt	IP.3	PT1	0BBH	Priority for timer1 interrupt
IE.2	EX1	AAH	Enable external1 interrupt	IP.2	PX1	0BAH	Priority for external1 interrupt
IE.1	ET0	A9H	Enable timer0 interrupt	IP.1	PT0	0BAH	Priority for timer0 interrupt
IE.0	EX0	A8H	Enable external0 interrupt	IP.0	PX0	0BAH	Priority for external0 interrupt

IV. Examples