

DESCRIPTION

ATF DEX III (UNIVERSAL) is multi-functional automatic transmission fluid for older cars requiring GM Dexron III plus a wide range of other vehicle applications. It is a blend of highly stable base oils and an advanced automatic transmission fluid additive technology to improve transmission durability, shift performance and minimize transmission shudder. It provides excellent oxidization and thermal stability resulting for excellent performance during its service life.

SUMMARY OF BENEFITS

- Anti-shudder durability for smooth shifting performance
- Enhanced wear protection
- Covers a wide range of automatic transmission applications to reduce stockholdings

SPECIFICATIONS

- GM ATF DEXRON III-H
- ALLISON C-4
- ZF TE-ML-14A
- VOLVO 97341
- HONDA Z1
- VOITH H55.6335.XX
- MAN 339 TYPE V-1, Z-1
- MITSUBISHI SP-II AND SP-III
- MB, VW AND BMW 4 AND 5 SPEED AUTOMATICS.
- JASO 1-A
- TOYOTA T-III, T-IV
- FORD MERCON V / 95LE
- NISSAN MATIC D & J

TECHNICAL DATA

CHARACTERISTICS	ATF DEX III (UNIVERSAL)
Specific gravity at 15 C	0.8673
Kinematic viscosity at 40 C, mm ² /s (cSt)	41.30
Kinematic viscosity at 100 C, mm ² /s (cSt)	8.0
Viscosity index	170.0

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C