

DESCRIPTION

ATF SYN ULV is the latest new generation, ultra-low-viscosity automatic transmission fluid manufactured from advanced synthetic base stocks and the latest ATF additive technology. It is specifically engineered for the new high-speed 9 and 10 speed step automatic transmissions. Formulated to provide fuel economy while providing exceptional friction characteristics, smooth driving and transmission durability.

SUMMARY OF BENEFITS

- Exceptional wear protection for transmission durability
- Superior low and high temperature performance with excellent oil flow at very low temperatures
- Full synthetic formulation provides oxidation resistance for longer service life and friction durability
- Smooth operation due to excellent anti-shudder ability

SPECIFICATIONS

Aisin Warner AW-2

PSA 16 350 560 80

VW G 053 001

Volvo 31492172 / 312492173

Mazda ATF A7

Toyota THS 5th Gen. / Toyota Noah, Voxy etc.

Ford WSS-M2C949-A

GM ULV

MB 236.15, 236.16, 236.17

Nissan Matic-P

BMW 83777413477 (ATF 7)

TECHNICAL DATA

CHARACTERISTICS	SYN ATF ULV
Specific gravity at 15 C	0.830
Kinematic viscosity at 40 C, mm ² /s (cSt)	18.0
Kinematic viscosity at 100 C, mm ² /s (cSt)	4.24
Viscosity index	146

- Safety Data Sheet for this product can be obtained by visiting TriTech Lubricants Website www.tritechlubricants.com
- All Packages should be stored under cover to avoid water contamination and fading. Products should not be stored over 60°C