

[Contact us](#)

Insight for DBAs   MySQL

[Subscribe to RSS Feed](#)

# Using Blue/Green Deployment For (near) Zero-Downtime Primary Key Updates in RDS MySQL

January 22, 2025

Roberto De Bem

Large tables can pose challenges for many operations when working with a database. Occasionally, we may need to modify the table definition. Since RDS replication does not use asynchronous for its replication, the typical switchover procedure is not feasible. However, the Blue/Green feature of RDS utilizes asynchronous replication, which allows us to update the table definition of large tables using the switchover procedure.

The Blue/Green deployment strategy involves creating two separate but identical environments for an application. The current environment where the application runs is referred to as “Blue,” while the environment that contains the modifications or new version is called “Green.” This continuous deployment method allows the database to be updated with minimal downtime.

In this blog post, I will demonstrate how to alter a table whose primary key is nearing its maximum value using the Blue/Green environment.

For the following blog, please assume the following environment:



**beto-blog** Refresh Modify Actions


Related

Filter by databases

DB identifier	Status	Role	Engine	Region	Size	Recommendations	CPU	Current ...	Mainten...
<input checked="" type="radio"/> beto-blog	Available	Regional cl...	Aurora My...	us-east-1	3 Instances		-	-	none
<input type="radio"/> beto-blog-instance-1	Available	Writer inst...	Aurora My...	us-east-1a	db.r7g.large		6.17%	0.02 ses	none
<input type="radio"/> beto-blog-instance-1-us-east-1c	Available	Reader inst...	Aurora My...	us-east-1c	db.r7g.large		5.50%	0.00 ses	none
<input type="radio"/> beto-blog-instance-2	Available	Reader inst...	Aurora My...	us-east-1d	db.r5.large		19.72%	0.00 ses	none

We can create a Blue/Green environment with the aforementioned environment in mind. This process will establish a new environment that mirrors the structure of the production environment. Please note that to create a Blue/Green environment, the cluster parameter must have `binlog_format` set to `row`.

To create the Blue/Green environment, use the dropdown menu for actions and select the "Create Blue/Green Deployment" button.



Set the identifier of the deployment:

Before creating the Blue/Green environment, please review the configuration carefully. Remember that you can change the Aurora version during the creation process. This option allows for validation checks before the upgrade since all data will be replicated in the green environment.

After creation, please wait until all nodes in the green environment are available.

Having the nodes available allows us to begin the modification process. However, changing the column data type in a replica environment may lead to replication issues. To avoid this, since we are increasing the column type from `int` to `bigint`, we need to set the value of `replica_type_conversions` in the cluster parameter group. We will set this variable to `ALL_NON_LOSSY` (<https://dev.mysql.com/doc/mysql-replication-excerpt/8.0/en/replication-features-different-data-types.html>).

It's important to take note of the following bug report: <https://bugs.mysql.com/bug.php?id=82599>, which could cause issues when using unsigned data. Once we have completed the necessary steps, we can proceed with all the required alterations.

Stopping the replica:

	MySQL
1	MySQL - Green > <code>CALL mysql.rds_stop_replication;</code>
2	+-----+
3	Message
4	+-----+
5	Replica is down or disabled
6	+-----+
7	1 row in set (1.02 sec)
8	Query OK, 0 rows affected (1.02 sec)

Consider the following table definitions for the changes:

```

1 MySQL - Green > SHOW CREATE TABLE jointitG
2 ***** 1. row *****
3      Table: jointit
4 Create Table: CREATE TABLE `jointit` (
5   `i` int NOT NULL AUTO_INCREMENT,
6   `s` varchar(64) DEFAULT NULL,
7   `t` time NOT NULL,
8   `g` int NOT NULL,
9   PRIMARY KEY (`i`),
10  KEY `g_fk` (`g`),
11  CONSTRAINT `jointit_ibfk_1` FOREIGN KEY (`g`) REFERENCES `jointit_fk` (`i`) ON DELETE
12 ) ENGINE=InnoDB AUTO_INCREMENT=4653058 DEFAULT CHARSET=latin1
13 1 row in set (0.02 sec)
14
15 MySQL - Green > SHOW CREATE TABLE jointit_fkG
16 ***** 1. row *****
17      Table: jointit_fk
18 Create Table: CREATE TABLE `jointit_fk` (
19   `i` int NOT NULL,
20   PRIMARY KEY (`i`)
21 ) ENGINE=InnoDB DEFAULT CHARSET=utf8mb4 COLLATE=utf8mb4_0900_ai_ci
22 1 row in set (0.01 sec)

```

Doing the alter change:

```

1 MySQL - Green > ALTER TABLE jointit DROP FOREIGN KEY jointit_ibfk_1;
2 Query OK, 0 rows affected (0.03 sec)
3 Records: 0 Duplicates: 0 Warnings: 0
4
5 MySQL - Green > ALTER TABLE jointit MODIFY COLUMN g bigint NOT NULL;
6 Query OK, 4194391 rows affected (1 min 39.09 sec)
7 Records: 4194391 Duplicates: 0 Warnings: 0
8
9 MySQL - Green > ALTER TABLE jointit_fk MODIFY COLUMN i bigint NOT NULL;
10 Query OK, 60 rows affected (0.09 sec)
11 Records: 60 Duplicates: 0 Warnings: 0
12
13 MySQL - Green > ALTER TABLE jointit ADD CONSTRAINT jointit_ibfk_1 FOREIGN KEY (`g`) REF
14 Query OK, 4194391 rows affected (1 min 45.66 sec)
15 Records: 4194391 Duplicates: 0 Warnings: 0

```

After completing the process, we can start the replication and wait for it to catch up.

```

1 MySQL - Green > CALL mysql.rds_start_replication;
2 +-----+
3 | Message |
4 +-----+
5 | Replica running normally. |
6 +-----+
7 1 row in set (2.18 sec)
8 Query OK, 0 rows affected (2.18 sec)
9
10 MySQL - Green > SHOW REPLICATION STATUSG
11 ***** 1. row *****
12      Replica_IO_State: Waiting for source to send event
13      Source_Host: 10.1.15.0
14      Source_User: rdsrepladmin
15      Source_Port: 3306
16      Connect_Retry: 60
17      Source_Log_File: mysql-bin-changelog.000004
18      Read_Source_Log_Pos: 112774
19      Relay_Log_File: relaylog.000002
20      Relay_Log_Pos: 82470
21      Relay_Source_Log_File: mysql-bin-changelog.000004
22      Replica_IO_Running: Yes
23      Replica_SQL_Running: Yes
24 [...]
25      Seconds_Behind_Source: 0
26 [...]
27 1 row in set (0.01 sec)

```

Maintaining the replica in sync will enable the switchover; it's also highly recommended that you stop the application writes during the switchover procedure.

By selecting the deployment option from the action button in the top right, we can access the switchover button action:

After clicking, a panel will appear to switch over:

Now, we just need to wait for the switchover:

After the procedure is complete, we can see that the green nodes, which are the ones where we changed the columns, are now referred to as “new-blue.” These nodes already have the endpoint used by the application. The blue environment is now called “old-blue”:

Once completed, we can perform any needed validation before deleting the nodes. The application can now return to regular operation, and after the validations are done, the deployment and old blue versions can be deleted.

## Conclusion

The switchover procedure is a common practice used for various purposes; however, as previously mentioned, it cannot be accomplished using standard RDS replication. This limitation arises because RDS replication does not use the default asynchronous replication method found with MySQL’s binary log. Therefore, adopting a Blue/Green deployment strategy is a viable solution.

For further reads regarding blue/green deployments, please refer to <https://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/blue-green-deployments.html>

Also, please be familiar with the limitations of the blue/green deployments. You may see those on the following link: <https://docs.aws.amazon.com/AmazonRDS/latest/UserGuide/blue-green-deployments-considerations.html>

## FAQ

### Is there any rollback?

Unfortunately, the Blue/Green Environment has no built-in rollback feature. However, it is possible to perform a manual rollback, as demonstrated in the following AWS blog post: <https://aws.amazon.com/blogs/database/implement-a-rollback-strategy-after-an-amazon-aurora-mysql-blue-green-deployment-switchover/>

## Can I do MySQL upgrades with it?

Yes, using the Blue/Green for the MySQL upgrades is possible.

## What happens if any error on the replica happens?

In case of a replica error, the switchover will not happen, and checking on the **Log & events** tab on the deployment, you'll be able to see a similar error message: "Switchover from DB cluster beto-blog to beto-blog-green-usht2d was canceled due to replication errors on beto-blog-green-usht2d. Correct the replication errors and then switch over."

### Share This Post!



 [Subscribe](#) ▼

[Login](#)

*Be the First to Comment!*

**B** *I* U         



**0 COMMENTS**

# Want to get weekly updates listing the latest blog posts?

Subscribe now and we'll send  
you an update every Friday at  
1pm ET.

Email

Subscribe

Related Blog Articles

RECOMMENDED ARTICLES

May 29, 2025

Arunjit  
Aravind

How to  
Safely  
Upgrade  
InnoDB  
Cluster  
From  
MySQL  
8.0 to 8.4

Insight for  
DBAs  
MySQL

May 28, 2025

Andrey

The  
Open  
Source  
Ripple  
Effect:  
How  
Valkey Is  
Redefinin  
g the  
Future of  
Caching,  
and Why

MOST POPULAR ARTICLES

June 20, 2023

Sergey P

Deploy  
Django  
on  
Kubernete  
s With  
Percona  
Operator  
for  
PostgreS  
QL

Cloud  
Insight for  
Developers  
Percona  
Software  
PostgreSQL

December 28,  
2012

Miguel A  
Nieto

Auditing  
Login  
attempts  
in MySQL

MySQL



It Matters

Insight for DBAs  
Open Source  
Valkey

May 16, 2016

Muhamn Irfan

MySQL “Got an error reading communication packet”

MySQL

May 27, 2025

David C

Beyond Guesswork: Enterprise-Grade PostgreSQL Tuning with pg\_stat\_statements

Insight for DBAs  
PostgreSQL

# Ready to get started?

Subscribe to our newsletter for updates on enterprise-grade open source software and tools to keep your business running better.

Email

First Name

Last Name

Company Name

**SUBMIT**

By submitting my information I agree that Percona may use my personal data in sending communication to me about Percona services. I understand that I can unsubscribe from the communication at any time in accordance with the [Percona Privacy Policy](#). This site is protected by reCAPTCHA and the Google [Privacy Policy](#) and [Terms of Service](#) apply.

**Follow us for updates**

## Featured

MySQL 5.7 End of Life

## Learn

Downloads

Resources

## Products

MySQL

MongoDB

PostgreSQL

Cloud Native

Monitoring

## Services

Support

Managed Services

Consulting

Policies

Training

Docs

Percona Toolkit

Use Cases

- Emergency Support
- High-Traffic Events
- Performance Tuning
- Migrations
- Upgrades
- Security

Discover

- Blog
- Community
- Percona Community Forum
- Events

About

- About Percona
- Partners
- In The News
- Careers

Terms of Use Privacy Copyright Legal Security Center

MySQL, PostgreSQL, InnoDB, MariaDB, MongoDB and Kubernetes are trademarks for their respective owners.

Copyright © 2006–2025 Percona LLC.