PRIVATE SEWAGE DISPOSAL SYSTEMS

Appendix G

TABLE G-4

Single-Family Dwellings Number of Bedrooms	Multiple Dwelling Units or Apartments – One Bedroom Each	Other Uses: Maximum Fixture Units Served per Table 7–4	Minimum Septic Tank Capacity in L
1 or 2		15	2,839
3		20	3,785
4	2 units	25	4,542
5 or 6	3	33	5,678
	4	45	7,571
	5	55	8,517
	6	60	9,464
	7	70	10,410
	8	80	11,356
	9	90	12,302
	10	100	13,249

*Note:

Extra bedroom, 568L (150 gal.) each.

Extra dwelling units over 10: 946L (250 gal.) each.

Extra fixture units over 100: 95L (25 gal.) per fixture unit.

Septic tank sizes in this table include sludge storage capacity and the connection of domestic food waste disposal units without further volume increase.

SI: 1L = 0.26 gal.

TABLE G-5

Estimated Waste/Sewage Flow Rates*				
Type of Occupancy	L/day			
1. Airports				
2. Auto washers	Check with equipment manufacturer			
3. Bowling alleys (snack bar only)	285 per lane			
4. Camps: Campground with central comfort station				
6. Dance halls	20 per person			
7. Factories No showers With showers Cafeteria, add	135 per employee			
8. Hospitals	95 per bed			
9. Hotels (no kitchen waste)	230 per bed (2 person)			
10. Institutions (Resident) Nursing home Rest home	475 per person			

SI: 1L = 0.26 gal.

