Table 27.6-2 MWFRS – Part 2: Wind Loads – Roof Exposure C

MWFRS - RoofV = 160-200 mph h = 130-160 ft.

	V (MPH)		160					180					200				
	,,	Load	Zone					Zone					Zone				
h (ft)	Roof Slope	Case	1	2	3	4	5	1	2	3	4	5	1	2	3	4	5
(',	Flat < 2:12 (9.46 deg)	1	NA	NA	-82.5	-73.6	-60.3	NA	NA	-104.4	-93.1	-76.3	NA	NA	-128.9	-114.9	-94.3
	(2	NA	NA	0.0	0.0	0.0	NA	NA	0.0	0.0	0.0	NA	NA	0.0	0.0	0.0
160	3:12 (14.0 deg)	1	-80.9	-58.3	-82.5	-73.6	-60.3	-102.5	-69.6	-104.4	-93.1	-76.3	-126.5	-86.0	-128.9	-114.9	-94.3
	' ' ' ' ' ' ' '	2	11.7	-16.4	0.0	0.0	0.0	14.8	-20.8	0.0	0.0	0.0	18.2	-25.7	0.0	0.0	0.0
	4:12 (18.4 deg)	1	-66.5	-53.7	-82.5	-73.6	-60.3	-84.2	-68.0	-104.4	-93.1	-76.3	-104.0	-83.9	-128.9	-114.9	-94.3
	` •	2	23.0	-23.6	0.0	0.0	0.0	29.2	-29.8	0.0	0.0	0.0	36.0	-36.8	0.0	0.0	0.0
	5:12 (22.6 deg)	1	-53.4	-53.7	-82.5	-73.6	-60.3	-67.6	-68.0	-104.4	-93.1	-76.3	-83.4	-83.9	-128.9	-114.9	-94.3
		2	30.7	-25.7	0.0	0.0	0.0	38.8	-32.5	0.0	0.0	0.0	47.9	-40.1	0.0	0.0	0.0
	6:12 (26.6 deg)	1	-42.9	-53.7	-82.5	-73.6	-60.3	-54.3	-68.0	-104.4	-93.1	-76.3	-67.0	-83.9	-128.9	-114.9	-94.3
		2	33.9	-25.7	0.0	0.0	0.0	42.9	-32.5	0.0	0.0	0.0	52.9	-40.1	0.0	0.0	0.0
	9:12 (36.9 deg)	1	-24.8	-53.7	-82.5	-73.6	-60.3	-31.4	-68.0	-104.4	-93.1	-76.3	-38.8	-83.9	-128.9	-114.9	-94.3
		2	40.5	-25.7	0.0	0.0	0.0	51.2	-32.5	0.0	0.0	0.0	63.2	-40.1	0.0	0.0	0.0
	12:12 (45.0 deg)	1	-14.0	-53.7	-82.5	-73.6	-60.3	-17.7	-68.0	-104.4	-93.1	-76.3	-21.9	-83.9	-128.9	-114.9	-94.3
		2	40.5	-25.7	0.0	0.0	0.0	51.2	-32.5	0.0	0.0	0.0	63.2	-40.1	0.0	0.0	0.0
	Flat < 2:12 (9.46 deg)	1	NA	NA	-81.4	-72.6	-59.5	NA	NA	-103.0	-91.8	-75.3	NA	NA	-127.2	-113.4	-93.0
		2	NA	NA	0.0	0.0	0.0	NA	NA	0.0	0.0	0.0	NA	NA	0.0	0.0	0.0
	3:12 (14.0 deg)	1	-79.9	-57.5	-81.4	-72.6	-59.5	-101.1	-68.7	-103.0	-91.8	-75.3	-124.8	-84.8	-127.2	-113.4	-93.0
		2	11.5	-16.2	0.0	0.0	0.0	14.6	-20.5	0.0	0.0	0.0	18.0	-25.3	0.0	0.0	0.0
	4:12 (18.4 deg)	1	-65.7	-53.0	-81.4	-72.6	-59.5	-83.1	-67.1	-103.0	-91.8	-75.3	-102.6	-82.8	-127.2	-113.4	-93.0
150		2	22.7	-23.3	0.0	0.0	0.0	28.8	-29.4	0.0	0.0	0.0	35.5	-36.4	0.0	0.0	0.0
	5:12 (22.6 deg)	1	-52.7	-53.0	-81.4	-72.6	-59.5	-66.7	-67.1	-103.0	-91.8	-75.3	-82.3	-82.8	-127.2	-113.4	-93.0
		2	30.3	-25.3	0.0	0.0	0.0	38.3	-32.1	0.0	0.0	0.0	47.3	-39.6	0.0	0.0	0.0
	6:12 (26.6 deg)	1	-42.3	-53.0	-81.4	-72.6	-59.5	-53.5	-67.1	-103.0	-91.8	-75.3	-66.1	-82.8	-127.2	-113.4	-93.0
		2	33.4	-25.3	0.0	0.0	0.0	42.3	-32.1	0.0	0.0	0.0	52.2	-39.6	0.0	0.0	0.0
140	9:12 (36.9 deg)	1	-24.5	-53.0	-81.4	-72.6	-59.5	-31.0	-67.1	-103.0	-91.8	-75.3	-38.3	-82.8	-127.2	-113.4	-93.0
		2	39.9	-25.3	0.0	0.0	0.0	50.5	-32.1	0.0	0.0	0.0	62.4	-39.6	0.0	0.0	0.0
	12:12 (45.0 deg)	1	-13.8	-53.0	-81.4	-72.6	-59.5	-17.5	-67.1	-103.0	-91.8	-75.3	-21.6	-82.8	-127.2	-113.4	-93.0
		2	39.9	-25.3	0.0	0.0	0.0	50.5	-32.1	0.0	0.0	0.0	62.4	-39.6	0.0	0.0	0.0
	Flat < 2:12 (9.46 deg)	1	NA	NA	-80.2	-71.5	-58.6	NA	NA	-101.5	-90.5	-74.2	NA	NA	-125.3	-111.7	-91.6
		2	NA 70.7	NA	0.0	0.0	0.0	NA	NA	0.0	0.0	0.0	NA 100.0	NA	0.0	0.0	0.0
	3:12 (14.0 deg)	1	-78.7	-56.7	-80.2	-71.5	-58.6	-99.6	-67.7	-101.5	-90.5	-74.2	-123.0	-83.6	-125.3	-111.7	-91.6
	4.40 (40.4 de a)	2	11.4	-16.0	0.0	0.0	0.0	14.4	-20.2	0.0	0.0	0.0	17.7	-24.9	0.0	0.0	0.0
	4:12 (18.4 deg)	1	-64.7	-52.2	-80.2	-71.5	-58.6	-81.9	-66.1	-101.5	-90.5	-74.2	-101.1	-81.6	-125.3	-111.7	-91.6
	5.40 (00 C do a)	1	-51.9	-22.9 -52.2	-80.2	-71.5	-58.6	28.4 -65.7	-29.0 -66.1	0.0 -101.5	-90.5	-74.2	35.0 -81.1	-35.8 -81.6	0.0 -125.3	0.0 -111.7	-91.6
	5:12 (22.6 deg)	2	29.8	-32.2	0.0	0.0	0.0	37.7	-31.6	0.0	0.0	0.0	46.6	-39.0	0.0	0.0	0.0
	6:12 (26.6 deg)	1	-41.7	-52.2	-80.2	-71.5	-58.6	-52.8	-66.1	-101.5	-90.5	-74.2	-65.2	-81.6	-125.3	-111.7	-91.6
	6:12 (26.6 deg)	2	32.9	-25.0	0.0	0.0	0.0	41.7	-31.6	0.0	0.0	0.0	51.4	-39.0	0.0	0.0	0.0
	9:12 (36.9 deg)	1	-24.1	-52.2	-80.2	-71.5	-58.6	-30.6	-66.1	-101.5	-90.5	-74.2	-37.7	-81.6	-125.3	-111.7	-91.6
	9.12 (30.9 deg)	2	39.4	-25.0	0.0	0.0	0.0	49.8	-31.6	0.0	0.0	0.0	61.5	-39.0	0.0	0.0	0.0
	12:12 (45.0 deg)	1	-13.6	-52.2	-80.2	-71.5	-58.6	-17.2	-66.1	-101.5	-90.5	-74.2	-21.3	-81.6	-125.3	-111.7	-91.6
	12.12 (40.0 deg)	2	39.4	-25.0	0.0	0.0	0.0	49.8	-31.6	0.0	0.0	0.0	61.5	-39.0	0.0	0.0	0.0
	Flat < 2:12 (9.46 deg)	1	NA	NA	-79.0	-70.4	-57.7	NA	NA	-100.0	-89.1	-73.1	NA	NA	-123.4	-110.0	-90.2
130	<u>.</u> (5.70 deg)	2	NA	NA	0.0	0.0	0.0	NA	NA	0.0	0.0	0.0	NA	NA	0.0	0.0	0.0
	3:12 (14.0 deg)	1	-77.5	-55.8	-79.0	-70.4	-57.7	-98.1	-66.7	-100.0	-89.1	-73.1	-121.1	-82.3	-123.4	-110.0	-90.2
	3 (,30 0.09)	2	11.2	-15.7	0.0	0.0	0.0	14.1	-19.9	0.0	0.0	0.0	17.5	-24.6	0.0	0.0	0.0
	4:12 (18.4 deg)	1	-63.7	-51.4	-79.0	-70.4	-57.7	-80.6	-65.1	-100.0	-89.1	-73.1	-99.5	-80.3	-123.4	-110.0	-90.2
	(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	2	22.1	-22.6	0.0	0.0	0.0	27.9	-28.6	0.0	0.0	0.0	34.5	-35.3	0.0	0.0	0.0
	5:12 (22.6 deg)	1	-51.1	-51.4	-79.0	-70.4	-57.7	-64.7	-65.1	-100.0	-89.1	-73.1	-79.9	-80.3		-110.0	-90.2
	(2	29.4	-24.6	0.0	0.0	0.0	37.2	-31.1	0.0	0.0	0.0	45.9	-38.4	0.0	0.0	0.0
	6:12 (26.6 deg)	1	-41.1	-51.4	-79.0	-70.4	-57.7	-52.0	-65.1	-100.0	-89.1	-73.1	-64.1	-80.3	-123.4		-90.2
	, , ,	2	32.4	-24.6	0.0	0.0	0.0	41.0	-31.1	0.0	0.0	0.0	50.6	-38.4	0.0	0.0	0.0
									-65.1				-37.1	-80.3	-123.4		-90.2
	9:12 (36.9 deg)	1	-23.8	-51.4	-79.0	-/(J.4	-5/./	- 30.1	-ba.	- 00.0.0	-89. I	- / a. l	-3/ 1	-00.0	- 120.4		
	9:12 (36.9 deg)	1 2	-23.8 38.7	-51.4 -24.6	-79.0 0.0	-70.4 0.0	-57.7 0.0	-30.1 49.0	-31.1	-100.0 0.0	-89.1 0.0	-73.1 0.0	60.5	-38.4	0.0	0.0	0.0
	9:12 (36.9 deg) 12:12 (45.0 deg)	1 2 1														0.0	