## SECTION 3407 GLASS REPLACEMENT

**3407.1 Conformance.** The installation or replacement of glass shall be as required for new installations.

## **SECTION 3408 CHANGE OF OCCUPANCY**

**3408.1 Conformance.** No change shall be made in the use or occupancy of any building that would place the building in a different division of the same group of occupancies or in a different group of occupancies, unless such building is made to comply with the requirements of this code for such division or group of occupancies. Subject to the approval of the *building official*, the use or occupancy of existing buildings shall be permitted to be changed and the building is allowed to be occupied for purposes in other groups without conforming to all the requirements of this code for those groups, provided the new or proposed use is less hazardous, based on life and fire risk, than the existing use.

**3408.2 Certificate of occupancy.** A certificate of occupancy shall be issued where it has been determined that the requirements for the new occupancy classification have been met.

**3408.3 Stairways.** An existing stairway shall not be required to comply with the requirements of Section 1009 where the existing space and construction does not allow a reduction in pitch or slope.

**3408.4 Seismic.** When a change of occupancy results in a structure being reclassified to a higher occupancy category, the structure shall conform to the seismic requirements for a new structure of the higher occupancy category. Where the existing seismic force-resisting system is a type that can be designated ordinary, values of R,  $\Omega_0$  and  $C_d$  for the existing seismic force-resisting system shall be those specified by this code for an ordinary system unless it is demonstrated that the existing system will provide performance equivalent to that of a detailed, intermediate or special system.

## **Exceptions:**

- 1. Specific seismic detailing requirements of Section 1613 for a new structure shall not be required to be met where the seismic performance is shown to be equivalent to that of a new structure. A demonstration of equivalence shall consider the regularity, over strength, redundancy and ductility of the structure.
- 2. When a change of use results in a structure being reclassified from Occupancy Category I or II to Occupancy Category III and the structure is located where the seismic coefficient  $S_{DS}$  is less than 0.33, compliance with the seismic requirements of Section 1613 is not required.

**3408.5 Plumbing Fixtures.** All plumbing fixtures which replace existing fixtures as part of a repair activity shall comply with Chapter 4 of the *Abu Dhabi Uniform Plumbing Code*. **SECTION 3409 HISTORIC BUILDINGS** 

**3409.1 Historic buildings.** The provisions of this code relating to the construction, repair, *alteration*, *addition*, restoration and movement of structures, and change of occupancy shall not be mandatory for *historic buildings* where such buildings are judged by the *building official* to not constitute a distinct life safety hazard.