

- lumen maintenance factor, 111
- survival factor, 111
- wall temperature, *see* Light source–ambient temperature
- Language laboratories, 46
- Large area low-luminance luminaire, 47, 58
- Laundries, 54
- Lavatories, 59
- Leather and leather goods, 55
- Lecture halls/theatres, 46
- Legislation, 40
- Lending libraries, 55
- Libraries, 55
- Library workrooms, 55
- Life of lighting installation, 111
- Light loss, 8
  - dirty environment, 35
  - obstruction, 66, 67, 70, 90, 94, 96
- Light:
  - modulation, 25
  - output ratio, 111
  - working, 111
  - output waveform, 26
- Light source:
  - ambient temperature, 86
  - compact fluorescent, 42
  - daylight match, 36
  - discharge, 25
  - end of life, 25
  - flicker, 26
  - fluorescent, 26, 42
  - high pressure sodium, 42
  - incandescent, 25, 73
  - life, 8, 73, 79
  - light control, 74
  - lumen maintenance, 73
  - metal halide, 42
  - operating hours, 40
  - operating position, 86
  - after glow, 26
  - restarting, 80
  - run-up time, 73, 80
  - selection, 36, 73
  - service conditions, 61
  - starting, 73
  - stroboscopic effect, 26
  - survival, 8
    - factor, 86, 87
  - switching cycle, 79, 87
  - test conditions, 86
  - tungsten-halogen, 40, 73
  - vibration, 74, 86
- Lighting:
  - energy targets, 41
  - fitting, *see* Luminaire
  - levels, 5
  - schedule, 30, 32, 42, 89
- Lighting for:
  - architecture, 8
  - circulation, 12, 72
  - cleaning, 41, 49, 80
  - colour, 8
  - contemplation, 9
  - display, 18, 19
  - elderly, 4, 31
  - emphasis, 8, 16, 36
  - entertainment, 9
  - exhibition, 16
  - form, 8
  - inspection, 15
  - leisure, 9
  - mood, 8, 16, 34, 65
  - partially sighted, 31
  - relaxation, 8, 12
  - safety, 45, 46, 49, 58, 59, 60
  - security, 41, 80
  - stimulation, 12
  - texture, 8, 19
  - visual coherence, 8
- Lighting Industry Federation, 81
- Limiting glare rating, 14, 42
- Liquidity index, *see* Payback
- Lithography, 58
- Livestock buildings, 43
- Load factor, 82
- Local lighting, 33, 46, 47, 53, 55, 58, 61, 62, 72, 111
  - ambient illumination, 72
- Loading ramps/bays, 55, 55
- Localised lighting, 33, 46, 54, 55, 62, 71, 111
  - ambient illuminance, 71
  - maintenance, 71
  - uplighter, 71
- Lounges in places of public assembly, 57
- Louvres, 4, 14
- Low-bay, *see* Luminaire
- Low brightness luminaire, *see* Luminaire – VDT
- Low-temperature starting, 48, 61
- Luggage:
  - offices, railway, 59
  - store rooms, 44
- Lumen:
  - maintenance, 8, 73
  - method, 11, 33, 70, 89
- Luminaire, 111
  - ambient temperature, 74
  - appearance, 75
  - bat-wing, 97
  - clinical examination, 51
  - dustproof, 45, 49, 60, 63
  - food factory, 48
  - hazardous area, 48, 49, 58, 63
  - high-bay, 44, 45, 47, 49, 57, 58
  - hostile area, 43, 45, 48, 49, 54, 58, 59, 63, 74
  - layout, 16, 95
  - low temperature, 60
  - luminance limits, 39
  - maintenance category, 45, 49, 60, 88
  - maintenance factor, 87, 88, 112
  - operating theatre, 52
  - orientation, 16
  - selection, 73, 74, 75
  - track-mounted, 40
  - vibration, 72
  - wall-washer, 77
- Luminance, 10, 112
  - adaptation, 33
  - average, 11