- 4. 2 wheelchair positions shall be provided in the cabin with a floor space of 865 mm by 1420 mm.
- 5. A forward facing securement shall be provided for each wheelchair position.
- 6. Staff shall be responsible to attach and detach the securement systems.
- 7. Visual and audio onboard announcement and safety displays shall be provided within the vicinity of the wheelchair travelers.
- 8. Emergency and evacuation procedures shall be provided in real time in audio and visual display.

## **12.3.4.** Water taxi

Water taxis are enclosed cabin vessels and are available by demand through online reservations.

- 1. Gangways/ramps shall be provided to bridge the horizontal and vertical gaps between the vessel and the berth.
- 2. The door from the landing deck to the cabin shall be 850 mm wide.
- 3. Door thresholds shall not exceed a height of 15 mm otherwise a bridge plate shall be used.
- 4. 2 accessible locations shall be provided in the cabin with a floor space of 865 mm by 1420 mm.
- 5. A forward facing securement shall be provided for each wheelchair position.
- 6. Staff shall be responsible to attach and detach the securement systems.
- 7. Visual and audio onboard announcement and printed safety manuals and displays shall be provided within the vicinity of the wheelchair travelers.
- 8. Emergency and evacuation procedures shall be provided in real time in audio and visual display.