**Velocity Pressure Exposure Coefficients, $K_h$ and $K_z$**

**Table 29.3-1**

| Height above ground level, z | | Exposure | | |
|---|---|---|---|---|
| ft | (m) | B | C | D |
| 0-15 | (0-4.6) | 0.57 | 0.85 | 1.03 |
| 20 | (6.1) | 0.62 | 0.90 | 1.08 |
| 25 | (7.6) | 0.66 | 0.94 | 1.12 |
| 30 | (9.1) | 0.70 | 0.98 | 1.16 |
| 40 | (12.2) | 0.76 | 1.04 | 1.22 |
| 50 | (15.2) | 0.81 | 1.09 | 1.27 |
| 60 | (18) | 0.85 | 1.13 | 1.31 |
| 70 | (21.3) | 0.89 | 1.17 | 1.34 |
| 80 | (24.4) | 0.93 | 1.21 | 1.38 |
| 90 | (27.4) | 0.96 | 1.24 | 1.40 |
| 100 | (30.5) | 0.99 | 1.26 | 1.43 |
| 120 | (36.6) | 1.04 | 1.31 | 1.48 |
| 140 | (42.7) | 1.09 | 1.36 | 1.52 |
| 160 | (48.8) | 1.13 | 1.39 | 1.55 |
| 180 | (54.9) | 1.17 | 1.43 | 1.58 |
| 200 | (61.0) | 1.20 | 1.46 | 1.61 |
| 250 | (76.2) | 1.28 | 1.53 | 1.68 |
| 300 | (91.4) | 1.35 | 1.59 | 1.73 |
| 350 | (106.7) | 1.41 | 1.64 | 1.78 |
| 400 | (121.9) | 1.47 | 1.69 | 1.82 |
| 450 | (137.2) | 1.52 | 1.73 | 1.86 |
| 500 | (152.4) | 1.56 | 1.77 | 1.89 |

**Notes:**

1. The velocity pressure exposure coefficient $K_z$ may be determined from the following formula:

   For 15 ft. $\leq z \leq z_g$ $\quad\quad$ For $z < 15$ ft.

   $K_z = 2.01\ (z/z_g)^{2/\alpha}$ $\quad\quad$ $K_z = 2.01\ (15/z_g)^{2/\alpha}$

   2. $\alpha$ and $z_g$ are tabulated in Table 26.9.1.
2. Linear interpolation for intermediate values of height z is acceptable.
3. Exposure categories are defined in Section 26.7.