

- Reflection (*continued*)
 - factor, *see* Reflectance
 - specular, 15, 22, 34, 47, 55
 - veiling, 14, 46, 72
- Reflections, 59
- Reflectometer, 115
- Reflector lamp *see* Light source
- Regional electricity companies, 82
- Regular array, *see also* Luminaire-layout, 70, 74, 75, 90, 97
- Repairs, laundry/dry cleaning, 54
- Restaurants, 54
- Re-strike *see* Light source-restarting
- Rest, sanitation and first aid rooms, 59
- Retail premises, 60
- Revealing form, 16
- Rolling:
 - ceramic, tiles and glassware, 45
 - mills, iron and steel works, 60
- Rooflight, 2, 4
- Room:
 - index, 41, 75, 89, 91, 95
 - perimeter, 96
 - surface, 34
 - maintenance factor, 86, 88, 115
- Rooms for medical attention, 59
- Rubber, 46
 - industry, 45
- Rubbing, leather skins, 55
- Saddlery work, 55
- Safety:
 - colours, 36, 45, 46, 49, 58, 59, 60
 - lenses/screens, 56
 - Signs Directive, 100
- Sales areas, 60
- Sand preparation, foundries and metal casting, 48
- Sanitation rooms, 59
- Satisfaction, visual, 6, 35
- Saw frame, 63
- Sawmills, 63
- Scalar (spherical) illuminance, 5
- Scalloping, 35
- Scanner rooms, 52
- Scatter, 28, 44
- Screen class, VDT, 38
- Scribing, 56
- School canteens, 46
- Schools, 46
- Security check areas, airport, 44
- Self-service restaurants, 54
- Semi-cylindrical illuminance, 115
- Semi-direct lighting, 115
- Semi-indirect lighting, 115
- Sewing:
 - leather, 55
 - textiles, 61
- Self-contained, *see* Emergency lighting
- Self-luminous display, 46
- Sewing, 61
- Shadows, 11, 72, 94
- Shake-out areas, foundries and metal casting, 48
- Shear line, rolling mill, 60
- Sheet metalwork, 56
- Shielding angle, minimum, 14
- Shoe manufacture, 54, 55
- Sick:
 - animal pens, 43
 - bays, 59
- Sign luminance, 100
- Silhouette, 16
- Sizing, textile processing, 61
- Skiving, leather, 55
- Sky, overcast, 14
- Slab stores, 60
- Slaughterhouses, 48
- Sodium lamp, *see* Light source
- Solar control, 14
 - blinds, 14
 - building form, 14
 - building orientation, 14
 - curtains, 14
 - external screen, 14
 - glass, 14
 - louvres, 14
- Solar radiation, 115
- Soldering, printed circuit board, 47
- Sorting, laundry, 54
- SOX, *see* Light source-sodium, low pressure
- Spacing, 115
 - to height ratio, 93, 95, 115
 - axial, 93
 - transverse, 93
- Spatial:
 - clarity, 34
 - distribution, 7
 - of luminous intensity, 115
 - variation, 9
- Spectral distribution, 4
- Spectrum, electromagnetic, 24
- Specular reflection, 12, 16, 34, 47, 55
- Spherical illuminance, 115
- Spinning, textile processing, 61
- Sports halls, 46
- Spotlighting, 115
- Spot:
 - replacement, 87
 - welding, 56
- Spray booths, 62
- Spraying, vehicle, 62
- Staff rooms, 53
- Stainless steel, 56
- Stairs, 46, 55
 - educational buildings, 46
- Stalls, calving, 43
- Standard maintained illuminance, *see* Maintained illuminance
- Standby lighting, 99
- Starterless circuit, *see* Ballast
- Statutory instrument, 66
- Steam pits, wood processing, 63
- Steel:
 - engraving, 58
 - fabrication, 56
 - works, 60
- Sterilisation rooms, 49
- Stitching, leather, 55
- Stock rooms, 61