## INDEX

| Hosoya, N., 564                                       | isolator unit, 165                     |
|---|--|
| hospital power supplies, 484                          | Isyumou, N., 433, 435                  |
| Hunt, J.C.R., 519                                     | Isyumov, N., 558, 576                  |
| hurricane prone regions, 243, 537t                    | •                                      |
| hurricane wind speeds, 246, 510                       | Jackson, P.S., 519                     |
| hydraulic structures, 149                             | joint, 60                              |
| hydrodynamic loads, 22, 417                           | Jones, K.F., 455, 457, 459, 460        |
| hydrostatic loads, 22, 417                            | Jones, 18.1., 155, 157, 159, 160       |
| hydrostatic pressure, soil loads and, 11–12, 365–366, | Kala, S., 570                          |
| 397–398   | Kareem, A., 519, `521, 524             |
| hysteretic damping, 191                               | Kavanagh, K.T., 558                    |
|   | •                                      |
| ICC (Intermetional Code Council) 226                  | King, A.B., 580                        |
| ICC (International Code Council), 236                 | Klinge, A.F., 428                      |
| ice accretion models, 459                             | Kopp, G.A., 564                        |
| ice loads. See atmospheric ice loads                  | Korean Power Engineering, 490          |
| ice-sensitive structures, 47, 457                     | Kriebel, D.L., 419, 422                |
| ice weight, 458–459                                   | Kuroiwa, D., 458                       |
| IEEE, 50  |  |
| impact loads, 14, 409–410, 418–423                    | Laflamme, J., 461                      |
| categories of, 418–419                                | Lake Superior/Fraser Valley, 54f       |
| special impact loads, 422                             | lateral loads, 408                     |
| impact protective system, 243                         | lateral pressures, 397                 |
| importance coefficient, 419t, 421                     | lattice frameworks, 313f               |
| importance factor, 1, 429                             | Layendecker, E.V., 378                 |
| in-cloud icing, 47, 457–458                           | Leavengood, D.C., 455                  |
| indirect design, 379                                  | Lee, N.H., 490                         |
| industrial buildings, 471                             | leeward step, 432–433                  |
| inherent damping, 191                                 | Lemelin, D.R., 519                     |
| inherent torsion, 91, 480                             | Lepage, M.F., 576                      |
| inspection, special, 60                               | Letchford, C.W., 563                   |
| inspection, special, 60                               | Leyendecker, E.V., 379, 394            |
| intermediate precast structural walls, 130            | library stack rooms, 407–408           |
| internal pressure coefficient, 257–258                | light-frame construction, 60           |
|   |  |
| International Civil Aviation Organization,<br>409     | light frame wall, 61                   |
|   | light frame wood shear wall, 61        |
| inverted pendulum-type structures                     | limit deformation, 58                  |
| defined, 60   | limited-deformability element, 58      |
| seismic design requirements, 78                       | limited local collapse, 378            |
| irregularities, 493                                   | limit state, 1                         |
| classification of, 81                                 | linear response history procedure, 480 |
| horizontal, 81, 83t                                   | analysis requirements, 161             |
| mass, 495   | ground motion, 161                     |
| stiffness and strength, 495                           | horizontal shear distribution, 162     |
| structural, 81  | modeling, 161                          |
| torsional, 495  | response parameters, 161–162           |
| vertical, 81, 84t                                     | Liu, H., 511                           |
| Irwin, P., 435  | live loads, 13-20, 407-414, 413f       |
| Irwin, P.A., 525, 526, 576                            | concentrated, 13, 409                  |
| isolation interface, 165                              | consensus standards/other referenced   |
| isolation system, 165, 167. See also seismically      | documents, 16                          |
| isolated structures                                   | crane loads, 16, 411                   |
| force-deflection characteristics of, 176              | definitions, 13                        |
| quality assurance, 361                                | impact loads, 14, 409–410              |
| * · · · · · · · · · · · · · · · · · · ·               | ± // //                                |